Isolation Transformer

For Texas Instruments SN6501 Transformer Driver

- Developed to work with Texas Instruments SN6501 Transformer Driver for Isolated Power Supplies
- Center tapped primary and secondary windings
- Designed to meet UL/CSA/IEC 60950 Basic Insulation with 1.5 mm creepage and clearance.

Core material Ferrite
Terminations RoHS tin-silver over tin over nickel over phos bronze. Other terminations available at additional cost.
Weight 0.98 g
Ambient temperature –40°C to +125°C
Storage temperature Component: –40°C to +125°C. Tape and reel packaging: –40°C to +80°C
Isolation 2500 Vrms, one minute, winding to winding
Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles
Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)
Failures in Time (FIT) / Mean Time Between Failures (MTBF) 38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332
Packaging 600/13″ reel Plastic tape: 24 mm wide, 0.37 mm thick, 16 mm pocket spacing, 6.1 mm pocket depth
PCB washing Only pure water or alcohol recommended

Part number[1]	Pri / sec voltage	Inductance[2] min (µH)	DCR max (Ohms)[3] pri	DCR max (Ohms)[3] sec	Leakage inductance[4] max (µH)	Volt-time product[5] (V-µsec)	Power[6] (W)	Turns ratio pri : sec
MA5632-AL_	3.3 V to 5.0 V	17.8	0.086	0.219	0.464	17.6	2.0	1 : 2

1. When ordering, please specify **termination** and **packaging** codes:

MA5632-ALD

Termination: **L** = RoHS compliant tin-silver over tin over nickel over phos bronze.
Special order: T = RoHS tin-silver-copper (95.5/4/0.5) or **S** = non-RoHS tin-lead (63/37).
Packaging: **D** = 13″ machine ready reel. EIA-481 embossed plastic tape (600 per full reel).
B = Less than full reel. In tape, but not machine ready. To have a leader and trailer added ($25 charge), use code letter D instead.

2. Inductance is tested between pins 4 and 3 at 500 kHz, 0.5 Vrms, 0 Adc.
3. DCR is per winding.
4. Leakage inductance is for the primary with both windings connected in series and with the secondary windings shorted.
5. Based on Bsat of the core at 25°C and number of turns on winding 4-3.
6. Calculated output power based on 150 kHz operating frequency. Power varies depending on application.
7. Electrical specifications at 25°C.

Refer to Doc 362 “Soldering Surface Mount Components” before soldering.



Coilcraft
www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 1022 Revised 08/24/12