

A Bayesian model for the inference of TF activation state: notes on implementation and preliminary results

University of Massachusetts Boston - November
9th 2018 - Argenis Arriojas




Outline

- Introduction
- The problem
- The model
- Implementing the model
 - Python OOP
- Some results on TGFB
 - Enrichment results
 - Bayesian inference results
- Speeding up the code
 - Cython approach
- What's next


Introduction

Introduction



- Proteins are complex molecules produced from DNA
- These have many different and very specific functions within an organism
 - Antibody
 - Enzyme
 - Messenger
 - Structural component
 - Transport/storage
- Transcription factors (TFs) regulate when and when not to produce certain proteins
- This regulation depends on many factors and is harmoniously orchestrated to achieve cellular objectives





Introduction




- Proteins are complex molecules produced from DNA
- These have many different and very specific functions within an organism
 - Antibody
 - Enzyme
 - Messenger
 - Structural component
 - Transport/storage
- Transcription factors (TFs) regulate when and when not to produce certain proteins
- This regulation depends on many factors and is harmoniously orchestrated to achieve cellular objectives

Transcriptional regulation

Transcription factors bind to promoter region of genes and may either activate or repress expression of a gene




Regulatory networks are complex



Problem:
We want to identify
relevant TFs given a
cellular context

Using data to discover TFs



What data?

Differentially expressed genes



Differentially expressed genes


- Micro-arrays, RNA-seq
 - Measures gene expression levels at RNA level
 - This is a good measure of the activity of a gene
 - Contrast between two conditions (contexts)
 - Wild-type
 - Special condition

If there is a change in expression level of a gene, there may be some TF responsible for it



Differentially expressed genes


If there is a change in expression level of a gene, there may be some TF responsible for it



Differentially expressed genes


If there is a change in expression level of a gene, there may be some TF responsible for it

It is actually hard to infer from large DEG data




A causal inference model

A causal inference model



A causal inference model



X : TF activation state $\{0, 1\}$

θ : TF activation strength

S : Mode of regulation $\{-1, 0, 1\}$

H : Hidden gene state $\{-1, 0, 1\}$

Y : Observed gene state $\{-1, 0, 1\}$

α : Observation noise parameter

β : Observation noise parameter

$X \sim \text{Binomial}$

$\theta \sim \text{Beta}$

$S \sim \text{Multinomial}$


$Y \sim \text{Multinomial}$

$\alpha \sim \text{Beta}$

$\beta \sim \text{Beta}$




Regulatory logic - the OR-NOR model






Regulatory logic - the OR-NOR model





Regulatory logic - the OR-NOR model





Regulatory logic - the OR-NOR model

$$Y_j \sim \text{Multinomial}(P_{Y_j}^{(-1)}, P_{Y_j}^{(0)}, P_{Y_j}^{(+1)})$$

$$P_{Y_j}^{(-1)} = 1 - \prod_i (1 - X_i \theta_i S_{ij}^{(-1)})$$

$$P_{Y_j}^{(+1)} = [1 - \prod_i (1 - X_i \theta_i S_{ij}^{(+1)})] \prod_i (1 - X_i \theta_i S_{ij}^{(-1)})$$

$$P_{Y_j}^{(0)} = 1 - P_{Y_j}^{(+1)} - P_{Y_j}^{(-1)}$$



Regulatory logic - the OR-NOR model

$$Y_j \sim \text{Multinomial}(P_{Y_j}^{(-1)}, P_{Y_j}^{(0)}, P_{Y_j}^{(+1)})$$

$$P_{Y_j}^{(-1)} = 1 - \prod_i (1 - X_i \theta_i S_{ij}^{(-1)})$$

$$P_{Y_j}^{(+1)} = [1 - \prod_i (1 - X_i \theta_i S_{ij}^{(+1)})] \prod_i (1 - X_i \theta_i S_{ij}^{(-1)})$$

$$P_{Y_j}^{(0)} = \prod_i (1 - X_i \theta_i S_{ij}^{(+1)}) \prod_i (1 - X_i \theta_i S_{ij}^{(-1)})$$



Regulatory logic - the OR-NOR model

$$Y_j \sim \text{Multinomial}(P_{Y_j}^{(0)}, P_{Y_j}^{(1)}, P_{Y_j}^{(2)})$$

$$P_{Y_j}^{(0)} = 1 - \prod_i (1 - X_i \theta_i S_{ij}^{(0)})$$

$$P_{Y_j}^{(2)} = [1 - \prod_i (1 - X_i \theta_i S_{ij}^{(2)})] \prod_i (1 - X_i \theta_i S_{ij}^{(0)})$$

$$P_{Y_j}^{(1)} = \prod_i (1 - X_i \theta_i S_{ij}^{(2)}) \prod_i (1 - X_i \theta_i S_{ij}^{(0)})$$

Regulatory logic - the OR-NOR model

```
class ORNOR_YLikelihood(Multinomial):
```

```
    __slots__ = []
```

```
    def get_model_likelihood(self):
```

```
        if self.value[0]:
```

```
            pr0 = 1.
```

```
            for x, t, s in self.in_edges:
```

```
                if s.value[0]:
```

```
                    pr0 *= 1. - t.value * x.value[1]
```

```
            pr0 = (1. - pr0)
```

```
            likelihood = pr0
```

```
        elif self.value[2]:
```

```
            pr0 = 1.
```

```
            pr2 = 1.
```

```
            for x, t, s in self.in_edges:
```

```
                if s.value[2]:
```

```
                    pr2 *= 1. - t.value * x.value[1]
```

```
                elif s.value[0]:
```

```
                    pr0 *= 1. - t.value * x.value[1]
```

```
            pr2 = (pr0 - pr2*pr0)
```

```
            likelihood = pr2
```

```
        else:
```

```
            pr1 = 1.
```

```
            for x, t, s in self.in_edges:
```

```
                if not s.value[1]:
```

```
                    pr1 *= 1. - t.value * x.value[1]
```

```
            likelihood = pr1
```

```
        return likelihood
```

Considering noise in DEG data



If there was no noise:

$$\begin{matrix} H_1 \\ Y_1 \end{matrix}$$

Conditional probability table $P(Y|H)$

| $P(Y H)$ | $H = -1$ | $H = 0$ | $H = 1$ |
|----------|----------|---------|---------|
| $Y = -1$ | 1 | 0 | 0 |
| $Y = 0$ | 0 | 1 | 0 |
| $Y = 1$ | 0 | 0 | 1 |

$Y \sim \text{Multinomial}$

Considering noise in DEG data



Incorporate noise:


Conditional probability table $P(Y|H)$

| $P(Y H)$ | $H = -1$ | $H = 0$ | $H = 1$ |
|----------|----------------------|---------------|----------------------|
| $Y = -1$ | $1 - \alpha - \beta$ | α | β |
| $Y = 0$ | α | $1 - 2\alpha$ | α |
| $Y = 1$ | β | α | $1 - \alpha - \beta$ |

$$\alpha > \beta$$

?False positive rate = α

?False negative rate = $(\alpha + \beta) / 2$




$Y \sim \text{Multinomial}$
 $\alpha \sim \text{Beta}$
 $\beta \sim \text{Beta}$

Considering noise in DEG data

```
def get_loglikelihood(self):  
  
    # remember the actual observed Y  
    curr_val = self.value  
  
    likelihood = 0.  
    for i, val in enumerate(self.possible_values):  
        # compute likelihood given possible values  
        # prob is given by noise table  
        self.value = val  
        likelihood += self.get_model_likelihood() * self.prob[i]  
  
    # restore the right value  
    self.value = curr_val  
  
    return np.log(likelihood)
```

Python implementation of model

Inheritance diagram





Results on real data

The experiment:

- TGF β and CXCL12 treated cells: N1 cells which were derived from a stromal nodule of benign prostatic hyperplasia, exhibit a fibroblastic morphology, express fibroblastic markers vimentin and calponin, and demonstrate secretion and proliferation profiles consistent with aging primary prostate fibroblasts
- ?? Embryonic Mouse Hypothalamus Cell Line N1 (mHypoE-N1)
- The TGF β /TGF β R and CXCL12/CXCR4 axes induce myofibroblast phenoconversion independently through Smads and MEK/Erk proteins, respectively

Can we identify TFs that are activated (or deactivated) by TGF β and CXCL12 signalling?



Fisher's test enrichment results

These results are from Causal Inference Engine developed in lab: Corey, Yasaman, Saman

TGFβ+
Fisher's
test
enrichment
results

| name | isTF | pval | adj.pval |
|---------|-------|--------------|----------|
| E2F4 | True | 7.271182e-07 | 0.000222 |
| STAT2 | True | 7.366951e-05 | 0.011271 |
| TFAP4 | True | 4.343193e-04 | 0.044301 |
| RUNX3 | True | 2.967426e-03 | 0.227008 |
| ZNF384 | True | 5.931348e-03 | 0.344132 |
| CHD2 | False | 7.265966e-03 | 0.344132 |
| FGFR1 | False | 7.872310e-03 | 0.344132 |
| CXXC1 | False | 1.380430e-02 | 0.528014 |
| TBP | True | 1.728868e-02 | 0.587815 |
| ING2 | False | 2.015356e-02 | 0.616699 |
| TFAP2C | True | 2.534239e-02 | 0.704979 |
| TCF3 | True | 2.980997e-02 | 0.760154 |
| ZKSCAN1 | True | 3.741597e-02 | 0.830770 |
| ZFX | True | 3.800911e-02 | 0.830770 |
| USF1 | True | 4.928034e-02 | 0.960629 |



Bayesian inference results

| name | activation | X+ | T |
|--------|------------|----------|----------|
| STAT2 | 0.787178 | 1.000000 | 0.787178 |
| E2F4 | 0.684481 | 1.000000 | 0.684481 |
| TFAP4 | 0.601267 | 1.000000 | 0.601267 |
| FGFR1 | 0.554466 | 0.990200 | 0.559954 |
| ZFX | 0.461331 | 0.908544 | 0.507769 |
| TFAP2C | 0.428740 | 0.924955 | 0.463526 |
| NFKB2 | 0.427217 | 0.999928 | 0.427248 |
| ELF3 | 0.420522 | 0.997735 | 0.421477 |
| CHD2 | 0.395436 | 0.999907 | 0.395472 |
| CXXC1 | 0.379562 | 0.999999 | 0.379562 |
| PHOX2B | 0.370017 | 0.750003 | 0.493355 |
| ZNF384 | 0.351120 | 0.839702 | 0.418149 |
| TBP | 0.338750 | 0.907094 | 0.373445 |
| USF1 | 0.326915 | 0.993218 | 0.329147 |
| E2F6 | 0.305269 | 0.985747 | 0.309683 |

TGFβ+
Bayesian
inference
results

TGFβ+
Fisher's
test
enrichment
results

| name | isTF | pval | adj.pval |
|---------|-------|--------------|----------|
| E2F4 | True | 7.271182e-07 | 0.000222 |
| STAT2 | True | 7.366951e-05 | 0.011271 |
| TFAP4 | True | 4.343193e-04 | 0.044301 |
| RUNX3 | True | 2.967426e-03 | 0.227008 |
| ZNF384 | True | 5.931348e-03 | 0.344132 |
| CHD2 | False | 7.265966e-03 | 0.344132 |
| FGFR1 | False | 7.872310e-03 | 0.344132 |
| CXXC1 | False | 1.380430e-02 | 0.528014 |
| TBP | True | 1.728868e-02 | 0.587815 |
| ING2 | False | 2.015356e-02 | 0.616699 |
| TFAP2C | True | 2.534239e-02 | 0.704979 |
| TCF3 | True | 2.980997e-02 | 0.760154 |
| ZKSCAN1 | True | 3.741597e-02 | 0.830770 |
| ZFX | True | 3.800911e-02 | 0.830770 |
| USF1 | True | 4.928034e-02 | 0.960629 |

| name | activation | X+ | T |
|--------|------------|----------|----------|
| STAT2 | 0.787178 | 1.000000 | 0.787178 |
| E2F4 | 0.684481 | 1.000000 | 0.684481 |
| TFAP4 | 0.601267 | 1.000000 | 0.601267 |
| FGFR1 | 0.554466 | 0.990200 | 0.559954 |
| ZFX | 0.461331 | 0.908544 | 0.507769 |
| TFAP2C | 0.428740 | 0.924955 | 0.463526 |
| NFKB2 | 0.427217 | 0.999928 | 0.427248 |
| ELF3 | 0.420522 | 0.997735 | 0.421477 |
| CHD2 | 0.395436 | 0.999907 | 0.395472 |
| CXXC1 | 0.379562 | 0.999999 | 0.379562 |
| PHOX2B | 0.370017 | 0.750003 | 0.493355 |
| ZNF384 | 0.351120 | 0.839702 | 0.418149 |
| TBP | 0.338750 | 0.907094 | 0.373445 |
| USF1 | 0.326915 | 0.993218 | 0.329147 |
| E2F6 | 0.305269 | 0.985747 | 0.309683 |

TGFβ+
Bayesian
inference
results



Bayesian inference results CXCL12+

| name | activation | X+ | T |
|--------|------------|----------|----------|
| STAT2 | 0.774442 | 1.000000 | 0.774442 |
| E2F4 | 0.756497 | 1.000000 | 0.756497 |
| ZFX | 0.643292 | 0.993420 | 0.647553 |
| TFAP4 | 0.537285 | 0.972271 | 0.552608 |
| ELF3 | 0.480099 | 1.000000 | 0.480099 |
| CHD2 | 0.479303 | 1.000000 | 0.479303 |
| TFAP2C | 0.447800 | 1.000000 | 0.447800 |
| SNAI2 | 0.406602 | 0.783812 | 0.518750 |
| FGFR1 | 0.393122 | 0.837609 | 0.469339 |
| TP73 | 0.385321 | 0.749276 | 0.514257 |
| TBP | 0.368697 | 1.000000 | 0.368697 |
| E2F6 | 0.344420 | 1.000000 | 0.344420 |
| PBX1 | 0.326379 | 1.000000 | 0.326379 |
| USF1 | 0.302572 | 0.848682 | 0.356519 |
| YY1 | 0.301797 | 1.000000 | 0.301797 |

CXCL12+
Bayesian
inference
results

| TGFβ+ Bayesian inference results | TGFβ+ Bayesian inference results | | | | CXCL12+ Bayesian inference results |
|---|----------------------------------|------------|----------|----------|---|
| | name | activation | X+ | T | |
| | STAT2 | 0.787178 | 1.000000 | 0.787178 | |
| | E2F4 | 0.684481 | 1.000000 | 0.684481 | |
| | TFAP4 | 0.601267 | 1.000000 | 0.601267 | |
| | FGFR1 | 0.554466 | 0.990200 | 0.559954 | |
| | ZFX | 0.461331 | 0.908544 | 0.507769 | |
| | TFAP2C | 0.428740 | 0.924955 | 0.463526 | |
| | NFKB2 | 0.427217 | 0.999928 | 0.427248 | |
| | ELF3 | 0.420522 | 0.997735 | 0.421477 | |
| | CHD2 | 0.395436 | 0.999907 | 0.395472 | |
| | CXXC1 | 0.379562 | 0.999999 | 0.379562 | |
| | PHOX2B | 0.370017 | 0.750003 | 0.493355 | |
| | ZNF384 | 0.351120 | 0.839702 | 0.418149 | |
| | TBP | 0.338750 | 0.907094 | 0.373445 | |
| | USF1 | 0.326915 | 0.993218 | 0.329147 | |
| | E2F6 | 0.305269 | 0.985747 | 0.309683 | |
| | name | activation | X+ | T | |
| | STAT2 | 0.774442 | 1.000000 | 0.774442 | |
| | E2F4 | 0.756497 | 1.000000 | 0.756497 | |
| | ZFX | 0.643292 | 0.993420 | 0.647553 | |
| | TFAP4 | 0.537285 | 0.972271 | 0.552608 | |
| | ELF3 | 0.480099 | 1.000000 | 0.480099 | |
| | CHD2 | 0.479303 | 1.000000 | 0.479303 | |
| | TFAP2C | 0.447800 | 1.000000 | 0.447800 | |
| | SNAI2 | 0.406602 | 0.783812 | 0.518750 | |
| | FGFR1 | 0.393122 | 0.837609 | 0.469339 | |
| | TP73 | 0.385321 | 0.749276 | 0.514257 | |
| | TBP | 0.368697 | 1.000000 | 0.368697 | |
| | E2F6 | 0.344420 | 1.000000 | 0.344420 | |
| | PBX1 | 0.326379 | 1.000000 | 0.326379 | |
| | USF1 | 0.302572 | 0.848682 | 0.356519 | |
| | YY1 | 0.301797 | 1.000000 | 0.301797 | |

| | name | activation | X+ | T |
|--|--------|------------|----------|----------|
| | STAT2 | 0.787178 | 1.000000 | 0.787178 |
| | E2F4 | 0.684481 | 1.000000 | 0.684481 |
| | TFAP4 | 0.601267 | 1.000000 | 0.601267 |
| | FGFR1 | 0.554466 | 0.990200 | 0.559954 |
| | ZFX | 0.461331 | 0.908544 | 0.507769 |
| | TFAP2C | 0.428740 | 0.924955 | 0.463526 |
| | NFKB2 | 0.427217 | 0.999928 | 0.427248 |
| | ELF3 | 0.420522 | 0.997735 | 0.421477 |
| | CHD2 | 0.395436 | 0.999907 | 0.395472 |
| | CXXC1 | 0.379562 | 0.999999 | 0.379562 |
| | PHOX2B | 0.370017 | 0.750003 | 0.493355 |
| | ZNF384 | 0.351120 | 0.839702 | 0.418149 |
| | TBP | 0.338750 | 0.907094 | 0.373445 |
| | USF1 | 0.326915 | 0.993218 | 0.329147 |
| | E2F6 | 0.305269 | 0.985747 | 0.309683 |

TGFβ+
Bayesian
inference
results

| | name | activation | X+ | T |
|--|--------|------------|----------|----------|
| | STAT2 | 0.774442 | 1.000000 | 0.774442 |
| | E2F4 | 0.756497 | 1.000000 | 0.756497 |
| | ZFX | 0.643292 | 0.993420 | 0.647553 |
| | TFAP4 | 0.537285 | 0.972271 | 0.552608 |
| | ELF3 | 0.480099 | 1.000000 | 0.480099 |
| | CHD2 | 0.479303 | 1.000000 | 0.479303 |
| | TFAP2C | 0.447800 | 1.000000 | 0.447800 |
| | SNAI2 | 0.406602 | 0.783812 | 0.518750 |
| | FGFR1 | 0.393122 | 0.837609 | 0.469339 |
| | TP73 | 0.385321 | 0.749276 | 0.514257 |
| | TBP | 0.368697 | 1.000000 | 0.368697 |
| | E2F6 | 0.344420 | 1.000000 | 0.344420 |
| | PBX1 | 0.326379 | 1.000000 | 0.326379 |
| | USF1 | 0.302572 | 0.848682 | 0.356519 |
| | YY1 | 0.301797 | 1.000000 | 0.301797 |

CXCL12+
Bayesian
inference
results

Improving performance



Python is an interpreted language

- Code is not pre-compiled
- Many uncertainties for the code interpreter
 - i.e. data types for variables
- Limited room for performance improvement
 - Many modules like Numpy are written in lower level code for performance improvement
 - First approach is to take advantage of highly optimized modules like Numpy

For the best performance we would need to use lower level programming like C/C++

However, there is a middle ground available for python code. Cython brings the opportunity to refactor key parts of Python code that are computationally intensive.



Cython

Some advantages:

- Reuse Python code
- Can use C libraries like GNU Scientific Library (GSL)
- Generates C/C++ compilable code
- Offers tools to identify computing bottlenecks, so we fix those first

Beware:

- It's not immediately magical



Performance comparison

```
[1]: from gbnet.models import ORNORModel
     from gbnet.cmodels import ORNORModel as ORNORModelC
     from gbnet.aux import genData
```

```
NX, NActvX, NY = 60, 5, 2000
Xgt, DEG, rels = genData(NX, NActvX, NY, AvgNTF=12)
print(len(rels), 'edges in rels')
```

23906 edges in rels

```
[2]: python_model = ORNORModel(rels, DEG, nchains=1)
     cython_model = ORNORModelC(rels, DEG, nchains=1)
```

```
[3]: %%timeit
     python_model.sample(N=1, njobs=1)
```

2.86 s ± 40.6 ms per loop (mean ± std. dev. of 7 runs, 1 loop each)

```
[4]: %%timeit
     cython_model.sample(N=1, njobs=1)
```

238 ms ± 4.3 ms per loop (mean ± std. dev. of 7 runs, 1 loop each)

Cython version is ~ 12 faster



Code profiling

Original nodes.py file

```
$ python3 profile_sampling.py
2404 edges in rels
Fri Nov 9 13:23:40 2018    Profile.prof

33244222 function calls in 65.554 seconds

Ordered by: internal time

ncalls  tottime  percall  cumtime  percall filename:lineno(function)
10576800  30.762    0.000    30.762    0.000 nodes.py:178(get_model_likelihood)
3525600  13.868    0.000    44.631    0.000 nodes.py:208(get_loglikelihood)
492800   3.114    0.000    42.536    0.000 nodes.py:62(get_outcome_probs)
1466400  2.067    0.000    34.995    0.000 nodes.py:84(get_loglikelihood)
2        2.024    1.012    65.554    32.777 chain.py:30(sample)
1035200  2.023    0.000    2.023    0.000 {method 'reduce' of 'numpy.ufunc' objects}
1466400  1.074    0.000    1.074    0.000 {method 'argmax' of 'numpy.ndarray' objects}
```




Code profiling

Only cythonize nodes.py file

```
$ python3 profile_sampling.py
2415 edges in rels
Fri Nov 9 13:25:15 2018    Profile.prof

31874810 function calls in 52.666 seconds

Ordered by: internal time
```

| ncalls | tottime | percall | cumtime | percall | filename:lineno(function) |
|----------|---------|---------|---------|---------|--|
| 10623000 | 19.650 | 0.000 | 19.650 | 0.000 | cythontest_nodes.pyx:179(get_model_likelihood) |
| 3541000 | 12.554 | 0.000 | 32.204 | 0.000 | cythontest_nodes.pyx:209(get_loglikelihood) |
| 495000 | 3.487 | 0.000 | 34.171 | 0.000 | cythontest_nodes.pyx:63(get_outcome_probs) |
| 2 | 2.088 | 1.044 | 52.666 | 26.333 | chain.py:30(sample) |
| 1039600 | 2.043 | 0.000 | 2.043 | 0.000 | {method 'reduce' of 'numpy.ufunc' objects} |
| 1473000 | 1.886 | 0.000 | 26.523 | 0.000 | cythontest_nodes.pyx:85(get_loglikelihood) |
| 495000 | 1.365 | 0.000 | 35.536 | 0.000 | cythontest_nodes.pyx:95(sample) |
| 1473000 | 1.051 | 0.000 | 1.051 | 0.000 | {method 'argmax' of 'numpy.ndarray' objects} |



Code profiling

Craft most classes in nodes.py, also cythonize other files

```
$ python3 profile_sampling.py
2419 edges in rels
Thu Nov  8 14:38:33 2018      Profile.prof

25584807 function calls in 7.571 seconds

Ordered by: internal time
```

| ncalls | tottime | percall | cumtime | percall | filename:lineno(function) |
|----------|---------|---------|---------|---------|---|
| 10639800 | 2.466 | 0.000 | 2.466 | 0.000 | cnodes.pyx:186(get_model_likelihood) |
| 2 | 1.488 | 0.744 | 7.571 | 3.786 | cchain.pyx:36(sample) |
| 3546600 | 1.069 | 0.000 | 3.535 | 0.000 | cnodes.pyx:222(get_loglikelihood) |
| 1475400 | 0.470 | 0.000 | 3.110 | 0.000 | cnodes.pyx:153(get_loglikelihood) |
| 2419000 | 0.286 | 0.000 | 2.640 | 0.000 | cnodes.pyx:222(get_loglikelihood (wrapper)) |
| 495800 | 0.170 | 0.000 | 3.280 | 0.000 | cnodes.pyx:123(get_outcome_probs) |




Cython code annotation

```
def get_model_likelihood(self):
    if self.value[0]:
        pr0 = 1.
        for x, t, s in self.in_edges:
            if s.value[0]:
                pr0 *= 1. - t.value * x.value[1]
        pr0 = (1. - pr0)
        likelihood = pr0

    elif self.value[2]:
        pr0 = 1.
        pr2 = 1.
        for x, t, s in self.in_edges:
            if s.value[2]:
                pr2 *= 1. - t.value * x.value[1]
            elif s.value[0]:
                pr0 *= 1. - t.value * x.value[1]
        pr2 = (pr0 - pr2*pr0)
        likelihood = pr2

    else:
        pr1 = 1.
        for x, t, s in self.in_edges:
            if not s.value[1]:
                pr1 *= 1. - t.value * x.value[1]
        likelihood = pr1

    return likelihood
```



Yellow lines represent Python overhead. We aim at reducing this overhead.

```
cdef double get_model_likelihood(self):
    cdef double likelihood, pr0, pr1, pr2
    cdef Multinomial x, s
    cdef Beta t

    if self.value[0]:
        pr0 = 1.
        for x, t, s in self.in_edges:
            if s.value[0]:
                pr0 *= 1. - t.value * x.value[1]
        pr0 = (1. - pr0)
        likelihood = pr0

    elif self.value[2]:
        pr0 = 1.
        pr2 = 1.
        for x, t, s in self.in_edges:
            if s.value[2]:
                pr2 *= 1. - t.value * x.value[1]
            elif s.value[0]:
                pr0 *= 1. - t.value * x.value[1]
        pr2 = (pr0 - pr2*pr0)
        likelihood = pr2

    else:
        pr1 = 1.
        for x, t, s in self.in_edges:
            if not s.value[1]:
                pr1 *= 1. - t.value * x.value[1]
        likelihood = pr1

    return likelihood
```



What's next

- Test our inference model against available DEG data
 - Harmonizome - <http://amp.pharm.mssm.edu/Harmonizome/>
 - CLUE.io - <https://clue.io/cmap>
- Incorporate prior knowledge on regulatory interactions
 - Use text mining to extract interactions
 - Use available public networks
- Implement the present work into C/C++
 - Seek the best possible performance