

---

# **ansible-runner-role Documentation**

***Release 1.2.1***

**Vladimir Botka**

**Jul 05, 2020**



**TABLE OF CONTENTS:**

<b>1</b>	<b>User's guide</b>	<b>3</b>
1.1	Introduction . . . . .	3
1.2	Installation . . . . .	4
1.3	Playbook . . . . .	4
1.4	Debug . . . . .	5
1.5	Tags . . . . .	5
1.6	Tasks . . . . .	5
1.7	Variables . . . . .	9
1.8	Default variables . . . . .	9
1.9	Best practice . . . . .	10
<b>2</b>	<b>Annotated source code</b>	<b>11</b>
2.1	Tasks . . . . .	11
<b>3</b>	<b>Copyright</b>	<b>19</b>
<b>4</b>	<b>Legal Notice</b>	<b>21</b>
<b>5</b>	<b>Indices and tables</b>	<b>23</b>



This [role](#) and the documentation is work in progress. Please feel free to [share your feedback and report issues](#). Contributions are welcome.



## USER'S GUIDE

### Table of Contents

- *User's guide*
  - *Introduction*
  - *Installation*
  - *Playbook*
  - *Debug*
  - *Tags*
  - *Tasks*
    - \* *Ansible Runner packages*
      - *Synopsis*
      - *Examples*
  - *Variables*
  - *Default variables*
  - *Best practice*

## 1.1 Introduction

Run this role to install and configure Ansible Runner. Optionally configure cron to periodically run Ansible playbooks.

- Ansible role: `ansible_runner`
- Supported systems:
  - FreeBSD Supported Production Releases
  - Ubuntu Supported Releases
- (Requirements in future releases: `ansible_lib`)

---

### Note:

- The utility *ansible-runner* is not part of standard Ansible installation. See [Installing Ansible Runner](#)

**See also:**

- [Ansible Runner documentation](#)
- [Ansible Runner source code](#)
- [REST API ansible-runner-service](#)

## 1.2 Installation

The most convenient way how to install an Ansible role is to use Ansible Galaxy CLI `ansible-galaxy`. The utility comes with the standard Ansible package and provides the user with a simple interface to the Ansible Galaxy's services. For example, take a look at the current status of the role

```
shell> ansible-galaxy info vbotka.ansible_runner
```

and install it

```
shell> ansible-galaxy install vbotka.ansible_runner
```

Install the library of tasks (for future releases)

```
shell> ansible-galaxy install vbotka.ansible_lib
```

**See also:**

- To install specific versions from various sources see [Installing content](#).
- Take a look at other roles `shell> ansible-galaxy search --author=vbotka`

## 1.3 Playbook

Below is a simple playbook that calls this role at a single host `srv.example.com` (2)

```
1 shell> cat ansible-runner.yml
2 - hosts: srv.example.com
3   gather_facts: true
4   connection: ssh
5   remote_user: admin
6   become: yes
7   become_user: root
8   become_method: sudo
9   roles:
10    - vbotka.ansible_runner
```

---

**Note:** `gather_facts: true` (3) must be set to gather facts needed to evaluate OS-specific options of the role. For example to install packages the variable `ansible_os_family` is needed to select the appropriate Ansible module.

---

**See also:**

- For details see [Connection Plugins](#) (4-5)



- See also [Understanding Privilege Escalation \(6-8\)](#)

## 1.4 Debug

To see additional debug information enable debug output in the configuration

```
lp_debug: true
```

, or set the extra variable in the command

```
shell> ansible-playbook ansible-runner.yml -e 'ar_debug=true'
```

---

**Note:** The debug output of this role is optimized for the **yaml** callback plugin. Set this plugin for example in the environment `shell> export ANSIBLE_STDOUT_CALLBACK=yaml`.

---

**See also:**

- [Playbook Debugger](#)

## 1.5 Tags

The tags provide the user with a very useful tool to run selected tasks of the role. To see what tags are available list the tags of the role with the command

```
shell> ansible-playbook ansible-runner.yml --list-tags

playbook: ansible-runner.yml

play #1 (srv.example.com): srv.example.com TAGS: []
    TASK TAGS: [always, ar_config, ar_debug, ar_links, ar_packages, ar_vars]
```

For example, display the list of the variables and their values with the tag `ar_debug` (when the debug is enabled `ar_debug: true`)

```
shell> ansible-playbook ansible-runner.yml -t ar_debug
```

See what packages will be installed

```
shell> ansible-playbook ansible-runner.yml -t ar_packages --check
```

Install packages and exit the play

```
shell> ansible-playbook ansible-runner.yml -t ar_packages
```

## 1.6 Tasks

Test single tasks at single remote host `test_01`. Create a playbook

```
shell> cat ansible.yml
- hosts: test_01
  become: true
  roles:
    - vbotka.ansible
```

Customize configuration in `host_vars/test_01/ar-*.yaml` and check the syntax

```
shell> ansible-playbook ansible-runner.yml --syntax-check
```

Then dry-run the selected task and see what will be changed. Replace `<tag>` with valid tag.

```
shell> ansible-playbook ansible-runner.yml -t <tag> --check --diff
```

When all seems to be ready run the command. Run the command twice and make sure the playbook and the configuration is idempotent

```
shell> ansible-playbook ansible-runner.yml -t <tag>
```

### 1.6.1 Ansible Runner packages

#### Synopsis

Ansible Runner can be installed by `pip` or from packages, and ports.

See also:

- Annotated Source code [packages.yml](#)
- [ansible-plugins](#)
- [Ansible project source code](#)

#### Examples

##### Example 1: Install ansible-runner in Ubuntu by pip for admin

Create a playbook

```
shell> ansible-runner.yml
- hosts: test_01
  become: true
  roles:
    - vbotka.ansible_runner
```

Create `host_vars/test_01/ansible-runner.yml`

```
shell> cat host_vars/test_01/ansible-runner.yml
ar_install: false
ar_pip_install: true
ar_debug: false
ar_owner: admin
```

Install ansible-runner

```

shell> ansible-playbook ansible-runner.yml -e "ar_install=true"
...
TASK [vbotka.ansible_runner : packages: Install Ansible Runner pip packages for_
↪admin]
ok: [test_01] => (item={'name': 'ansible-runner'})

```

Show ansible-runner package installed by pip for admin

```

shell> whoami
admin

shell> pip list | grep ansible-runner
ansible-runner          1.4.6

```

## Example 2: Install ansible-runner in FreeBSD from the port

Create a playbook

```

shell> ansible-runner.yml
- hosts: test_01
  become: true
  roles:
    - vbotka.ansible_runner

```

Create *host\_vars/test\_01/ansible-runner.yml*

```

shell> cat host_vars/test_01/ansible-runner.yml
<TBD>

```

Install ansible-runner

```

shell> ansible-playbook ansible-runner.yml -e "ar_install=true"
<TBD>
...
TASK [vbotka.ansible_runner : packages: Install Ansible Runner pip packages for_
↪admin]
ok: [test_01] => (item={'name': 'ansible-runner'})

```

Show ansible-runner package installed by pip for admin

```

<TBD>
shell> whoami

shell> which ansible-runner
ansible-runner          1.4.6

```

## Example 3: Configure cron to periodically run Ansible playbooks

<TBD>

## Example 1: Install ansible-runner in Ubuntu by pip for admin

Create a playbook

```
shell> ansible-runner.yml
- hosts: test_01
  become: true
  roles:
    - vbotka.ansible_runner
```

Create *host\_vars/test\_01/ansible-runner.yml*

```
shell> cat host_vars/test_01/ansible-runner.yml
ar_install: false
ar_pip_install: true
ar_debug: false
ar_owner: admin
```

Install ansible-runner

```
shell> ansible-playbook ansible-runner.yml -e "ar_install=true"
...
TASK [vbotka.ansible_runner : packages: Install Ansible Runner pip packages for_
↪admin]
ok: [test_01] => (item={'name': 'ansible-runner'})
```

Show ansible-runner package installed by pip for admin

```
shell> whoami
admin

shell> pip list | grep ansible-runner
ansible-runner      1.4.6
```

## Example 2: Install ansible-runner in FreeBSD from the port

Create a playbook

```
shell> ansible-runner.yml
- hosts: test_01
  become: true
  roles:
    - vbotka.ansible_runner
```

Create *host\_vars/test\_01/ansible-runner.yml*

```
shell> cat host_vars/test_01/ansible-runner.yml
<TBD>
```

Install ansible-runner

```
shell> ansible-playbook ansible-runner.yml -e "ar_install=true"
<TBD>
...
```

(continues on next page)

(continued from previous page)

```
TASK [vbotka.ansible_runner : packages: Install Ansible Runner pip packages for_
↪admin]
ok: [test_01] => (item={'name': 'ansible-runner'})
```

Show ansible-runner package installed by pip for admin

```
<TBD>
shell> whoami

shell> which ansible-runner
ansible-runner          1.4.6
```

### Example 3: Configure cron to periodically run Ansible playbooks

<TBD>

## 1.7 Variables

In this chapter we describe role's default variables stored in the directory **defaults**.

See also:

- Ansible variable precedence: Where should I put a variable?

## 1.8 Default variables

<TBD>

[defaults/main.yml]

```
1  ---
2  # defaults ansible_runner
3
4  ar_install: true
5  ar_debug: false
6  ar_backup_conf: false
7
8  # Install distro packages or pip
9  # false - distro packages, true - pip
10 # ar_pip_install: false # OS specific variable see vars/defaults
11
12 # FreeBSD
13 freebsd_install_retries: 10
14 freebsd_install_delay: 5
15 freebsd_install_method: "packages"
16 # freebsd_install_method: "ports"
17 freebsd_use_packages: true
18
19 # Linux
20 linux_install_retries: 10
```

(continues on next page)

(continued from previous page)

```
21 linux_install_delay: 5
22
23 # Python
24 pip_install_retries: 10
25 pip_install_delay: 5
26 # pip_extraargs: ""                # Optional
27
28 # pip package dependent
29 # ar_pip_executable: "pip3"        # OS specific variable see vars/defaults
30 # ar_pip_requirements: []          # Optional
31
32 # Configuration
33 ar_config: []
34
35 # Links
36 # ar_links: [] # OS specific variable see vars/defaults
37
38 # EOF
39 ...
```

## 1.9 Best practice

Display the variables for debug if needed. Then disable this task `ar_debug: false` to speedup the playbook

```
shell> ansible-playbook ansible-runner.yml -t ar_debug
```

Install packages Then disable this task `ar_install: false` to speedup the playbook

```
shell> ansible-playbook ansible-runner.yml -t ar_packages \
      -e 'ar_install=true'
```

The role and the configuration data in the examples are idempotent. Once the installation and configuration have passed there should be no changes reported by *ansible-playbook* when running the playbook repeatedly. Disable debug, and install to speedup the playbook

```
shell> ansible-playbook ansible-runner.yml
```

## ANNOTATED SOURCE CODE

### Table of Contents

- *Annotated source code*
  - *Tasks*
    - \* *main.yml*
    - \* *config.yml*
    - \* *debug.yml*
    - \* *links.yml*
    - \* *packages.yml*
    - \* *vars.yml*

## 2.1 Tasks

### 2.1.1 main.yml

Synopsis: Tasks of the playbook.

Description of the task.

[main.yml]

```
1 ---
2 # tasks for ansible_runner
3
4 - import_tasks: vars.yml
5   tags: [ar_vars, always]
6
7 - import_tasks: debug.yml
8   when: ar_debug|bool
9   tags: [ar_debug, always]
10
11 - import_tasks: packages.yml
12   when: ar_install|bool
13   tags: ar_packages
14
```

(continues on next page)

(continued from previous page)

```

15 - import_tasks: links.yml
16   tags: ar_links
17
18 - import_tasks: config.yml
19   tags: ar_config
20
21 # EOF
22 ...

```

## 2.1.2 config.yml

Synopsis: Configure config.

Description of the task.

[config.yml]

```

1 ---
2
3 - name: "config: configure ansible-runner"
4   debug:
5     msg: No config
6     when: ar_debug|bool
7
8 # EOF
9 ...

```

## 2.1.3 debug.yml

Synopsis: Configure debug.

Description of the task.

[debug.yml]

```

1 ---
2
3 - name: "debug: Ansible Runner"
4   vars:
5     msg: |
6       ansible_os_family [{{ ansible_os_family }}]
7       ansible_distribution [{{ ansible_distribution }}]
8       ansible_distribution_major_version [{{ ansible_distribution_major_version }}]
9       ansible_distribution_version [{{ ansible_distribution_version }}]
10      ansible_distribution_release [{{ ansible_distribution_release }}]
11      ansible_python_version [{{ ansible_python_version }}]
12
13      ar_install [{{ ar_install }}]
14
15      freebsd_install_method [{{ freebsd_install_method }}]
16      freebsd_use_packages [{{ freebsd_use_packages }}]
17      freebsd_install_retries [{{ freebsd_install_retries }}]
18      freebsd_install_delay [{{ freebsd_install_delay }}]
19
20      linux_install_retries [{{ linux_install_retries }}]

```

(continues on next page)



(continued from previous page)

```

21     linux_install_delay [{{ linux_install_delay }}]
22
23     pip_install_retries [{{ pip_install_retries }}]
24     pip_install_delay [{{ pip_install_delay }}]
25     pip_extraargs [{{ pip_extraargs|default('UNDEFINED') }}]
26
27     ar_pip_install [{{ ar_pip_install }}]
28     ar_pip_executable [{{ ar_pip_executable }}]
29     ar_pip_requirements [{{ pip_requirements|default('UNDEFINED') }}]
30
31     ansible_user_id [{{ ansible_user_id }}]
32
33     ar_owner [{{ ar_owner }}]
34     ar_backup_conf [{{ ar_backup_conf }}]
35
36     ar_packages
37     {{ ar_packages|to_nice_yaml }}
38     ar_links
39     {{ ar_links|to_nice_yaml }}
40
41     ar_config
42     {{ ar_config|to_nice_yaml }}
43
44     debug:
45         msg: "{{ msg.split('\n') }}"
46
47     # EOF
48     ...

```

## 2.1.4 links.yml

Synopsis: Configure links.

Description of the task.

[links.yml]

```

1  ---
2
3  - name: "links: Create directories for links"
4    file:
5      state: "directory"
6      dest: "{{ item.dest|dirname }}"
7      loop: "{{ ar_links }}"
8
9  - name: "links: Create links"
10   file:
11     state: "link"
12     src: "{{ item.src }}"
13     dest: "{{ item.dest }}"
14     force: "{{ item.force|default(false) }}"
15     loop: "{{ ar_links }}"
16
17   # EOF
18   ...

```

## 2.1.5 packages.yml

Synopsis: Configure packages.

Description of the task.

[packages.yml]

```

1  ---
2
3  # packages -----
4
5  # FreeBSD
6  - name: "packages: Install Ansible Runner FreeBSD packages"
7    block:
8      - name: "packages: Install Ansible Runner packages FreeBSD"
9        pkgng:
10          name: "{{ item.name }}"
11          loop: "{{ ar_packages }}"
12          register: result
13          until: result is succeeded
14          retries: "{{ freebsd_install_retries }}"
15          delay: "{{ freebsd_install_delay }}"
16      - name: "packages: Debug FreeBSD packages"
17        when: ar_debug|bool
18        debug:
19          var: result
20    when:
21      - not ar_pip_install
22      - ansible_os_family == "FreeBSD"
23      - freebsd_install_method|lower == "packages"
24
25  - name: "packages: Install FreeBSD ports"
26    block:
27      - name: "packages: Install Ansible Runner ports FreeBSD"
28        portinstall:
29          name: "{{ item.name }}"
30          use_packages: "{{ freebsd_use_packages }}"
31          loop: "{{ ar_packages }}"
32          register: result
33          until: result is succeeded
34          retries: "{{ freebsd_install_retries }}"
35          delay: "{{ freebsd_install_delay }}"
36      - name: "packages: Debug FreeBSD ports"
37        when: ar_debug|bool
38        debug:
39          var: result
40    when:
41      - not ar_pip_install
42      - ansible_os_family == "FreeBSD"
43      - freebsd_install_method|lower == "ports"
44
45  # Linux
46  - name: "packages: Install Ansible Runner packages Linux"
47    block:
48      - name: "packages: Install Ansible Runner packages Linux"
49        package:
50          name: "{{ item.name }}"
51          loop: "{{ ar_packages }}"

```

(continues on next page)

(continued from previous page)

```

52     register: result
53     until: result is succeeded
54     retries: "{{ linux_install_retries }}"
55     delay: "{{ linux_install_delay }}"
56 - name: "packages: Debug Linux"
57   when: ar_debug|bool
58   debug:
59     var: result
60 when:
61   - not ar_pip_install
62   - ansible_os_family == "RedHat" or ansible_os_family == "Debian"
63
64 # pip -----
65 - name: "packages: Test {{ ar_pip_executable }} exists"
66   when: ar_pip_install
67   block:
68     - name: "packages: Stat {{ ar_pip_executable }}"
69       stat:
70         path: "{{ ar_pip_executable }}"
71       register: result
72     - name: "packages: Not exists {{ ar_pip_executable }}"
73       fail:
74         msg: "[ERROR] {{ ar_pip_executable }} does not exist."
75       when: not result.stat.exists
76
77 - name: "packages: Install Ansible Runner pip packages for {{ ar_owner }}"
78   when: ar_pip_install
79   become_user: "{{ ar_owner }}"
80   become: true
81   changed_when: false # Note 1.
82   pip:
83     name: "{{ item.name }}"
84     executable: "{{ ar_pip_executable }}"
85     version: "{{ item.version|default(omit) }}"
86     state: "{{ item.state|default(omit) }}"
87     extra_args: "{{ pip_extraargs|default(omit) }}"
88   loop: "{{ ar_packages }}"
89   register: result
90   until: result is succeeded
91   retries: "{{ pip_install_retries }}"
92   delay: "{{ pip_install_delay }}"
93
94 - name: "packages: Debug pip packages"
95   when:
96     - ar_pip_install
97     - ar_debug|bool
98   debug:
99     var: result
100
101 - name: "packages: Install Ansible Runner pip requirements for {{ ar_owner }}"
102   when:
103     - ar_pip_install
104     - ar_pip_requirements is defined
105   become_user: "{{ ar_owner }}"
106   become: true
107   changed_when: false # Note 1.
108   pip:

```

(continues on next page)

(continued from previous page)

```

109     requirements: "{{{ ar_pip_requirements }}}}"
110     executable: "{{{ ar_pip_executable }}}}"
111     extra_args: "{{{ pip_extraargs|default(omit) }}}}"
112     register: result
113     until: result is succeeded
114     retries: "{{{ pip_install_retries }}}}"
115     delay: "{{{ pip_install_delay }}}}"
116
117 - name: "packages: Debug pip requirements"
118   when:
119     - ar_pip_install
120     - ar_debug|bool
121   debug:
122     var: result
123
124 # Note 1.
125 # The pip module isn't always idempotent #28952
126 # https://github.com/ansible/ansible/issues/28952
127
128 # EOF
129 ...

```

## 2.1.6 vars.yml

Synopsis: Configure vars.

Description of the task.

[vars.yml]

```

1 ---
2
3 - name: "Declare ar_owner when undefined"
4   when: ar_owner is undefined
5   set_fact:
6     ar_owner: "{{{ ansible_user_id }}}}"
7
8 - name: "Default vars for {{{ ansible_os_family }}}
9           {{{ ansible_distribution }}}
10          {{{ ansible_distribution_release }}}}"
11   include_vars: "{{{ item }}}}"
12   with_first_found:
13     - files:
14         - "{{{ ansible_distribution }}}-{{{ ansible_distribution_release }}}.yaml"
15         - "{{{ ansible_distribution }}}.yaml"
16         - "{{{ ansible_os_family }}}.yaml"
17         - "defaults.yaml"
18         - "default.yaml"
19     paths: "{{{ role_path }}}/vars/defaults"
20
21 - name: "Custom vars for {{{ ansible_os_family }}}
22           {{{ ansible_distribution }}}
23           {{{ ansible_distribution_release }}}}"
24   include_vars: "{{{ item }}}}"
25   with_first_found:
26     - files:

```

(continues on next page)

(continued from previous page)

```
27     - "{{ ansible_distribution }}-{{ ansible_distribution_release }}.yaml"
28     - "{{ ansible_distribution }}.yaml"
29     - "{{ ansible_os_family }}.yaml"
30     - "defaults.yaml"
31     - "default.yaml"
32     paths: "{{ role_path }}/vars"
33
34     # EOF
35     . . .
```



## **COPYRIGHT**

Redistribution and use in source (RST DocUtils) and ‘compiled’ forms (XML, HTML, PDF, PostScript, RTF and so forth) with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code (RST Docutils) must retain the above copyright notice, this list of conditions and the following disclaimer as the first lines of this file unmodified.

Redistributions in compiled form (transformed to other DTDs, converted to PDF, PostScript, RTF and other formats) must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Important: THIS DOCUMENTATION IS PROVIDED “AS IS” AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE PROVIDER BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS DOCUMENTATION, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.





## LEGAL NOTICE

All product names, logos, and brands are property of their respective owners.



## INDICES AND TABLES

- `genindex`
- `modindex`
- `search`