

ChemWorld: Programmable Chemical Worlds for Controlled and Replayable Agent Experimentation

Jiangjie Qiu¹, Yijun Li¹, Xiaonan Wang^{1,*}

¹Beijing Key Laboratory of Artificial Intelligence for Advanced Chemical Engineering Materials, State Key Laboratory of Chemical Engineering and Low-Carbon Technology, Department of Chemical Engineering, Tsinghua University, Beijing 100084, China

*Correspondence: wangxiaonan@tsinghua.edu.cn

Abstract

Autonomous chemistry increasingly depends on environments in which agents can repeatedly act, observe, and adapt. Physical laboratories provide essential real-material evidence but are costly to repeat and difficult to use for tightly matched interventions, whereas most digital environments keep the underlying experimental world largely fixed. We introduce ChemWorld, a programmable chemical environment in which reusable process and observation components are compiled into executable worlds. ChemWorld separates the public experimental contract available to an agent from evaluator-owned chemical and material laws. Researchers can therefore vary world composition and operating conditions, or change a single hidden law while holding the public task and interaction conditions fixed. Transactional execution records operations, failures, resource changes, and state transitions, allowing complete environment-action trajectories to be replayed exactly and audited. Full-census qualification covered the reference registry, 52 generated compositions, and module, interface, compilation, and invalid-action tests. Eight deterministic experimental cases demonstrated shared lifecycle semantics, failure recovery, and exact replay, while six parent-child world-fork pairs isolated the effects of single private-law interventions under matched public conditions. An independent agent also completed a full lifecycle in a non-reference world through the same public interface. Within the declared component and model domain, ChemWorld provides a controlled and replayable substrate for studying experimentation across systematically varied chemical worlds, complementary to physical-laboratory evidence and calibration.

1. Introduction

Recent advances in self-driving laboratories and chemistry agents are moving chemical research from algorithmic assistance toward autonomous experimentation. Agents can now plan experiments, call chemistry tools and interact with robots, automated instruments and cloud laboratories to execute synthesis, characterization and optimization workflows on real materials [1–9]. As agents assume a sustained role in experimental decisions, their capabilities depend not only on the model but also on the environment that defines available operations, observations and state transitions. Building environments for agent interaction, controlled study and evaluation is therefore becoming a foundational problem in autonomous chemistry.

Physical laboratories provide the most direct evidence from real materials and instruments, but large-scale repeated interaction is costly: it consumes reagents, samples and instrument time and is constrained by equipment, safety requirements and experimental turnaround. At the same time, physical experiments are difficult to restart from exactly the same initial state or to support strict comparisons in which only one factor changes and all others remain fixed. Software environments offer lower-cost repeatable interaction, and existing systems span reaction optimization and process control, virtual chemistry, interactive scientific discovery and embodied laboratory simulation [10–22].

However, these environments usually define the experimental world in advance and primarily study how an agent

completes a given task, operates a particular bench or adapts to fixed dynamics and hidden rules. It is less common to systematically alter the chemical processes and underlying laws that constitute the environment while keeping the agent-facing operations, instruments and observations unchanged. This limits another important class of controlled studies: under identical public experimental conditions, one may wish to change only a material property or process law and observe the resulting changes in the experimental process and agent behavior. Supporting such studies requires not just more predefined tasks, but an environment in which chemical worlds themselves can be constructed, modified, repeated and compared.

We therefore introduce ChemWorld, a programmable chemical-world platform for autonomous chemistry research (Fig. 1). ChemWorld treats world construction as a locus of experimental control: it represents chemical processes and observation models as reusable components and separates the agent-accessible public experimental interface from evaluator-owned chemical and material laws. Researchers can compose processes, change operating conditions and instrument configurations, or alter one hidden law while holding the public task, action sequence and bound randomness fixed. The system records operations, state transitions, resource use, failures and recovery, thereby supporting repeatable, auditable and attributable experiments.

This paper makes four contributions:

1. Programmable chemical-world construction.

Reusable process and observation components and a compatibility compiler construct executable worlds whose topology, operating conditions, instruments and private chemical or material laws can be varied systematically.

2. **A common experimental interface across worlds.** Compatible worlds share one agent-facing contract for operations, instruments, observations, resources, failure handling, termination and evaluation.
3. **Complete, replayable and attributable experimental records.** Each operation executes transactionally and records success, failure, rollback and resource changes, providing process-complete evidence for replay and intervention attribution. Complete environment-action traces can be reconstructed exactly, while single-private-law forks isolate the effect of a registered world change.
4. **Agent experimentation through the same environment.** Deterministic workflows and an independent agent use the same public interface while the evaluator retains the complete experimental process record without exposing private state.

This work establishes ChemWorld’s construction, qualification and agent-interface integration within the declared component and compatibility domain; comparative agent performance, universal chemical fidelity and physical-laboratory transfer remain outside the present scope.

2. Relation to existing experimental environments

Experimental environments for autonomous science have developed along four related lines with different primary emphases: autonomous experimentation in physical laboratories, laboratory simulation for embodied agents, interactive environments for scientific discovery, and virtual chemistry and process environments. We discuss these directions in turn to position ChemWorld within the existing landscape.

2.1 Autonomous experimentation in physical laboratories

Coscientist and ChemCrow connect language-model reasoning with chemistry tools, automated platforms and cloud laboratories. A-Lab, mobile robotic systems, ORGANA, ChemAgents and newer instrument-facing agents further demonstrate closed-loop synthesis, characterization, long-horizon experimental workflows and autonomous operation of scientific instruments on real materials [1–9]. These systems establish the real-material execution branch of autonomous chemistry. Their strength is direct physical experimental evidence, although large-scale, strictly matched repetition remains limited by samples, instrument access and experimental turnaround.

2.2 Simulated laboratories for embodied scientific agents

LabUtopia and Labimus use laboratory simulation to train and evaluate embodied scientific agents, covering scene understanding, object and material manipulation, instrument use and long-horizon experimental procedures [20, 21]. These environments primarily study how an agent carries out experimental procedures, reducing the cost and risk of training directly on physical hardware and complementing environments centered on scientific reasoning or chemical-process dynamics.

2.3 Interactive environments for scientific discovery agents

DiscoveryWorld, BoxingGym, SciGym, SciExplorer and NewtonBench organize scientific problems as sequential cycles of hypothesis formation, experiment selection, observation and inference. They evaluate whether agents can acquire evidence actively and recover scientific rules in initially unknown systems [14–18]. MADE extends this paradigm to budget-constrained closed-loop materials discovery [19], while SciDisco uses process-verifiable scientific-discovery environments for agentic reinforcement learning and assigns turn-level training signals to intermediate actions that produce verifiable evidence [22]. Together, these works establish interactive scientific environments as infrastructure for both agent evaluation and training.

2.4 Virtual chemistry and process environments

The closest prior work to ChemWorld lies in virtual chemistry and process environments. Summit and Olympus provide repeatable software benchmarks for reaction optimization and experiment planning, while PC-Gym extends this approach to chemical-process control with nonlinear dynamics, constraints and disturbances [10–12]. ChemGymRL constructs a modular virtual chemistry laboratory in which reaction, extraction, distillation and characterization are organized as interactive chemical benches. Stable action and observation interfaces support reinforcement-learning training and policy comparison [13].

ChemGymRL and ChemWorld both expose chemical processes through interactive software environments, but they operate at different levels of control. ChemGymRL makes virtual chemical benches configurable for agent training and evaluation; ChemWorld instead treats the composition and hidden laws of the chemical world itself as controlled experimental variables while preserving a common public agent interface. Researchers can therefore alter the underlying world while holding the task and interaction conditions fixed for strictly matched comparison. Transactional execution and evaluator-complete records further make these matched world changes exactly replayable and experimentally attributable. Table 1 summarizes this functional rather than performance-based distinction in terms of repetition, experimental intervention and record scope.




Figure 1. ChemWorld composes declared modules into executable worlds with transactional semantics, deterministic replay and controlled forks. **A**, Reusable process and instrument modules expose shared declarations. **B**, The compiler either produces a public contract W_{pub} with evaluator-owned private mechanisms or rejects an invalid composition before construction. **C**, Typed actions traverse preflight, runtime-precondition, candidate-execution and post-execution validation gates; non-commit branches preserve committed state and record declared attempt consequences. **D**, Replay reconstructs the bound world and submitted action trace, while controlled forks hold the public contract and actions fixed and change one private law.

Table 1. Complementary operating regimes for autonomous chemical experimentation. ChemWorld combines software-scale repetition with explicit world composition, private-law intervention and process-complete replay.

System class	Representative emphasis	Replication regime	Experimental intervention	Observable record
Physical SDL / chemistry robot	real-material execution and hardware integration	apparatus-, material- and time-bound physical repeats	protocol, material and hardware changes	sensor, automation and sample records
Embodied laboratory simulator	procedural and manipulative competence	resettable simulated episodes	scenes, objects, procedures or embodiment configurations	actions, observations and simulator state
Scientific-discovery environment	evidence gathering, hypothesis testing and law recovery	resettable interactive tasks	datasets, hypotheses, latent rules or oracle budgets	analyses, actions, observations and evidence
Optimization / virtual chemistry environment	objective optimization, process control and interactive chemistry	software-scale queries or control episodes	objectives, process models, bench configurations or operating conditions	objective histories, controller traces or task state
ChemWorld	controlled experiments over composable executable worlds	exact reset, matched repetition and version-bound replay without direct wet-laboratory consumable use	declared component composition plus single-private-law forks under an invariant public contract	typed actions, evaluator-complete state, public observations, failures, resources, termination, lineage and exact environment replay

3. Programmable chemical world construction

ChemWorld is designed not as another collection of fixed tasks, but as an experimental medium in which chemical worlds can be constructed and modified systematically. It first represents chemical processes as reusable components, compiles compatible declarations into executable worlds, and then executes every operation through one transactional runtime. This section defines that construction stack: the world representation, the compatibility compiler and the execution and replay semantics shared by all compiled worlds.

3.1 Composable chemical worlds

ChemWorld represents reaction, thermal, phase, separation, crystallization, distillation, continuous-flow, electrochemical and observation processes as reusable components. Each component declares its parameter domains, dependencies, owned state and public interfaces. Researchers define a chemical world by selecting components, specifying their topology and binding operating conditions and instruments, rather than implementing a separate environment for every task. Reaction and electrochemical components transform material state; thermal, phase, separation, crystallization, distillation and continuous-flow components supply process-specific transitions; and observation components attach synthetic instruments. All public operations are typed actions rather than unrestricted simulator mutations.

A complete world is represented as

$$\mathcal{W} = (W_{\text{pub}}, \theta), \quad T = (W_{\text{pub}}, S_{0,\text{pub}}, A, I, O, R, \tau, E).$$

Here W_{pub} contains the public component topology, public parameter domains and interfaces, whereas θ contains evaluator-owned constitutive laws, material properties, hidden parameters and private initialization. The public task contract T joins the public world description and initial-state projection with the allowed actions, instruments, observations, resources, termination rule and evaluation rule. The complete world identity therefore binds both W_{pub} and θ , while the agent interacts only through T .

We distinguish three identity levels so that task identity, world identity and randomness do not silently serve interchangeable roles:

$$\begin{aligned} \text{world-spec ID} &= \text{id}(W_{\text{pub}}, \theta), \\ \text{scenario ID} &= \text{id}(W_{\text{pub}}, \theta, \zeta_{\text{init}}, \zeta_{\text{dyn}}, \zeta_{\text{obs}}), \\ \text{task-world unit} &= (\text{task ID}, \text{scenario ID}). \end{aligned}$$

The qualification study uses the final level when testing overlap with the reference registry: a generated row overlaps only if both its task and scenario identities match a registered unit. This public/private separation also makes a second operation possible. A researcher can preserve the

agent-facing task contract while changing one registered element of θ , turning a private world law into a controlled experimental variable.

3.2 Compatibility compilation and experimental contracts

A world declaration specifies component selection and topology, public parameters, instrument configuration and the agent-facing task surface. ChemWorld does not execute this recipe directly. Its compatibility compiler first normalizes the declaration and then checks component dependencies, state ownership, unit agreement, supported parameter domains, resource feasibility, instrument availability, operation exposure and lifecycle closure.

Only declarations that satisfy all checks are compiled into executable worlds. An invalid declaration fails closed before environment construction and returns structured diagnostics, rather than leaving a partially constructed or semantically ambiguous environment. A successful compilation returns both the executable world and one public experimental contract that exposes the allowed typed operations, instruments, observations, resources, failure semantics, termination and evaluation, while evaluator-owned mechanisms and hidden state remain private.

Composability therefore does not mean arbitrary juxtaposition. A new world enters the runtime only when its component interfaces, resource conditions and lifecycle jointly satisfy the declared compatibility rules. Conversely, an additional process model or an empirically calibrated formulation can enter through the same interfaces without redesigning the public task contract, transaction layer or replay machinery. Compilation thus separates world authoring from both process-model implementation and agent integration.

3.3 Transactional execution and exact replay

Once a world has been compiled, every submitted action follows the same transactional sequence: preflight admission, runtime-precondition evaluation, candidate execution, post-execution validation and either commit or rollback. A schema, compatibility and resource predicate $P(s_t, a_t, R_t)$ first determines whether an action may enter the runtime. An admitted action is then tested against its context-dependent runtime preconditions. If those preconditions pass, the bound mechanism θ , committed state s_t , resource ledger R_t , action a_t and recorded random variates ξ_t generate a candidate transition:

$$(\tilde{s}_{t+1}, \tilde{R}_{t+1}, \tilde{e}_{t+1}) = F_{\theta}(s_t, R_t, a_t, \xi_t).$$

Candidate state is not installed immediately. A runtime commit-gate predicate $C \in \{0, 1\}$ covers both a runtime-precondition rejection before candidate generation and post-execution checks of state integrity, solver status, runtime invariants and the observation path. For a generated candidate, the latter gate is written $C(\tilde{s}_{t+1}, \tilde{R}_{t+1}, \tilde{e}_{t+1})$. The transaction commits only when admission and all applicable runtime checks pass:

$$P = 1, C = 1 \implies (s_{t+1}, R_{t+1}, e_{t+1}^*) = (\tilde{s}_{t+1}, \tilde{R}_{t+1}, e_{t+1}^{\text{acc}}).$$

The two non-commit branches remain distinct in the record. If $P = 0$, the runtime emits a preflight-rejection event and receipt without runtime execution. If $P = 1$ but $C = 0$, it emits a runtime-rollback event and receipt; this branch can occur before candidate generation at a declared runtime precondition or after candidate generation at a post-execution check. For $b \in \{\text{pre}, \text{roll}\}$,

$$s_{t+1} = s_t, \quad R_{t+1} = G_b(R_t, a_t, e_{t+1}^b), \quad e_{t+1}^* = e_{t+1}^b.$$

The branch-specific ledger function installs only the protocol-declared attempt cost or penalty. Candidate physical, observation and uncommitted resource effects are discarded. The committed runtime state also binds the observation-RNG state ρ_t ; a non-commit branch restores ρ_t , preventing an unsuccessful attempt from changing future observation noise. Public and evaluator records are separate projections of the realized branch,

$$o_{t+1} = \pi_{\text{pub}}(s_{t+1}, e_{t+1}^*), \quad \hat{o}_{t+1} = \pi_{\text{eval}}(s_{t+1}, e_{t+1}^*).$$

Exact replay binds the normalized contract, runtime, mechanism and scoring identities, together with the seeds and intervention record. It reconstructs the compiled world and resubmits the full submitted action/transaction trace—including committed actions, preflight rejections and runtime rollbacks—and compares public observations, transaction outcomes, affected-ledger declarations, world events, rewards and terminal flags at zero numerical tolerance. Resource deltas and rollback receipts are reconciled separately. Replay therefore reconstructs a version-bound environment/action trajectory, not merely its endpoint or action list, and is distinct from experience replay used to train a reinforcement-learning policy.

4. Qualification of composed chemical worlds

Programmability is useful only if newly composed worlds preserve the same executable contract. We therefore qualified ChemWorld at four connected levels: construction coverage, complete-world execution, module and interface semantics, and failure, resource and replay behavior. The design tests a finite declared construction domain; it does not claim exhaustive coverage of chemical space or all higher-order process interactions.

4.1 Qualification design and construction coverage

The public capability map contains 15 registered reference tasks, 28 typed operation kinds and five synthetic instrument contracts. These tasks anchor interpretable examples but do not define the boundary of the executable world space. The reference qualification set con-

tains 64 task-world units and 1,786 boundary and categorical recipes. To test construction beyond these reference examples, an execution protocol fixed eight component patterns and generated 52 additional compositions before authoritative qualification.

The generated set separates two forms of expansion. Eighteen compositions use three topologies absent from the reference registry: phase-observation, phase-separation-observation and reaction-thermal-continuous-flow-observation. Eight reaction-thermal-distillation-observation compositions reuse a registered topology but have zero exact task-world identity overlap with the frozen registry. These are protocol-frozen non-reference compositions. The remaining 26 rows provide additional coverage within registered topologies. The first row of the eight-case non-reference block was fixed in advance as the agent-integration target, rather than selected after observing its outcome.

Coverage selection combined pairwise rows for discrete component and instrument interactions, seeded Latin hypercube sampling for authored continuous domains, and ordered workflow targets for critical process sequences. The generated suite attained all registered targets: 60/60 discrete levels, 180/180 compatible discrete pairs, 212/212 continuous strata and 84/84 ordered workflow interactions. These denominators define a finite qualification sample within declared domains. They are not evidence of semantic completeness over all higher-order chemistry; higher-order behavior is tested only where it appears explicitly in a workflow, module probe or interface path.


4.2 World, module and interface qualification

Each task-world unit had to compile, execute a complete workflow, close its lifecycle exactly once, reconcile declared and observed resources, and replay exactly. All 64/64 reference units passed, and the boundary and categorical set produced 1,786/1,786 complete executions. All 52/52 generated compositions also passed, including all 8/8 protocol-frozen non-reference reaction-distillation worlds. There were no missing receipts, failure classes or undeclared private-field-exposure findings. Compilation alone was never a pass condition.


Qualification also tested the construction boundary. Seven deliberately invalid declarations covered missing dependencies, conflicting state ownership, unit mismatches, invalid parameter domains, resource impossibility and lifecycle gaps. All 7/7 failed closed before environment construction with the registered diagnostic class. The valid-world census and invalid-world mutants therefore test both sides of the compiler boundary.

Complete-world success depends in turn on the meaning of component transitions. Thirty-two module probes exercise zero input, declared parameter boundaries, monotonic directions, conservation and model-specific invariants. Seven cross-module paths test whether material amount, unit, identity and state meaning survive transfer between components and, where applicable, also test charge, energy and phase balance and event propagation.


A. From reference tasks to generated world families



B. Topology novelty vs. world-identity novelty



C. What actually varies in generated worlds



D. Composition changes the experiment surface




Figure 2. Construction coverage and qualification design. **A**, The 52 generated compositions separate into 18 topology-new worlds, eight identity-new reaction-distillation worlds that reuse a registered topology, and 26 additional registered-topology coverage rows. **B**, Topology novelty and exact task-world identity novelty are independent coordinates relative to the 64 reference task-world units. **C**, Protocol-frozen rows vary discrete component patterns, authored continuous operating conditions and ordered workflows. **D**, Composition changes topology, operating conditions, workflow ordering and the public instrument surface within one common contract structure. Coverage defines a finite construction sample rather than the extent of the world-design space; qualification outcomes are reported in Sections 4.2–4.3 and Appendix C.

All 32/32 module probes and 7/7 interface paths passed.

These results establish internally coherent executable formulations within their declared model-card domains. Their numerical fixtures and directional oracles are internal qualification checks, not independent reference implementations or external physical validation. The interfaces identify where alternative or empirically calibrated models may be introduced while retaining the public task contract, transaction layer and replay machinery.

4.3 Failure semantics, resource accounting and replay qualification

The mechanisms defined in Section 3.3 must also hold under invalid actions and exhausted resources. The frozen campaign contained 192 negative probes: 64 invalid-schema/unknown-operation probes, 64 campaign-resource-exhaustion probes and 64 runtime-precondition probes. Every probe produced its registered outcome and preserved committed physical state. The evidence therefore qualifies 128 $P = 0$ admission rejections and 64 $P = 1, C = 0$ runtime-precondition rollbacks. Solver-diagnostic and candidate-observation fault paths are implemented as fail-closed semantics, but this campaign did not assign them separate qualification denominators.

The resource ledger independently tracks material, sample, instrument use, process time, operation count and ter-

minal assay. Failed attempts retain only their declared costs or penalties, and observation checks require public packets to contain only task-declared fields. Exact replay then reconstructs the bound compiled world and resubmits the complete typed-action sequence, including accepted actions, admission rejections and runtime rollbacks. It compares rewards, public observations, termination flags, transaction metadata, affected-ledger declarations, world events, state-delta summaries and state-integrity checks with zero numerical tolerance; case qualification separately reconciles ledger deltas and rollback receipts. All reported replays yielded zero numerical mismatch. Thus the qualified reproducible unit is the complete environment/action trajectory, including failure and resource consequences, rather than an endpoint or simplified action list.

Table 2. Reader-visible branch census for the 192 negative probes. Counts are inherited from the frozen qualification report; no post hoc probe reclassification was used.

Branch	n	Registered class and outcome
$P = 0$	64	schema / unknown operation; validation rejection before runtime execution
$P = 0$	64	campaign-resource exhaustion; rejection before candidate installation
$P = 1, C = 0$	64	runtime precondition failure; rollback preserves committed physical and observation-RNG state

5. Controlled experiments over chemical worlds

Qualification establishes that ChemWorld constructs and executes worlds consistently. We next ask what controlled experiments this medium supports. The first study tests process-complete lifecycles, including planned failure and recovery, across diverse workflows. The second makes world construction itself experimental by changing one private law under otherwise matched public conditions.

5.1 Process-complete lifecycles and failure recovery

Eight protocol-frozen use cases span reaction-to-crystallization, resource-limited equilibrium characterization, planned failure and recovery, continuous flow, electrochemistry, distillation, partition and a second crystallization world. Together they cover single-stage and multistage processing, constrained measurement and multiple separation modalities. Each case is an independent experimental unit whose submitted actions are audited within one complete lifecycle.

Across the eight cases, all 89 submitted actions have complete schema, transaction, state-integrity, event, resource and public-observation receipts. Eighty-eight actions committed and one protocol-frozen action rolled back. Every case completed one final assay, closed its lifecycle, reconciled resources and replayed exactly with zero numerical error. The same lifecycle contract therefore supports distinct chemical workflows without process-specific failure, termination or recording semantics.

The failure-recovery case places one deliberate invalid operation inside an otherwise complete experiment. Its first action passed schema, compatibility and campaign-resource admission, but a runtime-precondition check found that no separable phase had yet formed. The transaction consequently entered the recorded $P = 1, C = 0$ branch before candidate physical state was generated. It preserved committed physical state and observation-RNG state, created no ghost state, and reconciled the declared failed-attempt consequences. The next 18 actions continued from the last committed state and completed the recovery path, final assay, resource reconciliation and exact replay of all 19 submitted actions.

Failure is therefore an experimental event rather than an episode-level exception. Its attempt and resource consequences remain auditable, while rejected physical state is excluded from subsequent execution. A workflow can recover without erasing committed history or restarting the experimental unit.

5.2 Controlled single-law counterfactuals

Process-complete execution and controlled attribution require different designs. The lifecycle study asks whether diverse workflows share one execution semantics; the counterfactual study asks whether one private world law can change while all public experimental conditions remain fixed. Parent and child worlds are defined as

$$\begin{aligned}\mathcal{W}_p &= (W_{\text{pub}}, \theta_p), & \mathcal{W}_c &= (W_{\text{pub}}, \theta_c), \\ \theta_p &\neq \theta_c, & T_p &= T_c = T.\end{aligned}$$

The qualification contains six parent-child pairs: two intervention classes evaluated over three seeds. Every pair preserves nine versioned public-contract components—task, actions, instruments, observations, resources, failures, scoring, material catalogue and the contracted invariant/safety surface—as well as the fixed typed-action sequence and bound randomness. Parent and child consequently have distinct complete-world identities while presenting the same public experiment. The admissible change is restricted to exactly one protocol-frozen private constitutive or material law.

The partition intervention changes the hidden response from $K^{1.00}$ to $K^{1.75}$; the registered terminal organic-product amount and public `product_in_organic` assay both increase. The electrochemical intervention keeps public material labels fixed while reassigning hidden electrolyte-response profiles; the registered selective-product amount and public `ohmic_efficiency` both decrease. For each intervention, direction is checked separately by the frozen divergence oracle, while the magnitude oracle requires both the protocol-frozen absolute and relative thresholds.

Repeating both variants produced 24 deterministic traces. All six pairs passed lineage, exactly-one-private-target, public-contract-invariance, same-sequence-executability, expected-state-divergence, expected-observation-divergence and exact-replay gates. Within the declared executable model and intervention domain, the resulting trajectory differences are therefore attributable to the registered private-law change under fixed actions and noise identity.

In the electrochemical fork, the permutation reassigns hidden response profiles to unchanged public material labels. It is therefore a matched change in private material properties, not an identifier remapping or a change in the public catalogue.

6. Agent interaction with ChemWorld

The preceding experiments use deterministic execution to qualify the worlds themselves. We finally test whether a qualified world can be exposed to an autonomous agent through the same public contract while preserving an evaluator-complete record. The goal is interface integration, not a comparison of agent capability.

6.1 Public agent interface and evaluator-complete records

ChemWorld separates agent-facing information from evaluator-side evidence. The agent receives the public task card, typed operations, instruments, public observations, available resources and termination and final-assay interfaces. It cannot directly inspect hidden material properties, private constitutive-law parameters, private initialization or complete simulator state. The evaluator retains

Table 3. Reader-visible specification of the two controlled-fork classes. Public task, actions, instruments, observations, resources, failures, scoring, material catalogue and the contracted invariant/safety surface remain unchanged in every row. Thresholds were frozen before execution and require both the listed absolute and relative magnitudes plus the stated direction.

Fork class	Private target	Parent $\rightarrow$ child law	Registered state channel	Registered public channel
Partition constitutive law	phase-partition response	partition-base response $K^{1.00} \rightarrow K^{1.75}$	terminal organic-product amount P_{org} increases; $\Delta \geq 10^{-4}$ mol and relative difference ≥ 0.05	final-assay product_in_organic increases; $\Delta \geq 0.02$ and relative difference ≥ 0.02
Electrochemical material law	hidden electrolyte-profile effects	public profile labels stay fixed; hidden effect-row mapping $(0, 1, 2, 3) \rightarrow (2, 1, 0, 3)$	terminal selective-product amount Red decreases; $\Delta \geq 10^{-6}$ mol and relative difference ≥ 0.01	final-assay ohmic_efficiency decreases; $\Delta \geq 0.05$ and relative difference ≥ 0.05




Figure 3. Execution, intervention and agent access. **A**, Eight frozen execution cases span crystallization, resource-limited characterization, planned failure and recovery, continuous flow, electrochemistry, distillation and partition workflows under one shared lifecycle semantics. **B**, A runtime-precondition failure at step 1 remains inside the same experimental record; recovery continues from committed state through 18 subsequent commits and final assay. **C**, Controlled private-law forks hold the public contract, typed action sequence and bound randomness fixed while changing one private law. **D**, A separate non-reference world supports deterministic qualification and a provider-driven agent lifecycle through the same public contract.

the complete state transitions, transaction outcomes, failure and resource consequences and environment/action trajectory.

This information boundary permits evaluation without exposing the mechanism being evaluated. ChemWorld groups 19 registered process coordinates into terminal commitment, evidence acquisition, evidence-conditioned action, resource deployment and outcome trajectory.

They remain separate coordinates rather than a composite score or a set of uniformly higher-is-better metrics; their numerators, denominators, null rules and boundary rules are specified in the process-coordinate contract in Appendix D.1.

The resulting record can support subsequent comparisons of measurement strategy, resource allocation, response to invalid actions and stopping behavior. For ex-

ample, an agent may choose between additional pH or UV-visible evidence under a limited sample budget, or revise a typed action after a structured rollback without losing committed history. The deterministic cases in Section 5 qualify these interaction primitives, but comparative policy behavior is outside the claims of this study.

6.2 Independent-agent integration in a non-reference world

World qualification and agent execution were kept as independent experimental units so that agent success could not serve as evidence for world correctness. The selected protocol-frozen non-reference world combines reaction, thermal, distillation and observation components. A deterministic 12-action path first qualified its construction, lifecycle closure and exact replay. Only after world qualification was complete did an independent agent enter the same public instrument contract and complete a separate 15-action lifecycle (Fig. 3D).

The experimental interface supplied the public task card, typed tool schemas, resource contract and explicit termination and final-assay requirements. The agent received no private world fields and issued every experimental operation, including termination and final assay. In one uninterrupted experiment, it submitted 15 actions; all 15 committed and closed the lifecycle, with no rollback, right-censoring or undeclared private-field exposure.

The environment used 8,158.454 of 10,440 simulated process seconds, four of four instrument uses and 0.00085 of 0.001 L sample. The evaluator-complete record links each decision to its public observation, hidden simulator consequence, transaction result and resource debit. The entire 15-step submitted-action trace replayed with zero numerical mismatch. An independent agent experiment can therefore enter the same auditable execution and replay framework as the deterministic studies. This demonstrates compatibility with the public instrument contract; it is not an agent benchmark, a model comparison or a claim of general chemical intelligence.

7. Discussion and Conclusion

7.1 The chemical world as an experimental variable

ChemWorld’s central methodological contribution is not a larger collection of predefined tasks, but the ability to construct and control the chemical world itself as an experimental variable. Component composition and operating conditions specify what may vary; a unified public experimental contract specifies what must remain comparable; and transactional execution with evaluator-complete records preserves the state, resource and failure consequences of every interaction. Researchers can therefore alter process composition, continuous operating conditions or hidden chemical and material laws while keeping the agent-facing action and observation interface fixed, enabling strictly matched experiments across different worlds.

The present study first establishes the reliability of this experimental substrate. Tests of reference worlds, generated worlds, process modules, component interfaces and invalid operations show that compatible compositions retain common execution, resource and replay semantics within the declared component and compatibility domain. Process-complete lifecycles then show that the same contract supports distinct chemical workflows and recovery after failure. Controlled forks further show that one private law can be changed while the public experimental conditions, action sequence and bound randomness remain fixed, allowing the corresponding trajectory differences to be attributed to that intervention. Finally, an independent agent completes a full lifecycle in a non-reference world through the same public interface, without its behavior being used to qualify the underlying world.

ChemWorld therefore provides a software experimental substrate for controlled studies of world construction, world intervention and agent-world interaction, rather than simply a larger fixed benchmark suite.

7.2 Implications for experimental-intelligence research

Many agent benchmarks compress an experimental process into a success rate, reward or terminal property. Such outcomes indicate whether a task was completed, but reveal little about how the result was obtained. ChemWorld instead retains the full process from evidence acquisition and subsequent decisions through resource deployment, failure, recovery and the terminal experimental outcome, making experimental strategy itself available for study.

Under a limited resource budget, for example, researchers can compare when an agent chooses to collect another measurement, when it stops, and how it allocates sample and instrument capacity. After an invalid operation, they can examine whether new observations alter the agent’s subsequent strategy. Within a controlled world fork, they can further test whether an agent detects, adapts to or learns a changed hidden law. The 19 process coordinates defined in this work provide a common record for such analyses, but are intentionally not collapsed into a single score, and this study does not use them to rank agents.

Controlled forks are especially important for these questions. Parent and child worlds retain the same public task, operations, instruments, resources, action sequence and bound randomness while differing in one prespecified hidden law. Within the registered design and qualification criteria, the associated state and observation differences can therefore be attributed to that world intervention. Future work can build on this substrate to study agent adaptation, law discovery and scientific decision-making, but those claims require separately frozen agent policies and evaluation protocols and lie beyond the present qualification.

7.3 Scope, extensibility and physical validation

The conclusions of this study are limited to the declared component vocabulary, compatibility rules and authored model domains. Qualification establishes consistent executable semantics and internally coherent behavior for these software models within their stated scope; it does not establish that ChemWorld fully reproduces real chemical systems. The current synthetic instruments are controlled software observation models rather than digital twins calibrated to particular devices. The coverage design systematically samples prespecified parameter and composition spaces but does not exhaust chemical space or all higher-order process interactions. Module fixtures and directionality oracles primarily test consistency with the authored models rather than an independent reference implementation or empirical ground truth. Exact replay is likewise restricted to the bound software identities, world identity and environment-action trace; it does not imply policy re-execution, cross-platform numerical identity or cross-version archival replay.

These boundaries do not require ChemWorld to remain fixed at its present level of fidelity. Component interfaces separate experimental semantics from individual model implementations, so experimentally calibrated kinetic and thermodynamic laws, unit-operation models and instrument-response models can in principle enter the same world-construction, transaction and agent-interface framework. The present study does not, however, establish that an independently authored third-party module automatically inherits every system guarantee without integration work. Each new model must be qualified against the relevant interface and runtime semantics.

ChemWorld and physical self-driving laboratories are therefore complementary experimental regimes rather than substitutes. Software worlds support rapid repetition, strictly matched controls, targeted intervention and complete process records; physical laboratories provide real-material evidence and model calibration. A natural workflow is to use software experiments to identify conditions, mechanisms and agent behaviors that merit closer study, then return questions requiring real chemical evidence to the physical laboratory.

In summary, ChemWorld establishes a programmable, repeatable and auditable chemical experimental environment in which researchers can systematically alter the world while preserving a common agent-facing interface. This work qualifies that capability within the current component and model domain and demonstrates complete experimental lifecycles, single-law controlled counterfactuals and independent-agent integration. Higher-fidelity chemical models, together with agent adaptation, law learning and scientific discovery in changing worlds, are natural directions enabled by this foundation.

8. Data and Code Availability

ChemWorld code, configuration files, processed evidence, figure data and released trajectories are available un-

der the MIT License at github.com/sunyrain/ChemWorld. The repository contains the materials required to reproduce the reported figures and statistics and to replay the released simulator trajectories.

References

- [1] Daniil A. Boiko, Robert MacKnight, Ben Kline, and Gabe Gomes. Autonomous chemical research with large language models. *Nature*, 624:570–578, 2023. doi: 10.1038/s41586-023-06792-0.
- [2] Andres M. Bran, Sam Cox, Oliver Schilter, Carlo Baldassari, Andrew D. White, and Philippe Schwaller. Augmenting large language models with chemistry tools. *Nature Machine Intelligence*, 6:525–535, 2024. doi: 10.1038/s42256-024-00832-8.
- [3] Nathan J. Szymanski et al. An autonomous laboratory for the accelerated synthesis of inorganic materials. *Nature*, 624:86–91, 2023. doi: 10.1038/s41586-023-06734-w.
- [4] Tianyi Dai, Sriram Vijayakrishnan, Filip T. Szczypiński, et al. Autonomous mobile robots for exploratory synthetic chemistry. *Nature*, 635:890–897, 2024. doi: 10.1038/s41586-024-08173-7.
- [5] Kourosh Darvish, Marta Skreta, Yuchi Zhao, et al. OR-GANA: A robotic assistant for automated chemistry experimentation and characterization. *Matter*, 8(2), 2025. doi: 10.1016/j.matt.2024.10.015.
- [6] Tao Song, Man Luo, Xiaolong Zhang, et al. A multiagent-driven robotic AI chemist enabling autonomous chemical research on demand. *Journal of the American Chemical Society*, 147(15):12534–12545, 2025. doi: 10.1021/jacs.4c17738.
- [7] Gihan Panapitiya, Emily Saldanha, Heather Job, et al. AutoLabs: cognitive multi-agent systems with self-correction for autonomous chemical experimentation. *Scientific Reports*, 16:19554, 2026. doi: 10.1038/s41598-026-45593-z.
- [8] Simone Pilon, Elia Savino, Oliver M. Bayley, et al. A flexible and affordable self-driving laboratory for automated reaction optimization. *Nature Synthesis*, 2026. doi: 10.1038/s44160-026-01053-0.
- [9] Aikaterini Vriza, Michael H. Prince, Tao Zhou, Henry Chan, and Mathew J. Cherukara. Operating advanced scientific instruments with AI agents that learn on the job. *npj Computational Materials*, 12:160, 2026. doi: 10.1038/s41524-026-02005-0.
- [10] Kobi C. Felton, Jan G. Rittig, and Alexei A. Lapkin. Summit: Benchmarking machine learning methods for reaction optimisation. *Chemistry-Methods*, 1:116–122, 2021. doi: 10.1002/cmtd.202000051.
- [11] Florian Häse, Matteo Aldeghi, Riley J. Hickman, Loïc M. Roch, Melodie Christensen, Elena Liles, Jason E. Hein, and Alán Aspuru-Guzik. Olympus: a benchmarking framework for noisy optimization and experiment planning. *Machine Learning: Science and Technology*, 2: 035021, 2021. doi: 10.1088/2632-2153/abedc8.
- [12] Maximilian Bloor, José Torracca, Ilya Orson Sandoval, et al. PC-Gym: Benchmark environments for process control problems, 2024. Preprint, arXiv:2410.22093.
- [13] Chris Beeler, Sriram Ganapathi Subramanian, Kyle Sprague, et al. ChemGymRL: A customizable interactive framework for reinforcement learning for digital chemistry. *Digital Discovery*, 3:742–758, 2024. doi: 10.1039/D3DD00183K.
- [14] Peter Jansen, Marc-Alexandre Côté, Tushar Khot, Erin Bransom, Bhavana Dalvi Mishra, Bodhisattwa Prasad Majumder, Oyvind Tafjord, and Peter Clark. Discovery-World: A virtual environment for developing and evaluating automated scientific discovery agents. In *Advances in Neural Information Processing Systems*, volume 37, 2024. doi: 10.52202/079017-0324.
- [15] Kanishk Gandhi, Michael Y. Li, Lyle Goodyear, Agam Bhatia, Louise Li, Aditi Bhaskar, Mohammed Zaman, and Noah D. Goodman. BoxingGym: Benchmarking progress in automated experimental design and model discovery, 2025. Preprint, arXiv:2501.01540.
- [16] Haonan Duan, Stephen Zhewen Lu, Caitlin Fiona Harrigan, Nishkrit Desai, Jiarui Lu, Michał Koziarski, Leonardo Cotta, and Chris J. Maddison. Measuring scientific capabilities of language models with a systems biology dry lab, 2025. Preprint, arXiv:2507.02083.
- [17] Maximilian Nägele and Florian Marquardt. Agentic exploration of physics models. *Physical Review X*, 16:031002, 2026. doi: 10.1103/xnqc-q6nt.
- [18] Tianshi Zheng, Kelvin Kiu-Wai Tam, Newt Hue-Nam K. Nguyen, et al. NewtonBench: Benchmarking generalizable scientific law discovery in llm agents. In *International Conference on Learning Representations*, 2026.
- [19] Shreshth A. Malik, Tiarnan Doherty, Panagiotis Tigas, Muhammed Razzak, Stephen J. Roberts, Aron Walsh, and Yarin Gal. MADE: Benchmark environments for closed-loop materials discovery. In *International Conference on Machine Learning*, 2026.
- [20] Rui Li, Zixuan Hu, Wenxi Qu, et al. LabUtopia: High-fidelity simulation and hierarchical benchmark for scientific embodied agents. In *Advances in Neural Information Processing Systems, Datasets and Benchmarks Track*, 2025.
- [21] Yuhan Wu, Zhao Jin, Tao Li, et al. Labimus: A simulation and benchmark for humanoid dexterous manipulation in chemical laboratory, 2026. Preprint.
- [22] Yucheng Xu, Keyi Zhang, Yuyang Yu, Min Zhang, Shiyuan Meng, Pei Chu, and Zhongying Tu. Scaling scientific discovery environments for turn-level agentic RL, 2026. Preprint, arXiv:2607.28990.

Appendix A. Qualification and Experimental Protocols

A.1 Qualification and coverage protocol

The authoritative protocol was frozen before execution. It specifies component patterns, discrete axes and compatible pairs, continuous bounds, seeds, ordered workflows and pass/fail criteria. Composition qualification first checks dependencies, state ownership, unit agreement, parameter domains, resource feasibility, exposed operations, instrument availability and lifecycle closure. Invalid declarations must return structured diagnostics without constructing an environment.

Discrete axes use pairwise covering rows, and continuous axes use seeded Latin hypercube samples within authored bounds. Each pattern has one or two ordered workflow targets. For every qualification unit, the report records normalized construction input, compiler diagnostics, public contract, submitted actions, transaction status, state-integrity checks, events, resource preflight and outcome, public observations, termination and exact replay. Missing receipts, non-finite quantities, unexpected transaction outcomes, undeclared private-field exposure, denominator drift or replay mismatch fail the unit.

Process-module qualification assigns reaction, thermal, phase, separation, crystallization, distillation, continuous flow and electrochemistry four probe classes each: zero-input bounded runtime, valid low/high input, directionality and runtime invariants. Numerical fixtures carry explicit tolerances; declared conceptual or synthetic oracles are used where no independent numerical fixture is claimed. Observation modules are checked separately for instrument availability, sample accounting, bounded signals and the public/private boundary. Invalid compiler probes cover missing dependencies, conflicting state ownership, unit mismatch, invalid parameter domains, lifecycle holes and resource impossibility.

A.2 Process-time limits

Process-time limits are derived by component pattern:

$$t_{\max} = t_{\text{required}} + t_{\text{reserve}} + t_{\text{repeat}}.$$

Table 4. Protocol-frozen process-time limits.

Pattern	Limit (s)
Phase observation	0
Reaction-thermal observation	3,600
Phase separation	1,860
Reaction crystallization	11,100
Reaction distillation	10,440
Continuous flow	7,200
Electrochemistry	5,400
Reaction-phase separation	7,500

The required term sums the upper bounds of necessary timed stages, the reserve covers authored quench and transfer operations, and the repeat term follows explicit per-operation repeat limits. Preflight rejects an action if

either cumulative process time or a repeat limit would be exceeded.

A.3 Deterministic use-case protocol

The cases, seeds, submitted-action sequences and terminal requirements in Table 5 were fixed before execution. Every case requires explicit termination and final assay. The failure-recovery case additionally fixes a runtime-precondition failure at its first submitted action and requires continuation from the restored committed state.

Table 5. Protocol-frozen deterministic use cases. Submitted actions include termination and final assay.

Case	Public identity	Seed / actions	Planned failure
U01	reaction-to-crystallization	0 / 12	none
U02	composed-equilibrium-characterization-demo	0 / 5	none
U03/E01	composed-reaction-purification-demo	0 / 19	step-1 runtime roll-back
U06-flow	flow-reaction-optimization	0 / 8	none
U06-electro	electrochemical-conversion	0 / 11	none
U06-distillation	reaction-to-distillation	0 / 12	none
U06-partition	partition-discovery	0 / 10	none
U06-crystallization	reaction-to-crystallization	1 / 12	none

A.4 Controlled-fork acceptance criteria

For an aligned checkpoint value p in the parent and c in the child, the acceptance oracle records

$$\delta = c - p, \quad \Delta = |\delta|, \quad r = \frac{\Delta}{\max(|p|, |c|, s_0)},$$

where s_0 is the registered positive scale floor. A fork passes only if the registered direction, absolute threshold, relative threshold, public-contract invariance, single-target lineage, same-sequence executability and exact-replay criteria are all satisfied.

A.5 Public-boundary and exact-replay checks

Public-boundary checks scan agent-facing task cards, observations and histories for undeclared evaluator-owned fields, private identifiers and absolute private paths. Inferential information obtained through task-declared measurements is not counted as direct exposure.

Replay reconstructs the bound world from its normalized contract, runtime, mechanism, observation and scoring identities together with recorded seeds and interventions, then resubmits every typed action in recorded order. Field-level comparison covers rewards, public observations, termination and truncation flags, operation types, transaction status, rollback reason, affected resource-ledger fields, world events, state-delta summaries and state-integrity checks. The replay result is reconciled with resource ledgers and rollback receipts; exact replay requires zero numerical tolerance and no field mismatch.

Appendix B. World Registry and Component Library

B.1 Reference-task registry

Table 6. Complete reference-task registry. Seed counts define the scenario identities exercised for each task.

Reference task identity	Component topology	World seeds	Public operation / instrument summary
electrochemical-conversion	reaction + electrochemistry + observation	5	6 operations; pH, UV-visible, final assay
equilibrium-characterization	reaction + thermal + observation	5	9 operations; pH, UV-visible, final assay
flow-reaction-optimization	reaction + continuous flow + observation	5	7 operations; HPLC, GC, UV-visible, final assay
low-budget-characterization	reaction + thermal + observation	3	9 operations; HPLC, GC, UV-visible, final assay
partition-discovery	reaction + phase + separation + observation	5	9 operations; HPLC, GC, UV-visible, final assay
public-private-generalization	reaction + thermal + observation	5	9 operations; HPLC, GC, UV-visible, final assay
purity-yield-tradeoff	reaction + thermal + phase + separation + observation	5	18 operations; HPLC, GC, UV-visible, final assay
reaction-mechanism-explanation	reaction + thermal + observation	3	9 operations; HPLC, GC, UV-visible, final assay
reaction-optimization-standard	reaction + thermal + observation	5	9 operations; HPLC, GC, UV-visible, final assay
reaction-safety-constrained	reaction + thermal + observation	5	9 operations; HPLC, GC, UV-visible, final assay
reaction-to-assay	reaction + thermal + observation	1	9 operations; HPLC, GC, UV-visible, final assay
reaction-to-crystallization	reaction + thermal + crystallization + observation	5	12 operations; HPLC, final assay
reaction-to-distillation	reaction + thermal + distillation + observation	5	12 operations; HPLC, GC, UV-visible, final assay
reaction-to-purification	reaction + thermal + phase + separation + observation	5	18 operations; HPLC, GC, UV-visible, final assay
tool-agent-planning	reaction + thermal + phase + separation + observation	2	18 operations; HPLC, GC, UV-visible, final assay

B.2 Component-pattern library

Table 7. Representative component-pattern library. Reusable combinations expose a common operation and instrument surface across single-process and multistage worlds.

Component pattern	Principal state or process	Representative public operations	Representative instruments
Phase + observation	bounded phase/equilibrium state	add solvent, add reagent, measure, terminate	pH, UV-visible, final assay
Reaction + thermal + observation	batch reaction and temperature history	add, heat, quench, sample	HPLC, GC, final assay
Phase + separation + observation	phase formation and transfer	mix, settle, separate, wash, transfer	HPLC, final assay
Reaction + thermal + crystallization + observation	reaction followed by solid formation	heat, seed, cool, filter	HPLC, particle sizing, final assay
Reaction + thermal + distillation + observation	reaction, evaporation and fractionation	heat, quench, evaporate, distil, collect	HPLC, GC, final assay
Reaction + thermal + continuous flow + observation	flow, residence time and conversion	set flow, set temperature, run, sample	HPLC, GC, final assay
Reaction + electrochemistry + observation	potential/current-driven conversion	set potential/current, electrolyse, sample	voltammetry, HPLC, final assay
Reaction + thermal + phase + separation + observation	multistage reaction and purification	react, quench, separate, wash, concentrate, transfer	HPLC, GC, final assay

B.3 Component model cards and extension points

Table 8. Component model cards and extension points. Each module declares its runtime formulation, authored model domain, qualification oracle and extension interface for future alternative or empirically calibrated implementations.

Component	Runtime formulation	Principal authored domain	Qualification oracle	Intended use and extension path
Reaction	stoichiometric mass-action network with Arrhenius temperature dependence	authored reaction families and bounded batch temperature/time	exact amount fixtures, monotonic response, material closure and runtime invariants	reaction-law extension point for future named-reaction calibration
Thermal	dynamic batch heat-release and jacket-energy balance	bounded temperature, duration, vessel pressure and volume	temperature/energy finiteness, bounds, event propagation and ledger reconciliation	thermal-contract extension point for future equipment-specific coefficients
Phase	stability-gated, activity-corrected liquid-liquid equilibrium with TPD-style diagnostics	declared phase identities, volumes and composition ranges	phase/material balance, directional partition response and state identity	activity-model extension point for future compound-specific thermodynamics
Separation	settling, entrainment, wash and transfer coupled to the phase model	bounded mix/settle time, extractant/wash volume and transfer fraction	amount/unit conservation, transfer identity and expected directional response	separation-interface extension point for future hardware-scale transport
Crystallization	van't Hoff solubility with seed, nucleation/growth cohorts, impurity occlusion and CSD summaries	bounded seed mass, cooling temperature and cooling time	material closure, solubility-direction checks, CSD and runtime-invariant receipts	law extension point for future calibrated nucleation and growth models
Distillation	bubble-gated, duty-limited VLE/Fenske fractionation with material and energy ledgers	bounded temperature/time, reflux ratio, fraction count and collected fraction	mass/energy closure, fraction identity, recovery/purity directions and equipment limits	operation-contract extension point for future compound and column models
Continuous flow	geometry-resolved plug-flow reactor with residence time, distributed thermal boundary and pressure drop	bounded flow, residence time and temperature	conversion direction, mass closure, pressure/geometry and solver diagnostics	runtime extension point for future reactor-specific transport or control models
Electrochemistry	Nernst potential, Butler-Volmer kinetics, limiting current, Randles transient and Faraday accounting	bounded potential, current and electrolysis time	charge/material closure, signed work, selectivity and limiting-current checks	electrochemical-law extension point for future material- and cell-specific parameters
Observation	state-coupled synthetic pH, UV-visible, HPLC, GC and final-assay contracts	task-declared instruments, sample and use budgets	instrument availability, sample consumption, finite/bounded signal and non-omniscience checks	instrument-schema extension point for future empirical response models

Appendix C. Coverage and Qualification Results

This appendix reports the complete frozen construction-coverage and qualification census referenced in Section 4.

C.1 Topology and identity decomposition

Table 9. Topology and identity decomposition of the generated block. Topology novelty compares exact component sets with the 15-task reference registry; task-world novelty uses exact registered identities.

Generated group	Cases	Topology relation	Exact task-world relation
phase-observation	6	absent from reference registry	zero overlap implied by component-set difference
phase-separation-observation	6	absent from reference registry	zero overlap implied by component-set difference
reaction-thermal-continuous-flow-observation	6	absent from reference registry	zero overlap implied by component-set difference
reaction-thermal-distillation-observation	8	registered topology	zero exact overlap in the protocol-frozen non-reference block
four remaining generated patterns	26	registered topologies	used for reference-topology coverage; no separate non-reference identity claim

C.2 Frozen coverage design

Table 10. Protocol-frozen coverage design. Bounds are inclusive authored domains; “none” denotes a purely discrete design.

Pattern	Seed	Continuous axes and bounds	Workflows	Cases
phase-observation	101	none	1	6
reaction-thermal-observation	102	heat 350–390 K; duration 600–1,800 s	2	6
phase-separation-observation	103	phase 0.010–0.020 L; extractant 0.010–0.025 L; mix 60–300 s; settle 120–600 s	2	6
reaction-thermal-crystallization-observation	104	reaction 350–390 K, 600–1,800 s; seed 0.002–0.010 g; cooling 275–305 K, 900–3,600 s	2	6
reaction-thermal-distillation-observation	105	reaction 350–390 K, 600–1,800 s; evaporation 325–345 K, 300–900 s; distillation 350–390 K, 900–2,400 s; reflux 1.0–3.0; transfer 0.65–0.95	2	8
reaction-thermal-continuous-flow-observation	106	flow 0.5–5.0 mL min ^{−1} ; residence 60–600 s; temperature 330–390 K	2	6
reaction-electrochemistry-observation	107	potential 0.5–1.8 V; current 25–150 mA; electrolysis 300–1,800 s	2	7
reaction-thermal-phase-separation-observation	108	reaction 350–390 K, 600–1,800 s; phase/extractant 0.010–0.020/0.010–0.025 L; mix 60–300 s; settle 120–600 s; wash 0.003–0.010 L; concentrate 300–900 s; transfer 0.65–0.95	2	7

C.3 Qualification census

Table 11. Qualification census. Every registered execution, probe, deterministic-use and controlled-fork denominator completed without missing receipts or unexpected outcomes.

Qualification unit	Passed	Denominator	Failure classes
Reference task-world units	64	64	0
Complete reference recipes	1,786	1,786	0
Coverage-generated compositions	52	52	0
Protocol-frozen non-reference reaction-distillation compositions	8	8	0
Invalid action probes	192	192	0 unexpected outcomes
Module probes	32	32	0
Cross-module interface paths	7	7	0
Invalid compile mutants	7	7	0 unexpected constructions
Deterministic use cases	8	8	0
Deterministic submitted actions	89	89	0 missing receipts
Controlled fork pairs	6	6	0
Controlled fork traces	24	24	0

Appendix D. Agent-Facing Evaluation Records

D.1 Process-coordinate dictionary

The 19 coordinates are campaign-level descriptions, not a composite score. N_p , N_c , N_a , N_d and N_m denote planned, closed, assayed, discarded and measured lifecycles, with $N_c = N_a + N_d$ because the frozen lifecycle contract closes only by assay or discard. Undefined conditional quantities remain null; they are never replaced by zero.

Table 12. The 19 process coordinates. Numerators, denominators, null rules and interpretation are fixed by the process-profile contract. None is interpreted as a globally better direction unless explicitly stated.

Coordinate	Definition	Null or boundary rule	Interpretation
<i>Terminal commitment</i>			
Closed lifecycle fraction	N_c/N_p	defined as 0 when $N_p > 0$ and none closes	completion gate; no preferred assay/discard mix
Assay commitment fraction	N_a/N_c	null when $N_c = 0$	fraction of closed lifecycles committed to final assay
Discard fraction	N_d/N_c	null when $N_c = 0$	fraction of closed lifecycles deliberately discarded
<i>Evidence acquisition</i>			
Measured lifecycle fraction	N_m/N_c	null when $N_c = 0$	prevalence of at least one committed non-final measurement
Instrument uses per closed lifecycle	committed non-final measurements / N_c	null when $N_c = 0$	measurement intensity
First-measurement timing	mean of preceding attempts / attempts through termination	null when $N_m = 0$	lower values mean earlier evidence acquisition, not higher quality
<i>Evidence-conditioned action</i>			
Post-measure continuation prevalence	lifecycles with a later committed physical operation / N_c	null when $N_c = 0$	prevalence of evidence followed by further investment among closed lifecycles
Post-measure operations per closed lifecycle	later committed physical operations / N_c	null when $N_c = 0$	deployment intensity after first evidence
Threshold-eligible fraction	lifecycles with the frozen diagnostic and finite signal / N_c	null when $N_c = 0$	denominator gate for the diagnostic decision rule
Evidence-to-terminal concordance	terminal choices matching the frozen signal rule / eligible lifecycles	null when no lifecycle is eligible	agreement between declared evidence rule and assay/discard decision
<i>Resource deployment</i>			
Attempted operations per closed lifecycle	charged operation attempts / N_c	null when $N_c = 0$	includes validation failures and transactional rollbacks
Committed operations per closed lifecycle	committed typed operations / N_c	null when $N_c = 0$	installed operation intensity
Cost per closed lifecycle	campaign cost-ledger debit / N_c	null when $N_c = 0$	includes declared failed-attempt charges
Risk debit per closed lifecycle	campaign risk-ledger debit / N_c	null when $N_c = 0$	resource-card-specific risk deployment
<i>Outcome trajectory</i>			
Global-best discovery fraction	$(j^* - 1)/(N_a - 1)$, $j^* \in \{1, \dots, N_a\}$	null for no assay; defined as 0 for one assay	lower values mean earlier discovery of the observed best
Online incumbent retention	later assays retaining at least 90% of the prior incumbent / $(N_a - 1)$	null when $N_a < 2$	stability after the first assay
Maximum incumbent drawdown	$\max(\text{prior incumbent} - \text{next assay}, 0)$	null when $N_a < 2$	largest observed loss from the running best
Loss-episode recovery rate	recovered loss episodes / observed loss episodes	null when no loss episode occurs; terminal unresolved losses count unrecovered	recovery after an observed loss
Terminal-to-best retention	terminal assayed score / observed best assayed score	null when no positive assay exists	closeness of the terminal assay to the observed best

D.2 Independent-agent protocol

The agent experiment consists of one complete lifecycle on the protocol-frozen non-reference reaction–distillation world. The agent interacts exclusively through the public instrument interface, is limited to at most 16 submitted actions, and must explicitly issue termination and final assay. The run passes only if the lifecycle closes correctly, all submitted actions commit, action and trajectory records agree, resource constraints are respected, no private fields are exposed, and the complete submitted-action trace replays exactly.