

ChemWorld: A Composable Executable Chemical-World Substrate and Programmable Virtual Instrument

Jiangjie Qiu¹, Yijun Li¹

¹Beijing Key Laboratory of Artificial Intelligence for Advanced Chemical Engineering Materials, State Key Laboratory of Chemical Engineering and Low-Carbon Technology, Department of Chemical Engineering, Tsinghua University, Beijing 100084, China

Abstract

Executable chemistry environments are often exposed as fixed task suites, while an instrument-like claim requires an explicit account of how worlds are constructed and how their interfaces behave under composition. We present ChemWorld as a composable executable chemical-world substrate and programmable virtual instrument. A v1 world is declared from a finite vocabulary of reusable physical and transactional components, their interfaces, parameters, resources, termination rules and evaluation surface. A task contract combines one such world with an initial state, operations, instruments, observations and a replayable trajectory. The 15 registered tasks are reference examples chosen to span this surface, not an exhaustive benchmark or a bound on the world space. Existing qualification provides typed operations and instruments, transactional failure handling, resource ledgers, exact environment replay and single-private-component forks with invariant public contracts. The central qualification programme tests coverage-guided compositions and frozen unseen compositions for compile-time compatibility, interface closure, physical and resource invariants, observation boundaries and replay. Complete agents are then used as instrument demonstrations: their records show what the apparatus can expose, not why an agent acted, how models rank, or whether a virtual world transfers to a laboratory. The resulting claim is deliberately bounded to the declared v1 component and compatibility domain: we validate reusable components and coverage-guided compositions, not every possible task.

1. Introduction

Executable chemistry environments are frequently described through a catalogue of tasks, but a catalogue alone does not specify what can be composed, which combinations are legal, or whether a new combination preserves the semantics of the underlying apparatus. The central problem for a reusable scientific environment is therefore architectural as well as evaluative: physical modules, operations, instruments, resources and termination must compose without silently changing units, state identity, failure behaviour or replay.

ChemWorld addresses this problem by treating a chemical world as an explicit, executable object rather than as an opaque task label. Its v1 vocabulary contains reusable reaction, thermal, phase, separation, crystallization, distillation, continuous-flow, electrochemical and observation components. A world is a compatible selection of these components, parameters and private laws. A task contract is then $T = (W, S_0, A, I, O, R, \tau, E)$: the world, initial state, operations, instruments, observations, resources, termination rule and evaluation surface. A concrete scenario instantiates that contract; a trajectory is the operation-observation sequence produced by an agent; and a world fork is a separate controlled intervention that changes one private component for attribution. Keeping these levels distinct prevents a fixed task list from being mistaken for the space of worlds or trajectories.

Existing evaluation regimes expose different parts of this problem. Prediction and digital optimization benchmarks enable controlled comparison but often represent an exper-

iment as a value-returning query [1, 2]. Self-driving laboratories and instrument-operating agents establish whether workflows can be executed in physical systems and automated reliably [3–6]. Those systems provide indispensable physical validity, but physical apparatuses are costly to replicate under matched identity. A complementary virtual instrument can make world construction, authority, resources, failure semantics, observations and replay explicit while retaining a clear boundary against laboratory transfer.

ChemWorld provides that substrate and apparatus through executable chemical and chemical-engineering worlds. Its organizing choice is that **the world is the reusable instrument substrate and the complete agent system is one possible instrument user**. Within a stateful, partially observable world, an agent chooses typed state-changing operations and measurements under explicit resource and termination rules. Accepted transitions, failures, instrument responses and ledger events are content-bound, so a trajectory and its resource history can be replayed exactly without claiming reproduction of model tokens or of a physical material batch.

This first paper reports the world substrate and its instrument contract. It asks whether declared components can be assembled through a public compatibility domain, whether coverage-guided and frozen unseen compositions preserve the declared runtime semantics, and whether a complete agent can use a newly generated world without changing the core runtime. Agent runs are capability

demonstrations rather than a representative sample of agent behaviour. Explaining why a system produced a trajectory, attributing behaviour to an internal model or scaffold mechanism, and measuring adaptation under changed laws require a separate explanatory study.

Programmability turns this environment from a fixed task suite into a controlled instrument. Existing world-fork evidence shows that one registered private component can be changed while the public action, observation, instrument, resource, failure and scoring contracts remain invariant, with exact replay of both sides. A fork is an attribution control, not a substitute for general multi-component composition. The new qualification programme therefore separates (i) the construction and compatibility surface, (ii) coverage-guided combinations, (iii) frozen combinations not present in the reference tasks, and (iv) single-component forks used for controlled causal contrast.

The paper is consequently organized around five contributions:

1. a public v1 vocabulary and task-contract model for composing executable chemical worlds from reusable physical and transactional components;
2. a unified compatibility and construction surface that exposes operations, instruments, resources, termination and evaluation without exposing private world state;
3. coverage-guided qualification of reference and unseen compositions, including interface, transaction, resource, observation-boundary and exact-replay checks;
4. controlled single-private-component forks that preserve the public contract and supply a bounded programmability control; and
5. agent demonstrations showing how a complete system can use the same instrument contract in a newly generated world, without turning those demonstrations into a model ranking.

The scope is deliberately bounded. ChemWorld does not replace a self-driving laboratory, validate transfer to physical chemistry, establish arbitrary multi-component authoring, rank agent systems on a universal scale, or demonstrate learning under changed world laws. The qualification target is the declared v1 component vocabulary and compatibility domain; coverage-guided evidence is not an exhaustive proof over all possible tasks. The 15 reference tasks demonstrate structural breadth and usage patterns, not a benchmark cardinality claim. Physical-bridge and explanatory studies remain separate work.

2. Relation to existing systems

2.1 Physical autonomous laboratories and chemistry agents

Chemistry agents and self-driving laboratories establish that machine-guided workflows can act on real materials. Coscientist connects language-model planning, documentation, code, liquid handling, and cloud-laboratory execution, while ChemCrow combines a language model with a broad

chemistry-tool suite and robotic synthesis [7, 8]. A-Lab and autonomous mobile-robot systems demonstrate closed-loop synthesis and characterization in physical laboratories [3, 4]. ORGANA and ChemAgents extend this line toward visual feedback, long workflows, multi-agent orchestration, and execution across chemistry tasks or laboratory settings [5, 9]. Peer-reviewed 2026 systems emphasize hardware-ready protocol generation, literature-to-robot translation, digital-twin checking, affordable modular automation, and teachable or adaptive instrument operation [6, 10–14].

These systems provide physical validity, perception, motion, safety, hardware integration, and deployment evidence that ChemWorld does not. Their laboratory scale and replication limits follow from the reality of the experiments rather than from a defect in their design. ChemWorld addresses a complementary measurement problem: it uses virtual chemical worlds to repeat a matched simulator-world identity, intervene on information or a preregistered private world component, and retain every operation, failure, resource event, and terminal decision for exact environment replay. It should therefore be read as a controlled behavioral apparatus that can inform later physical studies, not as a replacement for a self-driving laboratory or as evidence of virtual-to-real transfer. It does not replace a robotic laboratory; it is a controlled measurement apparatus for repeatable studies inside executable worlds.

2.2 Optimization suites and executable scientific worlds

Reaction-optimization and experiment-planning suites such as Summit and Olympus offer controlled, scalable comparisons over objective functions, and the PC-Gym preprint provides nonlinear process-control environments with disturbances and constraints [1, 2, 15]. ChemGymRL already establishes a fine-grained, operable virtual chemistry laboratory for reinforcement learning [16]. Peer-reviewed closed-loop materials frameworks further couple candidate generation, budgeted oracle feedback, constraints, memory, and multi-objective search [17, 18]. These systems answer important optimization, control, and discovery questions; ChemWorld does not claim that a chemistry simulator, a closed loop, a resource budget, or interactive chemical operations are new by themselves.

Interactive discovery environments broaden evaluation from optimization to active hypothesis formation, experiment selection, explanation, and law recovery. Discovery-World evaluates long-horizon scientific discovery in a virtual environment; the BoxingGym and SciGym preprints study active experimental design and model inference; and peer-reviewed SciExplorer and NewtonBench evaluate exploration or generalization across initially unknown or counterfactual physical systems [19–23]. ChemWorld is narrower in law diversity and discovery scope. Its distinctive experimental unit is a chemistry-native lifecycle in which typed operations change sample state, measurements consume resources, invalid actions preserve explicit failure consequences, and the agent itself chooses assay or

discard. The first paper uses controlled forks to qualify the apparatus; it does not demonstrate general rule learning or adaptation under changed laws, which remains a separate explanatory study.

2.3 Measuring agents as experimental subjects

Recent research also treats the agent and its environment as objects of measurement. A 2026 process-level preprint shows that successful scientific outputs need not coincide with scientifically grounded reasoning, and a peer-reviewed behavioral-science review calls for systematic observations and interventions on situated agents [24, 25]. An environment-engineering preprint shows that permissions, artifacts, budgets, and interaction structure can materially shape agent performance [26]. A 2026 robotic-chemistry stress-test preprint directly measures physical workflow executability and feedback-driven replanning over many workstations [27]. These studies preclude a priority claim for measuring scientific agency, studying process rather than outcome, or engineering an agent environment.

ChemWorld contributes a domain-specific intersection rather than a general behavioral science. The complete agent system is treated as the experimental subject; a stateful chemical runtime supplies controlled interventions and observable consequences. The registered readouts separate evidence acquisition, continued investment, terminal commitment, resource deployment, outcome, and trajectory dynamics. Known deterministic policies serve as a positive control before complete-system profiles are interpreted, and fresh sessions distinguish exactly replayable environment history from a new model decision trajectory. This supports bounded, auditable claims about behavior in virtual chemical worlds. It does not identify mental states, isolate a model-only causal effect, or establish a universal scalar ranking.

2.4 Position and boundary

The adjacent literatures therefore supply complementary strengths: physical laboratories establish execution and deployment; optimization and process-control suites establish scalable algorithmic comparison; interactive worlds test discovery and law recovery; and process-level evaluations establish that scientific behavior cannot be inferred from success alone. ChemWorld occupies their controlled overlap. It uses executable chemistry as a measurement apparatus for asking how evidence, prior information, resources, state-changing actions, and terminal choices shape an experimenting system’s trajectory. The present evidence covers a bounded virtual apparatus, two formally exercised task families in compiled controls, complete-system profiles in one primitive-control task, and two deliberately selected fresh-session worlds. It includes no visual manipulation, real instrument, wet-laboratory, or sim-to-real validation.

3. Constructing executable worlds

3.1 Object layers and public instrument contract

ChemWorld represents an experiment as a stateful sequence of typed operations and measurements inside a declared world. The world substrate owns physical state, transitions, constitutive laws and observation generation; the task contract owns the public goal, operation and instrument permissions, resources, termination and evaluation. Operations can change state; measurements consume resources and expose bounded synthetic signals; termination closes a lifecycle only through an explicit final assay or discard. The apparatus records transaction outcomes, resource events and evaluator inputs while keeping evaluator-only world identity and hidden state outside the agent view (Fig. 1A–B).

The public object layers are therefore distinct: a component is reusable physical or transactional functionality; a world is a compatible component selection with parameters and private laws; a task contract attaches the public operating surface; a scenario instantiates that contract; a trajectory records committed operation–observation events; and a world fork is a controlled single-component intervention. This separation makes a task list a reference map rather than a definition of the world space.

3.2 Public construction surface

The registered surface contains 15 live task contracts, 28 typed operation kinds and five public instrument contracts. Qualification executed 415 complete-experiment boundary recipes and resolved 62 ordered task-by-metric bindings, containing 43 unique endpoint metrics, to executable evaluators. These are distinct counting units: the 415 executions are qualification recipes, not tasks, agent trials, independent samples or physical experiments. The campaign-only explicit-discard decision is also outside the 28-member operation registry.

Together, these contracts allow the backend to instantiate a broader family of selected physical-chemistry worlds than the formal studies below exercise. The smaller formal set is intentional: it qualifies and illustrates the instrument’s controls and readouts, rather than sampling the full backend or estimating how frequently an agent behavior occurs across supported worlds.

The public construction surface is summarized in the capability map. It exposes a finite v1 vocabulary, typed operations, five measurement contracts, continuous and categorical parameter axes, resource and lifecycle rules, and explicit compatibility dependencies. The 15 registered tasks are reference points selected to span these axes. They are not the size of the composition space, and the existing reference-task qualification cannot replace coverage-guided generated combinations or frozen unseen combinations.

Before launching the instrument-use cases, we amended two public authoring examples so that their task contracts and deterministic reference paths are executable rather than merely compilable. The resource-limited `phase + observation` example uses the supported `balanced ob-`

jective and a five-action path that prepares a measurable sample, performs pH measurement, terminates and commits a final assay. The multi-stage **reaction + thermal + phase + separation + observation** example also uses **balanced**; its frozen 19-action path first submits an intentionally premature phase-separation action, which must roll back without changing physical state, and then follows an 18-action legal reaction–measurement–purification–termination recovery path. These are construction and lifecycle specifications, not agent-performance or physical-laboratory results.

All 28 registered operations committed in at least one valid context. In paired invalid probes, the pre-action simulator-state projection was preserved. Only a committed transaction installs a candidate state transition; validation failures, rollbacks and resource rejections preserve the pre-action simulator state while retaining the appropriate attempted-action or process accounting. The five instrument contracts likewise matched their declared cost, sample consumption and terminal preconditions. These checks qualify executable semantics, not laboratory instruments, real material custody or physical safety.

Exact replay reconstructs environment transitions, public observations and resource changes from an immutable trajectory. It does not reproduce a physical batch or a language model’s token sequence. The evidence layers below therefore retain their own analysis units rather than counting operations, replays or figure marks as independent samples. Composition results are counted by world/combination; fork results by parent–child pair; agent demonstrations by complete lifecycle; and process diagnostics by their declared world or trajectory replicate. These denominators remain separate throughout the paper.

The certificate is deliberately narrow. It does not establish untested multi-component recombination, a general world-authoring language, agent adaptation or law learning, model ranking, or transfer to a physical laboratory.

4. Coverage-guided composition and reference coverage

The 15 registered tasks are used as a reference basis rather than as a benchmark cardinality. Their contracts span reaction, phase, separation, crystallization, distillation, continuous-flow, electrochemical and equilibrium-characterization paths, with different operation, instrument, resource, termination and evaluation surfaces. This reference basis is the comparison frame for the composition qualification: it identifies which component and interface axes are already represented and which interactions must be generated outside the reference set.

The composition qualification is reported at the world/combination level. Discrete axes are covered with covering-array logic, continuous axes with space-filling samples, and ordered operation paths with explicit interaction targets. The resulting report must separate valid compilations, valid executions, replay closure and every rejection class. A frozen unseen composition is one generated after

the constructor and compatibility rules are frozen and not present in the 15 reference tasks; it follows the same construction and runtime path, without a core-runtime patch. These boundaries prevent a generated sample from being misread as an exhaustive task enumeration.

5. Interface, physical and transactional qualification

The qualification surface checks more than whether an action name is reachable. Every composition must close material identity, units, non-negativity, applicable charge and energy ledgers, phase/state transitions, event propagation and public observation rules. Module checks cover zero and boundary inputs, known directional behaviour, conservation and declared invariants. Cross-module checks verify that an upstream output retains its quantity, unit, identity and state meaning when consumed downstream.

Transactional checks require atomic commit, rollback without ghost state, exact material/time/ sample accounting, and rejection of post-terminal actions. Observation checks require that public packets contain only task-declared fields and that an already committed trajectory reconstructs the same world transition, public record and resource consequence. These checks qualify a virtual instrument within its declared model-card domain; they do not establish physical-laboratory accuracy.

6. Controlled single-component forks

The frozen programmability qualification changed one named private component at a time: either the private constitutive laws or private material laws. Each of six parent–child pairs—two intervention classes across three seeds—preserved all nine declared public-contract components while executing the same fixed midpoint action sequence (Fig. 1C–D). Repeating both variants produced $6 \text{ pairs} \times 2 \text{ variants} \times 2 \text{ executions} = 24$ traces with zero model-provider calls. All pairs passed lineage, single-target, public-invariance, same-sequence executability, preregistered state and observation divergence, exact replay and zero-provider gates. A fork is an attribution control, not evidence for arbitrary multi-component recombination.


7. Agent use of the instrument

7.1 Deterministic controls qualify the recording surface


Before interpreting complete agent systems, we asked whether the apparatus could recover behavior fixed in advance. The frozen 19-metric experimental-process profile keeps terminal commitment, evidence acquisition, evidence-conditioned action, resource deployment and outcome-trajectory organization separate, with endpoint context reported beside rather than inside those axes. The campaign profile is the primary unit; no composite intelligence score is formed.

We crossed five simulated electrochemical worlds, two information arms and three deterministic known policies.

a The agent is the subject; the world is the apparatus



b Identity, authority and replay controls stay explicit



c A fork changes one private component, not the interface



d All six fork pairs pass every frozen gate




Figure 1. ChemWorld apparatus and controlled world forks. **A**, An agent selects a typed action; the executable world returns only the public observation while recording the identity-bound transition. **B**, Hidden simulator-world and material identity, action authority, evidence access, resource accounting and replay are separate protocol controls. **C**, The frozen qualification changes one named private component while preserving nine public-contract components. **D**, Six parent-child pairs and 24 provider-free traces passed the registered programmability gates. These probes establish the tested executable-world interventions, not agent performance, arbitrary world recombination, rule adaptation or physical transfer.

The 30 primary campaigns contained 180/180 closed lifecycles and made zero provider calls (Fig. 2). The assay-all policy assayed every vessel; the immediate-discard policy discarded immediately after starting; and the measure-then-threshold policy acquired one UV-visible conversion signal, discarded values below an independently qualified threshold, and otherwise performed one additional electrolysis before termination and assay. The threshold policy produced 28 assays and 32 discards among its 60 primary lifecycles, so both branches were exercised.

The campaign-equal summaries recovered all six pre-registered orderings. Mean assay fractions were 1.000, 0.467 and 0.000 for assay-all, measure-then-threshold and immediate-discard, with the reverse ordering for discard. Only the threshold policy measured, used a non-final instrument and performed a further committed process action after measurement. Attempted operations per closed lifecycle ordered as threshold (6.933) > assay-all (6.000)

> immediate-discard (2.000). Conditional quantities remained null when their denominators did not exist rather than being coerced to zero, and all campaign ledgers reconciled to their committed paths.

All 12 frozen gates passed, including profile reconstruction, resource-ledger replay, conditional nulls, signatures, orderings, matched-arm invariance, exact replay and the zero-provider gate. A same-identity deterministic retest reproduced the controller, trajectory, profile and configuration for all 30 campaign pairs. Those additional 30 campaigns and 180 lifecycles are reliability evidence only; they do not double the primary sample. Because the policies never read the material dossier, matched-arm equality is an interface and identity check, not a causal information null.

The positive control establishes that the event ledger, metric definitions and aggregation pipeline recover prespecified differences among these constructed policies. Because




Figure 2. Known policies qualify the experimental-process profile. **A**, Three frozen policies specify distinct evidence and terminal-decision structures. **B**, Campaign-equal terminal profiles recover assay-all, threshold-gated and immediate-discard signatures. **C**, Evidence acquisition, continued investment and resource use remain separate readouts; registered undefined quantities remain null. **D**, All 30 same-identity deterministic retests match their primary campaigns. The primary evidence comprises 30 campaigns and 180 closed lifecycles; the additional 30 campaigns and 180 lifecycles are excluded reliability retests. This is a bounded positive control in the simulated apparatus, not an endpoint, agent or model ranking.

the policies were designed around the measured signatures, this is not independent evidence that the 19 metrics exhaust or externally validate a broader construct of agency. It does not establish chemical intelligence, stochastic-system reliability, endpoint superiority or transfer to a real laboratory. Appendix C provides the complete metric dictionary and registered null rules.

7.2 Complete agents demonstrate lifecycle use

We next placed two **distinct complete agent systems** in the same ten matched simulator-world-by-information cells. Model, scaffold, decision transport, evidence interface, retry behavior and execution provenance are all part of each system; the matching holds world, material, observation, scoring, workflow and campaign-resource contracts fixed. This is a complete-system portability and behavior-profile comparison, not an isolated model-backend intervention.

The environment contract was matched, but the two decision surfaces were not interface-symmetric. A final assay required prior termination, sample and instrument cost, whereas explicit discard was a direct campaign-closing action that returned no endpoint score and no consumed resources. The Codex-facing task profile explicitly recommended completing a chosen experiment through termination and final assay; the compact direct-LLM prompt omitted that recommended-strategy block. Both systems exposed current valid actions and disabled automatic action repair and closeout. The terminal counts below therefore show what the instrument records for the two deployed systems. They do not estimate an unprompted model preference for assay or discard, and they cannot establish that the all-assay pattern would persist under a different scaffold.

Both systems closed all 60 assigned batch lifecycles. The observed census was **120 closed lifecycles: 84 fi-**

nal assays and 36 explicit discards (Fig. 3A–B). The Codex-based system committed all 60 batches to final assay. The DeepSeek-based system committed 24 to assay and 36 to discard. Similar non-final instrument use—164 versus 163 events—coexisted with 815 versus 889 attempted primitive operations. These are repeated-event accounting totals within ten system cells, not independent observations. Equal closure therefore did not imply equal terminal commitment, evidence use or experimental policy.

Within the DeepSeek-based system, the five nominal-information cells contained 16 assays and 14 discards, whereas the five opaque-code cells contained 8 assays and 22 discards. The nominal arm also contained 67 more attempted operations and 17 more non-final instrument uses. These five-world paired descriptions do not identify a population information effect or explain the cross-system difference causally.

The 36 discards motivated a preregistered evaluator-only counterfactual question: what score would the exact pre-discard state receive if the original discard were replaced by the evaluator’s final assay? The contract froze all identities, thresholds, estimands, denominators and missingness rules before formal execution. Reconstructability preflight covered 36/36 checkpoints, but it executed no shadow assay and therefore did not exercise the terminal-replacement integration. The formal run failed its entry gate (Fig. 3C–D). All 36 receipts were retained: 6 resolved and 30 remained unresolved, including 11 prefix-identity mismatches, 18 resource-state mismatches and one final-assay precondition failure. Original trajectories and ledgers were unchanged, provider calls remained zero, and no result was repaired, rerun or replaced.

Terminal quality is consequently unresolved. All latent-dependent point estimates, the 60-lifecycle point-classification table and arm point contrasts are withheld. The six resolved receipts appear only in registered observed-only diagnostics and sharp finite-population bounds, never as a complete-case result. The mean latent-score bound was $[0.0000859, 0.833419]$ and the mean discard-minus-observed-best bound was $[-0.276951, 0.556382]$. At the primary threshold, the false-discard fraction remained bounded by $[0/36, 30/36]$. These support bounds are not confidence intervals and do not show whether discard was good, poor, efficient or resource-saving.

This failure qualifies the fail-closed reporting path but not the counterfactual terminal- evaluation module. That module remains unqualified in this study. Any future latent- quality claim requires a repaired implementation and a new independently registered discard cohort; the frozen 6/36 result will remain as the historical execution record.

The observed terminal census remains valid despite the failed counterfactual gate: lifecycle closure and terminal commitment are distinct measured coordinates. What cannot be inferred is the unobserved quality of the discarded states or the rationality of either complete system.

8. Process records beyond endpoints

7.3.1 8.1 Compiled controls separate outcome, prediction, calibration and claims

Compiled control supplies a bounded complete-experiment interface. It is not the target autonomy setting; it calibrates whether task outcome and epistemic diagnostics can be resolved separately across matched tasks, information conditions and classical search policies.

The complete vectors of ten paired-world differences are the primary results. Their mean nominal-minus-opaque score difference was 0.072 in electrochemical conversion (8/10 positive worlds) and 0.026 in reaction-to-crystallization (7/10 positive; Fig. 4A). The corresponding 97.5% world-bootstrap ranges, 0.007 to 0.155 and -0.013 to 0.063, are descriptive resampling-sensitivity summaries rather than confidence intervals or world-population coverage statements. The deliberately misindexed arm redirected the first material-sensitive action in 70% and 100% of the respective worlds. Misleading- action share subsequently fell from 0.54 to 0.24 in electrochemistry and from 0.86 to 0.50 in crystallization. Both tasks passed the behavior-change check, while correction and score restoration differed and neither passed the joint rule (Fig. 4B–D).

Outcome and epistemic diagnostics also produced different profiles. In the opaque arm, electrochemical conversion combined a 0.715 endpoint score with 0.744 held-out directional accuracy, a 0.186 Brier score and a 0.611 unsupported-claim rate. Reaction-to-crystallization yielded 0.535, 0.478, 0.298 and 0.714, respectively. None substitutes for another, and no unregistered composite is formed.

Complete world-level contrasts, exact sign summaries and leave-one-world-out ranges are retained in the sensitivity analysis. The result is capability decomposition inside the apparatus, not a language-model-versus-optimizer horse race.

7.3.2 8.2 Primitive control exposes complete experimental lifecycles

The terminal census is interpretable because the primitive-control interface records the full path to closure. Each vessel has a public workspace and typed tools, while its identity-bound trajectory and complete resource ledger remain external to the prompt. One descriptive seven-operation lifecycle places a UV-visible observation in public state before the system chooses termination and final assay (Fig. 5A). The observation can therefore condition the next action rather than appearing only after the campaign.

The immutable record distinguishes attempted actions, committed state changes, public evidence, resource events and explicit terminal commitment (Fig. 5B–D). A committed assay or discard closes a started vessel; a validation failure, rejected action or rollback can remain in the attempted-operation record without installing its candidate state transition. Evidence acquisition, continued




Figure 3. Lifecycle completion does not specify terminal policy. **A**, The 120 closed lifecycles partition into 84 final assays and 36 explicit discards: 60 assays for the Codex-based complete system and 24 assays plus 36 discards for the DeepSeek-based complete system. **B**, Terminal commitments by matched simulator world and information arm; system identities include model, scaffold, transport and run configuration. **C**, All 36 registered discard identities remain in the latent-terminal audit, with 6 resolved and 30 unresolved after the frozen entry gate failed. **D**, Registered censoring and finite-population bounds replace latent-dependent point estimates; the no-discard-opportunity cell remains structurally null. Shadow assays were evaluator-only counterfactual evaluations, were not agent choices or observations, and did not add original agent experiments.

investment, resource use, termination, assay and discard are consequently separate process coordinates.

The example is descriptive and is not part of the fresh-session estimand. Its role is to show how process evidence is recorded directly rather than inferred retrospectively from an endpoint.

7.3.3 8.3 Fresh trajectories reveal process structure omitted by endpoints

We deliberately selected simulator worlds 1 and 3 before replication because their development contrasts pointed in different directions. The protocol-frozen design crossed two worlds, five fresh trajectory replicates and two information arms, with six vessel opportunities per cell. Within each pair, hidden simulator-world, observation and resource identities matched; the provider exposed no controllable

sampling seed.

Eighteen of 20 cells completed. Two cells were right-censored after 50 and 56 accepted operations by provider-infrastructure failures, leaving four complete matched pairs in each selected world while retaining all ten planned pairs in the record (Fig. 6A). The authoritative matrix followed a launcher-level restart after a first-launch infrastructure incident; the restart rule was recorded before outcome inspection. Longer or more interaction-intensive trajectories may be more exposed to provider failure, so censoring cannot be assumed independent of process complexity. We therefore make no missing-at-random assumption, perform no imputation and keep the two incomplete pairs visible beside the complete-pair descriptions.

The primary endpoint diagnostic uses continuous pairwise contrasts. Across the eight complete pairs, nominal-minus-opaque best-of-campaign and raw terminal contrasts




Figure 4. Compiled controls separate outcome, prediction, calibration and claims. **A**, All paired nominal-minus-opaque endpoint differences across ten designed worlds per task; the intervals summarize resampling sensitivity of the finite set and are not population confidence intervals. **B**, Held-out prediction and calibration are displayed as separate raw metrics. **C**, Opaque-arm epistemic readouts retain registered missingness without imputation. **D**, Protocol-frozen manipulation, correction, performance-restoration and joint gates remain separate. Classical optimizers are calibration controls, not the target competition; the figure supports no scalar ranking or general population information effect.

were sign-discordant in 2/8 pairs, despite a descriptive Pearson correlation of +0.826 (Fig. 6B). In one complete pair from world 3, for example, the best-score contrast was -0.167 while the raw terminal contrast was $+0.240$. Even correlated endpoint summaries are therefore not interchangeable for an individual trajectory.

The process profile additionally separates discovery timing, online retention, drawdown, recovery and relative terminal retention (Fig. 6C–D). Under the frozen 75% classification, 6/8 selected world-by-lifecycle cells were mixed. This is threshold-sensitive supporting evidence, not the primary diagnostic: the mixed count ranges from two to eight across the complete threshold-by-zero-handling grid, whereas the continuous contrasts and both right-censored pairs remain visible without thresholding. Terminal-to-best ratio is a relative-retention readout and is not treated as algebraically independent of best score.

Fresh sessions thus expose both endpoint disagreement


within matched pairs and variation across full process profiles. They do not estimate population variability or isolate a provider sampling effect.

9. Discussion

ChemWorld is best understood as a composable world substrate with an instrument contract, not as a leaderboard of fixed tasks. The substrate makes reusable physical and transactional components executable; the contract makes their operations, instruments, resources, failures, observations, termination and replay explicit. An agent can then operate inside a world and leave an auditable process record, but the existence of that record is not a claim about why the agent acted or how it compares with another model.

The evidence should therefore be read as a staged qualification. First, the public object layers and construction rules define what a world, task, scenario, trajectory and

a One vessel exposes seven primitive operations




opaque condition · one simulated world · descriptive example

b Campaign receipts preserve units and denominators

closure	6 vessels · 6 closed · 6 final assays · 0 discards
actions	69 operation attempts · 17 non-final measurements
stocks	0.24 mol reagent · 0.48 L solvent
physical	2.763 cost · 39.0 h · 2.63 mL sample

trajectory-event alignment verified · resource receipt reconciled

c Identity, resources and replay stay external



The ledger is not prompt context; it is the auditable measurement spine

d Closure and failure accounting are explicit

closed lifecycles	60 / 60
final assays	60
invalid or rejected	0
right-censored	0
815 accepted operations · 164 non-final measurements repeated events, not independent sample units	

Figure 5. Primitive-control agents expose complete experimental lifecycles. **A**, One descriptive seven-operation lifecycle makes a UV-visible observation available before the next system decision and explicit final assay. **B**, The campaign resource receipt reports units and denominators outside the prompt. **C**, Identity, resource events and exact executable replay align the public process record with evaluator state. **D**, Failed, rejected and terminal actions retain their distinct transaction and closure semantics. Operations are repeated events within campaigns, not independent samples; replay concerns simulator state and records, not a physical batch or stochastic provider decision.

fork mean. Second, coverage-guided combinations and frozen unseen combinations test whether the declared interfaces remain closed under composition. Third, module-level and cross-module checks test bounded physical and transactional invariants. Existing single-component forks provide a separate attribution control by changing one private law while preserving the public contract. Agent runs come last as usage demonstrations of the same instrument surface.

9.1 What the world-and-instrument record establishes

The central record is not a single endpoint. It binds a declared world to an initial state, typed operations, instruments, observations, resources, termination and evaluation, then retains the committed trajectory and replay identity. This separation makes it possible to inspect evidence acquisition, failure and rollback, resource expen-

diture, lifecycle closure and terminal choice without silently collapsing them into a score. Existing process-profile and known-policy results remain useful positive controls for this logging surface, but they are instrument demonstrations rather than a universal construct of agency.

The 15 registered tasks have a deliberately narrower role in this story. They are reference examples selected to cover structural axes and usage patterns. They do not define the size of the world space, and their existing cross-world qualification cannot substitute for generated compositions or unseen-composition tests. A successful qualification therefore supports the declared v1 composition domain and its coverage targets, not every possible task or an unbounded authoring claim.

9.2 Limitations and scope

The world is virtual and intentionally bounded. Physical signals are state-coupled synthetic or reference-tested out-




Figure 6. Fresh trajectories reveal process structure omitted by endpoints. **A**, The frozen selected-world design contains eight complete matched pairs and two explicitly right-censored pairs. **B**, Best-of-campaign and raw terminal contrasts disagree in sign for 2/8 complete pairs; this is the primary endpoint diagnostic. **C**, Continuous contrasts separately display discovery, retention, drawdown, recovery and relative terminal retention. **D**, The 6/8 mixed classification is supporting and threshold-sensitive, ranging from two to eight across the frozen sensitivity grid. These deliberately selected worlds describe within-world process variation and are not pooled into a population-level model or information-effect claim.

puts within their module domains; resource receipts are simulator ledgers rather than laboratory custody, hazard, waste or monetary accounts. Exact replay reconstructs executable state transitions and public observations, not a physical batch, device or stochastic provider decision.

The qualification domain is the declared v1 component vocabulary and compatibility rules. Coverage-guided sampling is a principled way to test axes and interactions, but it is not an exhaustive proof over all combinations. The reference-task set is not a benchmark cardinality claim. A single-component fork is not evidence for arbitrary multi-component recombination, third-party authoring or agent adaptation to changed laws. The agent cases are capability demonstrations and cannot support a model ranking, causal provider claim or mechanistic explanation.

These boundaries also separate the first paper from later studies. Physical calibration, broader world families, explanatory interventions, adaptation under changed private

laws, and systematic comparisons across complete agent systems require their own protocols and evidence. They should not be inferred from the instrument qualification surface.

9.3 Complementarity and next steps

Once the v1 construction and qualification gates are closed, ChemWorld can support focused use cases such as multi-stage reaction-to-separation workflows, resource-limited characterization, failure and recovery, controlled world forks and agent use in generated unseen worlds. These cases test what the instrument exposes while keeping the scientific question, public contract, resource limits and process record explicit.

The next explanatory study can then use the same substrate to ask why a system chose a trajectory, how selected policies adapt to changed private laws, or which process coordinates survive calibration against physical

systems. Those questions are deliberately outside the first paper’s claim.

10. Methods

10.1 Registered apparatus and transaction qualification

We rebuilt the platform inventory from its active public definitions. A task was one distinct experimental contract, an operation kind was one typed action, and an instrument was one of the five public measurement interfaces. Explicit discard was counted separately as campaign control. Reuse of an endpoint definition across tasks still created a separate task–endpoint binding. Qualification required every public task to match the design matrix, every operation and instrument to be reachable, every task–endpoint binding to be executable and unique, and every task to have executable midpoint and boundary recipes.

For each of the 28 registered operation kinds, qualification executed a valid action through the runtime kernel and then submitted a paired invalid action from a fresh deterministic environment. A probe passed only when the valid action committed and the invalid action returned a validation failure or rollback without changing the hidden simulator-state projection. A constitution probe required atomic rollback of an invalid negative-volume candidate, and a hard resource-envelope probe exercised a resource rejection.

Campaign limits use a two-phase append-only ledger. Preflight derives and reserves the proposed resource delta; outcome recording applies committed-only material, vessel, instrument, assay and discard quantities while retaining operation attempts at preflight. The normalized action and its outcome share one event identity, and ledger state is reconstructed from ordered events and reconciled against the expected campaign state. A rejected or rolled-back attempt may therefore consume attempt budget without installing a stock, vessel, instrument or terminal debit.

Executable probes for HPLC, GC, UV–visible, pH and final assay checked declared cost, destructive sample-volume change and terminal preconditions. The first four instruments were permitted before termination; final assay required a terminated state. Instrument latencies are scheduling-contract fields and were not added to the process-state clock. All instrument maturity and calibration labels are interpreted only inside their synthetic/reference-tested model-card boundary.

10.2 Frozen world-fork protocol

The formal protocol fixed seeds 0, 1 and 2, a keyed-noise namespace, a public midpoint policy generated from a unit vector of 0.5, two intervention cases, their private target components, divergence oracles and an all-gates pass rule before execution. For each case and seed, a content-addressed parent and child were derived from the frozen component inventory. A pair was rejected unless exactly its declared private target changed and all nine public-contract components remained identical.

The same typed sequence ran on parent and child, and each execution was repeated from the same bound identity and noise contract. Exact replay, same-sequence executability, identity leakage, expected simulator-state and public-observation divergence, provider-call and lineage checks were evaluated for every pair. The scientific unit was one of the six parent–child pairs. The 24 traces are execution and replay accounting, not 24 independent experiments or agent trials. No target, seed, threshold, oracle, gate or display rule changed after formal outcomes.

10.3 Frozen known-policy profile qualification

In this study, an experimental-process profile is the observable organization of resource-constrained typed actions, active evidence acquisition, post-evidence action and lifecycle termination. The frozen profile contains 19 metrics across five operational axes. The profile is operational rather than a universal latent construct of agency. Mean and best assayed scores are separate endpoint-context fields and do not enter a composite. One primary observation is the campaign profile for a fixed world, arm and policy cell. Profiles were constructed within campaigns before ten equal-weight world- arm campaigns were aggregated for each policy; lifecycle rows and primitive operations were not pooled as independent samples. Appendix C lists all 19 definitions, denominators, ranges and null rules.

The schedule crossed five formal world seeds (0–4), two information arms and three policies, with six lifecycles per campaign. A primary lifecycle was a started vessel closed by one committed final assay or explicit discard. Only original executions had the primary role. Same-identity retests were excluded from the primary estimand, and provider calls had to remain zero. Within a world-policy pair, physics, probe order, keyed noise, policy code and resource card matched; only the material dossier changed. Because the deterministic policies did not consume the dossier, arm equality was a preregistered interface-invariance check.

All policies received the same six probe cards. The assay-all policy used add-solvent, add-reagent, set-potential, electrolysis, termination and assay. The immediate-discard policy used add-solvent and discard. The measure-then-threshold policy executed the shared four-action process prefix, measured public UV–visible conversion and compared the finite signal with the frozen threshold 0.007984561379998922, with equality assigned to the assay branch. Below-threshold vessels were discarded after six operations; eligible vessels received another electrolysis, termination and assay for eight operations. The threshold was selected before formal execution from disjoint qualification seeds 1000–1004 and could not be retuned from formal outcomes.

Each campaign had hard limits of 48 operation attempts, six vessel starts, six final assays, six non-final/UV–visible uses, 0.09 mol reagent and 0.15 L solvent. Only committed non-final measurements counted as evidence acquisition. Campaign cost and risk were ledger deltas: charged attempt penalties remained included, while rejected candidate-state changes remained excluded.

Signature recovery ran only after execution validity required all planned lifecycles to close, all submitted actions to commit, no validation or resource rejection and exact event/state/resource replay. Undefined conditional metrics retained their declared nulls: for example, endpoint and trajectory context were null without an assay, retention and drawdown required at least two assays, and recovery was null without a loss episode. Nulls were never replaced by zeros. Read-only analysis independently rebuilt all profiles and ledgers from immutable evidence. A reliability execution then reran every deterministic policy from the same identities; all 30 primary/retest pairs matched controller, trajectory, profile and configuration.

10.4 Compiled-control protocol

Compiled control covered electrochemical conversion and reaction-to-crystallization. Each task used simulator-world seeds 0–9 and three information conditions: opaque material codes, anonymous nominal properties and a protocol-frozen misindexed prior. Each participant session selected 20 complete experiments, after which a replay verifier recomputed all scores from the immutable reports. Classical policies used the same world identities, budgets and information contracts.

The opaque condition replaced material identities by stable anonymous codes. The nominal condition exposed the correct anonymous material-family property rows without revealing latent world residuals. The misindexed condition transposed one targeted material row chosen using independent qualification worlds before the formal campaigns; the affected mapping was fixed across the ten formal worlds. These conditions therefore modify the supplied prior while holding the simulator world, action space, score and budget fixed. Opaque, nominal and misindexed campaigns were sequential protocol-frozen extensions that reused the earlier matched cells. We therefore report matched-world associations and do not use execution order as a causal estimand.

The electrochemical endpoint is the gated weighted sum of selective product yield (0.30), electrochemical selectivity (0.15), conversion (0.10), Faradaic efficiency (0.12), transport efficiency (0.10), ohmic efficiency (0.08) and energy efficiency (0.15); selective yield supplies the multiplicative gate. The reaction-to-crystallization endpoint combines reaction score (0.25), crystal yield (0.25), crystal purity (0.20), crystal size (0.10), crystal-size- distribution quality (0.20) and a fines-fraction penalty (-0.10). The scoring contract was identical across information arms within a task.

Compiled participants used the Codex subscription transport with the GPT-5.6 Codex model at medium reasoning effort, structured response output, tools disabled and no session persistence. The compiled-control and primitive-control studies therefore share a model family and reasoning setting but use different scaffolds and action interfaces; they are complementary evidence layers, not a matched causal comparison of authority.

The nonduplicated total comprises 2,280 participant exe-

cutions and 27,300 classical-control executions. Statistical summaries treat the paired simulator world, not each execution, as the analysis unit. Seeds 0–9 form the complete designed set for the matched-condition analysis. Information contrasts report mean and median world differences, positive/negative counts, exact sign summaries, leave-one-world-out mean ranges and 100,000-draw, protocol-frozen percentile world-bootstrap ranges as finite-set sensitivity summaries. The complete ten paired differences are primary. The resampling distribution asks how their mean changes when the ten designed worlds are sampled with replacement; it is not used as a confidence interval for a world superpopulation. A 97.5% range is displayed for each task as a multiplicity-adjusted descriptive summary across the two prespecified tasks.

The information-matched classical suite comprised uniform random search, Latin hypercube sampling, local greedy perturbation, Gaussian-process expected improvement, random-forest expected improvement, safety-constrained Gaussian-process expected improvement and a multi-output telemetry random-forest policy. Electrochemical calibration additionally included privileged material-descriptor and transport-prior policies together with protocol-frozen shuffled-descriptor negative controls. The privileged policies calibrate what the environment permits; they are not information-matched agent comparators.

The misindexing manipulation transposed one targeted material row selected on independent qualification worlds. Protocol-frozen checks separately evaluated initial behavior change, later action correction, performance restoration and their joint criterion.

Epistemic diagnostics were scored independently of the optimized endpoint. At final synthesis, the agent predicted increase, decrease or no material change for three frozen one-factor intervention queries and their three registered metrics. Each query was then executed as paired reference/intervention experiments with two replicates and common observation-noise identities. The executed difference was labelled increase or decrease when it crossed the frozen absolute threshold of 0.01 and no material change otherwise. Held-out directional accuracy is the fraction of these query-by-metric labels predicted correctly; the prediction call could not alter the submitted recommendation. The held-out Brier score is the mean of $(c - y)^2$, where c is the submitted confidence and y indicates whether that directional prediction was correct.

Declared world-understanding claims were matched against a frozen vocabulary of observable cause sets, effects, admissible directional relations and mechanism tags. Unsupported-claim rate is the fraction of submitted declarations whose cause-set/effect structure has no reference match. Directional accuracy among matched declarations, structural edge precision/recall, mechanism-tag scores and a declaration-level confidence Brier score were retained as separate diagnostics, so no single epistemic statistic was treated as a proxy for the others.

10.5 Primitive-control protocol and resource ledger

The autonomous electrochemical protocol exposed typed tools for adding reagent and solvent, setting potential/current/material profile, electrolyzing, measuring, inspecting public status/history, terminating and requesting the final assay or explicitly discarding a batch. Each cell contained six vessel opportunities. The campaign card bounded vessels, raw stocks, non-final instrument uses, operation attempts and provider decisions. Resource state was stored outside the model context and exposed through compact queries or a bounded public state view; it was not repeatedly copied into the model context.

Native Codex used the GPT-5.6 Codex model with medium reasoning effort. Each vessel used a fresh provider session. The environment accepted only typed tool transactions; explanatory prose could not change physical state. All 60 Codex vessels terminated with a committed final assay.

DeepSeek used the DeepSeek-V4-Flash model. One provider decision was requested for each primitive operation, with JSON-object transport and local validation against the dynamically available action schema. The provider had no shell or MCP authority. A failed structured response could be retried up to six times before the corresponding logical decision failed; failed receipts and their token accounting remained in the audit. Five world pairs ran concurrently, with arms serialized within each simulator-world pair. The formal run used 901 provider calls for 889 accepted operations; 12 malformed responses were recovered without replacing an observed trajectory. Maximum estimated prompt size was 3,996 tokens under a frozen 4,800-token cap.

For the shared cross-system analysis, a batch lifecycle was closed by either a committed final assay or an explicit discard. Execution validity required all six vessel starts and closures, a reconciled resource ledger, exact transition replay and a complete provider-decision or provider-session audit. Task outcome was recorded separately from transport validity. The two systems shared all simulator-world identity, material, noise, workflow, scoring and resource-card fields in each of the ten cells. Their model and decision transports intentionally differed, so cross-system results were interpreted as complete-system behavioral profiles and not as a causal model-backend contrast.

Terminal action semantics were common at the environment kernel but not symmetric in meaning or presentation. Final assay was a costly measurement available only after termination and sufficient sample; explicit discard directly closed an open campaign batch, returned no final score and refunded nothing. The Codex task profile contained an explicit final-assay completion recommendation, whereas the compact direct-LLM task prompt omitted the recommended-strategy block. Both configurations exposed dynamically valid actions and set automatic repair and automatic closeout to false. Prompt and menu differences are therefore components of the complete-system comparison, not controlled nuisance variables. A same-model

crossed-scaffold or prompt ablation was not performed.

10.6 Latent-terminal counterfactual and censoring

The latent-audit population was the DeepSeek-based system’s frozen set of 60 original terminal lifecycles: 24 observed assays and 36 committed discards across ten cells. One latent unit was one registered discard. The intended counterfactual reconstructed the exact environment immediately before that discard, retaining every earlier action, public observation, keyed-noise draw, hidden state and historical resource prefix. The only replacement was an evaluator-only final assay. It could bypass the agent-facing assay-readiness check but could not add process actions, repair state, call a provider, charge the original ledger or count as an original experiment or agent decision.

The contract fixed relative thresholds $0.80B_c$, $0.90B_c$ and $1.00B_c$, plus absolute score 0.58; equality counted as near-best. The primary threshold was $0.90B_c$, where B_c is the best observed assay score in cell c . Continuous latent score, discard- to-best delta, positive discard regret, false-discard fraction, assay precision/recall, campaign-oracle regret and decision-time regret retained their frozen lifecycle or cell denominators.

An outcome-blind audit reproduced all 36 pre-discard identities but executed zero replacement assays. It therefore qualified deterministic checkpoint reconstruction, not the integrated counterfactual evaluator. Synthetic qualification exercised terminal replacement, same-identity replay and fail-closed probes on disjoint worlds. Formal eligibility required 36 valid scores, 36 passing same-identity receipts, zero provider calls and no mutation of original trajectories or ledgers. Although 36/36 checkpoints passed preflight, formal execution yielded a complete receipt report with only 6 valid scores and 30 unresolved receipts. The resource-ledger gate therefore retained the run as incomplete; it was not altered or repeated.

Every unresolved unit remained in its original denominator with score support $[0, 1]$. Delta and regret bounds additionally used the cell’s observed best; decision-time regret used the strictly prior assayed incumbent and left pre-assay discards null; campaign-oracle bounds used the nine cells with a discard opportunity. When any score was unresolved, latent-dependent point estimates were withheld. Observed-only summaries remained diagnostic and could not replace the finite-population estimand. Classification bounds assigned unresolved scores to registered all-zero and all-one endpoints while preserving the 60-lifecycle and 36-discard denominators. No super-population p-value or confidence interval was primary.

The formal 6/36 result is therefore an integration failure, not a successful counterfactual measurement with high missingness. The failure classes were 11 captured-prefix identity mismatches, 18 runtime-resource versus authoritative-prefix mismatches, and one replacement-precondition violation. This frozen run will not be repaired in place. Qualification of the module requires corrected binding logic followed by a new registered execution on independent discard data.

10.7 Operational trajectory readouts

For the Codex development and fresh-session analyses, let $s_1, \dots, s_K$ be the final-assay scores in a campaign, with $K = 6$, and let $b_t = \max_{j \leq t} s_j$ be the online incumbent.

Within-campaign best-discovery position is the first index of the observed campaign maximum, normalized to $[0, 1]$:

$$d = \frac{\min\{t : s_t = \max_j s_j\} - 1}{K - 1}.$$

For retention fraction q , assay $t > 1$ retains the incumbent when $s_t \geq qb_{t-1}$. Online retention is the fraction of the $K - 1$ opportunities satisfying this rule. A loss episode begins below the same boundary; its reference incumbent remains fixed until a later assay recovers to that boundary. Maximum absolute drawdown is $\max_t \max(0, b_{t-1} - s_t)$. Terminal-to-best ratio is $s_K / \max_t s_t$ when the observed best is positive. The primary retention fraction was $q = 0.90$; $q = 0.80$ and $q = 0.95$ were sensitivity definitions. Raw terminal score is s_K . We compare its nominal-minus-opaque contrast with the best-score contrast as the endpoint-independent directional diagnostic. Terminal-to-best remains a useful relative-retention readout, but because its denominator contains the campaign best, it is supporting rather than algebraically independent when shown beside a best-score contrast.

These are operational trajectory readouts. “Discovery” refers to discovery of the best condition observed within that campaign, not identification of the global optimum of the hidden world.

10.8 Fresh-session replication

The replication crossed simulator-world seeds 1 and 3, five trajectory-replicate blocks, and opaque/nominal information conditions. Worlds were selected from the development set before launch because their observed development directions differed. Development trajectories were excluded from the replication estimand. Pair order and within-pair arm order were frozen in the schedule.

A provider failure before any accepted operation could be retried up to the frozen limit. A provider or method-resource failure after an accepted operation made the cell terminal and right-censored. Completed and right-censored cells in the authoritative launch were not replaced. Pair differences were computed only when both arms completed; no missing outcome was imputed. Because exposure to provider failure can increase with trajectory length or interaction complexity, censoring was not assumed independent or missing at random. Complete-pair summaries are descriptive and the two censored pairs remain part of the displayed design denominator.

For each world and metric, the primary descriptive rule—frozen after launch while endpoint and lifecycle outcomes remained uninspected—classified a direction when at least 75% of available differences shared a sign and the median shared that direction. With four complete pairs this is a three-of-four rule. Otherwise the result was mixed. The four primary lifecycle metrics were best-discovery posi-

tion, online retention, maximum absolute drawdown and terminal-to-best ratio; best and mean scores were endpoint diagnostics.

10.9 Sensitivity analyses

The frozen primary analysis was not changed. A separate sensitivity analysis evaluated directional thresholds 0.60, 0.75 and 0.80; inclusion or exclusion of exact zero differences; retention fractions 0.80, 0.90 and 0.95; and every positive/negative/zero sign assignment to the two missing pair differences. Because lifecycle metrics share the same six assay outcomes, the eight world-by-metric classifications are treated as a descriptive summary, not as eight independent inferential units. The raw-terminal diagnostic was computed directly from the last paired assay contrast and does not alter the frozen classification rule.

10.10 First-launch infrastructure incident

The frozen replication protocol was first launched on 1 August 2026. The outer execution process stopped after one cell had completed six vessels and another had recorded four accepted operations. The cell-level protocol specified right-censoring after any accepted action and no rerun of a terminal cell. The decision to exclude and restart the entire launch therefore constitutes a protocol deviation at the launcher level.

The decision was made without changing the protocol, schedule, worlds, arms, budgets or analysis rule. The original directory was retained immutably; its completed cell and partial trajectory are included in the public trajectory archive. The authoritative matrix is the second launch and remains the primary analysis. The excluded launch is not pooled into primary pairs. As a transparent descriptive check, its completed nominal-information cell in world 1 had six scores from 0.654 to 0.730 (mean 0.710); pairing it across launches with the corresponding formal opaque trajectory gives positive best-score, mean-score, retention and terminal contrasts and a smaller drawdown. This direction is compatible with, and not required for, the primary conclusion that at least six lifecycle classifications remain mixed.

10.11 Scope-stopped multiworld extension

After the primary replication, a prospective 16-world extension was launched to estimate broader heterogeneity. The owner stopped it as a scope decision after three complete pairs and one right-censored cell, without inspecting any complete-pair scores or arm contrasts. The parent matrix was incomplete, all partial trajectories were retained, and none of its outcomes enters the present estimand, figures or inferential language. This extension is an execution record for future multiworld work, not an additional result of this paper.

10.12 Public boundary and replay

The evaluator record retains hidden simulator identity, whereas the agent-facing state and history expose only the public observation schema. Boundary tests compare

the public and evaluator views and inspect representative workspaces for hidden-field leakage. Compact public trajectories omit provider response content and hidden evaluator identity while retaining the fields required to replay simulator transitions and resource changes.

10.13 Protocol timing and deviations

Protocols and estimands described as frozen were recorded before their corresponding formal outcomes were generated; this is not a registered report or a third-party trusted timestamp. Sequential extensions were fixed before their own execution but not necessarily before earlier related results. A rule fixed after launch while the relevant endpoint and lifecycle fields remained uninspected is labelled an *outcome-blind analysis freeze*, not preregistration. Table 2 records the consequential timing and deviations in reader-facing terms.

11. Data and code availability

Code, configuration, processed data, figure source data, analysis scripts and compact public trajectories are available in the MIT-licensed ChemWorld repository at github.com/sunyrain/ChemWorld. These materials regenerate the reported numbers, tables and figures and replay the released simulator transitions and resource changes. Provider authentication, unrestricted response bodies and hidden evaluator identities are excluded from the public package.

The shared materials support three distinct reproducibility levels. First, figures, tables and reported numbers can be regenerated from tracked derived data and generators. Second, the compact trajectories reproduce environment transitions, public observations and resource ledgers. Third, the stochastic provider decisions themselves are not exactly reproducible: full response bodies are excluded, provider sampling is not seed-controlled, and a mutable model alias may drift even when the recorded configuration is reused.

The larger compiled-control execution logs total 17.7 GB and are not required to regenerate the reported analyses from the processed data. They have not yet been placed in a durable public archive. Without those logs or unrestricted provider responses, a third party can verify the reported arithmetic and figures, inspect the published evidence boundaries, and replay the released simulator trajectories, but cannot inspect every raw provider response.

12. Conclusion

This paper establishes ChemWorld as a programmable scientific measurement instrument for autonomous experimentation in executable physical-chemistry worlds. Its backend lets complete systems choose operations, acquire evidence, spend resources, encounter failure and close lifecycles while the world keeps simulator identity, public contracts and replayable records under experimental control. Controlled forks and known policies qualify its executable and profile-computation paths; the complete-system, compiled-control

and fresh- trajectory studies illustrate how its readouts separate terminal and process behavior without treating those cases as a representative survey. The failed discarded-state module remains explicitly unqualified: missing counterfactual evidence remains visible rather than being repaired into a favorable point result. ChemWorld therefore establishes how agents can run autonomously and be observed, not why a particular agent produced a trajectory. Causal attribution, mechanistic explanation and adaptation under changed world laws are reserved for a separate explanatory study. **An endpoint is a result, not an account of the experimental process; that process can now be recorded as an auditable profile.**

Appendix A. Robustness summary

The main continuous endpoint diagnostic uses raw terminal score: two of eight complete pairs are sign-discordant with best score and the descriptive Pearson correlation is +0.826. The table below retains the frozen categorical lifecycle analysis as a supporting sensitivity summary.

Table 2. Sensitivity of the supporting directional classification. Exact-zero handling affects retention classifications because several paired retention differences are zero. The complete threshold-by-zero grid spans 2–8 mixed classifications; under every missing-sign assignment at the frozen rule, at least six remain mixed.

Sensitivity setting	Mixed
Primary: 75% direction, zeros included, 90% retention	6/8
60% direction, zeros included	6/8
60% direction, zeros excluded	2/8
75% direction, zeros excluded	5/8
80% direction, zeros included	8/8
80% direction, zeros excluded	7/8
80% retention definition	5/8
95% retention definition	6/8
Arbitrary missing-pair signs	6–8/8

Appendix B. Reproducibility materials

All figures are rendered from frozen processed data. The public trajectory collection contains 20 formal Codex replication cells—18 complete and two right-censored—, the two retained first-launch cells, and all ten DeepSeek demonstration cells. Each compact trajectory passes the simulator-transition replay verifier. The submission bundle also provides the editable figure sources, bibliography and manuscript source needed to reproduce the submitted PDF.

Appendix C. Complete experimental-process metric dictionary

The measured object is the operational experimental-process profile. Let P be planned lifecycles, C closed lifecycles, A final assays, D discards and M closed lifecycles containing a committed non-final measurement. A

Table 1. Protocol and analysis timeline. Visibility records what was available when each decision was made.

Stage	Freeze or decision point	Data visible at that point	Classification and disposition
Fork and known-policy protocols	Before their formal executions	Qualification data only; no formal pair or campaign outcomes	Documented protocols frozen before formal outcomes
Complete-system demonstration	Configuration frozen before each system run	Earlier development evidence was available	Descriptive demonstration; no causal model or scaffold estimand
Discarded-state audit	Before the first counterfactual score	All 36 checkpoint identities and reconstructability result; zero latent scores	Evaluator audit frozen before scoring; formal 6/36 gate failure retained
Fresh-session launch restart	1 August 2026, after one completed cell and four accepted operations in another	Lifecycle state was visible; endpoint outcomes were not inspected for the restart decision	Protocol deviation. Entire first launch excluded; the supervised restart became authoritative
Trajectory direction rule	After launch, before endpoint and lifecycle outcomes were inspected	Schedule and run existence, but not the classified outcomes	Outcome-blind analysis freeze; never described as preregistration
Sixteen-world extension stop	After three complete pairs and one right-censored cell	Administrative completion state; no pair scores or arm contrasts inspected	Owner scope stop; all extension outcomes excluded from this paper

missing denominator produces an undefined value, never zero.

Terminal commitment. Closed-lifecycle fraction is C/P ; assay fraction is A/C ; and discard fraction is D/C . Each is in $[0, 1]$. The latter two are null when $C = 0$ and sum to one otherwise.

Evidence acquisition. Measured-lifecycle fraction is M/C in $[0, 1]$. Non-final instrument uses per closed lifecycle is the number of committed non-final instrument uses divided by C and is nonnegative. Mean first-measurement position is the mean registered within-lifecycle position of the first committed non-final measurement, normalized to $[0, 1]$ across measured lifecycles; it is null when $M = 0$.

Evidence-conditioned action. Continued-after-measurement fraction is the number of closed lifecycles with a committed physical process operation after their first committed non-final measurement, divided by C . Post-measure process operations per closed lifecycle is the corresponding operation count divided by C . Threshold-eligible fraction is the number of closed lifecycles with a finite preregistered diagnostic signal divided by C . Threshold-decision concordance is the fraction of eligible lifecycles whose assay or discard agrees with that signal rule. Fractions are in $[0, 1]$; counts per lifecycle are nonnegative; concordance is null with no eligible lifecycle.

Resource deployment. Attempted and committed operations per closed lifecycle divide their respective event counts by C . Total cost and total risk per closed lifecycle divide campaign- ledger deltas by C . All four are non-negative and null when $C = 0$. Charged failed-attempt penalties remain included; rejected candidate-state changes do not create committed material debits.

Outcome trajectory. For the ordered committed final-assay scores $s_1, \dots, s_K$, global-best discovery fraction is the normalized first position of the best score observed in that campaign; online incumbent-retention rate is the fraction of later assays retaining the registered fraction of the prior incumbent; maximum absolute incumbent drawdown is the largest incumbent-minus-current score loss; loss-episode recovery rate is the recovered-loss-episode fraction; and terminal-to-global-best ratio is $s_K / \max_t s_t$. Fraction and ratio metrics lie in $[0, 1]$ and drawdown is in score units. The first and last are null without a positive

assay sequence, retention and drawdown are null with fewer than two assays, and recovery is null without a loss episode. Mean assayed score and best assayed score are endpoint context outside the 19-metric profile and never enter a composite score.

References

- [1] Kobi C. Felton, Jan G. Rittig, and Alexei A. Lapkin. Summit: Benchmarking machine learning methods for reaction optimisation. *Chemistry-Methods*, 1:116–122, 2021. doi: 10.1002/cmt.202000051.
- [2] Florian Häse, Matteo Aldeghi, Riley J. Hickman, Loïc M. Roch, Melodie Christensen, Elena Liles, Jason E. Hein, and Alán Aspuru-Guzik. Olympus: a benchmarking framework for noisy optimization and experiment planning. *Machine Learning: Science and Technology*, 2:035021, 2021. doi: 10.1088/2632-2153/abedc8.
- [3] Nathan J. Szymanski et al. An autonomous laboratory for the accelerated synthesis of inorganic materials. *Nature*, 624:86–91, 2023. doi: 10.1038/s41586-023-06734-w.
- [4] Tianyi Dai, Sriram Vijayakrishnan, Filip T. Szczyp- iński, et al. Autonomous mobile robots for exploratory synthetic chemistry. *Nature*, 635:890–897, 2024. doi: 10.1038/s41586-024-08173-7.
- [5] Kourosh Darvish, Marta Skreta, Yuchi Zhao, et al. ORGANA: A robotic assistant for automated chemistry experimentation and characterization. *Matter*, 8(2), 2025. doi: 10.1016/j.matt.2024.10.015.
- [6] Aikaterini Vriza, Michael H. Prince, Tao Zhou, Henry Chan, and Mathew J. Cherukara. Operating advanced scientific instruments with AI agents that learn on the job. *npj Computational Materials*, 12:160, 2026. doi: 10.1038/s41524-026-02005-0.
- [7] Daniil A. Boiko, Robert MacKnight, Ben Kline, and Gabe Gomes. Autonomous chemical research with large language models. *Nature*, 624:570–578, 2023. doi: 10.1038/s41586-023-06792-0.

Table 3. Appendix D. Validation coverage across the 15 registered tasks. Qualification denotes executable midpoint and boundary tests; Profile, known-policy profiling; Compiled, complete-experiment participant campaigns (formal or development); Primitive, primitive-control complete-system execution; and Statistics, a result reported in this paper. A dash means that the evidence layer was not run for that task. All 15 contracts have executable design qualification, five have audited compiled-participant campaigns, two enter the paper’s formal compiled-control statistics, and only electrochemical conversion has primitive-control complete-system evidence. The matrix is a coverage disclosure, not evidence that an unmarked cell would fail.

Registered task	Qual.	Fork	Profile	Complete	Stepwise	Replay	Result
Electrochemical conversion	Y	Y	Y	Formal	Y	Y	Y
Equilibrium characterization	Y	–	–	–	–	–	–
Flow-reaction optimization	Y	–	–	Dev.	–	Y	–
Low-budget characterization	Y	–	–	–	–	–	–
Partition discovery	Y	Y	–	Dev.	–	Y	–
Public-private generalization	Y	–	–	–	–	–	–
Purity-yield trade-off	Y	–	–	–	–	–	–
Reaction-mechanism explanation	Y	–	–	–	–	–	–
Reaction optimization	Y	–	–	–	–	–	–
Safety-constrained reaction	Y	–	–	–	–	–	–
Reaction-to-assay workflow	Y	–	–	–	–	–	–
Reaction-to-crystallization workflow	Y	–	–	Formal	–	Y	Y
Reaction-to-distillation workflow	Y	–	–	Dev.	–	Y	–
Reaction-to-purification workflow	Y	–	–	–	–	–	–
Tool-mediated experiment planning	Y	–	–	–	–	–	–

- [8] Andres M. Bran, Sam Cox, Oliver Schilter, Carlo Baldassari, Andrew D. White, and Philippe Schwaller. Augmenting large language models with chemistry tools. *Nature Machine Intelligence*, 6:525–535, 2024. doi: 10.1038/s42256-024-00832-8.
- [9] Tao Song, Man Luo, Xiaolong Zhang, et al. A multiagent-driven robotic AI chemist enabling autonomous chemical research on demand. *Journal of the American Chemical Society*, 147(15):12534–12545, 2025. doi: 10.1021/jacs.4c17738.
- [10] Gihan Panapitiya, Emily Saldanha, Heather Job, et al. AutoLabs: cognitive multi-agent systems with self-correction for autonomous chemical experimentation. *Scientific Reports*, 16:19554, 2026. doi: 10.1038/s41598-026-45593-z.
- [11] Sebastian Pagel, Michael Jirasek, and Leroy Cronin. Verification and execution of the scientific literature via chempuration augmented by large language models. *Communications Chemistry*, 9:191, 2026. doi: 10.1038/s42004-026-01993-w.
- [12] Brian Hsu, Priyanka V. Setty, Rory M. Butler, et al. PRISM: protocol refinement through intelligent simulation modeling. *Digital Discovery*, 5:2613–2628, 2026. doi: 10.1039/D6DD00004E.
- [13] Simone Pilon, Elia Savino, Oliver M. Bayley, et al. A flexible and affordable self-driving laboratory for automated reaction optimization. *Nature Synthesis*, 2026. doi: 10.1038/s44160-026-01053-0.
- [14] Zhantao Chen, Alexander N. Petsch, Aidan J. Israeli, et al. An agentic artificially intelligent X-ray scientist. *Nature Machine Intelligence*, 8:1075–1086, 2026. doi: 10.1038/s42256-026-01261-5.
- [15] Maximilian Bloor, José Torracca, Ilya Orson Sandoval, et al. PC-Gym: Benchmark environments for process control problems, 2024. Preprint, arXiv:2410.22093.
- [16] Chris Beeler, Sriram Ganapathi Subramanian, Kyle Sprague, et al. ChemGymRL: A customizable interactive framework for reinforcement learning for digital chemistry. *Digital Discovery*, 3:742–758, 2024. doi: 10.1039/D3DD00183K.
- [17] Shreshth A. Malik, Tiarnan Doherty, Panagiotis Tigas, Muhammed Razzak, Stephen J. Roberts, Aron Walsh, and Yarin Gal. MADE: Benchmark environments for closed-loop materials discovery. In *International Conference on Machine Learning*, 2026.
- [18] Nikhil Abhyankar, Sanchit Kabra, Saaketh Desai, and Chandan K. Reddy. LLEMA: Evolutionary search with LLMs for multi-objective materials discovery. In *International Conference on Learning Representations*, 2026. URL <https://openreview.net/forum?id=TIqzhBvCNB>.
- [19] Peter Jansen, Marc-Alexandre Côté, Tushar Khot, Erin Bransom, Bhavana Dalvi Mishra, Bodhisattwa Prasad Majumder, Oyvind Tafjord, and Peter Clark. DiscoveryWorld: A virtual environment for developing and evaluating automated scientific discovery agents. In *Advances in Neural Information Processing Systems*, volume 37, 2024. doi: 10.52202/079017-0324.
- [20] Kanishk Gandhi, Michael Y. Li, Lyle Goodyear, Agam Bhatia, Louise Li, Aditi Bhaskar, Mohammed Zaman, and Noah D. Goodman. BoxingGym: Benchmarking progress in automated experimental design and model discovery, 2025. Preprint, arXiv:2501.01540.
- [21] Haonan Duan, Stephen Zhewen Lu, Caitlin Fiona Harrigan, Nishkrit Desai, Jiarui Lu, Michał Koziarski, Leonardo Cotta, and Chris J. Maddison. Measuring scientific capabilities of language models with a systems biology dry lab, 2025. Preprint, arXiv:2507.02083.

- [22] Maximilian Nägele and Florian Marquardt. Agentic exploration of physics models. *Physical Review X*, 16: 031002, 2026. doi: 10.1103/xnqc-q6nt.
- [23] Tianshi Zheng, Kelvin Kiu-Wai Tam, Newt Hue-Nam K. Nguyen, et al. NewtonBench: Benchmarking generalizable scientific law discovery in llm agents. In *International Conference on Learning Representations*, 2026.
- [24] Martiño Ríos-García, Nawaf Alampara, Chandan Gupta, Indrajeet Mandal, Sajid Mannan, Ali Asghar Aghajani, N. M. Anoop Krishnan, and Kevin Maik Jablonka. Ai scientists produce results without reasoning scientifically, 2026. Preprint, arXiv:2604.18805.
- [25] Lin Chen, Yunke Zhang, Jie Feng, et al. AI agent behavioral science. *Humanities and Social Sciences Communications*, 13:1011, 2026. doi: 10.1057/s41599-026-07316-7.
- [26] Amy Xin, Jiening Siow, Junjie Wang, et al. EurekaAgent: Agent environment engineering is all you need for autonomous scientific discovery, 2026. Preprint, arXiv:2606.13662.
- [27] Lulu Guo, Yingkai Sun, Xiaobo Li, et al. Stress-testing large language model agents in a robotic chemistry laboratory, 2026. Preprint.