

Executable Chemical Worlds Make Experimental Agency Measurable

Jiangjie Qiu¹, Yijun

¹Beijing Key Laboratory of Artificial Intelligence for Advanced Chemical Engineering Materials, State Key Laboratory of Chemical Engin

Abstract

Scientific agents are commonly judged by the best condition they report, but that endpoint cannot reveal the experimental policy that produced it. We present ChemWorld, an executable chemical-world apparatus that makes experimental agency observable. Agents choose typed state-changing operations, measurements, resource expenditure, termination, final assay and discard; every accepted transition is identity-bound and exactly replayable. Compiled controls comprising 29,580 simulator executions across two task families separate outcome, held-out prediction, calibration and claim reliability. Two independently configured primitive-control systems then closed 120 batch lifecycles in five matched worlds. Codex requested 60 final assays and no discards; DeepSeek V4 Flash requested 24 final assays and explicitly discarded 36 batches, despite nearly identical non-final instrument use. Fresh Codex sessions in two deliberately selected worlds yielded eight complete matched information-condition pairs. Best-of-campaign and raw terminal contrasts were directionally discordant in two pairs, while full trajectories separately resolved discovery, retention, drawdown and recovery. These results establish experimental agency as a measurable profile of decisions and trajectories, rather than a score recoverable from the endpoint alone.

1. Introduction

When a scientific agent reports a high-performing condition, the most important question is no longer only *what score did it obtain?* It is also *what kind of experimental process produced that score?* A condition may be found early and retained, found once and abandoned, recovered after a drawdown, or reached at the end of an otherwise uninformative search. These trajectories imply different capabilities even when their final values agree.

This distinction is difficult to measure with existing evaluation regimes. Prediction benchmarks remove the act of experimentation. Optimization benchmarks expose a value-returning oracle but usually collapse each experiment to a vector query. Self-driving laboratories and instrument-operating agents provide indispensable evidence about physical execution, automation and deployment [1–4], but a physical apparatus cannot usually be cloned many times while changing only the information supplied to the agent. As a result, the agent’s experimental behavior is often entangled with a particular laboratory, material batch and observation history.

ChemWorld fills this measurement gap with executable chemical and chemical-engineering worlds. The central design choice is simple: **the agent is the experimental subject; the chemical world is the apparatus.** Within a stateful, partially observable world, the agent selects additions, process conditions, measurements, termination and final assay. The environment records the consequence of every choice, including invalid operations, failed attempts and resource use. Matched hidden-world identities permit controlled information contrasts, while fresh sessions in the same physical world measure behavioral repeatability.

This apparatus changes what can be asked of a scientific agent. Instead of reducing performance to one

leaderboard value, we can measure lifecycle completion, within-campaign best-discovery position, retention of an incumbent, drawdown, recovery, terminal quality, prediction and claim reliability. These are operational readouts of behavior, not inferred mental states. Their non-equivalence is itself a scientific result: similar endpoint outcomes can arise from different experimental histories and capabilities.

We use three evidence layers. First, compiled experiments compare matched material-information conditions across two task families and separate optimization from prediction, calibration and claim reliability. Second, primitive-control campaigns show that distinct complete agent systems can close experimental lifecycles under a shared resource ledger while expressing different assay and discard policies. Third, fresh trajectories in matched physical worlds reveal which behavioral features recur and which vary between sessions. Together they establish the paper’s central result: **an experimental endpoint is an incomplete readout of experimental agency.**

Our contributions are:

1. an executable, chemistry-native apparatus with stateful operations, active measurements, failures, resource accounting, identity control and exact physical replay;
2. a primitive-control protocol, exercised by two complete agent systems, in which the agent—rather than a fixed recipe—chooses operations, observations, assay commitment and lifecycle termination;
3. matched information conditions and fresh sessions that make endpoint optimization, prediction, claims, discovery, retention, drawdown and recovery separately observable; and
4. empirical evidence that the endpoint underdetermines the process: raw terminal performance can change opposite to best-of-campaign performance, while full trajectories expose experimental policies that neither

scalar records.

2. Relation to existing systems

Self-driving laboratories optimize reactions and materials in real hardware, and chemistry agents increasingly connect language models to literature, planning tools and robotic execution [5–8]. Their defining strength is physical validity: they answer whether a proposed workflow can be executed and whether automation can operate reliably. ChemWorld addresses a complementary question—whether the experimenting agent can be isolated, intervened on and repeated under matched physical identity.

Digital optimization suites provide controlled objective functions and scalable algorithm comparison [9, 10]. Interactive science environments extend this idea toward stateful control, discovery and model identification [11–16]. ChemWorld’s distinctive unit is a chemical experiment as a resource-consuming sequence of typed operations and measurements, not a single parameter query. The same world can be replayed under different information and authority conditions without changing its hidden physical identity.

Recent work treats agents themselves as behavioral objects and studies how environment design changes scientific discovery [17–19]. ChemWorld brings that perspective to chemistry-native experimental lifecycles. Its contribution is the combination of matched chemical worlds, primitive action authority, evidence access, campaign-wide resources, immutable trajectories and within-world fresh-session replication. It does not replace a robotic laboratory; it provides the controlled measurement apparatus that a real laboratory cannot economically instantiate at scale.

3. ChemWorld makes experimental agency measurable

3.1 Executable worlds rather than value-returning oracles

A ChemWorld task defines a hidden physical state, public observation contract, typed operations, instrument responses, resource endowment, failure semantics and one or more evaluator-bound endpoints. Operations change state. Measurements are actions with costs and timing consequences. Termination closes a vessel, and a final assay is explicitly requested rather than automatically revealed.

The qualified environment surface contains 15 registered tasks, 28 operation types, five instrument classes, 415 deterministic complete-experiment boundary cases and 62 evaluator-bound endpoints (Fig. 1). Qualification establishes runtime reachability and evaluator binding. The empirical paper uses two tasks for compiled controls and one for autonomous primitive control, keeping platform scope and evidence scope explicit.

3.2 Controlled identity, resources and replay

Every run binds source, configuration, task, physical world, material instance, observation namespace and trajectory identity. The public agent view excludes hidden evaluator

state. Accepted operations are transactional: a successful transition updates state and consumes the corresponding resources; a rejected operation records its failure without silently repairing the action.

The campaign ledger spans raw materials, solvent, vessels, non-final instrument uses, operation attempts and provider sessions. This design makes opportunity cost part of the experimental record while keeping the ledger external to the prompt. Agents access compact status and history artifacts on demand rather than receiving a continually expanding transcript.

Exact replay means exact reconstruction of environment transitions, public observations and resource changes from the stored trajectory. It does not mean regeneration of the language model’s token sequence. Fresh-session replication therefore deliberately samples a new agent trajectory while holding the physical world fixed.

3.3 Evidence layers and analysis units

The number of executed world transitions measures use of the apparatus, not the number of statistically independent samples. Table 1 separates those quantities throughout the paper.

4. Compiled controls separate outcome from evidence use


Compiled control gives the agent a bounded complete-experiment interface. It is not the target autonomy setting; it is a controlled calibration that can be run across tasks, information conditions and classical optimization policies.

Across ten sequentially collected matched worlds, the nominal-information arm produced a mean nominal-minus-opaque score difference of 0.072 in electrochemical conversion (8/10 positive worlds; 97.5% per-task world-bootstrap interval 0.007 to 0.155) and 0.026 in reaction-to-crystallization (7/10 positive; interval -0.013 to 0.063). The two 97.5% intervals are multiplicity-adjusted descriptive stability intervals for the pre-specified two-task analysis. Thus the matched information conditions were associated with distinct outcome profiles in the two executable task families (Fig. 2A).


The deliberately misindexed arm provides a manipulation check. It redirected the first material-sensitive action in 70% of electrochemical worlds and 100% of crystallization worlds. Misleading-action share subsequently fell from 0.54 to 0.24 in electrochemistry and from 0.86 to 0.50 in crystallization (Fig. 2B). The distinction among action manipulation, later correction and performance restoration is important: both tasks passed the behavior-change check, while their correction and score-restoration checks differed, and neither passed the joint rule (Fig. 2C).

Outcome and epistemic diagnostics also gave different profiles. In the opaque arm, electrochemical conversion combined a 0.715 endpoint score with 0.744 held-out directional accuracy, a 0.186 Brier score and a 0.611 unsupported-claim rate. Reaction-to-crystallization yielded 0.535, 0.478, 0.298 and 0.714, respectively. These


A The chemical world is the experimental apparatus



B Controlled contrasts separate agent from world



C Each transition remains auditable



D Qualified surface and evidence scope



paper evidence: 2 compiled tasks · 1 autonomous task

Figure 1. ChemWorld is a controlled apparatus for measuring experimental agency. **A**, The agent selects a typed action, the executable world changes state, and only the public observation returns to the agent; the transition also writes a resource ledger and immutable trace. **B**, Physical identity and material information can be matched or intervened on while authority, evidence and resources remain explicit parts of the protocol. **C**, Typed state, transactions, receipts, traces and physical replay form an auditable spine; invalid actions and failures remain evidence. **D**, Qualified platform surface and the narrower evidence scope used in this paper.

Table 1. Evidence layers and effective analysis units. Execution counts describe the scale at which the apparatus was exercised; inference is organized around worlds and fresh session-level pairs.

Evidence layer	Purpose	Executions	Primary analysis unit
Platform qualification	Reachability and evaluator binding	415 boundary cases	declared task/endpoint
Compiled control	Task, information and diagnostic calibration	29,580 simulator executions	paired physical world; 10 per task and arm
Primitive-control systems	Lifecycle autonomy, interface portability and trajectory policy	120 closed vessels; 1,704 operations	complete agent system by world and arm; 2 systems, 5 worlds
Fresh-session replication	Within-world directional repeatability	114 started vessels; 112 final assays	world by session-level arm pair; 4 complete pairs per world

measurements are reported separately because none is a substitute for another (Fig. 2D).

Classical optimizers are retained as calibration controls rather than the paper’s target competition. Complete world-level contrasts for every baseline, including exact sign summaries and leave-one-world-out ranges, are provided in the sensitivity artifact. This keeps the empirical question aligned with the paper’s contribution: what aspects of experimental behavior become measurable once the world is a controlled apparatus?

5. One apparatus resolves distinct autonomous experimental policies

We exercised the primitive-control protocol with two complete agent systems on the same five physical worlds and two material-information arms. Both received the same typed action space, instrument access, campaign resource card, hidden world and material identities, observation noise and scoring contract. Native Codex (gpt-5.6-sol, medium reasoning) acted through a fresh MCP session for each vessel. DeepSeek V4 Flash made one schema-validated JSON decision per primitive operation through




Figure 2. Compiled controls distinguish task outcome, information response and epistemic readouts. **A**, Paired nominal-minus-opaque score differences across ten worlds per task; squares show means and multiplicity-adjusted 97.5% per-task world-bootstrap stability intervals. **B**, World-level early-to-late misleading-action shares under a deliberately misindexed material prior. **C**, Commit-frozen manipulation, correction, performance-restoration and joint criteria. **D**, Raw task-level endpoint, held-out prediction, calibration and unsupported-claim readouts. Circle area follows the favourable direction within each metric column; the printed number is the raw value.

a direct provider loop. Because model and scaffold change together, this is not an isolated backend comparison. It asks a more basic apparatus question: can distinct autonomous systems inhabit the same experimental world and leave comparable, auditable behavioral traces?

Both systems passed that test. Each closed all six batch opportunities in all ten cells, yielding 120 closed lifecycles under matched physical identity (Fig. 6). Their closure policies were sharply different. Codex requested a final assay for all 60 batches and discarded none. DeepSeek requested 24 final assays and explicitly discarded 36 batches. Yet their use of non-final instruments was nearly identical (164 versus 163), while their operation totals were 815 and 889. Thus a scalar completion flag would call both systems identical, and a score-only view would omit 36 deliberate abandonment decisions. The executable apparatus instead separates evidence acquisition, continued investment, terminal assay commitment and discard.

Material information also altered these policies within the DeepSeek system. Across the five nominal-information cells it committed 16 batches to final assay and discarded 14; under opaque codes it committed eight and discarded 22. The nominal arm additionally used 67 more primitive operations. Codex committed all 30 batches in each arm to final assay. With five paired worlds these are descriptive

system-specific profiles, not a population estimate, but they show that a material-information contrast can be expressed through resource and lifecycle decisions rather than endpoint score alone.

Figure 3 reconstructs the Codex implementation, for which each vessel received a public workspace and typed tools while the complete ledger remained external to the prompt. Figure 3A shows one vessel. The important feature is not the particular seven-operation sequence; it is the placement of observation before the next agent decision. A UV-visible measurement entered public state before the agent chose to terminate and request the final assay. Figure 3B shows this lifecycle across every Codex vessel and information arm, while Fig. 3C reconstructs its campaign-level resource receipt.

6. Endpoint scores conceal experimental trajectories

The six-assay Codex campaigns expose structure that a final recommendation cannot contain. Figure 4 follows six final assays in three development worlds. In world 0, the opaque trajectory lost its initial score, recovered by the fourth assay and finished near the nominal trajectory. In world 2, the opaque arm discovered its campaign best immediately and then lost it, whereas the nominal arm




Figure 3. A primitive-control agent closes complete experimental lifecycles. **A**, One seven-operation vessel in which a UV-visible observation is available before agent-selected termination and explicit final assay. **B**, All six Codex vessels reached final assay in each of ten world-by-information campaigns; navy denotes opaque codes and coral denotes nominal properties. **C**, The immutable trajectory reconstructs the campaign resource receipt. The example is descriptive and is not part of the fresh-session replication estimand.

improved and retained a higher terminal value. In world 4, both arms began similarly but their terminal behavior diverged sharply.

We operationalize these patterns with four lifecycle read-outs. Within-campaign best-discovery position records when the observed campaign maximum first appears. On-line retention asks whether a new assay remains within a pre-specified fraction of the pre-assay incumbent. Maximum absolute drawdown records the largest departure from that incumbent. Terminal-to-best ratio records how much of the observed campaign best remains at the final assay. Loss episodes and recovery delays provide additional summaries when a trajectory falls below its retention boundary.

Across the five development worlds, nominal information was associated with later within-campaign best discovery on average (0.80 versus 0.32 of the six-assay horizon), together with higher retention (0.72 versus 0.52), smaller mean maximum drawdown (0.092 versus 0.333), greater pooled recovery (0.80 versus 0.50) and higher terminal-to-best ratio (0.941 versus 0.671). Because each arm contains one session per development world, these values describe the five matched demonstration worlds. Their role is to show what the apparatus resolves: best discovery, retention, drawdown, recovery and relative terminal retention are simultaneously observable coordinates of a trajectory, none of which is recorded by the best score alone.

7. Fresh sessions test within-world repeatability

We selected physical worlds 1 and 3 before the replication launch because their development contrasts pointed in different directions. The commit-frozen design crossed two worlds, five fresh trajectory replicates and two information arms. Each cell received six vessel opportunities and the same physical, observation and resource identities as its within-replicate counterpart; the provider did not expose a controllable sampling seed.

Eighteen of 20 cells completed. Two cells were right-censored after 50 and 56 accepted operations by provider-infrastructure failures, leaving four complete pairs in each world. All ten planned pairs remain visible in Fig. 5. The 75% classification rule was frozen after launch while endpoint and lifecycle outcomes remained uninspected; it classified a world-by-metric result as directional when at least three of four available differences shared a sign and the median shared that direction.

The authoritative matrix followed a launcher-level restart after an infrastructure incident in the first launch; the restart decision was recorded before outcome inspection. The protocol deviation, excluded trajectories and separate sensitivity check are reported in Methods 10.7.

The continuous pairwise data provide an algebraically independent endpoint check. Across the eight complete pairs, nominal-minus-opaque best-of-campaign and raw terminal contrasts were sign-discordant in two pairs; their descriptive Pearson correlation was +0.826. The clearest instance was world 3/r01: the best-score contrast was




Figure 4. Similar endpoints can arise from different experimental trajectories. Selected development worlds illustrate early discovery followed by loss, gradual improvement, retention and terminal divergence. Open circles mark the first observed campaign best; squares mark terminal assays. Navy denotes opaque material codes and coral denotes nominal material properties. These examples motivate the lifecycle readouts but are not the replication estimand.

−0.167, whereas the raw terminal contrast was +0.240. Thus even strongly co-varying endpoint summaries are not interchangeable for an individual experimental trajectory.

Full process profiles expose substantially more structure (Fig. 5B). Each complete pair has separate signed contrasts for best score, raw terminal score, discovery timing, online retention, drawdown and relative terminal retention. The frozen 75% classification summarized six of eight selected world-by-lifecycle cells as mixed. That categorical count is supporting rather than the main result: across the complete threshold-by-zero-handling grid it ranges from two to eight, whereas the continuous contrasts and both right-censored pairs remain visible without thresholding. The terminal-to-best ratio is retained as a relative-retention readout; because it reuses the best score in its denominator, it is not treated as algebraically independent of the best-score contrast.

The fresh sessions therefore expose two forms of information that a best score cannot contain: raw terminal disagreement within a matched pair and trajectory-to-trajectory variation across the complete process profile. Both become directly observable because world identity, observation stream, resource card and action authority remain controlled.

8. Experimental agency is a profile, not a scalar

The compiled and primitive-control studies measure complementary parts of experimental agency. Compiled control separates task outcome from prediction, calibration and claim diagnostics. Primitive control additionally reveals what a system does with its experimental opportunities. Figure 6 makes that distinction concrete for two complete agent systems under the same matched apparatus.

The profile view supports a stronger evaluation standard

for scientific agents. Lifecycle closure, evidence acquisition, continued investment, assay commitment, discard, retention and recovery are distinct observables. ChemWorld provides a common apparatus that measures them separately and preserves the decisions from which each readout is computed.

9. Discussion

ChemWorld contributes a new experimental object: the process by which an agent experiments. Its value does not depend on replacing a self-driving laboratory or winning a universal optimization leaderboard. It occupies a different and useful role. A real laboratory establishes physical executability; an optimization suite calibrates search; an executable chemical world can clone physical identity, intervene on information and authority, preserve failures, and sample fresh decision trajectories at low marginal cost.

The present experiments demonstrate four consequences. First, matched information conditions are associated with different actions, endpoint outcome, prediction and claim reliability profiles. Second, two complete agent systems can close the same matched batch lifecycles while allocating terminal assays and discards very differently; the apparatus therefore measures experimental policy rather than merely interface compliance. Third, autonomous lifecycle completion does not specify how a high-performing condition was discovered, retained or recovered. Fourth, best-score and raw terminal contrasts can reverse sign within matched fresh sessions, while the full process profiles separate additional dimensions that neither endpoint records. The resulting conclusion is operational and direct: best-of-campaign performance underdetermines the experimental process that produced it.

The same apparatus makes a broader class of controlled studies possible. World mechanisms, observation channels,





Figure 5. Fresh trajectories expose information that endpoint summaries omit. **A**, Each point is one complete fresh-session pair in a fixed physical world. Shaded quadrants mark opposite signs for best-of-campaign and raw terminal score; two of eight pairs occupy them. Labels identify trajectory replicates, not shared model randomness. **B**, Continuous nominal-minus-opaque contrasts for all ten planned pairs. Positive values favour nominal information after orienting discovery and drawdown to their favourable directions; grey rows are right-censored. Relative retention is shown as a supporting process readout, not an endpoint-independent contrast.



Counts are complete-system behavioral profiles, not an isolated model-backend comparison.

Figure 6. Lifecycle completion does not specify experimental policy. **A**, Both complete agent systems closed all 60 matched batch lifecycles, but Codex committed every batch to final assay whereas DeepSeek V4 Flash explicitly discarded 36. **B**, Their non-final instrument use was nearly identical, while their primitive-operation use and terminal policies differed. Fractions use the common ten-campaign allowances. These are complete-system behavioral profiles, not an isolated model-backend comparison.

material semantics, instruments, resource endowments and failure laws are executable components rather than constraints imposed by one physical laboratory. They can therefore be recombined while agent authority and audit semantics remain fixed. This programmability is what turns experimental agency from an anecdotal trace into a scalable object of study.

The second agent system supplies an initial interface-transportability demonstration, not a general agent ranking. The next scientific use of this apparatus is a factorial measurement program: randomly sampled worlds, multiple mechanism families, multiple complete agent systems, controlled evidence access and matched resource endowments. Such experiments can estimate world heterogeneity, trajectory variability and intervention response hierarchically, and can test whether lifecycle reliability predicts transfer, recovery from misinformation or behavior under scarcity.

Synthetic instruments and scoring laws make those interventions inexpensive and repeatable. A calibrated physical or high-fidelity bridge can then test which trajectory phenomena transfer to a particular laboratory system. The two forms of evidence are complementary: executable worlds identify controlled behavioral structure; physical laboratories establish deployment validity.

10. Methods

10.1 Environment qualification

The task registry and runtime-domain audit declare task contracts, typed operations, instrument interfaces, state invariants and evaluator-bound success metrics. Qualification required deterministic reachability through 415 complete boundary cases and binding of all 62 declared endpoints to evaluator state. The qualified surface contains 15 tasks, 28 operation types and five instruments. These counts characterize supported environment capabilities; empirical agent results are reported only for the task families actually exercised.

10.2 Compiled-control protocol

Compiled control covered electrochemical conversion and reaction-to-crystallization. Each task used physical world seeds 0–9 and three information conditions: opaque material codes, anonymous nominal properties and a commit-frozen misindexed prior. Each participant session selected 20 complete experiments, after which a replay verifier recomputed all scores from the immutable reports. Classical policies used the same world identities, budgets and information contracts.

The opaque condition replaced material identities by stable anonymous codes. The nominal condition exposed the correct anonymous material-family property rows without revealing latent world residuals. The misindexed condition transposed one targeted material row chosen using independent qualification worlds before the formal campaigns; the affected mapping was fixed across the ten formal worlds. These conditions therefore modify the supplied prior while holding the physical world, action space, score and bud-

get fixed. Opaque, nominal and misindexed campaigns entered the release as sequential commit-frozen extensions that reused the earlier matched cells. We therefore report matched-world associations and do not use execution order as a causal estimand.

The electrochemical endpoint is the gated weighted sum of selective product yield (0.30), electrochemical selectivity (0.15), conversion (0.10), Faradaic efficiency (0.12), transport efficiency (0.10), ohmic efficiency (0.08) and energy efficiency (0.15); selective yield supplies the multiplicative gate. The reaction-to-crystallization endpoint combines reaction score (0.25), crystal yield (0.25), crystal purity (0.20), crystal size (0.10), crystal-size- distribution quality (0.20) and a fines-fraction penalty (-0.10). The scoring contract was identical across information arms within a task.

Compiled participants used the Codex subscription transport with model alias `gpt-5.6-sol` at medium reasoning effort, structured response output, Codex tools disabled and no session persistence. G0 and G2 therefore share a model alias and reasoning setting but use different scaffolds and action interfaces; they are complementary evidence layers, not a matched causal comparison of authority.

The nonduplicated total comprises 2,280 participant executions and 27,300 classical-control executions. Statistical summaries treat the paired physical world, not each simulator execution, as the analysis unit. Seeds 0–9 form the complete designed set for the matched-condition analysis. Information contrasts report mean and median world differences, positive/negative counts, exact sign summaries, leave-one-world-out mean ranges and 100,000-draw, commit-frozen percentile world-bootstrap intervals as finite-world stability summaries. A 97.5% interval is reported for each task as a multiplicity-adjusted descriptive stability interval across the two pre-specified tasks; no world-superpopulation coverage claim is made.

The information-matched classical suite comprised uniform random search, Latin hypercube sampling, local greedy perturbation, Gaussian-process expected improvement, random-forest expected improvement, safety-constrained Gaussian-process expected improvement and a multi-output telemetry random-forest policy. Electrochemical calibration additionally included privileged material-descriptor and transport-prior policies together with commit-frozen shuffled-descriptor negative controls. The privileged policies calibrate what the environment permits; they are not information-matched agent comparators.

The misindexing manipulation transposed one targeted material row selected on independent qualification worlds. Commit-frozen checks separately evaluated initial behavior change, later action correction, performance restoration and their joint criterion.

Epistemic diagnostics were scored independently of the optimized endpoint. At final synthesis, the agent predicted increase, decrease or no material change for three frozen one-factor intervention queries and their three reg-

istered metrics. Each query was then executed as paired reference/intervention experiments with two replicates and common observation-noise identities. The executed difference was labelled increase or decrease when it crossed the frozen absolute threshold of 0.01 and no material change otherwise. Held-out directional accuracy is the fraction of these query-by-metric labels predicted correctly; the prediction call could not alter the submitted recommendation. The held-out Brier score is the mean of $(c - y)^2$, where c is the submitted confidence and y indicates whether that directional prediction was correct.

Declared world-understanding claims were matched against a frozen vocabulary of observable cause sets, effects, admissible directional relations and mechanism tags. Unsupported-claim rate is the fraction of submitted declarations whose cause-set/effect structure has no reference match. Directional accuracy among matched declarations, structural edge precision/recall, mechanism-tag scores and a declaration-level confidence Brier score were retained as separate diagnostics, so no single epistemic statistic was treated as a proxy for the others.

10.3 Primitive-control protocol and resource ledger

The autonomous electrochemical protocol exposed typed tools for adding reagent and solvent, setting potential/current/material profile, electrolyzing, measuring, inspecting public status/history, terminating and requesting the final assay or explicitly discarding a batch. Each cell contained six vessel opportunities. The campaign card bounded vessels, raw stocks, non-final instrument uses, operation attempts and provider decisions. Resource state was stored in an external artifact and exposed through compact queries or a bounded public state view; it was not repeatedly copied into the model context.

Native Codex used model alias `gpt-5.6-sol` with medium reasoning effort. Each vessel used a fresh provider session. The environment accepted only typed tool transactions; explanatory prose could not change physical state. All 60 Codex vessels terminated with a committed final assay.

DeepSeek used the exact model identifier `deepseek-v4-flash`. One provider decision was requested for each primitive operation, with JSON-object transport and local validation against the dynamically available action schema. The provider had no shell or MCP authority. A failed structured response could be retried up to six times before the corresponding logical decision failed; failed receipts and their token accounting remained in the audit. Five world pairs ran concurrently, with arms serialized within each physical pair. The formal run used 901 provider calls for 889 accepted operations; 12 malformed responses were recovered without replacing an observed trajectory. Maximum estimated prompt size was 3,996 tokens under a frozen 4,800-token cap.

For the shared cross-system analysis, a batch lifecycle was closed by either a committed final assay or an explicit discard. Execution validity required all six vessel starts and closures, a reconciled resource ledger, exact transition

replay and a complete provider-decision or provider-session audit. Task outcome was recorded separately from transport validity. The two systems shared all physical identity, material, noise, workflow, scoring and resource-card fields in each of the ten cells. Their model and decision transports intentionally differed, so cross-system results were interpreted as complete-system behavioral profiles and not as a causal model-backend contrast.

10.4 Operational trajectory readouts

For the Codex development and fresh-session analyses, let $s_1, \dots, s_K$ be the final-assay scores in a campaign, with $K = 6$, and let $b_t = \max_{j \leq t} s_j$ be the online incumbent.

Within-campaign best-discovery position is the first index of the observed campaign maximum, normalized to $[0, 1]$:

$$d = \frac{\min\{t : s_t = \max_j s_j\} - 1}{K - 1}.$$

For retention fraction q , assay $t > 1$ retains the incumbent when $s_t \geq qb_{t-1}$. Online retention is the fraction of the $K - 1$ opportunities satisfying this rule. A loss episode begins below the same boundary; its reference incumbent remains fixed until a later assay recovers to that boundary. Maximum absolute drawdown is $\max_t \max(0, b_{t-1} - s_t)$. Terminal-to-best ratio is $s_K / \max_t s_t$ when the observed best is positive. The primary retention fraction was $q = 0.90$; $q = 0.80$ and $q = 0.95$ were sensitivity definitions. Raw terminal score is s_K . We compare its nominal-minus-opaque contrast with the best-score contrast as the endpoint-independent directional diagnostic. Terminal-to-best remains a useful relative-retention readout, but because its denominator contains the campaign best, it is supporting rather than algebraically independent when shown beside a best-score contrast.

These are operational trajectory readouts. "Discovery" refers to discovery of the best condition observed within that campaign, not identification of the global optimum of the hidden world.

10.5 Fresh-session replication

The replication crossed physical world seeds 1 and 3, trajectory replicates `r01-r05`, and opaque/nominal information conditions. Worlds were selected from the development set before launch because their observed development directions differed. Development trajectories were excluded from the replication estimand. Pair order and within-pair arm order were frozen in the schedule.

A provider failure before any accepted operation could be retried up to the frozen limit. A provider or method-resource failure after an accepted operation made the cell terminal and right-censored. Completed and right-censored cells in the authoritative launch were not replaced. Pair differences were computed only when both arms completed; no missing outcome was imputed.

For each world and metric, the primary descriptive rule—frozen after launch while endpoint and lifecycle outcomes remained uninspected—classified a direction when at least

75% of available differences shared a sign and the median shared that direction. With four complete pairs this is a three-of-four rule. Otherwise the result was mixed. The four primary lifecycle metrics were best-discovery position, online retention, maximum absolute drawdown and terminal-to-best ratio; best and mean scores were endpoint diagnostics.

10.6 Sensitivity analyses

The frozen primary analysis was not changed. A separately hashed P0 sensitivity artifact evaluated directional thresholds 0.60, 0.75 and 0.80; inclusion or exclusion of exact zero differences; retention fractions 0.80, 0.90 and 0.95; and every positive/negative/zero sign assignment to the two missing pair differences. Because lifecycle metrics share the same six assay outcomes, the eight world-by-metric classifications are treated as a descriptive summary, not as eight independent inferential units. The raw-terminal diagnostic was computed directly from the last paired assay contrast and does not alter the frozen classification artifact.

10.7 First-launch infrastructure incident

The commit-frozen replication protocol was first launched on 1 August 2026. A detached outer Python process disappeared after `cell-001` had completed six vessels and `cell-002` had recorded four accepted operations. The cell-level protocol specified right-censoring after any accepted action and no rerun of a terminal cell. The decision to exclude and restart the entire launch therefore constitutes a protocol deviation at the launcher level.

The decision was made without changing the protocol, schedule, worlds, arms, budgets or analysis rule. The original directory was retained immutably; its completed cell and partial trajectory are included in the public trajectory archive. The authoritative matrix is the second launch and remains the primary analysis. The excluded launch is not pooled into primary pairs. As a transparent descriptive check, its completed nominal world-1/`r01` cell had six scores from 0.654 to 0.730 (mean 0.710); pairing it across launches with the corresponding formal opaque trajectory gives positive best-score, mean-score, retention and terminal contrasts and a smaller drawdown. This direction is compatible with, and not required for, the primary conclusion that at least six lifecycle classifications remain mixed.

10.8 Scope-stopped multiworld extension

After the primary replication, a prospective 16-world extension was launched to estimate broader heterogeneity. The owner stopped it as a scope decision after three complete pairs and one right-censored cell, without inspecting any complete-pair scores or arm contrasts. The parent matrix was incomplete, all partial trajectories were retained, and none of its outcomes enters the present estimand, figures or inferential language. This extension is an execution record for future multiworld work, not an additional result of this paper.

10.9 Provenance, public boundary and replay

Source, configuration, world, material, observation and trajectory identities are SHA-256 bound. The evaluator trajectory contains hidden physical identity; the agent-facing `current.json` and `history.jsonl` expose only the public schema. Public-boundary tests compare those schemas and inspect representative workspaces for hidden-field leakage.

The release contains the self-hashed derived-data object, P0 sensitivity object, world-level tables, all 20 compact formal trajectories, both durable trajectories from the excluded first launch, a terminal file index and an independent verification attestation. Compact trajectories omit provider response content and hidden evaluator identity while retaining the fields required for exact physical-transition and resource replay.

11. Data and code availability

Code, configuration, derived data, figure generators, the arXiv source package and paper-sufficient public trajectories are publicly available in the MIT-licensed ChemWorld repository at github.com/sunyrain/ChemWorld. The versioned paper release is rooted at `benchmark/releases/chemworld-serious-v1`, and its manifest binds every paper artifact to its SHA-256 identity. The G0 raw-file index covers 1,441 files across four immutable source roots; the tracked world-level summaries and public derived-data object reproduce every main-text number, table and figure. The G2 public archive contains compact replayable Codex trajectories for all formal replication cells and for the first-launch infrastructure incident. A separate self-hashed artifact binds the matched Codex/DeepSeek complete-system comparison to both source audit identities and reports all ten physical-identity checks. The release additionally contains all ten compact DeepSeek trajectories (889 replay-verified primitive operations) and a terminal file-level hash index. Provider authentication, unrestricted provider responses and hidden evaluator identities are excluded from the public package. The 17.7-GB G0 raw roots are bound by the public file-level hash index but are not included in the repository and have not yet received a durable external archive identifier; raw-byte access is therefore not presently available from a permanent archive. The tracked world-level summaries and derived-data object are sufficient to regenerate the paper’s reported analyses.

12. Conclusion

ChemWorld turns the act of experimentation into a controlled scientific object. Its executable worlds allow an agent to choose operations, seek evidence, spend resources, experience failure and close experimental lifecycles while physical identity remains matched and every consequence remains replayable. The resulting evidence separates an endpoint from the process that produced it: distinct complete agent systems express different assay and discard policies, while task outcome, prediction, retention, recovery and fresh-session repeatability remain separate readouts.

The central message is therefore simple and actionable: **an endpoint is a result, not an explanation of experimental agency; the process itself can now be measured.**

Appendix A. P0 robustness summary

The main continuous endpoint diagnostic uses raw terminal score: two of eight complete pairs are sign-discordant with best score and the descriptive Pearson correlation is +0.826. The table below retains the frozen categorical lifecycle analysis as a supporting sensitivity summary.

Table 2. Sensitivity of the supporting directional classification. Exact-zero handling affects retention classifications because several paired retention differences are zero. The complete threshold-by-zero grid spans 2–8 mixed classifications; under every missing-sign assignment at the frozen rule, at least six remain mixed.

Sensitivity setting	Mixed
Primary: 75% direction, zeros included, 90% retention	6/8
60% direction, zeros included	6/8
60% direction, zeros excluded	2/8
75% direction, zeros excluded	5/8
80% direction, zeros included	8/8
80% direction, zeros excluded	7/8
80% retention definition	5/8
95% retention definition	6/8
Arbitrary missing-pair signs	6–8/8

Appendix B. Reproducibility artifacts

The paper-data object, sensitivity object, cross-agent-system comparison and figure manifest are self-hashed. All figures are rendered from these frozen objects. The public trajectory archives contain 20 formal Codex replication cells—18 complete and two right-censored—, the two durable first-launch cells, and all ten DeepSeek demonstration cells. Each compact trajectory passes the repository’s physical replay verifier. The arXiv bundle includes the exact figure PDFs, BibTeX database, generated `main.tex` and source Markdown used to produce the submitted PDF. A self-hashed build manifest accompanies the bundle and records the identities of the PDF, source archives and included source files.

References

- [1] Nathan J. Szymanski et al. An autonomous laboratory for the accelerated synthesis of inorganic materials. *Nature*, 624:86–91, 2023. doi: 10.1038/s41586-023-06734-w.
- [2] Tianyi Dai, Sriram Vijayakrishnan, Filip T. Szczypinski, et al. Autonomous mobile robots for exploratory synthetic chemistry. *Nature*, 635:890–897, 2024. doi: 10.1038/s41586-024-08173-7.
- [3] Kourosh Darvish, Marta Skreta, Yuchi Zhao, et al. ORGANA: A robotic assistant for automated chemistry experimentation and characterization. *Matter*, 8(2), 2025. doi: 10.1016/j.matt.2024.10.015.
- [4] Aikaterini Vriza, Michael H. Prince, Tao Zhou, Henry Chan, and Mathew J. Cherukara. Operating advanced scientific instruments with AI agents that learn on the job. *npj Computational Materials*, 12:160, 2026. doi: 10.1038/s41524-026-02005-0.
- [5] Daniil A. Boiko, Robert MacKnight, Ben Kline, and Gabe Gomes. Autonomous chemical research with large language models. *Nature*, 624:570–578, 2023. doi: 10.1038/s41586-023-06792-0.
- [6] Andres M. Bran, Sam Cox, Oliver Schilter, Carlo Baldassari, Andrew D. White, and Philippe Schwaller. Augmenting large language models with chemistry tools. *Nature Machine Intelligence*, 6:525–535, 2024. doi: 10.1038/s42256-024-00832-8.
- [7] Gihan Panapitiya, Emily Saldanha, Heather Job, et al. AutoLabs: cognitive multi-agent systems with self-correction for autonomous chemical experimentation. *Scientific Reports*, 16:19554, 2026. doi: 10.1038/s41598-026-45593-z.
- [8] Simone Pilon, Elia Savino, Oliver M. Bayley, et al. A flexible and affordable self-driving laboratory for automated reaction optimization. *Nature Synthesis*, 2026. doi: 10.1038/s44160-026-01053-0.
- [9] Kobi C. Felton, Jan G. Rittig, and Alexei A. Lapkin. Summit: Benchmarking machine learning methods for reaction optimisation. *Chemistry–Methods*, 1:116–122, 2021. doi: 10.1002/cmtd.202000051.
- [10] Florian Häse, Matteo Aldeghi, Riley J. Hickman, Loïc M. Roch, Melodie Christensen, Elena Liles, Jason E. Hein, and Alán Aspuru-Guzik. Olympus: a benchmarking framework for noisy optimization and experiment planning. *Machine Learning: Science and Technology*, 2:035021, 2021. doi: 10.1088/2632-2153/abedc8.
- [11] Chris Beeler, Sriram Ganapathi Subramanian, Kyle Sprague, et al. ChemGymRL: A customizable interactive framework for reinforcement learning for digital chemistry. *Digital Discovery*, 3:742–758, 2024. doi: 10.1039/D3DD00183K.
- [12] Maximilian Bloor, José Torracca, Ilya Orson Sandoval, et al. PC-Gym: Benchmark environments for process control problems, 2024. Preprint, arXiv:2410.22093.
- [13] Peter Jansen, Marc-Alexandre Côté, Tushar Khot, Erin Bransom, Bhavana Dalvi Mishra, Bodhisattwa Prasad Majumder, Oyvind Tafjord, and Peter Clark. DiscoveryWorld: A virtual environment for developing and evaluating automated scientific discovery agents. In *Advances in Neural Information Processing Systems*, volume 37, 2024. doi: 10.52202/079017-0324.

- [14] Kanishk Gandhi, Michael Y. Li, Lyle Goodyear, Agam Bhatia, Louise Li, Aditi Bhaskar, Mohammed Zaman, and Noah D. Goodman. BoxingGym: Benchmarking progress in automated experimental design and model discovery, 2025. Preprint, arXiv:2501.01540.
- [15] Haonan Duan, Stephen Zhewen Lu, Caitlin Fiona Harrigan, Nishkrit Desai, Jiarui Lu, Michał Koziarski, Leonardo Cotta, and Chris J. Maddison. Measuring scientific capabilities of language models with a systems biology dry lab, 2025. Preprint, arXiv:2507.02083.
- [16] Maximilian Nägele and Florian Marquardt. Agentic exploration of physics models. *Physical Review X*, 16: 031002, 2026. doi: 10.1103/xnqc-q6nt.
- [17] Lin Chen, Yunke Zhang, Jie Feng, et al. AI agent behavioral science. *Humanities and Social Sciences Communications*, 13:1011, 2026. doi: 10.1057/s41599-026-07316-7.
- [18] Amy Xin, Jiening Siow, Junjie Wang, et al. EurekaAgent: Agent environment engineering is all you need for autonomous scientific discovery, 2026. Preprint, arXiv:2606.13662.
- [19] Martiño Ríos-García, Nawaf Alampara, Chandan Gupta, Indrajeet Mandal, Sajid Mannan, Ali Asghar Aghajani, N. M. Anoop Krishnan, and Kevin Maik Jablonka. Ai scientists produce results without reasoning scientifically, 2026. Preprint, arXiv:2604.18805.