



```
printf("hello, world!\n");
```

Practice Mode

supachawal@gmail.com | [Contest scoreboard](#) | [Sign out](#)

Qualification Round 2015

A. Standing Ovation[B. Infinite House of Pancakes](#)[C. Dijkstra](#)[D. Ominous Omino](#)[Questions asked](#)

- Submissions

Standing Ovation

7pt	Not attempted 22964/26528 users correct (87%)
10pt	Not attempted 19346/22732 users correct (85%)

Infinite House of Pancakes

9pt	Not attempted 7805/17231 users correct (45%)
12pt	Not attempted 5442/6704 users correct (81%)

Dijkstra

11pt	Not attempted 6663/9721 users correct (69%)
17pt	Not attempted 2492/4819 users correct (52%)

Ominous Omino

8pt	Not attempted 7342/9200 users correct (80%)
26pt	Not attempted 686/4030 users correct (17%)

- Top Scores

kyc	100
ksun48	100
darnley	100
AntiForest	100
shik	100
Nicolas16	100
ProjectYoung	100
azariamuh	100

Problem A. Standing Ovation

This contest is open for practice. You can try every problem as many times as you like, though we won't keep track of which problems you solve. Read the [Quick-Start Guide](#) to get started.

Small input
7 points

Solve A-small

Judge's response for last submission: Correct.

Large input
10 points

Solve A-large

Judge's response for last submission: Correct.

Problem

It's opening night at the opera, and your friend is the prima donna (the lead female singer). You will not be in the audience, but you want to make sure she receives a standing ovation -- with every audience member standing up and clapping their hands for her.

Initially, the entire audience is seated. Everyone in the audience has a *shyness level*. An audience member with shyness level S_i will wait until at least S_i other audience members have already stood up to clap, and if so, she will immediately stand up and clap. If $S_i = 0$, then the audience member will always stand up and clap immediately, regardless of what anyone else does. For example, an audience member with $S_i = 2$ will be seated at the beginning, but will stand up to clap later after she sees at least two other people standing and clapping.

You know the shyness level of everyone in the audience, and you are prepared to invite additional friends of the prima donna to be in the audience to ensure that everyone in the crowd stands up and claps in the end. Each of these friends may have any shyness value that you wish, not necessarily the same. What is the minimum number of friends that you need to invite to guarantee a standing ovation?

Input

The first line of the input gives the number of test cases, T . T test cases follow. Each consists of one line with S_{\max} , the maximum shyness level of the shyest person in the audience, followed by a string of $S_{\max} + 1$ single digits. The k th digit of this string (counting starting from 0) represents how many people in the audience have shyness level k . For example, the string "409" would mean that there were four audience members with $S_i = 0$ and nine audience members with $S_i = 2$ (and none with $S_i = 1$ or any other value). Note that there will initially always be between 0 and 9 people with each shyness level.

The string will never end in a 0. Note that this implies that there will always be at least one person in the audience.

wo...	100
ctunoku	100

Output

For each test case, output one line containing "Case #x: y", where x is the test case number (starting from 1) and y is the minimum number of friends you must invite.

Limits

$1 \leq T \leq 100$.

Small dataset

$0 \leq S_{\max} \leq 6$.

Large dataset

$0 \leq S_{\max} \leq 1000$.

Sample

Input	Output
4	Case #1: 0
4 11111	Case #2: 1
1 09	Case #3: 2
5 110011	Case #4: 0
0 1	

In Case #1, the audience will eventually produce a standing ovation on its own, without you needing to add anyone -- first the audience member with $S_i = 0$ will stand up, then the audience member with $S_i = 1$ will stand up, etc.

In Case #2, a friend with $S_i = 0$ must be invited, but that is enough to get the entire audience to stand up.

In Case #3, one optimal solution is to add two audience members with $S_i = 2$.

In Case #4, there is only one audience member and he will stand up immediately. No friends need to be invited.

All problem statements, input data and contest analyses are licensed under the [Creative Commons Attribution License](https://creativecommons.org/licenses/by/4.0/).

© 2008-2015 Google [Google Home](https://www.google.com/) - [Terms and Conditions](https://policies.google.com/terms) - [Privacy Policies and Principles](https://policies.google.com/privacy)

