

ORBIT COFFEE - PREFLIGHT REPORT

Overall status: HOLD FOR SOURCE / FACTORY PROFILE CONFIRMATION. Production geometry and nominal output resolution pass. The approved master is a low-resolution flattened RGB preview, so the PDF is suitable for controlled factory proofing but not recommended for final plate release without the actions below.

FILE	VALUE
Production PDF	orbit-coffee_production_120x200mm_CMYK_v0.pdf
Pages	2 - front, back
Trim / bleed	120 x 200 mm / 3 mm each side
Page size	126 x 206 mm
Color / raster	DeviceCMYK + embedded Generic CMYK output intent / 1488 x 2433 px

CHECK	STATUS	RESULT
Front and back supplied	PASS	2 pages: page 1 front, page 2 back.
Finished size 120 x 200 mm	PASS	TrimBox is exactly 120 x 200 mm on both pages.
3 mm bleed	PASS	BleedBox/MediaBox is 126 x 206 mm; TrimBox inset is 3 mm per edge.
CMYK	PASS	Page raster is DeviceCMYK; Generic CMYK ICC output intent is embedded.
300 dpi output	PASS	Each page raster is 1488 x 2433 px, approximately 300 ppi at 126 x 206 mm.
300 ppi source detail at final size	FAIL	Approved flattened panel provides approximately 104 ppi effective detail at 120 mm width; resampling does not create original detail.
Preserve front composition and brand wordmark	PASS	Central approved front pixels were uniformly scaled only; no wordmark redraw, stretch, or element repositioning.
Adapt approved square panel to 120 x 200 mm	PASS	Only perimeter background was extended above/below; approved central panel remains centered and undistorted.
No presentation guides in production art	PASS	Crop marks, FRONT/BACK labels, sheet background, and dotted layout-guide strokes are excluded from production pages.
Back information area clear and editable	WARN	Area is visually clear, but remains flattened raster; layered/vector source is required for true text editability.
Press-specific CMYK conversion	WARN	No printer ICC profile was supplied; Generic CMYK is used and must be confirmed or replaced by the factory.
No missing fonts or live transparency	PASS	Production pages contain flattened opaque CMYK raster only; no font dependency or transparency objects.

REQUIRED BEFORE FINAL PLATE RELEASE

1. Supply a layered/vector master or native 300 ppi artwork at 120 x 200 mm. 2. Confirm the factory CMYK ICC/output condition. 3. Confirm whether the centered background-extension adaptation is accepted. 4. Supply layered back copy if the information fields must remain editable.