Google Discussions

Exam Professional Cloud Network Engineer All Questions
View all questions & answers for the Professional Cloud Network Engineer exam

Go to Exam

EXAM PROFESSIONAL CLOUD NETWORK ENGINEER TOPIC 1 QUESTION 190 DISCUSSION

Actual exam question from Google's Professional Cloud Network Engineer
Question #: 190
Topic #: 1
[All Professional Cloud Network Engineer Questions]

Your organization wants to set up hybrid connectivity with VLAN attachments that terminate in a single Cloud Router with 99.9% uptime. You need to create a network design for your on-premises router that meets those requirements and has an active/passive configuration that uses only one VLAN attachment at a time. What should you do?

A. Create a design that uses the LOCAL_PREF BGP attribute to influence the egress path from Google Cloud to the on-premises environment.

B. Create a design that uses an equal-cost multipath (ECMP) with flow-based hashing on your on-premises devices.

C. Create a design that uses a BGP multi-exit discriminator (MED) attribute to influence the egress path from Google Cloud to the on-premises environment.

D. Create a design that uses the AS_PATH BGP attribute to influence the egress path from Google Cloud to the on-premises environment.

Show Suggested Answer

by b0b25 at *Feb. 22, 2025, 3:05 a.m.*

Comments

Type your comment...

Submit

n2183712847 10 months, 4 weeks ago

Selected Answer: C

BGP multi-exit discriminator (MED)

upvoted 1 times

mohitms1996 12 months ago

Selected Answer: C

You're absolutely right! Local Preference (LOCAL_PREF) is a BGP attribute used to influence egress traffic within the same Autonomous System (AS). It helps on-premises routers decide which path to use when sending traffic to Google Cloud.

However, in the given scenario, we need to influence Google Cloud's egress path to on-premises. Multi-Exit Discriminator (MED) is the preferred attribute for this because it influences the egress traffic from Google Cloud towards on-premises.

upvoted 1 times

RKS_2021 1 year ago

Selected Answer: C

Changing answer to C

upvoted 1 times

rich_maverick 1 year ago

Selected Answer: A

A is correct. MED is a negotiated attribute between routers and is not guaranteed. Local Preference has higher priority than MED.

upvoted 1 times

1f01b87 1 year ago

Selected Answer: C

The BGP multi-exit discriminator (MED) attribute is used in BGP configurations to influence the choice of path in an active/passive setup by prioritizing one path over another for egress traffic. This is ideal for a design that uses only one VLAN attachment at a time.

upvoted 1 times

1f01b87 1 year ago

Selected Answer: C

It's C as per this google doc.

https://cloud.google.com/network-connectivity/docs/interconnect/how-to/dedicated/configuring-onprem-routers#configuring-devices-for-activepassive-forwarding

upvoted 3 times

RKS_2021 1 year ago

Selected Answer: A

A is correct

upvoted 1 times

b0b25 1 year, 1 month ago

Selected Answer: A

Local Preference is used to influence egress traffic within an Autonomous System (AS). It determines which exit point to use for outbound traffic

upvoted 2 times

kirrim 3 months ago

Local Preference might indeed be what you want to configure on your on-prem routers to influence path selection for traffic leaving on-prem and headed towards GCP. But (A) is incorrect, because it specifically says Local Preference would be used to influence egress traffic coming from GCP towards on-prem. Which is backwards.

upvoted 1 times

EXAMTOPICS

Platform

- Home
- All Exams
- Examtopics PRO

© 2026 ExamTopics

Examtopics.com (https://www.examtopics.com/) is operated by Learners Ltd: Office 15, 321-323 High Road, Chadwell Heath, Essex, England, RM6 6AX.