

SuperCampus

Backend API Reference

Implementation-synchronized contract generated from the Rust Axum routes. Rate limiting, OAuth, webhooks, file APIs, and 422 responses are not implemented.

SPECIFICATION

OpenAPI 3.1.0

API VERSION

0.1.0

OPERATIONS

81

SCHEMAS

30

Base URL `http://localhost:4000` (Local development)

In deployment the browser calls the Next.js origin at `/api/*`, which proxies to this service. WebSocket upgrades are not proxied and must address this API directly.

Generated 07 August 2026 from `docs/openapi.yaml`

Contents

System	2	CRM Pipeline	13
Authentication	7	CRM Dashboard	6
User State	2	CRM Events	1
Platform	7	CRM Forms	13
Configuration	2	CRM Communications	3
Dynamic Records	5	CRM Templates	4
CRM System	1	CRM Configuration	3
CRM Access	2	Authentication schemes	3
CRM Leads	6	Schema reference	30
CRM Assignment	4		

Authentication schemes

Scheme	Type	Carried in	Notes
bearerAuth	http / bearer	JWT	HS256 access JWT
accessCookie	apiKey	cookie: sc_access	
refreshCookie	apiKey	cookie: sc_session	

System

GET /health

Get process health

Auth: Public · Operation: getHealth

RESPONSES

Code	Meaning	Body
200	Healthy	HealthDocument
500	Unexpected storage or service failure	—

GET /ready

Check runtime and PostgreSQL readiness

Auth: Public · Operation: getReadiness

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
500	Unexpected storage or service failure	—

Authentication

POST /api/auth/forgot-password

Request a password reset link

Auth: Public · Operation: forgotPassword

Emails a single-use reset link when the address belongs to an active account. Always answers 202 with an identical body so the endpoint cannot be used to discover registered addresses. Throttled to 3 requests per account per 15 minutes.

REQUEST BODY required

ForgotPasswordRequest

RESPONSES

Code	Meaning	Body
202	Request accepted, whether or not the address has an account	DataResponse
400	Malformed request or validation failure	—
500	Unexpected storage or service failure	—

POST /api/auth/login

Create access JWT and refresh session

Auth: Public · Operation: login

REQUEST BODY required

LoginRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
500	Unexpected storage or service failure	—

POST /api/auth/logout

Revoke session and clear cookies

Auth: bearerAuth or accessCookie or refreshCookie · Operation: logout

RESPONSES

Code	Meaning	Body
204	No content	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—

GET /api/auth/me

Get current authenticated session

Auth: bearerAuth or accessCookie · **Operation:** getSession

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—

POST /api/auth/realtime-token

Mint a short-lived realtime handshake token

Auth: Public · **Operation:** realtimeToken

Returns a 60-second token for the CRM WebSocket. Browsers cannot set headers on a WebSocket handshake and Next.js does not proxy upgrades, so the socket dials the API directly and presents this token as ?access_token=. The query credential is honoured only on /api/v1/crm/events.

RESPONSES

Code	Meaning	Body
200	Token and its expiry	DataResponse
401	Authentication required or credential invalid	—
500	Unexpected storage or service failure	—

POST /api/auth/refresh

Rotate refresh token and issue access JWT

Auth: refreshCookie · **Operation:** refreshSession

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
500	Unexpected storage or service failure	—

POST /api/auth/reset-password

Complete a password reset

Auth: Public · **Operation:** resetPassword

Consumes a single-use reset token, replaces the password, and revokes every active session for the account. Returns 400 when the token is unknown, expired, or already used.

REQUEST BODY **required**

ResetPasswordRequest

RESPONSES

Code	Meaning	Body
200	Password updated and all sessions revoked	DataResponse
400	Malformed request or validation failure	—
500	Unexpected storage or service failure	—

User State

GET /api/state

Get current user UI state

Auth: bearerAuth or accessCookie · Operation: getUserState

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—

PUT /api/state

Save current user UI state

Auth: bearerAuth or accessCookie · Operation: putUserState

REQUEST BODY **required**

SaveStateRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—

Platform

GET /api/v1/

Get API index

Auth: bearerAuth or accessCookie · Operation: `getApiIndex`

RESPONSES

Code	Meaning	Body
200	Successful response	<code>DataResponse</code>
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—

GET /api/v1/bootstrap

Get tenant/user bootstrap catalogs

Auth: bearerAuth or accessCookie · Operation: `getBootstrap`

RESPONSES

Code	Meaning	Body
200	Successful response	<code>DataResponse</code>
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—

GET /api/v1/modules

List registered modules

Auth: bearerAuth or accessCookie · Operation: `listModules`

RESPONSES

Code	Meaning	Body
200	Successful response	<code>DataResponse</code>
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—

GET /api/v1/modules/{module_key}

Get a registered module

Auth: bearerAuth or accessCookie · Operation: `getModule`

PARAMETERS

Name	In	Required	Type	Description
module_key	path	yes	string	

RESPONSES

Code	Meaning	Body
200	Successful response	<code>DataResponse</code>
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
500	Unexpected storage or service failure	—

GET /api/v1/navigation

Navigation the caller may see

Auth: Public · Operation: `getNavigation`

Workspace and settings sections resolved from the institution's navigation configuration and the caller's live effective grants. A tenant administrator controls what a user can reach by composing role permissions; changes apply without a new token or redeploy. Returns permissions, roles and scopes alongside the sections.

RESPONSES

Code	Meaning	Body
200	Sections visible to the caller	<code>DataResponse</code>
401	Authentication required or credential invalid	—
500	Unexpected storage or service failure	—

GET /api/v1/services

List platform services

Auth: bearerAuth or accessCookie · Operation: `listServices`

RESPONSES

Code	Meaning	Body
200	Successful response	<code>DataResponse</code>
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—

GET /api/v1/services/{service_key}

Get a platform service

Auth: bearerAuth or accessCookie · **Operation:** getService

PARAMETERS

Name	In	Required	Type	Description
service_key	path	yes	string	

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
500	Unexpected storage or service failure	—

Configuration

GET /api/v1/configuration/{namespace}

Get tenant configuration document

Auth: bearerAuth or accessCookie · Operation: getConfiguration

PARAMETERS

Name	In	Required	Type	Description
namespace	path	yes	string	

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
500	Unexpected storage or service failure	—

PUT /api/v1/configuration/{namespace}

Upsert tenant configuration document

Auth: bearerAuth or accessCookie · Operation: putConfiguration

PARAMETERS

Name	In	Required	Type	Description
namespace	path	yes	string	

REQUEST BODY **required**

PutConfigurationRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—

Dynamic Records

GET /api/v1/{module_key}/records

List tenant module records

Auth: bearerAuth or accessCookie · Operation: listDynamicRecords

PARAMETERS

Name	In	Required	Type	Description
module_key	path	yes	string	

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
500	Unexpected storage or service failure	—

POST /api/v1/{module_key}/records

Create tenant module record

Auth: bearerAuth or accessCookie · Operation: createDynamicRecord

PARAMETERS

Name	In	Required	Type	Description
module_key	path	yes	string	

REQUEST BODY **required**

CreateRecordRequest

RESPONSES

Code	Meaning	Body
201	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
500	Unexpected storage or service failure	—

DELETE /api/v1/{module_key}/records/{record_id}

Delete tenant module record

Auth: bearerAuth or accessCookie · **Operation:** deleteDynamicRecord

PARAMETERS

Name	In	Required	Type	Description
module_key	path	yes	string	
record_id	path	yes	string	

RESPONSES

Code	Meaning	Body
204	No content	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
500	Unexpected storage or service failure	—

GET /api/v1/{module_key}/records/{record_id}

Get tenant module record

Auth: bearerAuth or accessCookie · **Operation:** getDynamicRecord

PARAMETERS

Name	In	Required	Type	Description
module_key	path	yes	string	
record_id	path	yes	string	

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
500	Unexpected storage or service failure	—

PATCH /api/v1/{module_key}/records/{record_id}

Update tenant module record data

Auth: bearerAuth or accessCookie · **Operation:** updateDynamicRecord

PARAMETERS

Name	In	Required	Type	Description
module_key	path	yes	string	
record_id	path	yes	string	

REQUEST BODY **required**

UpdateRecordRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
500	Unexpected storage or service failure	—

CRM System

GET /api/v1/crm/health

Get CRM health

Auth: Public · Operation: getCrmHealth

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

CRM Access

GET /api/v1/crm/permissions/effective

Get effective CRM permissions

Auth: bearerAuth or accessCookie · Operation: `getEffectiveCrmPermissions`

RESPONSES

Code	Meaning	Body
200	Successful response	<code>DataResponse</code>
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	<code>CrmError</code>

GET /api/v1/crm/roles

List CRM roles

Auth: bearerAuth or accessCookie · Operation: `listCrmRoles`

RESPONSES

Code	Meaning	Body
200	Successful response	<code>DataResponse</code>
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	<code>CrmError</code>

CRM Leads

GET /api/v1/crm/leads

List role-scoped leads

Auth: bearerAuth or accessCookie · Operation: listCrmLeads

PARAMETERS

Name	In	Required	Type	Description
stage	query	no	string	
substate	query	no	string	
owner	query	no	string	
source	query	no	string	
globalStatus	query	no	string	
priority	query	no	string	
programId	query	no	string	
search	query	no	string	
createdFrom	query	no	string	
createdTo	query	no	string	
includeArchived	query	no	boolean	
limit	query	no	integer	
offset	query	no	integer	

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/leads

Create and optionally auto-assign a lead

Auth: bearerAuth or accessCookie · **Operation:** createCrmLead

REQUEST BODY required

CreateLeadRequest

RESPONSES

Code	Meaning	Body
201	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

DELETE /api/v1/crm/leads/{id}

Soft-delete a lead

Auth: bearerAuth or accessCookie · **Operation:** deleteCrmLead

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

RESPONSES

Code	Meaning	Body
204	No content	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

GET /api/v1/crm/leads/{id}

Get a lead

Auth: bearerAuth or accessCookie · Operation: getCrMLead

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrMError

PATCH /api/v1/crm/leads/{id}

Update a lead

Auth: bearerAuth or accessCookie · Operation: updateCrMLead

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

UpdateLeadRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrMError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrMError

GET /api/v1/crm/leads/{id}/timeline

Get stage and communication timeline

Auth: bearerAuth or accessCookie · Operation: `getCrmLeadTimeline`

PARAMETERS

Name	In	Required	Type	Description
<code>id</code>	path	yes	string	

RESPONSES

Code	Meaning	Body
200	Successful response	<code>DataResponse</code>
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	<code>CrmError</code>

CRM Assignment

GET /api/v1/crm/assignment/counselors

List counselor capacity/workload

Auth: bearerAuth or accessCookie · Operation: listCrmCounselors

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

PUT /api/v1/crm/assignment/counselors

Upsert counselor capacity

Auth: bearerAuth or accessCookie · Operation: putCrmCounselor

REQUEST BODY **required**

CounselorCapacityRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/leads/{id}/assign

Assign a lead

Auth: bearerAuth or accessCookie · Operation: assignCrmLead

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

AssignLeadRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/leads/{id}/reassign

Reassign a lead

Auth: bearerAuth or accessCookie · Operation: `reassignCrmLead`

PARAMETERS

Name	In	Required	Type	Description
<code>id</code>	path	yes	string	

REQUEST BODY **required**

`AssignLeadRequest`

RESPONSES

Code	Meaning	Body
200	Successful response	<code>DataResponse</code>
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	<code>CrmError</code>
500	Unexpected storage or service failure	—
503	CRM database is not configured	<code>CrmError</code>

CRM Pipeline

POST /api/v1/crm/leads/{id}/archive

Archive lead (compatibility alias)

Auth: bearerAuth or accessCookie · **Operation:** archiveCrmLeadAlias

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

ArchiveRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/leads/{id}/defer

Defer lead (compatibility alias)

Auth: bearerAuth or accessCookie · **Operation:** deferCrmLeadAlias

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

IntakeStatusRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/leads/{id}/hold

Place lead on hold (compatibility alias)

Auth: bearerAuth or accessCookie · **Operation:** holdCrmLeadAlias

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

HoldRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/leads/{id}/prospect

Mark lead as prospect (compatibility alias)

Auth: bearerAuth or accessCookie · **Operation:** markCrmLeadProspectAlias

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

IntakeStatusRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/leads/{id}/release-hold

Release hold (compatibility alias)

Auth: bearerAuth or accessCookie · **Operation:** releaseCrmLeadHoldAlias

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY required

ReasonRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/leads/{id}/stage/archive

Archive a lead

Auth: bearerAuth or accessCookie · Operation: archiveCrmLead

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

ArchiveRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/leads/{id}/stage/defer

Defer lead to an intake

Auth: bearerAuth or accessCookie · **Operation:** deferCrmLead

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

IntakeStatusRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/leads/{id}/stage/hold

Place lead on hold

Auth: bearerAuth or accessCookie · Operation: holdCrmLead

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

HoldRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/leads/{id}/stage/move

Move lead stage/substate

Auth: bearerAuth or accessCookie · Operation: moveCrmLeadStage

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

MoveStageRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/leads/{id}/stage/prospect

Mark lead as prospect

Auth: bearerAuth or accessCookie · Operation: markCrmLeadProspect

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

IntakeStatusRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/leads/{id}/stage/release-hold

Release lead hold

Auth: bearerAuth or accessCookie · **Operation:** releaseCrmLeadHold

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

ReasonRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/leads/{id}/stage/unarchive

Restore an archived lead

Auth: bearerAuth or accessCookie · **Operation:** unarchiveCrmLead

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

UnarchiveRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/leads/{id}/unarchive

Restore lead (compatibility alias)

Auth: bearerAuth or accessCookie · **Operation:** unarchiveCrmLeadAlias

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

UnarchiveRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

CRM Dashboard

GET /api/v1/crm/dashboard

Get CRM dashboard board payload

Auth: bearerAuth or accessCookie · Operation: `getCrmDashboard`

PARAMETERS

Name	In	Required	Type	Description
stage	query	no	string	
substate	query	no	string	
owner	query	no	string	
source	query	no	string	
globalStatus	query	no	string	
priority	query	no	string	
programId	query	no	string	
search	query	no	string	
createdFrom	query	no	string	
createdTo	query	no	string	
includeArchived	query	no	boolean	
limit	query	no	integer	
offset	query	no	integer	

RESPONSES

Code	Meaning	Body
200	Successful response	<code>DataResponse</code>
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	<code>CrmError</code>

GET /api/v1/crm/kanban/board

Get role-scoped Kanban board

Auth: bearerAuth or accessCookie · **Operation:** getCrmKanbanBoard

PARAMETERS

Name	In	Required	Type	Description
stage	query	no	string	
substate	query	no	string	
owner	query	no	string	
source	query	no	string	
globalStatus	query	no	string	
priority	query	no	string	
programId	query	no	string	
search	query	no	string	
createdFrom	query	no	string	
createdTo	query	no	string	
includeArchived	query	no	boolean	
limit	query	no	integer	
offset	query	no	integer	

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

GET /api/v1/crm/kanban/my-board

Get current actor Kanban board

Auth: bearerAuth or accessCookie · **Operation:** getMyCrmKanbanBoard

PARAMETERS

Name	In	Required	Type	Description
stage	query	no	string	
substate	query	no	string	
owner	query	no	string	
source	query	no	string	
globalStatus	query	no	string	
priority	query	no	string	
programId	query	no	string	
search	query	no	string	
createdFrom	query	no	string	
createdTo	query	no	string	
includeArchived	query	no	boolean	
limit	query	no	integer	
offset	query	no	integer	

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

GET /api/v1/crm/kanban/stages

List CRM stage definitions

Auth: bearerAuth or accessCookie · **Operation:** listCrmStages

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

GET /api/v1/crm/kanban/stages/{stage}/count

Get paged lead count for a stage

Auth: bearerAuth or accessCookie · **Operation:** getCrMStageCount

PARAMETERS

Name	In	Required	Type	Description
stage	path	yes	string	
stage	query	no	string	
substate	query	no	string	
owner	query	no	string	
source	query	no	string	
globalStatus	query	no	string	
priority	query	no	string	
programId	query	no	string	
search	query	no	string	
createdFrom	query	no	string	
createdTo	query	no	string	
includeArchived	query	no	boolean	
limit	query	no	integer	
offset	query	no	integer	

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrMError

GET /api/v1/crm/kanban/stages/{stage}/leads

List leads in a stage

Auth: bearerAuth or accessCookie · **Operation:** listCrmStageLeads

PARAMETERS

Name	In	Required	Type	Description
stage	path	yes	string	
stage	query	no	string	
substate	query	no	string	
owner	query	no	string	
source	query	no	string	
globalStatus	query	no	string	
priority	query	no	string	
programId	query	no	string	
search	query	no	string	
createdFrom	query	no	string	
createdTo	query	no	string	
includeArchived	query	no	boolean	
limit	query	no	integer	
offset	query	no	integer	

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

CRM Events

GET /api/v1/crm/events

Upgrade to resumable tenant event stream

Auth: bearerAuth or accessCookie · **Operation:** streamCrmEvents

PARAMETERS

Name	In	Required	Type	Description
cursor	query	no	integer	

RESPONSES

Code	Meaning	Body
101	WebSocket protocol upgrade	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

CRM Forms

GET /api/v1/crm/forms

List form definitions

Auth: bearerAuth or accessCookie · Operation: listCrmForms

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/forms

Create form definition

Auth: bearerAuth or accessCookie · Operation: createCrmForm

REQUEST BODY **required**

CreateFormRequest

RESPONSES

Code	Meaning	Body
201	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

DELETE /api/v1/crm/forms/{id}

Soft-delete form

Auth: bearerAuth or accessCookie · **Operation:** deleteCrmForm

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

RESPONSES

Code	Meaning	Body
204	No content	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

GET /api/v1/crm/forms/{id}

Get form definition

Auth: bearerAuth or accessCookie · **Operation:** getCrmForm

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

PATCH /api/v1/crm/forms/{id}

Update form definition (same behavior as PUT)

Auth: bearerAuth or accessCookie · Operation: patchCrmForm

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

UpdateFormRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

PUT /api/v1/crm/forms/{id}

Update form definition

Auth: bearerAuth or accessCookie · Operation: replaceCrmForm

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

UpdateFormRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/forms/{id}/publish

Publish form

Auth: bearerAuth or accessCookie · Operation: publishCrmForm

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

GET /api/v1/crm/forms/{id}/submissions

List form submissions

Auth: bearerAuth or accessCookie · Operation: listCrmFormSubmissions

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/forms/{id}/submit

Submit internal or published form

Auth: bearerAuth or accessCookie · Operation: submitCrmForm

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

REQUEST BODY **required**

SubmitFormRequest

RESPONSES

Code	Meaning	Body
201	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/forms/{id}/unpublish

Return form to draft

Auth: bearerAuth or accessCookie · **Operation:** unpublishCrmForm

PARAMETERS

Name	In	Required	Type	Description
id	path	yes	string	

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

GET /api/v1/crm/forms/published

List every published form

Auth: Public · **Operation:** listPublishedCrmForms

All forms the tenant administrator has published, whatever types they defined. Lets the workspace discover available forms without knowing type names at build time.

RESPONSES

Code	Meaning	Body
200	Published forms	DataResponse
401	Authentication required or credential invalid	—

GET /api/v1/crm/forms/published/type/{form_type}

Published form of one type

Auth: Public · **Operation:** `getPublishedCrmFormByType`

The newest published form of the given type, for example application or document_checklist. enquiry and lead_capture are interchangeable aliases for the intake form. Returns 404 while the form is still a draft.

PARAMETERS

Name	In	Required	Type	Description
<code>form_type</code>	path	yes	string	

RESPONSES

Code	Meaning	Body
200	Published form definition	<code>DataResponse</code>
404	Resource not found	—

POST /api/v1/crm/public/forms/{id}/submit

Submit public enquiry form

Auth: Public · **Operation:** `submitPublicCrmForm`

PARAMETERS

Name	In	Required	Type	Description
<code>id</code>	path	yes	string	
<code>x-tenant-id</code>	header	yes	string	Tenant slug for public enquiry routing

REQUEST BODY **required**

`SubmitFormRequest`

RESPONSES

Code	Meaning	Body
201	Successful response	<code>DataResponse</code>
400	Malformed request or validation failure	—
404	Resource not found	—
409	CRM state conflicts with existing data	<code>CrmError</code>
500	Unexpected storage or service failure	—
503	CRM database is not configured	<code>CrmError</code>

CRM Communications

POST /api/v1/crm/communications/calls

Record call outcome

Auth: bearerAuth or accessCookie · Operation: logCrmCall

REQUEST BODY **required**

SendCommunicationRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/communications/email

Record/queue email communication

Auth: bearerAuth or accessCookie · Operation: sendCrmEmail

REQUEST BODY **required**

SendCommunicationRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/communications/whatsapp

Record/queue WhatsApp communication

Auth: bearerAuth or accessCookie · **Operation:** sendCrMWhatsapp

REQUEST BODY **required**

SendCommunicationRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
404	Resource not found	—
409	CRM state conflicts with existing data	CrMError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrMError

CRM Templates

GET /api/v1/crm/communications/templates

List templates (compatibility alias)

Auth: bearerAuth or accessCookie · **Operation:** listCrmCommunicationTemplates

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/communications/templates

Create template (compatibility alias)

Auth: bearerAuth or accessCookie · **Operation:** createCrmCommunicationTemplate

REQUEST BODY **required**

CreateTemplateRequest

RESPONSES

Code	Meaning	Body
201	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

GET /api/v1/crm/templates

List communication templates

Auth: bearerAuth or accessCookie · Operation: listCrmTemplates

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

POST /api/v1/crm/templates

Create or update communication template

Auth: bearerAuth or accessCookie · Operation: createCrmTemplate

REQUEST BODY **required**

CreateTemplateRequest

RESPONSES

Code	Meaning	Body
201	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

CRM Configuration

GET /api/v1/crm/configuration

Get workflow and automation configuration

Auth: bearerAuth or accessCookie · Operation: getCrmConfiguration

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

PUT /api/v1/crm/configuration/automation-toggles

Upsert automation policy

Auth: bearerAuth or accessCookie · Operation: putCrmAutomationToggle

REQUEST BODY **required**

AutomationToggleRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

PUT /api/v1/crm/configuration/workflow-toggles

Upsert workflow transition policy

Auth: bearerAuth or accessCookie · **Operation:** putCrmWorkflowToggle

REQUEST BODY **required**

WorkflowToggleRequest

RESPONSES

Code	Meaning	Body
200	Successful response	DataResponse
400	Malformed request or validation failure	—
401	Authentication required or credential invalid	—
403	Tenant, role, ownership, or configured policy denied	—
409	CRM state conflicts with existing data	CrmError
500	Unexpected storage or service failure	—
503	CRM database is not configured	CrmError

Schema reference

DataResponse

Property	Type	Required	Notes
data		yes	

HealthDocument

Property	Type	Required	Notes
status	string	yes	
service	string	yes	
version	string	yes	

PlatformError

Property	Type	Required	Notes
error	string	yes	
code	string	yes	

CrmError

Property	Type	Required	Notes
error	object	yes	

LoginRequest

Property	Type	Required	Notes
email	string	yes	
password	string	yes	format: password; write-only

ForgotPasswordRequest

Property	Type	Required	Notes
email	string	yes	format: email

ResetPasswordRequest

Property	Type	Required	Notes
token	string	yes	Single-use token from the emailed reset link
password	string	yes	format: password; minLength: 12; write-only

SaveStateRequest

Property	Type	Required	Notes
state		yes	
action	string null	no	

PutConfigurationRequest

Property	Type	Required	Notes
value		yes	

CreateRecordRequest

Property	Type	Required	Notes
recordType	string	yes	minLength: 1
data		no	

UpdateRecordRequest

Property	Type	Required	Notes
data		yes	

StudentInput

Property	Type	Required	Notes
name	string	yes	minLength: 1
email	string null	no	
phone	string null	no	
whatsapp	string null	no	
parentName	string null	no	
parentPhone	string null	no	

CommunicationPreferences

Property	Type	Required	Notes
preferredChannel	string null	no	
consentGiven	boolean	no	

CreateLeadRequest

Property	Type	Required	Notes
source	string	yes	
sourceDetail		no	
student	StudentInput	yes	
academic		no	
interest		no	
communication	CommunicationPreferences	no	
priority	string null	no	
followUpAt	string null	no	format: date-time
customFields		no	

UpdateLeadRequest

Property	Type	Required	Notes
fullName	string null	no	
email	string null	no	
phone	string null	no	
whatsapp	string null	no	
parentName	string null	no	
parentPhone	string null	no	
academic		no	
interest		no	
priority	string null	no	
followUpAt	string null	no	format: date-time
feePaymentConfirmed	boolean null	no	
documentsVerified	boolean null	no	
scholarshipStatus	string null	no	
customFields		no	

AssignLeadRequest

Property	Type	Required	Notes
userId	string	yes	
reason	string null	no	

MoveStageRequest

Property	Type	Required	Notes
toStage	string	yes	
toSubstate	string null	no	
reason	string null	no	
notes	string null	no	

IntakeStatusRequest

Property	Type	Required	Notes
intakeYear	integer	yes	
intakeMonth	string null	no	
programId	string	yes	
reason	string null	no	

HoldRequest

Property	Type	Required	Notes
reason	string	yes	
holdUntil	string null	no	format: date
reminderDate	string null	no	format: date

ReasonRequest

Property	Type	Required	Notes
reason	string	yes	

ArchiveRequest

Property	Type	Required	Notes
archiveReason	string	yes	
notes	string null	no	

UnarchiveRequest

Property	Type	Required	Notes
restoreToStage	string	yes	
restoreToSubstate	string null	no	
reason	string	yes	

CreateFormRequest

Property	Type	Required	Notes
name	string	yes	minLength: 1
formType	string	yes	minLength: 1
programId	string null	no	
intakeYear	integer null	no	
schema		yes	

UpdateFormRequest

Property	Type	Required	Notes
name	string null	no	
schema		yes	

SubmitFormRequest

Property	Type	Required	Notes
leadId	string null	no	format: uuid
data		yes	

SendCommunicationRequest

Property	Type	Required	Notes
leadId	string	yes	format: uuid
templateKey	string null	no	
subject	string null	no	
content		no	
outcome	string null	no	

CreateTemplateRequest

Property	Type	Required	Notes
templateKey	string	yes	
channel	string	yes	
name	string	yes	
content	string	yes	
language	string null	no	

CounselorCapacityRequest

Property	Type	Required	Notes
userId	string	yes	
displayName	string	yes	
active	boolean null	no	
maxCapacity	integer null	no	
sourceCategories		no	
programIds		no	
territories		no	
averageResponseMinutes	number null	no	
conversionRate	number null	no	

WorkflowToggleRequest

Property	Type	Required	Notes
fromStage	string	yes	
toStage	string	yes	
allowedRoles		no	
requiresApproval	boolean null	no	
approvalRole	string null	no	
enabled	boolean null	no	

AutomationToggleRequest

Property	Type	Required	Notes
stage	string	yes	
triggerName	string	yes	
action	string	yes	
templateKey	string null	no	
conditions		no	
enabled	boolean null	no	