

2 DOOR ASSEMBLY 8303209 12 SHIM-LOCK CATCH 8154781 11 WASHER - #10 LOCK 120217 10 NUT-#10-32 HEX. 120614 9 SCREW-PLO-32 OVAL HEAD CROSS RECESS 157125 8 LOCK ASSEMBLY 8158536 DOOR ASSEMBLY 8303009 DOOR ASSEMBLY **8**303026 5 DOOR ASSEMBLY 83C3212 4 DOOR ASSEMBLY 6303205 3 DOOR ASSEMBLY 8303212 2 DOOR ASSEMBLY 6303202 1 BLECTRO-NOTIVE DIVISION HOW INCREMENTATIONS USE INCOME HOUSE HOUSE HOUSE HOUSE 8303640 TYPICAL--(I) SHIM UNDER LOCK CATCH
WHEN NECESSARY TO PROVIDE
CORRECT PRESSURE ON LOCK HANDLE SECTION C-C SECTION A-A SECTION B-B PLAN VIEW DOOR DIAGRA -JB (TYPICAL 8 (HINGE MUST BE FLAT AGAINST SURFACE) 

Lidentical door arrangement used on right side of hood except doors are turned 180° vertically.

Left side of hood shown.

**(A)** 

BREAK ALL SHARP CORNERS UNLESS OTHERWISE SPECIFIED.
COUNTERSINK ALL TAPPED HOLES IIE'X ONE THIRD. DEEP.
SURFACE FINISH SPECS. ARE IN ACCORDANCE WITH G.M. ENGR. STDS.
PERMISSIBLE VARIATION ON COMMON FRACTION DIMENSIONS TO MACHINED SURFACES TO BE "E JOIO UNLESS OTHERWISE SPECIFIED.
FABRICATION TOLERANCE. ± 1/32

PM 8303640 2 2!