



NOTE: ALL SURFACES TO BE SMOOTH * FREE OF PROJECTIONS

(B) "G" INDICATES SNAG GRIND

| | | | | | | | | | | · | - | | |
|---|----------|----------------|-----------------------|---------|----------|-------------|-----|--------|------------|----------|----------|---------------------|----------------|
| - | | <u></u> | , | | | | | | MATERIAL | | | NAME OF PART | PART NO. |
| , | | CI | NOTE ADDED | | | | | 187 | CAST STEEL | | EEL | | |
| 1 | V-7075 | C | CASTING TOL. ADDED | 8-4-6 | BICK | MAKE R | KMA | 155 | | EMS 16. | | ELECTRO-MOTIVE DIV | |
| | U-4872 | Bı | NOTE ADDED. | 711 | | - | 1 | ¥ 5 | 00. | 140 | DATE | GENERAL MOTORS CORI | HOITAHO |
| | | B | RELIEF REVISED | 7-12-57 | Buch | Buck | | 95 | K | LLE | 12:29-48 | LA GRANGE, ILLINO | is v.s. |
| , | | A3 | A RELIEF ADDED | | | | | 1 | 34 | trem | 1-31-69 | TOCKING T | ית מג |
| | | A ₂ | RELIEF ADDED | | - - | | 6 | CM. CI | CK. SUP. | | | JACKING BY | 14 Ju |
| | H2415 | | FIRST USED ON G. P.17 | 54.49 | 22 | W5. | 14 | WELD | | CL N. /2 | | | المع بالمسترام |
| | | | | - 1 | | | | 1 | ,, | 1 | 5-14-44 | DATE OF PRINT | FA |
| | R. F. C. | REV. | The best stone | | † | | | BATL | | ENGS. | 5. | | |