[illegible]


1.	SEC. C-C ADDED				
2.	01MS REMIND- 2 PLCS				
3.	NWS 41 PIA. PAGES 675				
4.	ITS 5.C.T. 15.72 H ADDED				
5.	IT4 W5428895 C REGR				
6.	IT3 W5430074 C				
7.	IT122 CTR- BEND				
8.					
9.					
10.					
11.					
12.					
13.					
14.					
15.					
16.					
17.					
18.					
19.					
20.					
21.					
22.					
23.					
24.					
25.					
26.					
27.					
28.					
29.					
30.					
31.					
32.					
33.					
34.					
35.					
36.					
37.					
38.					
39.					
40.					
41.					
42.					
43.					
44.					
45.					
46.					
47.					
48.					
49.					
50.					
51.					
52.					
53.					
54.					
55.					
56.					
57.					
58.					
59.					
60.					
61.					
62.					
63.					
64.					
65.					
66.					
67.					
68.					
69.					
70.					
71.					
72.					
73.					
74.					
75.					
76.					
77.					
78.					
79.					
80.					
81.					
82.					
83.					
84.					
85.					
86.					
87.					
88.					
89.					
90.					
91.					
92.					
93.					
94.					
95.					
96.					
97.					
98.					
99.					
100.					

ELECTRO-MOTIVE DIVISION
CENTRAL MOTOR CORPORATION
LA GRANGE, ILLINOIS, U.S.A.




CENTER SECTION
UNDERFRAME

830105


830105



SECTION C - C



SECTION A



SECTION E

BREAK ALL SHARP CORNERS
UNLESS OTHERWISE SPECIFIED
COUNTERSINK ALL TAPPED HOLES
1/8" X ONE THIRD DEEP
SURFACE FINISH SPECS ARE IN
ACCORDANCE WITH Q.M. ENGR. STDS
PERMISSIBLE VARIATION ON COMMON
FRACTION DIMENSIONS TO MACHINED
SURFACES TO $\pm .010$ UNLESS
OTHERWISE SPECIFIED
FABRICATION TOLERANCE: $\pm .1$
CASTING TOLERANCE:
FORMING TOLERANCE: