

CS 534: Computer Vision Texture

Spring 2005
Ahmed Elgammal
Dept of Computer Science
Rutgers University

CS 534 – Ahmed Elgammal – Texture - 1

Outlines


- Finding templates by convolution
- What is Texture
- Co-occurrence matrices for texture
- Spatial Filtering approach
- Multiresolution processing, Gaussian Pyramids and Laplacian Pyramids
- Gabor filters and oriented pyramids
- Texture Synthesis

CS 534 – Ahmed Elgammal – Texture - 2

Convolution as a Dot Product

- Applying a filter at some point can be seen as taking a dot-product between the image and some vector
- Convoluting an image with a filter is equivalent to taking the dot product of the filter with each image window.

$$R_{ij} = \sum_{u,v} G_{i-u,j-v} H_{uv} = g \cdot h$$




CS 534 – Ahmed Elgammal – Texture - 3


- Largest value when the vector representing the image is parallel to the vector representing the filter
- Filter responds most strongly at image windows that looks like the filter.
- Filter responds stronger to brighter regions! (drawback)

Insight:

- filters look like the effects they are intended to find
- filters find effects they look like



Ex: Derivative of Gaussian used in edge detection looks like edges




CS 534 – Ahmed Elgammal – Texture - 4

Normalized Correlation

- Convolution with a filter can be used to find templates in the image.
- Normalized correlation output is filter output, divided by root sum of squares of values over which filter lies
- Consider template (filter) M and image window N :

$$C = \frac{\sum_{i=1}^n \sum_{j=1}^n M(i,j)N(i,j)}{[\sum_{i=1}^n \sum_{j=1}^n M(i,j)^2 \sum_{i=1}^n \sum_{j=1}^n N(i,j)^2]^{1/2}}$$



CS 534 – Ahmed Elgammal – Texture - 5

Normalized Correlation


$$C = \frac{\sum_{i=1}^n \sum_{j=1}^n M(i,j)N(i,j)}{[\sum_{i=1}^n \sum_{j=1}^n M(i,j)^2 \sum_{i=1}^n \sum_{j=1}^n N(i,j)^2]^{1/2}}$$

- This correlation measure takes on values in the range $[0,1]$
- it is 1 if and only if $N = cM$ for some constant c
- so N can be uniformly brighter or darker than the template, M , and the correlation will still be high.
- The first term in the denominator, $\sum \sum M^2$ depends only on the template, and can be ignored
- The second term in the denominator, $\sum \sum N^2$ can be eliminated if we first normalize the grey levels of N so that their total value is the same as that of M - just scale each pixel in N by $\sum M / \sum N$

CS 534 – Ahmed Elgammal – Texture - 6




Zero mean image, -1:1 scale





Positive responses

Zero mean image, -max:max scale




Zero mean image, -1:1 scale



Positive responses

Zero mean image, -max:max scale






Figure from "Computer Vision for Interactive Computer Graphics," W.Freeman et al, IEEE Computer Graphics and Applications, 1998 copyright 1998, IEEE

Texture

- What is texture ? Easy to recognize hard to define
 - Views of large number of small objects: grass, foliage, brush, pebbles, hair
 - Surfaces with patterns: spots, stripes , wood, skin
- Texture consists of organized patterns of quite regular subelements.
- Whether an effect is referred to as texture or not depends on the scale at which it is viewed.



CS 534 – Ahmed Elgammal – Texture - 11

Texture

Problems related to Texture:


- Texture analysis: how to represent and model texture
- Texture segmentation: segmenting the image into components within which the texture is constant
- Texture synthesis: construct large regions of texture from small example images
- Shape from texture: recovering surface orientation or surface shape from image texture.



CS 534 – Ahmed Elgammal – Texture - 12

Shape from Texture

- Texture looks different depending on the viewing angle.
- Texture is a good cue for shape and orientation
- Humans are very good at that.



CS 534 – Ahmed Elgammal – Texture - 13

Representing Texture

- What we should look for ?
- Texture consists of organized patterns of quite regular subelements. “Textons”
- Find the subelements, and represent their statistics
- Reason about their spatial layout.
- Problem: There is no known canonical set of textons.



CS 534 – Ahmed Elgammal – Texture - 14

Texture Analysis

Different approaches:


- Co-occurrence matrices (classical)
- Spatial Filtering
- Random Field Models

Co-occurrence Matrix Features

Objective: Capture spatial relations

A co-occurrence matrix is a 2D array C in which

- Both the rows and columns represent a set of possible image values
- $C_d(i,j)$ indicates how many times value i co-occurs with value j in a particular spatial relationship d .
- The spatial relationship is specified by a vector $d = (d_r, d_c)$.



From C_d we can compute N_d , the normalized co-occurrence matrix, where each value is divided by the sum of all the values.

CS 534 – Ahmed Elgammal – Texture - 17

Co-occurrence Features

From Co-occurrence matrices extract some quantitative features:

$$Energy = \sum_i \sum_j N_d^2(i, j) \quad (7.7)$$

$$Entropy = - \sum_i \sum_j N_d(i, j) \log_2 N_d(i, j) \quad (7.8)$$

$$Contrast = \sum_i \sum_j (i - j)^2 N_d(i, j) \quad (7.9)$$

$$Homogeneity = \sum_i \sum_j \frac{N_d(i, j)}{1 + |i - j|} \quad (7.10)$$

$$Correlation = \frac{\sum_i \sum_j (i - \mu_i)(j - \mu_j) N_d(i, j)}{\sigma_i \sigma_j} \quad (7.11)$$

where μ_i, μ_j are the means and σ_i, σ_j are the standard deviations of the row and column sums.

CS 534 – Ahmed Elgammal – Texture - 18

Disadvantages:


- Computationally expensive
- Sensitive to gray scale distortion (co-occurrence matrices depend on gray values)
- May be useful for fine-grain texture. Not suitable for spatially large textures.



Spatial Filtering Approaches


- Look for the subelements
- But what are the subelements, and how do we find them?
- Find subelements by applying filters, looking at the magnitude of the response
- Spots and bars detectors at various scales and orientations.

Typically:


- “Spot” filters are Gaussians or weighted sums of concentric Gaussians.
- “Bar” filters are differentiating oriented Gaussians








- How many filters and at what orientations ?
- Filter responses are not unique
- Tradeoff: using more filters leads to a more detailed and more redundant representation of the image
- How to control the amount of redundant information?
- At what scale?
- There are two scales:
 - The scale of the filter
 - The scale over which we consider the distributions of the filters.
- What statistics should be collected from filters responses.




There are two scales:

- The scale of the filter
- The scale over which we consider the distributions of the filters.



Classification:

- Texture is classified into four categories: vertical, horizontal, both or neither.



Scaled representations: Multiresolution


Use a multiresolution representation (Image Pyramid)

- Search over scale
 - Spatial Search
 - Feature Tracking
- Examples:
- Search for correspondence
 - look at coarse scales, then refine with finer scales
 - Edge tracking
 - a “good” edge at a fine scale has parents at a coarser scale
 - Control of detail and computational cost in matching
 - e.g. finding stripes
 - terribly important in texture representation

Gaussian Filter and Smoothing

Gaussian Filter is Low-Pass Filter:

- Recall: Convolution in the image domain is equivalent to multiplication in the Frequency domain.
- Recall: FT of a Gaussian with $sd=\sigma$ is a Gaussian with $sd=1/\sigma$
- Therefore, convolving an image with a Gaussian with $sd=\sigma$ is equivalent to multiplying it's FT with a Gaussian with $sd=1/\sigma$
- Therefore we will get rid of high frequencies.
- Smoothing with a Gaussian with a very small $\sigma \Rightarrow$ get rid of highest spatial frequencies
- Smoothing with a Gaussian with a very large $\sigma \Rightarrow$ averaging



CS 534 – Ahmed Elgammal – Texture - 29


The Gaussian pyramid

- Smooth with gaussians, because
 - a gaussian*gaussian=another gaussian
- Forming a Gaussian Pyramid:
 - Set the finest scale layer to the image
 - For each layer going up (coarser)
 - Obtain this layer by smoothing the previous layer with a Gaussian and subsampling it

$$P_{\text{Gaussian}}(I)_{n+1} = S^{\downarrow}(G_{\sigma} * P_{\text{Gaussian}}(I)_n)$$

$$P_{\text{Gaussian}}(I)_1 = I$$

CS 534 – Ahmed Elgammal – Texture - 30



The Laplacian Pyramid

- Gaussians are low pass filters, so response is redundant
- A coarse level layer of the Gaussian pyramid predicts the appearance of the next finer layer
- Laplacian Pyramid
 - preserve differences between upsampled Gaussian pyramid level and Gaussian pyramid level
 - band pass filter - each level represents spatial frequencies (largely) unrepresented at other levels

$$P_{\text{Laplacian}}(I)_m = P_{\text{Gaussian}}(I)_m$$



$$P_{\text{Laplacian}}(I)_k = P_{\text{Gaussian}}(I)_k - S^{\uparrow}(P_{\text{Gaussian}}(I)_{k+1})$$


Laplacian Pyramid

- Building a Laplacian Pyramid:
 - Form a Gaussian pyramid
 - Set the coarsest layer of the Laplacian pyramid to be the coarsest level of the Laplacian pyramid
 - For each layer going from next to coarsest to finest (top to bottom):
 - Obtain this layer by upsampling the coarser layer and subtracting it from this layer of the Gaussian pyramid.


$$P_{\text{Laplacian}}(I)_m = P_{\text{Gaussian}}(I)_m$$

$$P_{\text{Laplacian}}(I)_k = P_{\text{Gaussian}}(I)_k - S^\uparrow(P_{\text{Gaussian}}(I)_{k+1})$$






- Synthesis: Obtaining an Image from a Laplacian Pyramid:
 - Start at the coarsest layer
 - For each layer from next to coarsest to finest
 - Upsample the current image and add the current layer to the result




- Laplacian pyramid layers are band-pass filters.
- Laplacian pyramid is orientation independent
- Apply an oriented filter to determine orientations at each layer
- Look into spatial frequency domain:



CS 534 – Ahmed Elgammal – Texture - 37

Oriented Pyramids




Reprinted from "Shiftable MultiScale Transforms," by Simoncelli et al., IEEE Transactions on Information Theory, 1992, copyright 1992, IEEE


CS 534 – Ahmed Elgammal – Texture - 38

Gabor Filters

- Fourier coefficients depend on the entire image (Global): We lose spatial information.
- Objective: Local Spatial Frequency Analysis
- Gabor kernels: look like Fourier basis multiplied by a Gaussian
 - The product of a symmetric Gaussian with an oriented sinusoid
 - Gabor filters come in pairs: symmetric and antisymmetric
 - Each pair recover symmetric and antisymmetric components in a particular direction.
 - (k_x, k_y) :the spatial frequency to which the filter responds strongly
 - σ : the scale of the filter. When $\sigma = \text{infinity}$, similar to FT
- We need to apply a number of Gabor filters at different scales, orientations, and spatial frequencies.


$$G_{\text{symmetric}}(x, y) = \cos(k_x x + k_y y) \exp\left\{-\frac{x^2 + y^2}{2\sigma^2}\right\}$$
$$G_{\text{antisymmetric}}(x, y) = \sin(k_x x + k_y y) \exp\left\{-\frac{x^2 + y^2}{2\sigma^2}\right\}$$

CS 534 – Ahmed Elgammal – Texture - 39



CS 534 – Ahmed Elgammal – Texture - 40


Final texture representation

- Form an oriented pyramid (or equivalent set of responses to filters at different scales and orientations).
- Square the output
- Take statistics of responses
 - e.g. mean of each filter output (are there lots of spots)
 - std of each filter output
 - mean of one scale conditioned on other scale having a particular range of values (e.g. are the spots in straight rows?)

CS 534 – Ahmed Elgammal – Texture - 41

Texture synthesis

- Variety of approaches.
- Example: Synthesis by Sampling Local Models: Efros and Leung 1999 (Nonparametric texture matching)
 - Use image as a source of probability model
 - Choose pixel values by matching neighborhood, then filling in



Find Matching Image Neighborhood and chose value uniformly randomly from these matches

CS 534 – Ahmed Elgammal – Texture - 42





Figure from Texture Synthesis by Non-parametric Sampling, A. Efros and T.K. Leung, Proc. Int. Conf. Computer Vision, 1999 copyright 1999, IEEE

ut it becomes harder to lau
ound itself, at "this daily
ving rooms," as House Der
scribed it last fall. He fal
at he left a ringing questio
ore years of Monica Lewit
nda Tripp?" That now seer
Political comedian Al Fra
ext phase of the story will

ut it becomes harder to lau
ound itself, at "this daily
ving rooms," as House Der
scribed it last fall. He fal
at he left a ringing questio
ore years of Monica Lewit
nda Tripp?" That now seer
Political comedian Al Fra
ext phase of the story will

Figure from Texture Synthesis by Non-parametric Sampling, A. Efros and T.K. Leung, Proc. Int. Conf. Computer Vision, 1999 copyright 1999, IEEE

- The size of the image neighborhood to be matched makes a significant difference



CS 534 – Ahmed Elgammal – Texture - 45


Variations

- Texture synthesis at multiple scales
- Texture synthesis on surfaces
- Texture synthesis by tiles
- “Analogous” texture synthesis

CS 534 – Ahmed Elgammal – Texture - 46

Shape from Texture

- Texture looks different depending on the viewing angle.
- Texture is a good cue for shape and orientation
- Humans are very good at that.



CS 534 – Ahmed Elgammal – Texture - 47

Sources

- Forsyth and Ponce, Computer Vision a Modern approach: chapter 9.
- L. G. Shapiro and G. C. Stockman “Computer Vision”, Prentice Hall 2001.
- R. Gonzalez and R.E. Woods, “Digital Image Processing”, 2002.
- Slides by
 - D. Forsyth @ UC Berkeley
 - G.C. Stockman @MSU

CS 534 – Ahmed Elgammal – Texture - 48