| Reference | Value | TME Electronic | SeedStudio | GoTronic | Lextronic | Conrad |
|------------------|--------------------------------------|-----------------------------|------------|----------|-----------|--------|
| U3 | A000005 | | | | | |
| J2 | PinHeader_1x02_P2.54mm | | | | | |
| D4 | R 2v | SLR-56VR3F | | | | |
| R2, R4 | 10k - 1 % | MRS25000C1002FCT00 | | | | |
| J4 | PinHeader_1x03_P2.54mm | | | | | |
| U4 | Emetteur | | 113990010 | 05294 | | |
| U2 | 24LC256-I_P | | | | | |
| R6, R7 | 4k7 - 1 % | MBB02070C4701FCT00 | | | | |
| J3 | PinHeader_1x01_P2.54mm | | | | | |
| D3 | R 2v | SLR-56VR3F | | | | |
| R8 | 1K5 - 1 % | MRS25000C1501FCT00 | | | | |
| D5 | R 2v | SLR-56VR3F | | | | |
| F1 | 100mA | | | | | |
| Support Fusible | | | | | | 530127 |
| D2 | V 2v | OSNG5134A | | | | |
| R1, R3, R5 | 3K9 - 1 % | MBB02070C3901FC100 | | | | |
| U1 | L7809 | NTE1910 | | | | |
| Refroidisseur | | FK210SACB | | | | |
| | Pâte thermique KP12 4.2 g 10 W/mK | | | | | 189069 |
| C3 | 100nf | CCK-100N | | | | |
| C2 | 330nf | BFC233820334 | | | | |
| C1 | 2200uf | KM2200/25 | | | | |
| TR1 | BVEI3022938 220v -12v -1,2VA | BVEI3022938 | | | | |
| D1 | B40C1500G | B40C1500G-E4/51 | | | | |
| J1 | Conn_01x03 | MKDS 1,5/ 3-5,08 1715734 | | | | 743464 |
| Support 8b | | | | | | |
| Fil pour Arduino | | | | 25932 | | |
| Strap | | | | | 15-AT | |
| Con Header mâle | | | | 48004 | CC076 | |
| | | | | | | 1 |