

Monte Carlo Path Tracing

Today

- Path tracing starting from the eye
- Path tracing starting from the lights
- Which direction is best?
- Bidirectional ray tracing
- Random walks and Markov chains

Next

- Irradiance caching
- Photon mapping

CS348B Lecture 14

Pat Hanrahan, Spring 2010

The Rendering Equation

$$L(x, \omega) = L_e(x, \omega) + \int_{H^2} f_r(x, \omega' \rightarrow \omega) L(x^*(x, \omega'), -\omega') \cos \theta' d\omega'$$

$$L = L_e + K \circ L$$

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Solving the Rendering Equation

Rendering Equation

$$L = L_e + K \circ L$$

$$(I - K) \circ L = L_e$$

Solution

$$L = (I - K)^{-1} \circ L_e$$


$$= (I + K + K^2 + K^3 + \dots) \circ L_e$$

$$= (I + K(I + K(I + K \dots))) \circ L_e$$

CS348B Lecture 14

Pat Hanrahan, Spring 2010


Successive Gathers




L_e




$K \circ L_e$




$K \circ K \circ L_e$




$K \circ K \circ K \circ L_e$




L_e



$L_e + K \circ L_e$



$L_e + \dots + K^2 \circ L_e$




$L_e + \dots + K^3 \circ L_e$

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Light Path


$$S(x_0, x_1) = L_e(x_0, x_1)$$



CS348B Lecture 14

Pat Hanrahan, Spring 2010

Light Path



$$L_S(x_0, x_1, x_2, x_3) = S(x_0, x_1)G(x_0, x_1)f_r(x_0, x_1, x_2)G(x_1, x_2)f_r(x_1, x_2, x_3)$$

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Solving the Rendering Equation

One path

$$L_S(x_0, x_1, x_2, x_3) = S(x_0, x_1)G(x_0, x_1)f_r(x_0, x_1, x_2)G(x_1, x_2)f_r(x_1, x_2, x_3)$$

Solution is the integral over all paths

$$L(x_{k-1}, x_k) \\ = \sum_{k=1}^{\infty} \int_{M^2} \cdots \int_{M^2} L_S(x_0, \cdots, x_{k-2}, x_{k-1}, x_k) dA(x_0) \cdots dA(x_{k-2})$$

Solve using Monte Carlo Integration

Question: How to generate a random path?

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Path Tracing from the Eye


Path Tracing: From Camera

```
Step 1. Choose a camera ray  $r$  given the  
       $(x, y, u, v, t)$  sample  
      weight = 1;  
Step 2. Find ray-surface intersection  
Step 3.  
      if hit light  
        return weight *  $L_e(r)$ ;  
      else  
        weight *= reflectance( $r$ )  
        Choose new ray  $r' \sim \text{BRDF}(O|I)$   
        Go to Step 2.
```


CS348B Lecture 14

Pat Hanrahan, Spring 2010

Penumbra: Trees vs. Paths



4 eye rays per pixel
16 shadow rays per eye ray




64 eye rays per pixel
1 shadow ray per eye ray

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Path Tracing



CS348B Lecture 14

10 paths / pixel

Pat Hanrahan, Spring 2010


M. Fajardo Arnold Path Tracer



CS348B Lecture 14

Pat Hanrahan, Spring 2010


M. Fajardo Arnold Path Tracer



CS348B Lecture 14

Pat Hanrahan, Spring 2010


M. Fajardo Arnold Path Tracer



CS348B Lecture 14

Pat Hanrahan, Spring 2010

M. Fajardo Arnold Path Tracer



CS348B Lecture 14

Pat Hanrahan, Spring 2010

M. Fajardo Arnold Path Tracer



CS348B Lecture 14

Pat Hanrahan, Spring 2010

M. Fajardo Arnold Path Tracer



Street scene 1

1536x654, 16 paths/pixel, 2 bounces, 250,000 faces, 18 min., dual PIII-800

CS348B Lecture 14

Pat Hanrahan, Spring 2010

How Many Bounces?

Avoid paths that carry little energy

Terminate when the weight is low

Photons with similar power is a good thing

Think of importance sampling

Integrand is $f(x)/p(x)$ which is constant

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Russian Roulette

Terminate photon with probability p

Adjust weight of the result by $1/(1-p)$

$$E(X) = p \cdot 0 + (1-p) \frac{E(X)}{1-p} = E(X)$$

Intuition:

Reflecting from a surface with $R=.5$

100 incoming photons with power 2 W

1. Reflect 100 photons with power 1 W
2. Reflect 50 photons with power 2 W

Path Tracing: Include Direct Lighting

Step 1. Choose a camera ray r given the
 (x, y, u, v, t) sample

`weight = 1;`

`L = 0`

Step 2. Find ray-surface intersection

Step 3.


`L += weight * Sum (fr * Le(light))`

`weight *= reflectance(x)`


Choose new ray $r' \sim \text{BRDF pdf}(r)$

Go to Step 2.

Variance Decreases with N



10 rays per pixel



100 rays per pixel

From Jensen, Realistic Image Synthesis Using Photon Maps

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Fixed Sampling (Not Random Enough)




CS348B Lecture 14

Pat Hanrahan, Spring 2010

Light Ray Tracing

Early Example [Arvo, 1986]



“Backward” ray tracing

Path Tracing: From Lights

Step 1. Choose a light ray.

Choose a ray from the light source
distribution function

$\mathbf{x} \sim p(\mathbf{x})$

$\mathbf{d} \sim p(\mathbf{d}|\mathbf{x})$

$\mathbf{r} = (\mathbf{x}, \mathbf{d})$

weight = Φ ;

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Path Tracing: From Lights

Step 1. Choose a light ray

Step 2. Find ray-surface intersection

Step 3. Reflect or transmit

$u = \text{Uniform}()$

if $u < \text{reflectance}(\mathbf{x})$

Choose new direction $\mathbf{d} \sim \text{BRDF}(\mathbf{O}|\mathbf{I})$

goto Step 2

else $u < \text{reflectance}(\mathbf{x}) + \text{transmittance}(\mathbf{x})$

Choose new direction $\mathbf{d} \sim \text{BTDF}(\mathbf{O}|\mathbf{I})$

goto Step 2

else // absorption = 1 - reflectance - transmittance


terminate on surface; deposit energy

CS348B Lecture 14

Pat Hanrahan, Spring 2010


Bidirectional Path Tracing

Symmetric Light Path



$$M = S(x_0, x_1)G(x_0, x_1)f_r(x_0, x_1, x_2)G(x_1, x_2)f_r(x_1, x_2, x_3)G(x_2, x_3)R(x_2, x_3)$$

Symmetric Light Path




$$M = S(x_0, x_1)G(x_0, x_1)f_r(x_0, x_1, x_2)G(x_1, x_2)f_r(x_1, x_2, x_3)G(x_2, x_3)R(x_2, x_3)$$

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Symmetric Light Path




$$M = R(x_3, x_2)G(x_3, x_2)f_r(x_3, x_2, x_1)G(x_2, x_1)f_r(x_2, x_1, x_0)G(x_1, x_0)S(x_1, x_0)$$

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Bidirectional Ray Tracing


$$k = l + e$$



CS348B Lecture 14

Pat Hanrahan, Spring 2010

Path Pyramid



CS348B Lecture 14


Pat Hanrahan, Spring 2010

Comparison

Same amount of time



Bidirectional path tracing
25 rays per pixel



Path tracing
56 rays per pixel

From Veach and Guibas

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Which Direction?

Solve a linear system $Mx = b$

Solve for a single x_i ?

Solve the reverse equation

Source x_i

Estimator $\langle (x_i + Mx_i + M^2x_i + \dots), b \rangle$

More efficient than solving for all the unknowns


[von Neumann and Ulam]

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Discrete Random Walk

Discrete Random Process




Assign probabilities to each process

p_i^0 : probability of creation in state i

$p_{i,j}$: probability of transition from state $i \rightarrow j$

p_i^* : probability of termination in state i $p_i^* = 1 - \sum_j p_{i,j}$

Discrete Random Process



Equilibrium number of particles in each state

$$P_i = \sum_j p_{i,j} P_j + p_i^0 \quad M_{i,j} = p_{i,j}$$
$$P = MP + p^0$$

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Equilibrium Distribution of States

Total probability of being in states P


Solve this equation

$$(I - M)P = p^0$$
$$P = (I - M)^{-1} p^0$$
$$= (I + M + M^2 + \dots) p^0$$

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Discrete Random Walk



1. Generate random particles from sources.
2. Undertake a discrete random walk.
3. Count how many terminate in state i

[von Neumann and Ulam; Forsythe and Leibler; 1950s]

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Monte Carlo Algorithm

Define a random variable on the space of paths

Path: $\alpha_k = (i_1, i_2, \dots, i_k)$

Probability: $P(\alpha_k)$

Estimator: $W(\alpha_k)$

Expectation:

$$E[W] = \sum_{k=1}^{\infty} \sum_{\alpha_k} P(\alpha_k) W(\alpha_k)$$

CS348B Lecture 14

Pat Hanrahan, Spring 2010

Monte Carlo Algorithm

Define a random variable on the space of paths

Probability: $P(\alpha_k) = p_{i_1}^0 \times p_{i_1, i_2} \cdots p_{i_{k-1}, i_k} \times p_{i_k}^*$

Estimator: $W_j(\alpha_k) = \frac{\delta_{i_k, j}}{p_{i_k}^*}$

Estimator

Count the number of particles terminating in state j

$$\begin{aligned} E[W_j] &= \sum_{k=1}^{\infty} \sum_{i_k} \cdots \sum_{i_1} (p_{i_1}^0 p_{i_1, i_2} \cdots p_{i_{k-1}, i_k} p_{i_k}^*) \frac{\delta_{i_k, j}}{p_j^*} \\ &= [p^0]_j + [Mp^0]_j + [M^2 p^0]_j \cdots \end{aligned}$$

Equilibrium Distribution of States

Total probability of being in states P

$$P = (I + M + M^2 + \dots)p^0$$

Note that this is the solution of the equation

$$(I - M)P = p^0$$

Thus, the discrete random walk is an unbiased estimate of the equilibrium number of particles in each state