

Key: Overdue inspection Due within 30 days

[illegible]

Component	What to check	Item 1	Item 2	Item 3	Item 4	Item 5	Item 6	Item 7	Item 8	Item 9	Item 10
WEBBING & STRAPS											
	Cuts, nicks, tears, abrasion or fraying										
	Burns, heat damage, friction glazing or discolouration										
	Chemical damage, paint contamination or staining										
	UV degradation (fading, powdery/brittle surface)										
	Mould, mildew or rot										
	Excessive stretching or deformation										
STITCHING											
	Broken, cut, pulled or abraded stitches										
	Loose or missing threads at load-bearing seams										
	Damage or discolouration of stitching pattern										
METAL COMPONENTS (buckles, D-rings, adjusters)											
	Cracks, distortion, sharp edges or burrs										
	Corrosion, rust or pitting										
	Correct buckle function — engages and locks securely										
	D-rings free from wear grooves and deformation										
CONNECTORS / KARABINERS (EN 362)											
	Gate opens, closes and locks correctly (self-locking action)										
	No distortion, cracks or corrosion of body or gate										
	Rivets/hinge pins secure, no excessive play										
ENERGY ABSORBER (fall arrest lanyards, EN 355)											

Component	What to check	Item 1	Item 2	Item 3	Item 4	Item 5	Item 6	Item 7	Item 8	Item 9	Item 10
	Pouch/cover intact — no signs of deployment or activation										
	Tell-tale / deployment indicator not triggered										
	No damage to outer cover or stitched tear-ply visible										
ROPE / KERMANTEL LANYARD ELEMENTS											
	No cuts, flat spots, soft spots, lumps or core exposure										
	Splices/terminations intact and secure										
	Ferrules/thimbles free from damage and corrosion										
LABELS & MARKINGS											
	ID/serial label present and legible										
	CE / UKCA marking and EN standard legible										
	Date of manufacture legible; item within manufacturer's service life										
FUNCTION & FIT (harnesses)											
	All adjusters operate through full range and hold position										
	Attachment points (dorsal/sternal) undamaged and secure										
	Elasticated keepers/comfort padding serviceable										
OVERALL RESULT (PASS / FAIL / MONITOR)											
Next Inspection Due											
Comments / Defects											

Inspector signature:

GUIDANCE NOTES

Inspection regime for harnesses and lanyards (work at height PPE):

- Pre-use check — by the user, before each use. Visual and tactile check of the whole item.
- Detailed / thorough examination — by a competent person at intervals not exceeding 6 months (3 months in arduous conditions), recorded on the Inspection Checklist sheet and logged in the Register.
- Interim inspections — where risk assessment identifies conditions causing accelerated deterioration (e.g. hot works, chemicals, grit blasting).

Key rules:

- Any item that has arrested a fall must be withdrawn from service immediately.
- Any item that fails inspection must be quarantined so it cannot be used, then destroyed or returned to the manufacturer.
- Do not exceed the manufacturer's stated service life (commonly 10 years from date of manufacture for textile items — check the user instructions).
- Keep manufacturer instructions with this register. Record every thorough examination.

Relevant standards & legislation: Work at Height Regulations 2005; LOLER 1998 (where equipment lifts/lowers persons); PUWER 1998; BS EN 365 (marking & periodic examination); BS 8437; INDG367 'Inspecting fall arrest equipment made from webbing or rope' (HSE).

Register sheet: 'Next Inspection Due' and 'Days Until Due' calculate automatically from the Last Inspection Date and interval. Rows highlight amber when due within 30 days and red when overdue.