

# Simply Typed Lambda Calculus

From Untyped to Simply Typed Lambda Calculus

---

Sven Tennie

September 13, 2018

Dream IT

<https://dreamit.de>

# Untyped Lambda Calculus

---

# Untyped Lambda Calculus - Recapitulation

We can boil down computation to a tiny calculus

# Untyped Lambda Calculus - Recapitulation

We can boil down computation to a tiny calculus

All we need is:

- Function Definition / Abstraction ( $\lambda x.e$ )
- Function Application ( $e e$ )
- Parameters / Variables ( $x$ )

# Untyped Lambda Calculus - Recapitulation

We can boil down computation to a tiny calculus

All we need is:

- Function Definition / Abstraction ( $\lambda x.e$ )
- Function Application ( $e e$ )
- Parameters / Variables ( $x$ )

Then we get:

PL constructs

- Booleans
- Numerals
- Data Structures
- Control Flow

# Untyped Lambda Calculus - Recapitulation

We can boil down computation to a tiny calculus

All we need is:

- Function Definition / Abstraction ( $\lambda x.e$ )
- Function Application ( $e e$ )
- Parameters / Variables ( $x$ )

Then we get:

PL constructs

- Booleans
- Numerals
- Data Structures
- Control Flow

Turing Completeness

- Turing Completeness
  - If it can be computed, it can be computed in Lambda Calculus!

# Build an Interpreter

## Let's build an interpreter

- Deepen our intuition
- Later move on to the *Simply Typed Lambda Calculus*
  - Why do we need types?
  - How does a type checker work?
  - How does it restrict the programs we might write?
- On our way we'll learn some math mumbo-jumbo: *Natural Deduction*
  - Found in many papers about Type Systems and Programming Language Evaluation

$e ::=$

$x$

$\lambda x.e$

$e\ e$

Expressions:

Variable

Abstraction

Application


$\lambda x.e$  Function Definition

$e\ e$  Function Application



# Abstract Syntax Tree

$(\lambda x.x) y$



## Meaning:

- Identity function  $(\lambda x.x)$  is applied to a variable  $(y)$

# Interpreter - Syntax

---

```
module UntypedSyntax where

type Name = String

data Expr          -- e ::=      Expressions:
  = Var Name       --          x    Variable
  | Lambda Name    --           $\lambda x.e$  Abstraction
      Expr
  | App Expr       --          e e   Application
      Expr
  deriving (Eq, Show)
```

---

# Interpreter - Syntax - Examples

---

```
module UntypedSyntaxExamples where

import UntypedSyntax

-- true  $\equiv \lambda p. \text{lambda} q. p$ 
true :: Expr
true = Lambda "p" (Lambda "q" (Var "p"))

-- false  $\equiv \lambda p. \text{lambda} q. q$ 
false :: Expr
false = Lambda "p" (Lambda "q" (Var "p"))

-- if_then_else  $\equiv \lambda p. \lambda a. \lambda b. p a b$ 
if_then_else :: Expr
if_then_else =
  Lambda "p" (Lambda "a" (Lambda "b" (App (App (Var "p") (Var "a")) (Var "b")))))
```

---

# Natural Deduction

---

## Proof: 2 is a Natural Number

$$\frac{}{0 : \text{Nat}} \quad (\text{A1})$$

$$\frac{n : \text{Nat}}{\text{succ}(n) : \text{Nat}} \quad (\text{A2})$$

$$\frac{\frac{\frac{}{0 : \text{Nat}} \quad (\text{A1})}{\text{succ}(0) : \text{Nat}} \quad (\text{A2})}{\text{succ}(\text{succ}(0)) : \text{Nat}} \quad (\text{A2})$$

### Meaning:

**A1** 0 is a natural number (by definition)

**A2** The successor of a natural number is a natural number

→ Thus the successor of the successor of 0 (2) must be a 7

## Evaluation Rules - Call by Value - E-App1

$$\frac{e_1 \rightarrow e'_1}{e_1 e_2 \rightarrow e'_1 e_2} \quad \text{E-App1}$$

### Meaning:

- Under the condition that  $e_1$  can be reduced further, do it.

$$\frac{e_2 \rightarrow e'_2}{v_1 e_2 \rightarrow v_1 e'_2} \quad \text{E-App2}$$

### Meaning:

- Under the condition that  $e_2$  can be reduced further and  $v_1$  is a value, do it.
- Pure Untyped Lambda Calculus:
  - Only Lambdas (functions) are values.
  - But you can add Ints, Booleans, etc. (and loose purity)

$$(\lambda x.e)v \rightarrow [x/v]e$$

E-AppLam

### Meaning:

- If a lambda (function) is applied to a value, substitute that value for it's parameter.
- "substitute" : replace it for every occurrence in the lambda's body



# Interpreter - Evaluation

---

```
module NaiveUntypedEval where

import UntypedSyntax

eval :: Expr -> Expr
-- No rule for variables
eval variable@(Var _) = variable
-- No rule for lambdas
eval lambda@(Lambda _ _) = lambda
eval (App e1 e2)
  -- 
$$\frac{e_1 \rightarrow e'_1}{e_1 e_2 \rightarrow e'_1 e_2} \quad (E - App1)$$

  =
    let e1' = eval e1
    -- 
$$\frac{e_2 \rightarrow e'_2}{v_1 e_2 \rightarrow v_1 e'_2} \quad (E - App2)$$

    in let e2' = eval e2
       in case e1'
         of
           -- 
$$(\lambda x. e) v \rightarrow [x/v]e \quad (E - AppLam)$$

           (Lambda name e1'_body) -> eval $ substitute name e2' e1'_body
           e1' -> App e1' e2'
```

---

# Interpreter - Substitution

---

```
substitute :: String -> Expr -> Expr -> Expr
substitute name substitution var@(Var varName)
  | name == varName = substitution
  | otherwise = var
substitute name substitution (App term1 term2) =
  App (substitute name substitution term1) (substitute name substitution term2)
substitute name substitution (Lambda varName term) =
  if name == varName
  then Lambda varName term
  else Lambda varName (substitute name substitution term)
```

---

# Interpreter with Environment

---

```
module UntypedEval where

import UntypedSyntax

import qualified Data.Map.Strict as Map

type Environment = Map.Map Name Expr

eval :: Environment -> Expr -> Maybe Expr
eval env (Var name) = find env name
eval env (App term1 term2) = case eval env term1 of
    Just (Lambda name term) -> eval (Map.insert name term2 env) term
    Just term                -> Just (App term term2)
    Nothing -> Nothing
eval env lambda@(Lambda _ _) = Just lambda

find :: Environment -> Name -> Maybe Expr
find env name = Map.lookup name env
```

---



# Simply Typed Lambda Calculus

---

$e ::=$

$x$

$\lambda x : \tau. e$

$e e$

Expressions:

Variable

Abstraction

Application

**Progress** : If an expression is well typed then either it is a value, or it can be further evaluated by an available evaluation rule.

**Preservation** : If an expression  $e$  has type  $\tau$ , and is evaluated to  $e'$ , then  $e'$  has type  $\tau$ .

## **Dynamic rules stay the same!**

- Type checking is done upfront





# Typing Rules

$$\frac{x : \sigma \in \Gamma}{\Gamma \vdash x : \sigma}$$

T-Var

$$\frac{\Gamma, x : \tau_1 \vdash e : \tau_2}{\Gamma \vdash \lambda x : \tau_1. e : \tau_1 \rightarrow \tau_2}$$

T-Lam

$$\frac{\Gamma \vdash e_1 : \tau_1 \rightarrow \tau_2 \quad \Gamma \vdash e_2 : \tau_1}{\Gamma \vdash e_1 e_2 : \tau_2}$$

T-App

$$\Gamma \vdash n : \text{Int}$$

T-Int

$$\Gamma \vdash \text{True} : \text{Bool}$$

T-True

# Type Checker

---

```
module TypedSyntax where

import qualified Data.Map.Strict as Map

type Name = String

type Environment = Map.Map Name Type

data Type
  = TInt
  | TBool
  | TArr Type
      Type
  deriving (Eq, Show)

data Expr
  = IntValue Int
  | BoolValue Bool
  | Var Name
  | App Expr
      Expr
  | Lambda Name
      Type
      Expr
  deriving (Eq, Show)
```

---

# Type Checker - Literals & Variables

```
module TypedCheck where

import Data.Either.Extra
import qualified Data.Map.Strict as Map

import TypedSyntax

find :: Environment -> Name -> Either String Type
find env name = maybeToEither "Var not found!" (Map.lookup name env)

check :: Environment -> Expr -> Either String Type
--
--  $\Gamma \vdash n : \text{Int} \quad (T\text{-Int})$ 
--
check _ (IntValue _) = Right TInt
--
--  $\Gamma \vdash \text{True} : \text{Bool} \quad (T\text{-True})$ 
--
check _ (BoolValue True) = Right TBool
--
--  $\Gamma \vdash \text{False} : \text{Bool} \quad (T\text{-False})$ 
--
check _ (BoolValue False) = Right TBool
--
--  $\frac{x:\sigma \in \Gamma}{\Gamma \vdash x:\sigma} \quad (T\text{-Var})$ 
--
check env (Var name) = find env name
```

# Type Checker - Lambda & Application

---

```
--  
--       $\frac{\Gamma, x:\tau_1 \vdash e:\tau_2}{\Gamma \vdash \lambda x:\tau_1. e:\tau_1 \rightarrow \tau_2}$  (T-Lam)  
--
```

```
check env (Lambda name atype e) = do  
  t <- check (Map.insert name atype env) e  
  return $ TArr atype t
```

```
--  
--       $\frac{\Gamma \vdash e_1:\tau_1 \rightarrow \tau_2 \quad \Gamma \vdash e_2:\tau_1}{\Gamma \vdash e_1 e_2:\tau_2}$  (T-App)  
--
```

```
check env (App e1 e2) = do  
  (TArr ta1 ta2) <- check env e1  
  t2 <- check env e2  
  if ta1 == t2  
    then Right ta2  
    else Left $ "Expected " ++ (show ta1) ++ " but got : " ++ (show t2)
```

---