

[illegible]

1. ACCUMULATIVE DIMENSIONS ARE TAKEN FROM THE "00" LINE.	累积尺寸必须追溯到 "00" 开始计算。
2. ALL GUSSET-ORIENTED CUTS WILL HAVE A RADIUS OF 25mm.	所有朝向补强板切割的切口必须具有 25mm 的圆角半径。
3. ALL SUMMARIES THIS SHEET TO BE PREPARED (01-AC232-01-0-01)	本表格所有补强板汇总表必须按照 01-AC232-01-0-01 表格格式编制。
4. ASSEMBLY MARK TO BE STAMPED ON THE FACE WHERE INDICATED THRU.	所有打样必须在 指定位置打样。
5. "X" DENOTES THE TOUCH FACE OF MEMBERS, SHOP MUST STAMP THEM.	"X" 为接触面标志, 工厂必须标注清楚。
6. ALL THE DIAMETER OF SCALOP IS 25mm (100%)	所有切口圆角半径均为 25mm, 必须 100% 符合。
7. ALL WELDS SHALL BE CONTINUOUS, UGLY.	所有焊缝必须连续, 必须光滑。
8. SEAL WELDS OF SCALP FILLET WELD SHALL BE PROVIDED BY WELDED CONNECTIONS.	密封焊缝必须由焊接接头提供。
9. TEMPORARY SCALP SHALL BE WELD COATED TO DISINTEGRATE FROM THE PERMANENT GALT.	临时密封焊缝必须涂漆防止与永久焊缝分离。

1	B/1-2/QNHD +19.000
QTY	MEMBERS LOCATION