

ASSEMBLY BOLT LIST (FOR 1 ASSEMBLY)						
Dia.	Grade		Pay Code	Length	No.	Site/Shop
20	A325M	G	C1	55	6	Site
(Mechanical galvanized only for DTI washer)						



1. ACCUMULATIVE DIMENSIONS ARE TAKEN FROM THE "RD LINE" 累积尺寸是从基准线“RD”引出的
2. ALL GAS RES-ENTRANT CUTS WILL HAVE A RADIUS OF 15mm 所有的气体密封切口必须有15mm的圆角, 密封所需。
3. ALL DIM SUMMARIS THIS SHEET TO BE PREPARED (361-RC3210-S-01) 此图的所有标注尺寸面要制 (361-RC3210-S-01)
4. ASSEMBLY MARK TO BE STAMPED ON THE FACE WHERE INDICATED THUS: 零件号在 标注上
5. "S" DENOTES THE TOUCH FACE OF MEMBERS, SHOP MUST STAMP "S" 为零件的结合面, 工厂需标注。
6. ALL THE DIAMETER OF SCALLOP IS 25mm U.O. 所有圆形切口直径为25mm, 所有所需。
7. ALL WELDS SHALL BE CONTINUOUS U.O. 所有焊缝必须是连续焊, 25mm。
8. SEAL WELDS OF 3MM FILL WELD SHALL BE PROVIDED IN WELDED CONNECTIONS. 焊接节缝的厚度是3mm而密封。
9. TYPING BOARD SHALL BE RED COATED TO DISTINGUISH FROM THE PERMANENT BOLT 焊接板要用红色的漆, 以区分永久板。