

am BE022

North Field South Project
Onshore LNG Facilities



TITLE
INLET AREA
STEEL STRUCTURE DRAWING
361-RC3210-S-01-BE022

SCALE 1:10		PROJECT NO. LTC/C/NFS/5496/21		
PROJECT NFS	PROJECT DOCUMENT NO. <u>5496_21-ST20301-02045</u>	SHEET No. 1	SIZE A2	REVISION 01

1	A-B/1-2/QNHD +10.400
QTY	MEMBERS LOCATION

1. ACCUMULATIVE DIMENSIONS ARE TAKEN FROM THE "RD" LINE. 积累尺寸是从该段线 "RD" 开始计算。
2. ALL GAS RE-ENTRANT OUTS WILL HAVE A RADIUS OF 0.0125mm (1/20"). 所有气体回流出口必须有 1/20 英寸的圆角。
3. ALL SUBMARIS THIS SHEET TO BE PREPARED: 301-30220(S-0-1). 这些潜水艇的制造图必须按照 301-30220(S-0-1) 来准备。
4. ASSEMBLY MARK TO BE STAMPED ON THE FACE WHERE INDICATED THIS. 零件号要在 标上。
5. ">" DENOTES THE TOUCH FACE OF MEMBERS SHIP MUST STOP THIS. ">" 为两性的凸面, 工厂需标此面。
6. ALL THE DIAMETER OF SCALLOP IS 25mm (1") 所有扇形凹口的直径是 25mm, 所有扇形凹口。
7. ALL WELDS SHALL BE CONTINUOUS. 所有焊缝必须是连续焊缝。
8. SEAL WELDS OF 3MM FILLET WELD SHALL BE PROVIDED IN WELDED CONNECTIONS. 焊接节点点的焊接是 3mm 的焊缝。
9. TEMPORARY BOLTS SHALL BE RED COTTED TO DISTINGUISH FROM THE PERMANENT BOLT. 临时螺栓要红色的, 以区别于永久螺栓。