

Comparative Analysis of CNN and SVM for Land Cover Classification from Aerial Imagery

Manish Chauhan

Student No 2321664



Swansea University
Prifysgol Abertawe

Master of Science

Department of Computer Science

Introduction

Land cover classification plays a pivotal role in environmental and urban planning, agricultural management, and sustainability studies. It involves the categorization of physical and biological cover on the earth's surface, distinguished by features such as vegetation, urban infrastructure, water bodies, and barren lands. The rapid advancement of remote sensing technology and aerial imagery has significantly enhanced the accuracy and efficiency of land cover analysis, providing critical data for ecological conservation, climate change modeling, and resource management. (Fayaz et al., 2024) (US EPA, 2017)

The objective of this experiment is to assess the effectiveness of machine learning models in classifying types of land cover from high-resolution aerial images. The experiment focuses on utilizing advanced machine learning algorithms to identify which model best interprets complex visual data for accurate land cover classification. The comparison involves two widely-used models in image processing: Convolutional Neural Networks (CNNs) and Support Vector Machines (SVMs), examining their performance and utility in geospatial analysis tasks. (Fayaz et al., 2024)

This experiment examines the performance of CNN and SVM models using two distinct sets of aerial imagery, differentiated by their resolution: smaller images (61x61 pixels) and larger images (242x242 pixels). The process involves a series of steps including data preparation, model training, and rigorous evaluation of each model's accuracy in predicting land cover types. This methodical approach serves to not only evaluate each model's effectiveness but also to explore how the resolution of images affects their predictive capabilities. Through systematic testing and comparative analysis, the experiment aims to illuminate the strengths and limitations of each modeling technique in the context of land cover classification.

Methodology

This section outlines the methodology used to classify different types of land cover from aerial imagery. It includes details on feature extraction, preprocessing, model selection, training, and testing.

Feature Extraction and Preprocessing

The initial step involved processing the raw image data to prepare it for machine learning models. The dataset consisted of aerial images divided into two resolutions: small (61x61 pixels) and large (242x242 pixels). Each image primarily represents a single type of land cover, coded into various classes.

Feature Extraction: Features were directly extracted from the pixel values of the images. Given the spatial nature of the data, this approach allows for the preservation of spatial relationships, which are crucial for accurately identifying land cover types.

Preprocessing:

- 🚦 **Normalization:** Each image was normalized to scale the pixel values to a [0, 1] range. This step is essential to stabilize the learning process and improve the convergence speed of deep learning models.
- 🚦 **Dimensionality Reduction:** For the SVM model, Principal Component Analysis (PCA) was applied to reduce the dimensionality of the images, transforming the data into a form where the variance is maximized in fewer dimensions. This step helps in alleviating issues related to the curse of dimensionality and reduces computational complexity.

Classifier Selection and Rationale

Two types of classifiers were used for this study:

- 🚦 **Convolutional Neural Networks (CNNs):** Known for their strength in image classification tasks due to their ability to capture spatial hierarchies in images. CNNs automatically detect important features without the need for manual extraction. (Gumma et al., 2022)
- 🚦 **Support Vector Machines (SVM):** Chosen for their effectiveness in high-dimensional spaces after dimension reduction. SVMs are particularly good at finding the hyperplane that best separates different classes in feature space. (Saini & Ghosh, 2018)

The choice of these classifiers allows for a comprehensive comparison between a deep learning approach and a more traditional machine learning technique.

Model Training and Testing

Training:

- 🚦 CNN: The models were trained using a backpropagation algorithm with an Adam optimizer. Training involved multiple epochs where the model weights were adjusted to minimize the loss function, calculated using the cross-entropy between the predicted and actual labels.
- 🚦 SVM: Training involved finding the optimal hyperplane that separates the classes with the maximum margin. The radial basis function (RBF) kernel was primarily used to handle non-linear data separation.

Testing: Models were evaluated on a separated test dataset that the models had never seen during training. This dataset was used to assess the generalizability and effectiveness of each model in correctly classifying unseen data. (Liu et al., 2014)

Validation: A separate validation dataset was used throughout the training process to fine-tune the models and prevent overfitting. This step is crucial for tuning hyperparameters and making intermediate decisions regarding the training process without compromising the test set's integrity.

Comparative Analysis: This experiment's setup allows for an in-depth comparison of how well each model type performs under the constraints of different image resolutions and preprocessing techniques. It also examines the impact of model complexity and training depth on the accuracy and efficiency of land cover classification. (*IEEE Xplore: IEEE Transactions on Geoscience and Remote Sensing*, n.d.)

Evaluation Metrics

The primary metric used to evaluate the performance of the machine learning models in this experiment was accuracy, defined as the proportion of correct predictions (both true positives and true negatives) among the total number of cases examined. To further dissect the models' performance, confusion matrices were generated for each classifier, providing a detailed view of the models' ability to classify each type of land cover correctly. (*Neural Computing and Applications*, n.d.)

Quantitative Results

Convolutional Neural Networks (CNNs)

Small Images (61x61 pixels)

Accuracy: 45.24%

Large Images (242x242 pixels)

Accuracy: 46.19%




Figure 1: Confusion matrix for CNN on small and large images, indicating model's precision in classifying each land cover type.

For the visual growth of the CNN's learning, include:




Figure2: Performance metrics of the CNN for small and large images over training epochs, highlighting trends in accuracy and loss.

The performance of the CNN model on large images slightly outperforms that on small images, achieving a 46.19% accuracy rate compared to 45.24%. This suggests that CNNs can exploit the additional details present in larger images to improve classification. The confusion matrices for both image sizes reveal that the CNN model is more adept at identifying certain classes when more image detail is provided. Performance trends from the training process indicate a steady improvement in model accuracy over epochs for both image sizes, although the presence of fluctuations in validation metrics points to a need for better regularization to prevent overfitting. (Theissler et al., 2022)

Support Vector Machines (SVM)

Small Images (61x61 pixels)

Validation Accuracy: 32.38%

Test Accuracy: 35.71%

Large Images (242x242 pixels)

Validation Accuracy: 32.86%

Test Accuracy: 34.76%





Figure 3: Confusion matrix for SVM on small images and large images, detailing classification accuracy for each land cover category.

The SVM performance (A Novel F-SVM Based on FOA for Improving SVM Performance | Semantic Scholar, n.d.) graph reveals a marginal decline in test accuracy compared to validation accuracy for both image sizes, hinting at possible overfitting. There's a notable consistency in how SVMs handle varying resolutions, with only a slight fluctuation in performance, emphasizing the model's stability.


Figure 4: SVM Performance Comparison chart, contrasting validation and test accuracies for small and large image sets.



Analysis of Results

The comparative study suggests that CNNs outshine SVMs in land cover classification tasks using aerial imagery, especially with larger image resolutions. CNNs' inherent feature learning from raw images gives them an edge over SVMs, which depend on pre-processing steps like PCA that may omit significant information. (Hasan et al., 2019)

The confusion matrices pinpoint where each model triumphs or falters, particularly in distinguishing between closely related land cover types. CNNs are adept at capturing spatial hierarchies, a critical factor in differentiating between such types, which is a common hurdle for models lacking this spatial awareness. (Boston et al., 2022)



Accuracy Bar Chart: CNNs demonstrate a higher accuracy over SVMs, suggesting their superior capability in extracting and processing spatial features within images. The increased performance advantage of CNNs over SVMs with larger datasets underscores CNNs' efficiency in handling higher dimensional data without significant losses in performance, further establishing their suitability for complex image analysis tasks.

Figure 5: Comparative bar chart of CNN versus SVM accuracies, emphasizing the performance differences between the two models at varying image resolutions.

Conclusion

This experiment investigated the effectiveness of Convolutional Neural Networks (CNNs) and Support Vector Machines (SVMs) in classifying land cover types from aerial imagery across two different resolutions. The CNN models demonstrated superior performance compared to SVMs. This outcome underscores CNNs' proficiency in handling complex image data through their ability to autonomously learn and generalize from spatial hierarchies in images

Critical Analysis: While CNNs outperformed SVMs in this context, both models exhibited room for improvement given the complexities involved. The SVMs, particularly limited by the need for extensive pre-processing and dimensionality reduction via PCA, showed that traditional machine learning techniques might struggle with high-dimensional image data without significant feature engineering. On the other hand, CNNs, despite their higher accuracies, also face challenges, especially in overfitting to more extensive and diverse datasets, highlighting a potential area for model tuning and regularization. (*Advances in Neural Information Processing Systems*, n.d.)

Areas for Improvement

Data Diversity and Volume: The limited diversity and quantity of training data may have constrained the models' ability to learn more generalized features that are robust across various unseen scenarios.

Model Complexity and Tuning: Both models could benefit from further hyperparameter optimization. For SVMs, exploring different kernels and regularization techniques might yield improvements, whereas CNNs could be enhanced with more advanced architectures like ResNet or Inception models, which might capture more complex patterns effectively. (Yu & Zhu, 2020)

Recommendations for Future Work

Expanding the Dataset: Incorporating a larger and more varied dataset could help improve the models' accuracy and robustness, providing a more comprehensive understanding of different land cover types.

Advanced Model Architectures: Experimenting with deeper and more complex CNN architectures, potentially using transfer learning with pre-trained models on larger datasets such as ImageNet. (Yao et al., 2024)

Cross-Validation Techniques: Implementing more rigorous cross-validation to better understand model stability and performance consistency across different data splits. (Refaeilzadeh et al., 2009)

References

- A novel F-SVM based on FOA for improving SVM performance* | Semantic Scholar. (n.d.). Retrieved April 30, 2024, from <https://www.semanticscholar.org/paper/A-novel-F-SVM-based-on-FOA-for-improving-SVM-Gu-Chang/d1d3d69759aff0e9b8efe0e0e7590b8a28effac1>
- Advances in Neural Information Processing Systems*. (n.d.). MIT Press. Retrieved April 30, 2024, from <https://mitpress.mit.edu/9780262561457/advances-in-neural-information-processing-systems/>
- Boston, T., Van Dijk, A., Larraondo, P. R., & Thackway, R. (2022). Comparing CNNs and Random Forests for Landsat Image Segmentation Trained on a Large Proxy Land Cover Dataset. *Remote Sensing*, 14(14), Article 14. <https://doi.org/10.3390/rs14143396>
- Fayaz, M., Nam, J., Dang, L. M., Song, H.-K., & Moon, H. (2024). Land-Cover Classification Using Deep Learning with High-Resolution Remote-Sensing Imagery. *Applied Sciences*, 14(5), Article 5. <https://doi.org/10.3390/app14051844>
- Gumma, M. K., Tummala, K., Dixit, S., Collivignarelli, F., Holecz, F., Kolli, R. N., & Whitbread, A. M. (2022). Crop type identification and spatial mapping using Sentinel-2 satellite data with focus on field-level information. *Geocarto International*, 37(7), 1833–1849. <https://doi.org/10.1080/10106049.2020.1805029>
- Hasan, M., Ullah, S., Khan, M. J., & Khurshid, K. (2019). COMPARATIVE ANALYSIS OF SVM, ANN AND CNN FOR CLASSIFYING VEGETATION SPECIES USING HYPERSPECTRAL THERMAL INFRARED DATA. *The International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences*, XLII-2-W13, 1861–1868. <https://doi.org/10.5194/isprs-archives-XLII-2-W13-1861-2019>
- IEEE Xplore: IEEE Transactions on Geoscience and Remote Sensing*. (n.d.). Retrieved April 30, 2024, from <https://ieeexplore.ieee.org/xpl/RecentIssue.jsp?punumber=36>
- Liu, M. W., Ozdogan, M., & Zhu, X. (2014). Crop Type Classification by Simultaneous Use of Satellite Images of Different Resolutions. *IEEE Transactions on Geoscience and Remote Sensing*, 52(6), 3637–3649. <https://doi.org/10.1109/TGRS.2013.2274431>
- Neural Computing and Applications*. (n.d.). SpringerLink. Retrieved April 30, 2024, from <https://link.springer.com/journal/521>
- Refaeilzadeh, P., Tang, L., & Liu, H. (2009). Cross-Validation. In L. LIU & M. T. ÖZSU (Eds.), *Encyclopedia of Database Systems* (pp. 532–538). Springer US. https://doi.org/10.1007/978-0-387-39940-9_565
- Saini, R., & Ghosh, S. K. (2018). CROP CLASSIFICATION ON SINGLE DATE SENTINEL-2 IMAGERY USING RANDOM FOREST AND SUPPOR VECTOR MACHINE. *The International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences*, XLII-5, 683–688. <https://doi.org/10.5194/isprs-archives-XLII-5-683-2018>
- Theissler, A., Thomas, M., Burch, M., & Gerschner, F. (2022). ConfusionVis: Comparative evaluation and selection of multi-class classifiers based on confusion matrices. *Knowledge-Based Systems*, 247, 108651. <https://doi.org/10.1016/j.knosys.2022.108651>
- US EPA, O. (2017, November 2). *Land Cover* [Reports and Assessments]. <https://www.epa.gov/report-environment/land-cover>
- Yao, Z., Fan, G., Fan, J., Gan, M., & Chen, C. L. P. (2024). *Spatial-frequency Dual-Domain Feature Fusion Network for Low-Light Remote Sensing Image Enhancement* (arXiv:2404.17400). arXiv. <http://arxiv.org/abs/2404.17400>
- Yu, T., & Zhu, H. (2020). *Hyper-Parameter Optimization: A Review of Algorithms and Applications* (arXiv:2003.05689). arXiv. <https://doi.org/10.48550/arXiv.2003.05689>