Piccalilli

Front-end education for the real world. Since 2018.

From set.studio





Articles

Links

Newsletter

About

A (more) Modern CSS Reset

Published: 18 September 2023 Written by: Andy Bell

I know I also have a terrible record with open source maintenance, so I thought I'd <u>archive the original</u> and just post this instead. Do with it what you want!

To be super clear, this is a reset that works for me, personally and us at <u>Set Studio</u>. Whenever I refer to "we", that's who I'm referring to.

The reset in whole

```
CSS
                                         COPY TO CLIPBOARD
/* Box sizing rules */
*,
*::before,
*::after {
  box-sizing: border-box;
}
/* Prevent font size inflation */
html {
  -moz-text-size-adjust: none;
  -webkit-text-size-adjust: none;
  text-size-adjust: none;
}
/* Remove default margin in favour of better control in
body, h1, h2, h3, h4, p,
figure, blockquote, dl, dd {
 margin-block-end: 0;
}
/* Remove list styles on ul, ol elements with a list ro
ul[role='list'],
ol[role='list'] {
  list-style: none;
}
/* Set core body defaults */
body {
  min-height: 100vh;
```

```
line-height: 1.5;
}
/* Set shorter line heights on headings and interactive
h1, h2, h3, h4,
button, input, label {
  line-height: 1.1;
}
/* Balance text wrapping on headings */
h1, h2,
h3, h4 {
  text-wrap: balance;
}
/* A elements that don't have a class get default style
a:not([class]) {
  text-decoration-skip-ink: auto;
 color: currentColor;
}
/* Make images easier to work with */
img,
picture {
 max-width: 100%;
 display: block;
}
/* Inherit fonts for inputs and buttons */
input, button,
textarea, select {
  font-family: inherit;
  font-size: inherit;
```

```
/* Make sure textareas without a rows attribute are not
textarea:not([rows]) {
    min-height: 10em;
}

/* Anything that has been anchored to should have extra
:target {
    scroll-margin-block: 5ex;
}
```

Breakdown

As is tradition, let's break it down:

```
/* Box sizing rules */
*,
*::before,
*::after {
  box-sizing: border-box;
}
```

This rule is pretty self explanatory, but in short, I'm setting all elements and pseudo-elements to use the border-box, <u>rather</u> than the default content-box for sizing. Now we're focussing

more on letting the <u>browser do more work</u> with <u>flexible</u> <u>layouts</u> with <u>fluid type and space</u>, this rule isn't as useful as it once was. But, it's rare that a project doesn't have some explicit sizing somewhere, so it's still got a place in the reset.

```
/* Prevent font size inflation */
html {
   -moz-text-size-adjust: none;
   -webkit-text-size-adjust: none;
   text-size-adjust: none;
}
```

The <u>best explainer for this is by Kilian</u>. He also explains why we still need those ugly prefixes too.

```
/* Remove default margin in favour of better control in body, h1, h2, h3, h4, p, figure, blockquote, d1, dd {
   margin-block-end: 0;
}
```

I'll always favour stripping out user agent styles for margin in favour of <u>defining flow and space at a more macro level</u>. With logical properties, I'm removing the end margin now instead of all sides in the older reset. It seems to work well in production.

```
/* Remove list styles on ul, ol elements with a list roul[role='list'],
ol[role='list'] {
  list-style: none;
}
```

Safari do some wild shit, which includes <u>this one</u>: if you remove list styling, they'll remove the semantics for VoiceOver. Some will say it's a feature and some will say it's a bug. I say it's daft, but to make sure that a <u>role</u> is added, I remove the list styling by default for it as a little reward.

```
/* Set core body defaults */
body {
   min-height: 100vh;
   line-height: 1.5;
}
```

I like a nice legible line height that gets inherited. Setting a min height as 100vh on the body is pretty handy too, especially if you're gonna be setting decorative elements. It might be tempting to use a new unit like dvh, but if you delve deep like

Ahmad has, you'll see that can cause more problems than solutions, which is not what you want your reset to be doing!

The svh unit seems better than dvh, but I'm happy with vh. Always make sure you understand the newer units before diving head first into them, or recommending them as gospel is my advice. If something is already working for you, there's no need to change it!

```
/* Set shorter line heights on headings and interactive h1, h2, h3, h4, button, input, label { line-height: 1.1; }
```

Just like it's handy to have a generous line-height globally, it's equally handy to have a shorter line-height for headings and buttons etc. It's definitely worth removing or modifying this rule if your font has large ascenders and descenders though. The last thing you want is those clashing with each other and creating an accessibility issue.

```
/* Balance text wrapping on headings */
h1, h2,
```

```
h3, h4 {
  text-wrap: balance;
}
```

This rule is rather specific to our projects, but the newish textwrap property makes headings look lovely. I imagine some people will find this not appropriate, so you might want to remove this one.

```
/* A elements that don't have a class get default style
a:not([class]) {
  text-decoration-skip-ink: auto;
  color: currentColor;
}
```

This rule is first making sure the text decoration doesn't interfere with ascenders and descenders. I think this is mostly default in browsers now, but it's a good insurance policy to set it too. We like to set links to inherit the currentColor of text too by default at the studio, but if you don't, you probably want to remove it.

```
/* Inherit fonts for inputs and buttons */
input,
```

```
button,
textarea,
select {
  font-family: inherit;
  font-size: inherit;
}
```

It's useful to let form elements and buttons inherit some font properties at this point. It's mostly going to affect <textarea> elements, but there's no harm in applying it to other form elements too because it saves on some CSS later on in a project.

```
/* Make sure textareas without a rows attribute are not textarea:not([rows]) {
   min-height: 10em
}
```

Speaking of <textarea> elements, this rule is handy. By default, if you don't add a rows attribute, they can be super teeny. This isn't ideal with coarse pointers such as fingers and by proxy, <textarea> elements tend to be used for multiple lines of text. It makes sense to make that easier.

```
CSS COPY TO CLIPBOARD 🔾
```

```
/* Anything that has been anchored to should have extra
:target {
   scroll-margin-block: 5ex;
}
```

Finally, if an element is anchored, it makes sense to add a bit more space above it with scroll-margin, which is only accounted for if that element is targeted. A little tweak with lots of user experience power! You might want to adjust this if you have a fixed header though.

Wrapping up

Will this reset last another 4 years? Maybe! The <u>other</u> <u>one</u> certainly hasn't caused issues.

Regardless, it's pretty useful as a base to start projects, here at <u>the studio</u>. We don't go back and retroactively update the other reset on client projects either because that one works absolutely fine.

Resets are one of those things that people get worked up about, but really, with browsers being so bloody good now, you probably don't even need one in the first place. My advice is take bits you like from ones you find on the web and create your own, that works for you and your team.

You can also read this post in Japanese.

This post and source code is licensed under a <u>Creative Commons</u> Attribution License.

COURSE

Complete CSS

Take your CSS skills beyond the next level



Launching late-2024. Sign up for updates.



By Andy Bell

Designer, developer and founder of Piccalilli and Set Studio.

» More about Andy Bell

Topic(s).

css

Get new articles in your inbox		P.
Enter your email		RSS.
	SUBSCRIBE	
Powered by <u>Buttondown</u> <u>Privacy policy</u>		



From set.studio

Code of Conduct

Privacy and cookie policy

Contact

RSS