24. Design a C program to demonstrate UNIX system calls for file management.

```
#include <stdio.h>
#include <fcntl.h>     // for open() and O_* constants
#include <unistd.h>    // for read(), write(), close()
#include <stdlib.h>
int main() {
   int fd;
   char buffer[100];
   fd = open("demo.txt", O_CREAT | O_RDWR, 0777);
   if (fd < 0) {
      printf("Error opening file!\n");
      exit(1);
   }
   printf("File created/opened successfully.\n");
   write(fd, "Hello, UNIX System Calls!\n", 26);
   printf("Data written to file.\n");
   lseek(fd, 0, SEEK_SET);
   int n = read(fd, buffer, sizeof(buffer));
   buffer[n] = '\0';
   printf("Data read from file: %s", buffer);
   close(fd);
   printf("File closed successfully.\n");

   return 0;
}
```

OUTPUT-



```
(globals)
lab 1.cpp
#include <stdio.h>
#include <fcntl.h>      // for open() and O_* constants
#include <unistd.h>     // for read(), write(), close()
#include <stdlib.h>
int main() {
    int fd;
    char buffer[100];
    fd = open("demo.txt", O_CREAT | O_RDWR, 0777);
    if (fd < 0) {
        printf("Error opening file!\n");
        exit(1);
    }
    printf("File created/opened successfully.\n");
    write(fd, "Hello, UNIX System Calls!\n", 26);
    printf("Data written to file.\n");
    lseek(fd, 0, SEEK_SET);
    int n = read(fd, buffer, sizeof(buffer));
    buffer[n] = '\0';
    printf("Data read from file: %s", buffer);
    close(fd);
    printf("File closed successfully.\n");

    return 0;
}
```

```
C:\Users\ROJAYADAV\OneDri
File created/opened successfully.
Data written to file.
Data read from file: Hello, UNIX System Calls!
File closed successfully.

--------------------------------
Process exited after 2.138 seconds with return value 0
Press any key to continue . . .
```