

Make My Figure — Quick Start

From installation to an exported figure

MakeMyFigure version 1.1.0
Documentation generated from commit 473d495
Date 2026-09-11

Built from the current code and the running application. Screenshots and example figures use bundled synthetic data only.

Page references in the Contents count from the first body page.

Contents

Make My Figure — Quick Start · 1

1. What Make My Figure does · 1
2. Installation · 1
3. Open the app · 3
4. Load data · 5
5. Make a basic figure · 6
6. Use recommendations · 7
7. Run statistics · 7
8. Matrix workflow · 9
9. Save a Figure preset · 10
10. Figure Builder (multi-panel figures) · 11
11. Export · 11
12. Where to get help · 12

Make My Figure — Quick Start

MakeMyFigure version: 1.1.0

Documentation generated from commit: 473d495


Date: 2026-09-11

This manual describes the application exactly as built at the commit above. Where the packaged installers of an earlier release differ, the text says so.

1. What Make My Figure does

Make My Figure turns a table you already have — a CSV, a TSV, or an Excel workbook — into a manuscript-style scientific figure, and records how the figure was made so it can be rebuilt later.

The path through the application is always the same:



Multi-panel assembly (Figure Builder) and Figure presets sit alongside every step.

Figure 1. The Make My Figure workflow: load, map columns, choose a plot (or take a recommendation), optional statistics, style and annotate, export with a PlotSpec record.

1. **Load** a table (or one worksheet of a workbook).
2. **Map columns** to roles — you confirm which column is x, y, group, p-value, time, event, and so on. The program never guesses biological meaning silently.
3. **Choose a plot type** from the 38 in the registry, or take one of the *advisory* recommendations.
4. **Optionally run statistics** — you choose the method; results are stored and every p-value drawn on the figure comes from a stored result.
5. **Style** the figure with the single **Publication** style (fonts, palette, layout, legend), add annotations.
6. **Assemble** several plots into a multi-panel figure if you need one.
7. **Export** SVG, PDF, PNG (and TIFF/EPS) together with a **PlotSpec** JSON that records the configuration — or **Save Figure Package** to get one portable `.mmfpackage` that also freezes the data.

Two interfaces share one engine: a **desktop app** (Qt) and a **browser app** (Streamlit). Both run entirely on your computer; nothing is uploaded anywhere.

Note: Make My Figure is a plotting and reporting tool. It computes the statistics you ask for and recommends plots from the *shape* of your table, but the choice of method, the interpretation, and journal compliance remain yours. Publication is a general manuscript style, not a journal template.

2. Installation

A. Packaged application (no Python needed)

Download the installer for your system from the project's GitHub **Releases** page (release **v1.1.0**):

System	File	Steps
macOS	MakeMyFigure-1.1.0.dmg	open the DMG, drag <i>Make My Figure</i> to <i>Applications</i> , launch it. The bundle is not notarised: on first launch right-click → Open (or allow it under <i>System Settings</i> → <i>Privacy & Security</i>).
Windows	MakeMyFigure-1.1.0-Setup.exe (or MakeMyFigure-1.1.0-windows.zip)	run the installer (or unzip and start MakeMyFigure\MakeMyFigure.exe). SmartScreen may warn about an unsigned program; choose <i>More info</i> → <i>Run anyway</i> if you trust the source.
Linux	MakeMyFigure-1.1.0.AppImage (or MakeMyFigure-1.1.0-linux.tar.gz)	chmod +x MakeMyFigure-1.1.0.AppImage && ./MakeMyFigure-1.1.0.AppImage, or unpack the tarball and run MakeMyFigure/MakeMyFigure.
WSL2 (Linux under Windows)	not a native package	use the source install below with WSLg (Windows 11) or run the browser app and open it in a Windows browser.

SHA256SUMS.txt on the release page lists the checksum of every file. The status bar (desktop) shows Make My Figure v1.1.0 · <commit> · <platform> · <backend> on launch, and **Help** → **About** shows the version.

B. From source (desktop and browser apps)

Requirements: **Python 3.10–3.12** (the metadata allows 3.9, but Apple's bundled 3.9 failed pip's byte-compile step on a PySide6 file during testing — use a newer interpreter), git, and about 1 GB of disk for the Qt binding.

```
git clone https://github.com/surPoudel/make-my-figure.git
cd make-my-figure
python3 -m venv .venv
source .venv/bin/activate          # Windows PowerShell:
.venv\Scripts\Activate.ps1
python -m pip install --upgrade pip
python -m pip install --no-compile -r requirements.txt
python -m pip install --no-compile -e ".[desktop]"      # adds PySide6 for the
desktop app
```

`--no-compile` skips a byte-compile step that fails on one PySide6 template file with some interpreters; Python compiles what it needs on first import.

Verify the build you are running:

```
python -c "from make_my_figure_core.version import build_banner;
print(build_banner())"
```

The line shows the version, the git commit, the platform and the Matplotlib backend. The same banner appears in the desktop status bar on launch and in the browser sidebar, so you can always confirm the manual matches the app.

Linux / WSL only: the Qt binding needs system libraries that minimal images lack:

```
sudo apt install -y libxkbcommon0 libxkbcommon-x11-0 libgl1 libegl1 libxcb-cursor0 \
```

```
libxcb-xinerama0 libxcb-keysyms1 libxcb-randr0 libxcb-render-util0 libxcb-shape0
\
libxcb-icccm4 libxcb-image0 libxcb-xfixes0 libdbus-1-3
```

If the desktop app cannot start it prints exactly this list. The browser app needs none of it.

3. Open the app

Desktop:

```
python -m apps.desktop_app.main
```

Browser:

```
streamlit run apps/streamlit_app/streamlit_app.py
```

and open the address Streamlit prints (normally `http://localhost:8501`).

The desktop app opens on the **Home / Upload** page. Drop a file onto it, choose **File** → **Open data file...**, or pick a bundled example from **File** → **Open example**.



Figure 2. Desktop app on launch: the Home / Upload page. Everything runs locally.

After data loads you are in the **plot workspace**: controls on the left (plot type, recommendations, column mapping, options, labels, Figure preset, Publication style, Statistics, Export), the data preview and messages at the top right, and the figure below them.




Figure 3. Desktop workspace with the bundled bar-plot example loaded: controls (left), data preview and messages (top

right), live figure (bottom right).

The browser app has the same sections in its sidebar, numbered 1–6, with the table, the figure preview, Publication QC and Export in the main column.

Reset / Upload new data

Make My Figure v1.1.0 · cea313c · Linux · Agg

Diagnostics

1. Data

Data source

- Bundled sample
- Upload file
- Open PlotSpec

Example dataset (by plot type)

Bar plot with error bars

Synthetic example — Compare a mean readout across experimental conditions with replicate error bars.

Workflow

- Quick plot
- Matrix workflow (guided)

2. Plot type

Plot type

Bar plot with error bars

3. Style

Style

Publication

4. Column mapping

x

condition

y

measurement

color

condition

Error bar

sem

Figure preset

5. Publication style

Figure

Typography

Axes & labels

Legend

Colorbar

Not applicable to barplot with error bar: Style control 'marker_size' bars have no markers or data lines; error-bar and edge widths come from the profile; it was ignored for this barplot_with_error_bar.

Style control 'line_width_pt' bars have no markers or data lines; error-bar and edge widths come from the profile; it was ignored for this barplot_with_error_bar.

Style control 'legend_pt' bars have no markers or data lines; error-bar and edge widths come from the profile; it was ignored for this barplot_with_error_bar.

Style control 'legend_outside' bars have no markers or data lines; error-bar and edge widths come from the profile; it was ignored for this barplot_with_error_bar.

6. Statistics

Statistical tests & annotations

Make My Figure

Manuscript-ready scientific figures in a single, polished Publication style. This is a general publication-ready visual style — not an official journal template, and not a guarantee of submission compliance.

Table — barplot_with_error_bar (example)

Edit cells directly to update the figure. Add/remove rows with the controls at the bottom of the table.

V_1 condition	V_1 replicate	V_1 measurement	V_1 unit	V_1 experiment_batch
Control	R1		1.037 relative_signal	Batch_1
Control	R2		0.875 relative_signal	Batch_1
Control	R3		1.09 relative_signal	Batch_1
Control	R4		1.113 relative_signal	Batch_2
Control	R5		0.766 relative_signal	Batch_1
Control	R6		0.844 relative_signal	Batch_2
Drug_A	R1		1.615 relative_signal	Batch_1
Drug_A	R2		1.562 relative_signal	Batch_1
Drug_A	R3		1.598 relative_signal	Batch_1
Drug_A	R4		1.498 relative_signal	Batch_2

Rows 24Columns 5Numeric columns 1

Define groups (no metadata file needed)

Recommended figures

Figure preview

condition	measurement (mean ± SEM)
Control	~0.95 ± 0.1
Drug_A	~1.6 ± 0.05
Drug_B	~0.7 ± 0.05
Combination	~2.1 ± 0.05

Publication check: passed

Style control 'marker_size' bars have no markers or data lines; error-bar and edge widths come from the profile; it was ignored for this barplot_with_error_bar.

Style control 'line_width_pt' bars have no markers or data lines; error-bar and edge widths come from the profile; it was ignored for this barplot_with_error_bar.

Style control 'legend_pt' bars have no markers or data lines; error-bar and edge widths come from the profile; it was ignored for this barplot_with_error_bar.

Style control 'legend_outside' bars have no markers or data lines; error-bar and edge widths come from the profile; it was ignored for this barplot_with_error_bar.

Publication QC — ready-to-export checks

Render metadata

Export

SVG

PNG

PDF

PlotSpec JSON

Figure 4. Browser app with the same example: numbered sidebar sections, editable table, figure preview, export

Make My Figure — Quick Start · v1.1.0 · 473d495

4


buttons.

4. Load data

Supported files: **CSV**, **TSV**, **TXT/TAB** (delimited text) and **Excel .xlsx, .xlsm, .xls**. Put column names in the first row and one observation per row. Numeric measurements should be numeric columns; identifiers and labels can be text.

- **Desktop:** drag a file onto the window, or **File** → **Open data file...**
- **Browser:** sidebar **1. Data** → **Upload file** → **Upload CSV / TSV / XLSX**

Excel workbooks with several sheets. Every worksheet is listed and selectable, including notes and empty sheets. Pick one in the  **Worksheet** box (desktop) or sidebar (browser). Each sheet is classified — *differential results, matrix, metadata, enrichment, documentation, generic, empty* — as a hint, not a decision; you can plot from any sheet.



The screenshot shows the 'Make My Figure' web application interface. On the left is a sidebar with sections: '1. Data' (containing 'Data source' with 'Upload file' and 'Open PlotSpec' options, and 'Worksheet' with a list of 40 worksheets including 'Bar_error'), '2. Plot type', '3. Style', '4. Column mapping', '5. Publication style', and '6. Statistics'. The main workspace is titled 'Make My Figure' and displays a table titled 'Table — Make_My_Figure_All_Example_Data.xlsx [Bar_error]'. The table has 5 columns: 'R1_condition', 'R1_replicate', 'R1_measurement', 'R1_unit', and 'R1_experiment_batch'. Below the table, it shows 'Rows: 24', 'Columns: 5', and 'Numeric columns: 1'. There are also buttons for 'Define groups (no metadata file needed)' and 'Recommended figures'. A 'Figure preview' section at the bottom indicates 'Data loaded. Choose a plot type to render a figure, or open Matrix workflow for a guided feature-matrix workflow.'

R1_condition	R1_replicate	R1_measurement	R1_unit	R1_experiment_batch
Control	R1	1.097	relative_signal	Batch_1
Control	R2	0.875	relative_signal	Batch_2
Control	R3	1.09	relative_signal	Batch_1
Control	R4	1.113	relative_signal	Batch_1
Control	R5	0.766	relative_signal	Batch_1
Control	R6	0.844	relative_signal	Batch_2
Drug_A	R1	1.615	relative_signal	Batch_1
Drug_A	R2	1.562	relative_signal	Batch_1
Drug_A	R3	1.596	relative_signal	Batch_1
Drug_A	R4	1.408	relative_signal	Batch_2

Figure 5. Browser app with the bundled example workbook: 40 worksheets listed, the selected sheet's detected type,

and the header-row selector.

In the browser app you can also choose the **Header row** (first row, a chosen row, two stacked rows, or no header) and, for spreadsheets whose group label is written once over a block of replicate columns, tick **Carry a group label across blank cells**. Merged Excel cells are recovered automatically. The desktop app reads the first row as the header.

Matrix tables (features in rows, samples in columns, e.g. an expression or intensity matrix) work in the ordinary editor for heatmaps, clustering and PCA, and have their own guided **Matrix workflow** (section 8).

5. Make a basic figure

Use the bundled example so the steps match the screenshots exactly: **File** → **Open example** → **Bar plot with error bars** (desktop) or **Bundled sample** → **Bar plot with error bars** (browser).

1. **Plot type** is already *Bar plot with error bars*; the **Style** is *Publication* (the only style).
2. **2. Map columns:** $x \rightarrow \text{condition}$, $y \rightarrow \text{measurement}$, $\text{color} \rightarrow \text{condition}$. With your own data, set each role yourself — the defaults only prefill when a matching column exists.
3. **3. Options:** **Error bar** → *sem*, *sd*, *ci95* or *none*; **X-axis label angle**.
4. The figure re-renders as you change anything (the desktop debounces continuous controls so dragging stays responsive).
5. **4. Labels & size:** title, axis labels, **Figure width** preset (default / single / onehalf / double column) and **Raster DPI**.
6. **5. Publication style** — tick the box to enable it (desktop) or open the expanders (browser): typography, palette, tick angles, padding, legend location, colorbar, margins.

5. Publication style

② Typography

Palette (publication default)

Font (publication default)

Title pt 14

Axis label pt 12

Tick label pt 10

Annotation pt 10

Marker size 45

Line width 1.80

Axis/spine width 1.10

Grid ☐

③ Axes_labels

X tick angle auto

Y tick angle auto

X label padding 0.00

Y label padding 0.00

Title padding 0.00

④ Legend

Location auto

Legend pt 10

Legend outside ☐

⑤ Colorbar (heatmaps etc.)

Location default

Pad (0 = default) 0.00

Size 1.00

① Figure margins

Left (0 = auto) 0.00

Right (0 = auto) 0.00

Top (0 = auto) 0.00

Bottom (0 = auto) 0.00

Auto-fix layout ☐

Reset to publication defaults

Figure 6. The Publication style group: ② Typography, ③ Axes and labels, ④ Legend, ⑤ Colorbar, ① Figure margins,

and Reset to publication defaults.

1. **Export:** desktop **5. Export** → **Export SVG / PNG / PDF / Export PlotSpec JSON (specification only), Save Figure Package (.mmfpackage) or Export all as ZIP** (figures + specs + package); browser **Export** → **SVG / PNG / PDF / PlotSpec JSON / Figure Package** download buttons. The PlotSpec JSON records the configuration but *not* the data — it needs the source table to reopen. The **figure package** is the file to move or share: it holds the specification **and** a frozen copy of the data, and reopens anywhere with **Open Figure Package**.




Figure 7. Desktop Export group: SVG, PNG, PDF, PlotSpec JSON, ZIP bundle, template table, and the multi-panel buttons.

Controls that do not apply to the current plot are reported rather than silently ignored — for a bar plot, for example, the marker-size and line-width controls do nothing and the app says so.

6. Use recommendations

When a table loads, Make My Figure profiles it (numeric vs. categorical columns, identifiers, p-value-like columns, matrix shape, edge lists, survival columns...) and suggests plots with a match score and the reason.




Figure 8. Recommended plots for a grouped-observation table: each card explains the match and offers Generate, Add to Figure Builder, or Dismiss.

- **Desktop:** the **Recommended figures** group under the plot type; **Generate** switches to that plot with the suggested mapping; **Add to Figure Builder** saves it as a panel.
- **Browser:** the  **Recommended figures** expander above the figure.

Recommendations are **advisory**. The score is a rule-based heuristic on the table's shape, not a measure of scientific appropriateness. You remain responsible for choosing what the figure should show.

7. Run statistics

Example: **Box / violin plot with points** (bundled). In **6. Statistics** (desktop: tick the group box, then **Enable statistics**; browser: **Statistical tests & annotations** expander):

1. **Test** — e.g. *Welch's t-test*. Eighteen methods are available (t-tests, Mann-Whitney, Wilcoxon, ANOVA variants, Kruskal-Wallis, Dunn, chi-square, Fisher, log-rank, Cox, Pearson, Spearman,

linear regression, GLM). *Auto-suggest* proposes one from the mapping; it is a suggestion, not a decision.

2. **Comparison** — all groups pairwise, compare to a control, within each x category, selected pairs, or omnibus only.
3. **Correction** — Benjamini–Hochberg FDR, Bonferroni, Holm, or none.
4. **Annotation shows / placement** — stars, exact p, adjusted p, statistic, effect size...; brackets between compared groups, or one label above each bar when comparing to a control.
5. **Run statistics.** The results table lists each comparison with p, adjusted p, effect size and n, and a **method sentence** is written for your Methods section. Export the table (CSV) or the method report (Markdown).

☒ 6. Statistics

☒ Enable statistics

Test

Welch's t-test

Comparison

Compare all groups (pairwise)

Group column

(none)

Subgroup column

(none)

Subject/pair ID

(none)

Control group

(none)

Correction

Benjamini-Hochberg FDR

Annotation shows

Stars only

Annotation placement

Bracket between the compared bars

Custom template

☐ Show effect size on figure
☐ Hide non-significant annotations
☐ Post-hoc pairwise after omnibus

P-value decimals

3

Annotation font pt

9.50

Run statistics

Clear

Reset

Suggested: One-way ANOVA. Three or more groups: one-way ANOVA or Kruskal-Wallis, optionally with post-hoc pairwise tests and correction.

	Comparison	Test	p	adj p	effect	n
1	Healthy vs Disease	Welch's t-test	5.971e-12	1.791e-11	Hedges' g=-2.67	48
2	Healthy vs Treated	Welch's t-test	3.051e-05	4.577e-05	Hedges' g=-1.33	48
3	Disease vs Treated	Welch's t-test	0.0006929	0.0006929	Hedges' g=1.03	48

Statistical analyses were performed with Python (scipy 1.17.1, statsmodels 0.14.6, numpy 2.1.2). Tests used: Welch's t-test. P-values were adjusted across 3 comparisons using Benjamini-Hochberg FDR correction. Exact p-values are reported unless otherwise noted. Non-finite values were removed listwise before testing. Users are responsible for confirming that each test is appropriate for their experimental design.

Export stats table

Export method report

Copy method sentence

Figure 9. The Statistics panel after Run statistics on the box/violin example: Welch's t-test, all pairs, BH correction,

Warning: the program performs the calculation you request. It does not verify that a test suits your design. Check assumptions (independence, pairing, distribution) before you rely on a result.

8. Matrix workflow

For a feature-by-sample matrix, open **Matrix workflow...** (desktop) or choose **Workflow → Matrix workflow (guided)** (browser).

Map a feature-by-sample matrix, define groups, then generate publication plots. Nothing is plotted until you confirm the mapping — annotation columns are never treated as measurements. Generic feature matrix (no raw-count pipeline, no R).

① Map columns ② Define groups ③ Preprocess (raw-like) ④ Validation ⑤ Recommend_generate

Feature ID column:

Feature display column:

Value scale (you confirm):

Select the VALUE (sample/measurement) columns. Numeric annotation columns (e.g. a 1/2/3 level code) are left unselected by default — check them only if they are real measurements. Everything unselected becomes an annotation column.

gene
Ctrl_1
Ctrl_2
Ctrl_3
Ctrl_4
DrugA_1
DrugA_2
DrugA_3
DrugA_4
DrugB_1
DrugB_2
DrugB_3
DrugB_4

Confirm mapping

Close

Figure 10. Matrix workflow, step ① Map columns: feature ID column, value columns, and the value scale you confirm before anything is plotted.

1. ① **Map columns** — the feature ID column, optional display column, the **value (sample) columns**, and the **value scale** (normalized, log_normalized, raw_numeric, or unknown_user_confirmed). Numeric annotation columns are left unselected until you tick them. Click **Confirm mapping**.
2. ② **Define groups** — upload a metadata file, take one from another worksheet, or type a group per sample column; then **Confirm groups**.
3. ③ **Preprocess (raw-like)** — optional, for raw-like data: **Run diagnostics** (suspected data type, skew, zeros, negatives), preview a **QC plot**, pick one of the **recommended preprocessing** recipes (e.g. *Total-sum normalize → log2 → z-score*; nothing is applied automatically), then **Apply preprocessing → use processed matrix**. Each step is recorded; the original matrix is never modified; **Save before/after QC report...** writes the report.
4. ④ **Validation** — a report of the confirmed mapping and groups (features, samples, groups, missing values, duplicate ids) with warnings or ✓ *Validation passed*.
5. ⑤ **Recommend & generate** — an optional two-group **differential summary** (test, correction, groups A/B), then recommended plots (heatmap, PCA, box plots, volcano/MA once a summary exists) with **Quick preview** and **Open in plot editor**, which hands the derived table to the full editor with its provenance.

9. Save a Figure preset

A **Figure preset** is your configuration without your data. Configure a figure once, save the preset, and apply it to a new dataset of the same plot type later.

- **Figure style only** — fonts, palette, line/marker sizes, tick angles, margins, legend and colorbar placement, export size/DPI, and visual plot options (violin vs box, colormap, node colours...). Portable: this is the lab's *Lab_Default_Heatmap.mmfpreset.json*.
- **Full figure configuration** — everything above plus column roles, thresholds, axis labels and the statistics test. On new data it applies what fits and lists the columns it could not find, for you to map — it never guesses.

Preset name

☒ Figure style only - fonts, colours, layout, legend, export. Portable: apply to any data of this plot type.

☐ Full figure configuration - also column roles, thresholds, axis labels and statistics. Asks for remapping on new data.

Neither kind contains your data or the table's name.

Figure 11. Save Figure Preset: name it and choose style-only or full configuration. Neither kind contains your data.

Desktop: the **Figure preset** group (above Publication style) — choose a preset, **Apply**, **Save preset...**, **Delete**, **Import...**, **Export...**, **Reset to Publication defaults**; the same actions are in **File** → **Figure preset**. **Browser:** the **Figure preset** expander in the sidebar.

Lab scatter style [style]

2 presets for this plot type.

Figure 12. The Figure preset group with saved presets listed for the current plot type.

A **PlotSpec** is different: it is the exact record of *one* figure, including the table name and column names — but not the values; the source table is required to reopen it. An existing PlotSpec can be loaded as a full preset.

A **Figure package** (*.mmfpackage*) is the third kind of file: the PlotSpec (or FigureSpec) *plus* a frozen copy of the exact data, the StatsSpec results, the Matrix Workflow records where they apply, imported images, previews and a checksum for every file. It is the one file to send to a collaborator; **Open Figure Package** reproduces the figure without the original data files. Because it contains data, share it only with people who may see those data.





Figure 13. PlotSpec versus Figure preset: what each contains, and what never enters a preset.

In the desktop app, click **Save current plot as panel** for each plot you want, then **Open Figure Builder....**



- Note:** the composite embeds each panel's content as a raster image at the export DPI; panel letters and titles stay vector text. For a fully vector single panel, export that plot directly as SVG or PDF. The browser app has a simpler Figure Builder (columns only) inside the guided Matrix workflow.

11

Format	Type	DPI	Text	Typical use
SVG	vector	—	editable	edit further in Illustrator/Inkscape; journals accepting SVG
PDF	vector	—	editable (embedded Type 42 fonts)	manuscript submission, print
EPS	vector	—	editable	legacy journal systems (core/ZIP export)
PNG	raster	150–600 (set in Raster DPI)	—	slides, previews, journals requiring raster
TIFF	raster (LZW)	as PNG	—	journals requiring TIFF (core/ZIP export)

Export PlotSpec JSON writes `name.plot_spec.json` (specification only); **Export all as ZIP** bundles SVG/PNG/PDF, `name.plot_spec.json`, `name.stats_spec.json` when statistics ran, and `name.mmfpackage`. **Save Figure Package** writes the package alone.

Sharing a reproducible figure

1. Finalise the plot.
2. **Save Figure Package**.
3. Send the one `.mmfpackage` file.
4. The collaborator opens Make My Figure.
5. **Open Figure Package** (landing page or File menu).
6. Integrity is verified (every SHA-256).
7. The figure opens with the frozen data and configuration.
8. Inspect, edit and export as usual.

	PlotSpec	Figure preset	Figure package
purpose	recipe for one plot	reusable configuration	portable reproducibility bundle
contains data	no — source data required	no	yes — frozen copy + specifications
file	<code>.plot_spec.json</code>	<code>.mmfpreset.json</code>	<code>.mmfpackage</code>

12. Where to get help

- **Desktop Help menu:** **Help...** (plot types, how to format your data, privacy, the Publication-style disclaimer), **About** (version), **Copy debug info**.
- **Browser sidebar:** the version banner and 🐞 **Diagnostics**.
- The full **User Manual** (this folder) documents every control, plot, statistic and file.
- **Repository:** <https://github.com/surPoudel/make-my-figure> (issues, if the repository is public for you).

Always quote the banner line (version · commit · platform · backend) when reporting a problem.