TEST CASE 1:

```
    /usr/local/bin/python3 "/Users/surabhiraghavan/Desktop/Algo Design/Proj1Array.py"
●  surabhiraghavan@Surabhis-MacBook-Pro Algo Design % /usr/local/bin/python3 "/Users/surabhiraghavan/Desktop/Algo Design/Proj1Array.py"
    Enter elements of the first sorted subarray (space-separated):
    Enter elements of the second sorted subarray (space-separated): 3 7 9

    Merged Sorted Array
    [3, 7, 9]
○  surabhiraghavan@Surabhis-MacBook-Pro Algo Design %
```

TEST CASE 2:

```
    /usr/local/bin/python3  /Users/surabhiraghavan/Desktop/Algo Design/Proj1Array.py
●  surabhiraghavan@Surabhis-MacBook-Pro Algo Design % /usr/local/bin/python3 "/Users/surabhiraghavan/Desktop/Algo Design/Proj1Array.py"
    Enter elements of the first sorted subarray (space-separated): 2 7 9
    Enter elements of the second sorted subarray (space-separated): 1

    Merged Sorted Array
    [1, 2, 7, 9]
○  surabhiraghavan@Surabhis-MacBook-Pro Algo Design %
```

TEST CASE 3:

```
●  surabhiraghavan@Surabhis-MacBook-Pro Algo Design % /usr/local/bin/python3 "/Users/surabhiraghavan/Desktop/Algo Design/Proj1Array.py"
    Enter elements of the first sorted subarray (space-separated): 1 7 10 15
    Enter elements of the second sorted subarray (space-separated): 3 8 12 18

    Merged Sorted Array
    [1, 3, 7, 8, 10, 12, 15, 18]
```

TEST CASE 4:

```
●  surabhiraghavan@Surabhis-MacBook-Pro Algo Design % /usr/local/bin/python3 "/Users/surabhiraghavan/Desktop/Algo Design/Proj1Array.py"
    Enter elements of the first sorted subarray (space-separated): 1 3 5 5 15 18 21
    Enter elements of the second sorted subarray (space-separated): 5 5 6 8 10 12 16 17 17 20 25 28

    Merged Sorted Array
    [1, 3, 5, 5, 5, 5, 6, 8, 10, 12, 15, 16, 17, 17, 18, 20, 21, 25, 28]
```