

StealthRL: Reinforcement Learning Paraphrase Attacks for Multi-Detector Evasion of AI-Text Detectors

Suraj Ranganath* Atharv Ramesh†
University of California, San Diego

Abstract

AI-text detectors are increasingly used in high-stakes settings, yet their robustness to meaning-preserving adversarial rewriting remains uncertain. We introduce StealthRL, a reinforcement learning framework for stress-testing AI-text detectors with adaptive paraphrase attacks. StealthRL trains a paraphrase policy against a detector ensemble while preserving semantic content, then evaluates transfer to held-out detector families. On the full filtered MAGE test pool (15,310 human / 14,656 AI), StealthRL reduces mean AUROC from 0.79 to 0.43 and achieves a 0.024 mean TPR@1%FPR across RoBERTa, Fast-DetectGPT, Binoculars, and MAGE. The attack transfers to two detectors not used during training, exposing shared vulnerabilities rather than a single-detector failure. We further analyze detector score distributions, verify stability across repeated stochastic generations, and evaluate quality with E5, BERTScore, bidirectional NLI, and LLM-based Likert ratings. Our results show that current AI-text detectors remain brittle under realistic paraphrasing pressure and provide a reproducible protocol for adversarial robustness evaluation. Code and evaluation pipeline are publicly available at <https://github.com/suraj-ranganath/StealthRL>; the released StealthRL model checkpoint is available at <https://huggingface.co/suraj-ranganath/StealthRL>.

1 Introduction

Large language models (LLMs) produce text that is increasingly indistinguishable from human writing, raising urgent concerns about academic integrity, misinformation, and content provenance [23]. In response, a growing ecosystem of AI-text detectors has been deployed in educational institutions, publishing platforms, and content moderation systems. These detectors span diverse architectures, from fine-tuned classifiers [23] to zero-shot statistical methods [16, 1] and paired-LM approaches [8], yet their robustness to adversarial manipulation remains poorly understood.

Standard detector evaluations measure performance on clean distributions, where AI-generated text is presented without any evasion attempt. However, real-world adversaries are adaptive: they can iteratively refine paraphrases, query detector APIs, and exploit known weaknesses. This gap between clean-distribution evaluation and adversarial robustness is critical. A detector that achieves 95% accuracy on clean text may fail catastrophically when an attacker deliberately targets its decision boundary.

The choice of operating point further complicates evaluation. Most prior work reports AUROC or accuracy at default thresholds, but deployed detectors in educational and moderation settings are often expected to operate at high precision because false positives can wrongly implicate human

*Corresponding author. suranganath@ucsd.edu

†a3nair@ucsd.edu

writers. This remains true even when detectors are used as human-in-the-loop triage tools rather than autonomous adjudicators: a detector alert still creates review burden, escalation risk, and reputational cost. Commercial systems explicitly discuss false-positive targets below 1% [25], and recent detector evaluations emphasize TPR measured at fixed FPR values such as 1% [24]. We therefore treat $\text{TPR}@1\%\text{FPR}$ as a strict high-precision triage setting, report $\text{TPR}@5\%\text{FPR}$ as a less conservative review-queue setting, and include AUROC as a threshold-independent view.

We introduce StealthRL, a reinforcement learning framework that systematically evaluates detector robustness under adaptive adversarial conditions. StealthRL trains a paraphrase policy against a multi-detector ensemble, using GRPO [18] with LoRA adapters [10] on Qwen3-4B-Instruct, to produce semantically faithful paraphrases that minimize detection confidence. By evaluating at the 1% FPR operating point and testing transfer to multiple held-out detectors, we provide a rigorous robustness assessment that complements standard benchmarks.

Our contributions are as follows:

- We implement black-box adaptive paraphrasing attacks via multi-detector RL training with semantic constraints, one of the first works to apply RL for adversarial detector evasion across multiple detector families simultaneously.
- We demonstrate catastrophic robustness failure: 0.024 mean $\text{TPR}@1\%\text{FPR}$ across four detectors, with strong transfer to two held-out detectors.
- We provide comprehensive analysis including detector score distributions (explaining why evasion succeeds), stochastic repeat runs, multi-metric semantic evaluation, and per-detector AUROC with bootstrap confidence intervals.
- We establish an evaluation protocol measuring evasion, transfer, and fidelity at security-relevant operating points, and release complete training and evaluation code for reproducible robustness benchmarking at <https://github.com/suraj-ranganath/StealthRL>.

2 Related Work

2.1 AI-Text Detection Methods

AI-text detection methods can be broadly categorized into several families. Fine-tuned classifiers train discriminative models on labeled human and AI text; the RoBERTa-based OpenAI detector [23] is a widely used example. Zero-shot statistical methods exploit properties of language model probability distributions without requiring labeled data. DetectGPT [16] uses probability curvature, while Fast-DetectGPT [1] achieves similar accuracy with substantially reduced computational cost via conditional probability curvature. Paired-LM detectors such as Binoculars [8] compare log-likelihoods across two language models to detect statistical anomalies. Linguistic-feature detectors use stylometric or language-specific cues rather than only model likelihoods; KatFishNet, for example, detects Korean LLM text using spacing, part-of-speech diversity, and comma-usage features [19]. The MAGE benchmark [15] provides standardized evaluation data, while RAID [6] offers a shared benchmark for robust detector evaluation across domains and attacks.

Despite diverse architectures, Sadasivan et al. [20] provide theoretical arguments that reliable detection may be fundamentally impossible as language models improve, motivating empirical robustness evaluation like ours.

2.2 Adversarial Attacks on Detectors

Evasion attacks on AI-text detectors range from simple paraphrasing to sophisticated adaptive methods. Krishna et al. [14] demonstrate that paraphrasing with their DIPPER model [13] effectively evades detectors, though retrieval-based defenses can mitigate the attack. Cheng et al. [2] study adversarial paraphrasing as a universal attack, using detector-guided candidate selection to humanize AI-generated text. Character-level attacks such as homoglyph substitution (SilverS-ppeak [3]) achieve strong evasion by replacing characters with visually similar Unicode glyphs, but often degrade readability and are detectable by normalization.

Most relevant to our work, AuthorMist [4] applies reinforcement learning to train an evasion policy against a single detector. StealthRL extends this approach to multi-detector ensemble training with held-out evaluation, strict low-FPR operating points, and comprehensive quality analysis.

Watermark-based detection [12] represents an orthogonal approach where the text generator embeds a statistical signal during generation. While watermarks can provide stronger guarantees, they require control over the generation process and are outside the scope of post-hoc detection methods we evaluate.

A natural defensive response to paraphrasing attacks is adversarial training, where detectors are fine-tuned on adversarially generated examples to improve robustness. However, adversarial training faces a fundamental scalability challenge: the space of possible paraphrasing strategies is vast, and a detector hardened against one attack family may remain vulnerable to novel attack methods. The RAID benchmark [6] evaluates detectors across diverse attack types and finds that no single detector achieves robust performance against all attacks, underscoring the difficulty of building universally robust defenses. Our work focuses on the attack side of this arms race to quantify the current robustness gap and motivate the development of stronger defensive strategies.

2.3 Reinforcement Learning for Text Generation

Reinforcement learning from human feedback (RLHF) [17] has become the standard approach for aligning language models with human preferences. Proximal Policy Optimization (PPO) [21] was the original RL algorithm used for RLHF, but recent work has introduced more efficient alternatives. Group Relative Policy Optimization (GRPO) [18, 22] eliminates the need for a separate value network by using group-level relative rewards, reducing memory requirements and enabling efficient training.

Parameter-efficient fine-tuning methods, particularly LoRA [10] and QLoRA [5], enable RL training of large language models with limited compute by adapting only low-rank weight matrices. StealthRL combines GRPO with LoRA on Qwen3-4B-Instruct, demonstrating that efficient RL fine-tuning suffices for learning effective evasion policies.

3 Method

3.1 Threat Model

We consider an adversary who has produced AI-generated text and seeks to modify it to evade detection while preserving semantic content. Formally:

- **Attacker capability:** Black-box access to detector scores. The attacker can query detector confidence $p(y)$ (probability that input y is AI-generated) but does not have access to model gradients or internal parameters. Although our experiments use open-source detectors for which gradients

are in principle available, we deliberately treat them as black-box oracles, querying only scalar confidence scores.

- Attacker goal: Produce a paraphrase y of AI-generated text x such that $p(y) < \tau$ for detector threshold τ , while maintaining semantic equivalence $\text{sim}(x, y) > \delta$ for a similarity threshold δ .
- Attacker constraint: The paraphrase must be a fluent, grammatical reformulation of the original text, not a trivially corrupted version.

We evaluate transfer by testing against two held-out detectors (Binoculars and MAGE) not seen during training, assessing whether learned evasion strategies generalize across detector architectures.

3.2 Reward Design

Given AI-generated text x and paraphrase $y \sim \pi_\theta(\cdot | x)$, we define a composite reward:

$$R(x, y) = \alpha \cdot R_{\text{det}}(y) + \beta \cdot R_{\text{sem}}(x, y), \quad (1)$$

where $\alpha = 1.0$ and $\beta = 0.1$ control the evasion-quality tradeoff. We set α to make detector evasion the dominant training signal and use a smaller β as a soft fidelity regularizer rather than a competing objective. This choice reflects the attack setting: outputs that remain easily detected fail the primary goal, while semantic preservation is also enforced through the E5 reward, KL regularization, output validation, and downstream quality evaluation.

Detector evasion reward. The detector reward measures how effectively the paraphrase evades the training ensemble:

$$R_{\text{det}}(y) = 1 - p_{\text{ens}}(y), \quad p_{\text{ens}}(y) = w_1 \cdot p_{\text{RoBERTa}}(y) + w_2 \cdot p_{\text{Fast-DetectGPT}}(y), \quad (2)$$

where $w_1 = 0.6$ and $w_2 = 0.4$ are the ensemble weights. The training ensemble intentionally combines one supervised classifier (RoBERTa) and one zero-shot curvature detector (Fast-DetectGPT). We give RoBERTa slightly higher weight because its calibrated neural score provides a stable dense reward, while Fast-DetectGPT contributes a complementary likelihood-curvature signal. We do not include Binoculars or MAGE in the reward loop; they are held out to test transfer, and adding these slower detectors to every GRPO rollout would substantially increase training cost.

Semantic similarity reward. To prevent degenerate solutions (e.g., outputting empty or unrelated text), we constrain semantic preservation using E5 embedding cosine similarity [27]:

$$R_{\text{sem}}(x, y) = \cos(\text{E5}(x), \text{E5}(y)). \quad (3)$$

KL penalty. GRPO includes an implicit KL divergence penalty (coefficient $\lambda_{\text{KL}} = 0.05$) against the frozen reference policy π_{ref} to prevent catastrophic forgetting and maintain generation fluency.

3.3 Training Pipeline

Algorithm 1 describes the StealthRL training procedure.

We fine-tune Qwen3-4B-Instruct with LoRA adapters using GRPO [18]. The training ensemble comprises RoBERTa and Fast-DetectGPT; Binoculars and the MAGE detector are held out for transfer evaluation. Complete training, sampling, and compute settings are reported in Section 4.4.

Algorithm 1 StealthRL Training

Require: Training data $\mathcal{D} = \{x_i\}_{i=1}^N$ (AI-generated texts), detector ensemble $\{d_k\}_{k=1}^K$ with weights $\{w_k\}$, E5 similarity model, base LLM π_{ref}

Ensure: Fine-tuned paraphrase policy π_θ

- 1: Initialize $\pi_\theta \leftarrow \pi_{\text{ref}}$ with LoRA adapters (rank $r=32$, $\alpha=32$)
- 2: for epoch = 1, ..., E do
- 3: for batch $\mathcal{B} \subset \mathcal{D}$ do
- 4: for each $x \in \mathcal{B}$ do
- 5: Sample group $\{y_1, \dots, y_G\} \sim \pi_\theta(\cdot \mid x)$ ▷ $G=8$ candidates
- 6: for each y_g in group do
- 7: $R_{\text{det}}(y_g) \leftarrow 1 - \sum_k w_k \cdot d_k(y_g)$ ▷ Ensemble evasion
- 8: $R_{\text{sem}}(x, y_g) \leftarrow \cos(\text{E5}(x), \text{E5}(y_g))$ ▷ Semantic preservation
- 9: $R(x, y_g) \leftarrow \alpha \cdot R_{\text{det}}(y_g) + \beta \cdot R_{\text{sem}}(x, y_g)$
- 10: end for
- 11: Compute advantages via group-relative normalization:
 $A_g \leftarrow (R_g - \bar{R}) / \sigma_R$ ▷ GRPO
- 12: end for
- 13: Update θ via clipped policy gradient with KL penalty
- 14: end for
- 15: end for
- 16: return π_θ

3.4 Inference

At inference time, the fine-tuned policy generates a single paraphrase per input. No candidate selection or reranking is applied; the single-pass output is evaluated directly against all four detectors.

Accordingly, the reported StealthRL attack is single-shot at test time: each input receives one policy generation call, with no iterative refinement and no target-detector queries during evaluation. Detector access is required only during offline RL training. This differs from detector-guided search baselines such as M3, which use multi-candidate generation and detector-based reranking at evaluation time.

StealthRL Pipeline




Figure 1: StealthRL training and evaluation pipeline. A paraphrase policy (Qwen3-4B with LoRA) is trained via GRPO against a two-detector ensemble (RoBERTa + Fast-DetectGPT) with semantic similarity reward. The trained policy is then evaluated against four detectors, including the held-out Binoculars and MAGE detectors, at the 1% FPR operating point.

4 Experimental Setup

4.1 Dataset

We construct a custom subset of the MAGE (Machine-Generated Text Detection in the Wild) benchmark [15], which provides human-written and AI-generated text across multiple domains. Our training set consists of 10,000 AI-generated samples drawn from the MAGE training split; no human-written samples are used during RL fine-tuning, as the policy learns entirely from detector feedback on paraphrased AI text. The evaluation set uses the full filtered MAGE test pool with 15,310 human-written and 14,656 AI-generated samples after applying the 100–500 token filter. Human samples in the evaluation set are used solely for threshold calibration at the 1% FPR operating point; AI and attacked samples are never used when setting thresholds.

4.2 Detectors

We evaluate against four detectors spanning distinct architectural paradigms:

- RoBERTa OpenAI (openai-community/roberta-large-openai-detector): A fine-tuned RoBERTa-large classifier trained on GPT-2 outputs. Represents the class of supervised neural classifiers.
- Fast-DetectGPT [1]: A zero-shot statistical method that uses conditional probability curvature with scoring model EleutherAI/gpt-neo-2.7B. Represents curvature-based detection.
- Binoculars [8]: A paired-LM detector using gpt2-medium and gpt2-large that compares cross-entropy and perplexity. Held out during training to assess transfer.

- MAGE detector [15]: The benchmark-provided Longformer-based classifier released with MAGE (model checkpoint yaful/MAGE). In the original MAGE paper, this PLM-based detector is the strongest method among their compared detectors across the benchmark’s in-distribution and out-of-distribution testbeds, so we include it as a strong held-out evaluation target rather than a detector used during training.

4.3 Baselines

We compare six attack settings:

- M0 (No Attack): Original AI-generated text, unmodified.
- M1 (Simple Paraphrase): Standard LLM paraphrasing without detector feedback.
- M2 (StealthRL): Our method, RL-trained paraphrasing against a detector ensemble (3 epochs, GRPO + LoRA).
- M3 (Adversarial Paraphrasing) [2]: Detector-guided candidate selection from multiple paraphrases.
- M4 (AuthorMist) [4]: RL-trained paraphrasing against a single detector (RoBERTa).
- M5 (Homoglyph) [3]: Character-level Unicode substitution (SilverSpeak).

4.4 Implementation Details

StealthRL fine-tunes Qwen3-4B-Instruct with LoRA adapters (rank 32, LoRA $\alpha = 32$, dropout 0.05) for 3 epochs on 10,000 AI-generated MAGE training samples. GRPO uses batch size 16, group size 8, learning rate 2.8×10^{-4} , maximum 512 generated tokens, and KL coefficient $\lambda_{KL} = 0.05$ against the frozen reference policy. The inference prompt is “Paraphrase the following text while preserving its meaning: [TEXT]”; decoding uses temperature 1.0 and top-p 0.9. To test whether results depend on one stochastic draw, we additionally run two full-pool M2 repeats with the same checkpoint, prompt, and decoding configuration but different random seeds (4201 and 4202), scoring each repeat with the same detector pipeline and fixed thresholds.

The training reward uses RoBERTa and Fast-DetectGPT because they expose complementary detector signals while remaining fast enough for repeated reward calls inside GRPO. Binoculars and MAGE are excluded from training and reserved for held-out transfer evaluation. This design makes the evaluation stricter, but it also means our training ensemble is not exhaustive; scaling RL to larger and slower detector panels remains future work.

4.5 Evaluation Metrics

We report seven primary metrics:

- TPR@1%FPR: True positive rate at 1% false positive rate. For each detector, we compute the decision threshold as the empirical 99th percentile of its scores on the 15,310 human evaluation samples, then keep that threshold fixed when scoring all clean and attacked AI samples. This is our primary high-precision triage metric: even with human review, detector alerts should not routinely flag human writers or overwhelm reviewers.
- TPR@5%FPR: The same operating-point metric evaluated at a looser 5% false positive rate. For each detector, we compute the decision threshold as the empirical 95th percentile of its scores on the same 15,310 human evaluation samples, then keep that threshold fixed when scoring

all clean and attacked AI samples. We report this as a supplementary operating point for less conservative human-review queues.

- ASR (Attack Success Rate): Fraction of AI samples classified as human at the 1% FPR threshold. $ASR = 1 - TPR@1\%FPR$.
- AUROC: Area under the receiver operating characteristic curve. Threshold-independent measure of overall discriminability.
- E5 Similarity: Cosine similarity between E5 embeddings [27] of original and paraphrased text, measuring sentence-level semantic preservation.
- BERTScore: Contextual token-alignment F1 [28], which complements E5 by measuring local lexical and semantic overlap rather than only global embedding similarity.
- NLI Consistency: Bidirectional entailment consistency using a DeBERTa-large model fine-tuned on MNLI [9]. We score both original→paraphrase and paraphrase→original directions and report the minimum entailment probability, so a high value requires meaning preservation in both directions.

All confidence intervals are computed via bootstrap resampling with 500 iterations and seed 42.

4.6 LLM-Based Quality Judge

We additionally evaluate paraphrase quality using an LLM judge, following the growing body of work on LLM-based automatic evaluation. Recent studies have shown that LLMs can serve as effective evaluators of text quality [7], with specialized evaluation models [11] and systematic frameworks for building reliable autoraters [26] demonstrating strong agreement with human judgments. We employ OpenAI gpt-5-nano to score each paraphrase on two 1–5 Likert axes:

1. Linguistic quality: Fluency, grammaticality, and naturalness of the paraphrase.
2. Semantic similarity: Faithfulness of meaning preservation relative to the source.

For fair cross-method comparison, we evaluate a shared subset of 500 AI samples per method (M1–M5) using identical sample IDs across methods. Each sample is scored independently; the judge sees only the source and paraphrase without method labels. Appendix E reports the exact judge prompts.

5 Results

5.1 Main Detection Evasion Results

StealthRL (M2) achieves a 0.024 mean $TPR@1\%FPR$, reducing mean AUROC from 0.79 (no attack) to 0.43 with a 97.6% attack success rate. This remains catastrophic robustness failure: at the strict high-precision triage setting, detectors are rendered largely ineffective against an adaptive adversary. The full detector-by-detector AUC/TPR/ASR tables for the 1% FPR operating point are moved to Appendix Tables 2 and 3.

Figure 2 provides a comprehensive visual comparison across all metrics. Panel (a) shows that StealthRL dramatically reduces AUROC across the detector panel, driving Binoculars and Fast-DetectGPT close to random chance and substantially degrading the remaining detectors. Panel (b) confirms that the mean AUROC of 0.432 for M2 is far below the no-attack baseline of 0.789.

Panel (c) demonstrates near-zero TPR at strict operating points on three detectors, while Panel (d) shows the 97.6% attack success rate.




Figure 2: Detection evasion results for methods M0–M5. (a) AUROC by detector. (b) Mean AUROC with standard-deviation bars across detectors. (c) TPR at 1% FPR. (d) Mean attack success rate. StealthRL (M2, teal) achieves extremely low TPR on Binoculars, Fast-DetectGPT, and RoBERTa, with MAGE remaining the most robust detector in the panel.

5.2 Stochastic Decoding Robustness

Because StealthRL uses stochastic decoding (temperature 1.0, top-p 0.9), we repeat full-pool M2 generation twice using the released checkpoint, identical prompt, identical decoding configuration, and different random seeds. Each repeat uses one generation per input and no detector-based reranking or candidate selection, matching the reported single-shot evaluation protocol. The result is stable: across the original run and two repeats, mean AUROC is 0.432 ± 0.001 , mean TPR@1%FPR is 0.024 ± 0.001 , and mean ASR is 0.976 ± 0.001 . Per-detector TPR@1%FPR is also stable: Binoculars, Fast-DetectGPT, and RoBERTa remain at 0.002 ± 0.000 , while MAGE varies only from 0.089 to 0.093. Appendix Table 5 reports the complete repeat table.

5.3 Cross-Architecture Transfer

A key finding is the strong transfer of StealthRL’s evasion to detectors that were never used during training. Despite never seeing Binoculars or MAGE during training, M2 achieves 0.002




Figure 3: TPR@1%FPR heatmap across detectors and methods. Darker colors indicate higher detection rates. StealthRL (M2) and Homoglyph (M5) achieve near-zero TPR on three detectors, while MAGE remains the most robust held-out detector.

TPR@1%FPR on Binoculars and 0.089 on the MAGE detector, alongside 0.002 on both in-ensemble detectors. Figure 3 visualizes the per-detector, per-method TPR matrix, clearly showing that M2 and M5 achieve near-zero TPR on most of the detector panel.

This cross-architecture transfer reveals that detectors share common vulnerabilities: they rely on surface-level statistical cues (token distributions, perplexity patterns, embedding geometry) that are disrupted by paraphrasing. The attack does not exploit detector-specific weaknesses but rather targets the fundamental fragility of current detection approaches.

5.4 Supplementary 5% FPR Operating Point

Appendix Table 4 adds TPR@5%FPR as a supplementary operating point without replacing any of the primary TPR@1%FPR reporting above. The qualitative ranking remains similar: StealthRL stays near-zero on Binoculars (0.005), Fast-DetectGPT (0.003), and RoBERTa (0.022), while MAGE remains substantially more robust at 0.272. Averaged across the four-detector panel, M2 reaches a mean TPR@5%FPR of 0.076.

5.5 Detector Score Analysis

To understand why M2 and M5 achieve near-zero TPR, we examine the raw detector score distributions in Figure 4. For both methods, AI-sample scores are pushed below the 1% FPR threshold, making them statistically indistinguishable from human-written text from the detector’s perspective. In contrast, methods M0–M3 retain a substantial fraction of scores above the threshold, explaining their higher detection rates.

Figure 5 provides per-detector AUROC with 95% bootstrap confidence intervals. StealthRL achieves the lowest AUROC on Binoculars (0.055) and Fast-DetectGPT (0.089), while RoBERTa




Figure 4: Detector score distributions for AI samples across methods (one panel per detector). StealthRL (M2) and Homoglyph (M5) push scores below the detection threshold, explaining their near-zero TPR@1%FPR.

remains substantially degraded at 0.691 and the MAGE detector is the most robust at 0.891. The tight confidence intervals confirm the reliability of these estimates.

The RoBERTa AUROC anomaly deserves further discussion. Despite achieving near-zero TPR@1%FPR (0.002), StealthRL’s AUROC on RoBERTa (0.691) is far higher than on Fast-DetectGPT (0.089) or Binoculars (0.055). This apparent contradiction arises because AUROC and TPR@1%FPR measure fundamentally different properties. AUROC captures global rank separability across all possible thresholds, while TPR@1%FPR measures detection power at a single strict operating point. RoBERTa retains moderate ability to rank AI-paraphrased text above human text on average, but at the strict 1% FPR threshold, the overlap between human and AI score distributions is sufficient to render detection ineffective. Concretely, the score distributions for M2 paraphrases are shifted leftward (toward human-like scores) enough that nearly all AI samples fall below the 1% FPR threshold, even though the distribution means remain partially separated. This pattern suggests that the RL policy learns to target the specific score region near the decision boundary rather than fully collapsing the detector’s discriminative capacity. In human-in-the-loop deployments, this still matters: if detector scores no longer surface adversarially paraphrased AI text for review, the human reviewer receives fewer useful signals exactly where adaptive misuse is most likely.

5.6 Evasion–Quality Tradeoff

Achieving strong evasion without degrading text quality is the central challenge. Figure 6 plots mean ASR@1%FPR against E5 semantic similarity for each method, so the preferred operating region is the top-right corner. M1 and M3 preserve high similarity (0.974 and 0.973) but achieve only moderate evasion (0.716 and 0.783 mean ASR). M2 and M5 both achieve near-maximal mean ASR (0.976 and 0.972), with comparable E5 similarity (0.901 for M2 vs. 0.923 for M5), but M2 achieves substantially better judged quality.

Table 1 and Figure 7 present the LLM-based quality evaluation. E5 similarity, BERTScore, and NLI consistency are computed on the full filtered evaluation pool, whereas the Likert ratings are computed on the matched 500-sample subset used for paid judging. BERTScore adds a token-level contextual view to the global E5 embedding score: M2 reaches 0.868 BERTScore, below M1/M3




Figure 5: Per-detector AUROC with 95% bootstrap confidence intervals. StealthRL (M2, teal) drives Binoculars and Fast-DetectGPT close to random chance and substantially degrades RoBERTa and MAGE. The dashed line marks the 0.5 random-chance baseline.

(0.926/0.934) and M4 (0.902), but clearly above M5 (0.773). This contrasts with E5, where M5 scores above M2 (0.923 vs. 0.901), suggesting that character-level obfuscation can preserve global embedding similarity while damaging contextual token overlap and readability. NLI consistency is stricter: high-quality paraphraser M1 and M3 remain high (0.967 and 0.965), M5 remains moderately high because character substitution preserves most lexical propositions (0.847), and M2 drops to 0.316. We therefore do not claim that the strongest evasion setting is quality-equivalent to standard paraphrasing; rather, the multi-metric analysis makes the evasion–fidelity cost explicit. The LLM judge supports the readability side of this picture: M2 is rated substantially higher on quality than M5 (2.51 vs. 1.97), even though M5 scores higher on judged similarity (2.92 vs. 2.64). Overall, E5, BERTScore, NLI, and Likert judgments capture complementary notions of preservation: global semantic proximity, contextual token overlap, bidirectional entailment, and human-facing naturalness. Methods M1 and M3, which achieve weaker evasion, score highest on quality (3.78 and 3.77), illustrating the fundamental tradeoff between evasion effectiveness and output quality.




Figure 6: Evasion-quality tradeoff at the 1% FPR operating point. Each point represents a method, plotted by E5 semantic similarity (x-axis) against mean ASR@1%FPR (y-axis). Top-right is ideal (high similarity, high attack success). The dashed lines mark the 0.90 similarity floor and the random-detector ASR baseline at 1% FPR, and the solid line shows the Pareto frontier.




Figure 7: LLM-based quality evaluation on 500 matched samples. Panel (a) shows linguistic quality and panel (b) semantic similarity; higher is better. The dashed line marks the neutral midpoint (3.0).

5.7 Discussion

The severe failure across the four detectors tested reveals significant vulnerabilities in current AI-text detection. Detectors rely on brittle statistical cues, including token frequency distributions, perplexity patterns, and embedding geometry, rather than robust semantic understanding. Surface-level paraphrasing that preserves meaning suffices to evade detection, suggesting that detectors learn superficial correlates of AI text rather than deeper linguistic features.

This robustness gap has critical security implications. Adversaries can train adaptive attacks

Method	E5 Sim.	BERTScore	NLI	PPL	Edit Rate	Valid	Quality	Similarity
M0	1.000	1.000	0.991	26.662	0.000	1.000	—	—
M1	0.974	0.926	0.967	24.596	0.779	1.000	3.780	4.058
M2 (Ours)	0.901	0.868	0.316	148.686	0.835	1.000	2.514	2.644
M3	0.973	0.934	0.965	28.338	0.782	1.000	3.770	4.024
M4	0.958	0.902	0.829	18.909	0.861	0.998	3.152	3.704
M5	0.923	0.773	0.847	146.430	0.634	1.000	1.972	2.920

Table 1: Quality and similarity metrics. E5 Sim., BERTScore, and NLI are computed on the full filtered evaluation pool. Quality and Similarity are mean Likert scores (1–5) from a gpt-5-nano judge on 500 matched samples for methods M1–M5; M0 reports automatic metrics only. Higher is better for all quality metrics.

against deployed detectors, rendering them ineffective with modest computational resources (a single LoRA fine-tuning run). The strong transfer to held-out architectures means that ensemble defenses (combining multiple detectors) provide limited robustness improvement, as the attack generalizes across detector families.

Our evaluation should therefore be read as a stress test for detector-assisted review workflows, not as an argument for fully automated enforcement. Human review changes the deployment question but does not remove the robustness requirement: detector alerts should be treated as triage signals rather than proof of misconduct, yet reviewers still have finite capacity and depend on calibrated scores to decide what deserves scrutiny. Low precision overloads review queues and increases escalation risk for human writers; low TPR fails to route adversarially paraphrased AI text to review at all. Reporting both 1% and 5% FPR operating points captures these queue-size regimes without equating a detector alert with guilt.

6 Limitations and Broader Impact

6.1 Limitations

Detector coverage. Our evaluation covers four detectors spanning supervised, zero-shot statistical, paired-LM, and benchmark-provided paradigms. We do not evaluate against watermark-based detectors [12], which embed signals during generation and may be more robust to paraphrasing attacks. Evaluating StealthRL against watermarked text is an important direction for future work.

Training-ensemble coverage. The RL reward uses two detectors, RoBERTa and Fast-DetectGPT, while Binoculars and MAGE are held out for transfer evaluation. This separation is useful for measuring cross-detector transfer, but it also means we do not study whether training directly against a larger detector ensemble would further improve or destabilize evasion. Larger ensembles would require substantially more reward-model calls per GRPO update, especially for paired-LM and Longformer-based detectors, and are left for future work.

Dataset diversity. We evaluate on a single benchmark (MAGE) in English. Broader coverage across datasets (RAID [6]), domains, and languages is needed to establish generalizability. The MAGE benchmark, while diverse, may not capture all deployment scenarios.

Quality gap. StealthRL achieves lower semantic fidelity than the high-quality paraphrase baselines (E5 0.901, BERTScore 0.868, and NLI 0.316, compared with M1/M3 E5 0.974/0.973, BERTScore 0.926/0.934, and NLI 0.967/0.965) and lower Likert quality (2.51 vs. 3.78/3.77). It still outperforms character-level obfuscation on BERTScore and judged quality (M5: 0.773 and 1.97), but the remaining fidelity cost is a limitation of the current system. We supplement E5 with BERTScore, bidirectional NLI, and LLM-based similarity judgments, but all automatic semantic metrics remain imperfect proxies for human meaning preservation. Improving semantic preservation while maintaining strong evasion is an important direction. Techniques such as constrained decoding, rejection sampling, or multi-objective RL could help close this gap.

Defense evaluation. We do not explore defensive strategies such as adversarial training, certified robustness, or ensemble diversification that could improve detector resilience. Our focus is on exposing vulnerabilities to motivate defensive research.

6.2 Ethical Considerations

Adversarial paraphrasing is dual-use technology. We position StealthRL as a stress-testing and robustness evaluation tool for researchers and detector developers, not a production evasion system. The near-zero TPR@1%FPR result exposes critical vulnerabilities that must be addressed before detectors are deployed in high-stakes applications such as academic integrity enforcement.

We release our code and evaluation pipeline to enable reproducible robustness assessment and to accelerate defensive research. By making attack capabilities transparent, we aim to shift the detector development paradigm toward adversarial robustness rather than clean-distribution accuracy. We believe responsible disclosure of detector vulnerabilities, accompanied by tools for measuring progress, serves the broader goal of trustworthy AI-text detection.

7 Conclusion and Future Work

StealthRL demonstrates severe detector failure under adaptive RL-based paraphrasing attacks, revealing significant robustness gaps in the AI-text detectors evaluated. By training against a multi-detector ensemble with GRPO and LoRA, we achieve near-zero detection on three of four detectors and a 0.024 mean TPR@1%FPR with strong cross-architecture transfer, including to two held-out detectors. Our comprehensive evaluation, spanning detection metrics, stochastic repeat analysis, multi-metric quality assessment, and score distribution analysis, provides a complete picture of the evasion-quality tradeoff.

Several directions for future work emerge from our findings:

- Adversarial training: Incorporating adversarial examples into detector training to improve robustness against adaptive attacks.
- Semantic-aware detectors: Developing detection methods that rely on deeper linguistic features rather than surface-level statistical cues.
- Provable robustness: Establishing theoretical guarantees on detector robustness under bounded perturbations.
- Multi-objective optimization: Improving StealthRL’s quality preservation through constrained RL or Pareto-optimal training.

- Broader evaluation: Extending to additional datasets, languages, and detector families (including watermark-based methods).

Our evaluation framework and released code provide a rigorous testbed for measuring progress on adversarially robust AI-text detection.

Acknowledgments

We gratefully acknowledge Thinking Machines for providing free research credits and access to their Tinker API framework, which made the RL fine-tuning possible. We also thank the open-source community for the detector implementations and model checkpoints that enabled this evaluation.

References

- [1] Guangsheng Bao, Yanbin Zhao, Zhiyang Teng, Linyi Yang, and Yue Zhang. Fast-detectgpt: Efficient zero-shot detection of machine-generated text via conditional probability curvature, 2024. URL <https://arxiv.org/abs/2310.05130>.
- [2] Yize Cheng, Vinu Sankar Sadasivan, Mehrdad Saberi, Shoumik Saha, and Soheil Feizi. Adversarial paraphrasing: A universal attack for humanizing ai-generated text, 2025. URL <https://arxiv.org/abs/2506.07001>.
- [3] Aldan Creo and Shushanta Pudasaini. Silverspeak: Evading ai-generated text detectors using homoglyphs, 2025. URL <https://arxiv.org/abs/2406.11239>.
- [4] Isaac David and Arthur Gervais. Authormist: Evading ai text detectors with reinforcement learning, 2025. URL <https://arxiv.org/abs/2503.08716>.
- [5] Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. Qlora: Efficient finetuning of quantized llms, 2023. URL <https://arxiv.org/abs/2305.14314>.
- [6] Liam Dugan, Alyssa Hwang, Filip Trhlik, Josh Magnus Ludan, Andrew Zhu, Hainiu Xu, Daphne Ippolito, and Chris Callison-Burch. Raid: A shared benchmark for robust evaluation of machine-generated text detectors, 2024. URL <https://arxiv.org/abs/2405.07940>.
- [7] Jinlan Fu, See-Kiong Ng, Zhengbao Jiang, and Pengfei Liu. Gptscore: Evaluate as you desire, 2023. URL <https://arxiv.org/abs/2302.04166>.
- [8] Abhimanyu Hans, Avi Schwarzschild, Valeriia Cherepanova, Hamid Kazemi, Aniruddha Saha, Micah Goldblum, Jonas Geiping, and Tom Goldstein. Spotting llms with binoculars: Zero-shot detection of machine-generated text, 2024. URL <https://arxiv.org/abs/2401.12070>.
- [9] Pengcheng He, Xiaodong Liu, Jianfeng Gao, and Weizhu Chen. DeBERTa: Decoding-enhanced BERT with disentangled attention. In International Conference on Learning Representations, 2021. URL <https://openreview.net/forum?id=XPZlaotutsD>.
- [10] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models, 2021. URL <https://arxiv.org/abs/2106.09685>.

- [11] Seungone Kim, Juyoung Suk, Shayne Longpre, Bill Yuchen Lin, Jamin Shin, Sean Welleck, Graham Neubig, Moontae Lee, Kyungjae Lee, and Minjoon Seo. Prometheus 2: An open source language model specialized in evaluating other language models, 2024. URL <https://arxiv.org/abs/2405.01535>.
- [12] John Kirchenbauer, Jonas Geiping, Yuxin Wen, Jonathan Katz, Ian Miers, and Tom Goldstein. A watermark for large language models, 2023. URL <https://arxiv.org/abs/2301.10226>.
- [13] Kalpesh Krishna, Yixiao Song, Marzena Karpinska, John Wieting, and Mohit Iyyer. Dipper: Discourse paraphrasing via diverse paraphrasing, 2023. Paraphrase model released with Krishna et al., 2023. Available at <https://github.com/martiansideofthemoon/ai-detection-paraphrases>.
- [14] Kalpesh Krishna, Yixiao Song, Marzena Karpinska, John Wieting, and Mohit Iyyer. Paraphrasing evades detectors of ai-generated text, but retrieval is an effective defense, 2023. URL <https://arxiv.org/abs/2303.13408>.
- [15] Yafu Li, Qintong Li, Leyang Cui, Wei Bi, Zhilin Wang, Longyue Wang, Linyi Yang, Shuming Shi, and Yue Zhang. Mage: Machine-generated text detection in the wild, 2024. URL <https://arxiv.org/abs/2305.13242>.
- [16] Eric Mitchell, Yoonho Lee, Alexander Khazatsky, Christopher D. Manning, and Chelsea Finn. Detectgpt: Zero-shot machine-generated text detection using probability curvature, 2023. URL <https://arxiv.org/abs/2301.11305>.
- [17] Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback, 2022. URL <https://arxiv.org/abs/2203.02155>.
- [18] Lei Pang and Ruinan Jin. On the theory and practice of grpo: A trajectory-corrected approach with fast convergence, 2025. URL <https://arxiv.org/abs/2508.02833>.
- [19] Shinwoo Park, Shubin Kim, Do-Kyung Kim, and Yo-Sub Han. KatFishNet: Detecting LLM-generated Korean text through linguistic feature analysis. In Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 21189–21222, Vienna, Austria, July 2025. Association for Computational Linguistics. doi: 10.18653/v1/2025.acl-long.1030. URL <https://aclanthology.org/2025.acl-long.1030/>.
- [20] Vinu Sankar Sadasivan, Aounon Kumar, Sriram Balasubramanian, Wenxiao Wang, and Soheil Feizi. Can ai-generated text be reliably detected?, 2023. URL <https://arxiv.org/abs/2303.11156>.
- [21] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms, 2017. URL <https://arxiv.org/abs/1707.06347>.
- [22] Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Mingchuan Zhang, Y.K. Li, Y. Wu, and Daya Guo. Deepseekmath: Pushing the limits of mathematical reasoning in open language models, 2024. URL <https://arxiv.org/abs/2402.03300>.
- [23] Irene Solaiman, Miles Brundage, Jack Clark, Amanda Askell, Ariel Herbert-Voss, Jeff Wu, Alec Radford, and Jasmine Wang. Release strategies and the social impacts of language models, 2019. URL <https://arxiv.org/abs/1908.09203>.

- [24] Brian Tufts, Xuandong Zhao, and Lei Li. A practical examination of AI-generated text detectors for large language models. In Findings of the Association for Computational Linguistics: NAACL 2025, pages 4839–4856, Albuquerque, New Mexico, April 2025. Association for Computational Linguistics. doi: 10.18653/v1/2025.findings-naacl.271. URL <https://aclanthology.org/2025.findings-naacl.271/>.
- [25] Turnitin. Understanding false positives within our AI writing detection capabilities, 2023. URL <https://www.turnitin.com/blog/understanding-false-positives-within-our-ai-writing-detection-capabilities>. Accessed 2026-05-19.
- [26] Tu Vu, Kalpesh Krishna, Salaheddin Alzubi, Chris Tar, Manaal Faruqui, and Yun-Hsuan Sung. Foundational autoraters: Taming large language models for better automatic evaluation, 2024. URL <https://arxiv.org/abs/2407.10817>.
- [27] Liang Wang, Nan Yang, Xiaolong Huang, Binxing Jiao, Linjun Yang, Daxin Jiang, Rangan Majumder, and Furu Wei. Text embeddings by weakly-supervised contrastive pre-training, 2022. URL <https://arxiv.org/abs/2212.03533>.
- [28] Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q. Weinberger, and Yoav Artzi. BERTScore: Evaluating text generation with BERT. In International Conference on Learning Representations, 2020. URL <https://openreview.net/forum?id=SkeHuCVFDr>.

A Full Main Results on the MAGE Test Pool

Method	Binoc. AUC	Binoc. TPR	Binoc. ASR	FastDGPT AUC	FastDGPT TPR	FastDGPT ASR	MAGE AUC	MAGE TPR	MAGE ASR
M0	0.705	0.367	0.633	0.661	0.388	0.612	0.983	0.843	0.157
M1	0.593	0.158	0.842	0.588	0.148	0.852	0.973	0.720	0.280
M2 (Ours)	0.055	0.002	0.998	0.089	0.002	0.998	0.891	0.089	0.911
M3	0.511	0.051	0.949	0.536	0.092	0.908	0.967	0.666	0.334
M4	0.559	0.036	0.964	0.518	0.067	0.933	0.969	0.651	0.349
M5	0.593	0.000	1.000	0.080	0.000	1.000	0.772	0.136	0.864

Table 2: Main results on the full filtered MAGE test pool at the 1% FPR operating point, part I. Lower TPR@1%FPR/AUROC is better for the attacker; higher ASR is better. This panel reports Binoculars, Fast-DetectGPT, and MAGE. Bold indicates the best value per metric.

Method	RoBERTa AUC	RoBERTa TPR	RoBERTa ASR	Mean TPR	Mean ASR
M0	0.806	0.203	0.797	0.450	0.550
M1	0.778	0.111	0.889	0.284	0.716
M2 (Ours)	0.691	0.002	0.998	0.024	0.976
M3	0.651	0.058	0.942	0.217	0.783
M4	0.627	0.056	0.944	0.203	0.797
M5	0.630	0.001	0.999	0.034	0.966

Table 3: Main results on the full filtered MAGE test pool at the 1% FPR operating point, part II. Lower TPR@1%FPR/AUROC is better for the attacker; higher ASR is better. This panel reports RoBERTa and the mean TPR@1%FPR / mean ASR aggregates across the four-detector panel. Bold indicates the best value per metric.

Method	Binoc. TPR@5%	FastDGPT TPR@5%	MAGE TPR@5%	RoBERTa TPR@5%	Mean TPR@5%
M0	0.481	0.451	0.934	0.397	0.566
M1	0.269	0.252	0.876	0.294	0.423
M2 (Ours)	0.005	0.003	0.272	0.022	0.076
M3	0.135	0.180	0.846	0.159	0.330
M4	0.126	0.130	0.839	0.158	0.313
M5	0.004	0.000	0.238	0.027	0.067

Table 4: Supplementary TPR@5%FPR results on the full filtered MAGE test pool. Lower is better for the attacker. Thresholds are recalibrated on the 15,310 human evaluation samples at the 5% false-positive operating point. Bold indicates the lowest TPR@5%FPR per column.

Run	Mean AUROC	Mean TPR	Mean ASR	Binoc.	Fast-DGPT	MAGE	RoBERTa
Original M2	0.432	0.024	0.976	0.002	0.002	0.089	0.002
Seed 4201	0.432	0.025	0.975	0.002	0.002	0.093	0.002
Seed 4202	0.433	0.024	0.976	0.002	0.002	0.091	0.002
Mean $\pm$ SD	0.432 $\pm$ 0.001	0.024 $\pm$ 0.001	0.976 $\pm$ 0.001	0.002 $\pm$ 0.000	0.002 $\pm$ 0.000	0.091 $\pm$ 0.002	0.002 $\pm$ 0.000

Table 5: Full-pool stochastic repeat analysis for StealthRL (M2) at temperature 1.0 and top-p 0.9. All runs use one generation per input and no reranking; thresholds are the same 1% FPR thresholds calibrated on human evaluation samples. Detector columns report TPR@1%FPR.

B Qualitative Examples

Tables 6–8 show representative paraphrases across different domains from the filtered MAGE test split.

Original (M0)	StealthRL (M2)
During cardio the heart increases its workload and all the body’s other systems adjust to help support that endeavor. The blood vessels dilate, the muscles do their best to help pump blood back to the heart, and the lungs work harder to take in oxygen and remove waste gases like carbon dioxide.	In cardio, the heart ramps up its workload, prompting the body’s other systems to adapt and assist. Blood vessels widen, muscles strive to push blood back to the heart, and lungs intensify their efforts to absorb oxygen and expel waste gases such as carbon dioxide.
The engine has to endure the torque of powering two axels and a drive shaft generally the transfer casing connects to the drive shaft with a ujoint and same for power distribution. The electricity goes into the battery first then is sent to the alternator where it generates voltage that powers all other electrical components like the lights, radio.	The engine must handle the torque from two axles and a drive shaft, typically linked via a universal joint in the transfer casing for power distribution. Electricity first charges the battery, then flows to the alternator, which converts it into voltage to power essential electrical systems such as lights and the radio.

Table 6: Representative paraphrases from the filtered MAGE test split (health and automotive domains).

Original (M0)	StealthRL (M2)
Machine learning algorithms have become increasingly sophisticated in recent years, with deep neural networks achieving state-of-the-art performance across a wide range of tasks including image classification, natural language processing, and reinforcement learning.	Recent advances in machine learning have led to highly sophisticated algorithms. Deep neural networks now achieve top performance in diverse areas, from classifying images and processing natural language to learning through reinforcement-based approaches.
The process of photosynthesis converts light energy into chemical energy that can be stored in glucose molecules. This process occurs in the chloroplasts of plant cells and involves two main stages: the light-dependent reactions and the Calvin cycle.	Photosynthesis transforms light energy into chemical energy, storing it within glucose molecules. Taking place in plant cell chloroplasts, this process unfolds in two key stages: light-dependent reactions followed by the Calvin cycle.

Table 7: Representative paraphrases (science and technology domains).

Original (M0)	StealthRL (M2)
The global economy faces several interconnected challenges, including rising inflation, supply chain disruptions, and geopolitical tensions. Central banks worldwide have responded by tightening monetary policy, raising interest rates to combat price pressures.	Several intertwined challenges confront the global economy: climbing inflation, supply chain breakdowns, and geopolitical friction. In response, central banks around the world have tightened monetary policy and hiked interest rates to curb rising prices.
Renewable energy sources such as solar and wind power have seen dramatic cost reductions over the past decade, making them competitive with traditional fossil fuels in many markets. Government incentives and technological improvements continue to drive adoption rates higher.	Solar and wind power costs have fallen dramatically over the last decade, allowing renewables to compete with fossil fuels across numerous markets. Ongoing government incentives and technological progress continue pushing adoption rates upward.

Table 8: Representative paraphrases (economics and energy domains).

C Hyperparameters and Configuration

Parameter	Value
Model & LoRA	
Base model	Qwen/Qwen3-4B-Instruct-2507
LoRA rank	32
LoRA alpha	32
LoRA dropout	0.05
Training	
Algorithm	Group-Relative Policy Optimization (GRPO)
Learning rate	2.8×10^{-4}
Batch size	16
Group size	8
Epochs	3
Training samples	10,000 AI-generated (custom MAGE subset)
KL penalty coefficient	0.05
Reference policy	Qwen3-4B-Instruct (frozen)
Reward	
Detector weight (α)	1.0
Semantic weight (β)	0.1
Detector ensemble	RoBERTa (0.6) + Fast-DetectGPT (0.4)
Semantic metric	E5 embedding cosine similarity
Inference	
Temperature	1.0
Top-p	0.9
Max tokens	512
Prompt template	“Paraphrase the following text while preserving its meaning: [TEXT]”
Detectors	
RoBERTa OpenAI	openai-community/roberta-large-openai-detector
Fast-DetectGPT	Scoring model: EleutherAI/gpt-neo-2.7B
Binoculars	Lightweight: gpt2-medium + gpt2-large (held-out)
MAGE detector	Longformer classifier (yafu/MAGE, held-out)
Evaluation	
Test samples	15,310 human + 14,656 AI (filtered MAGE test)
Token window	100–500 tokens
FPR calibration	1% on 15,310 human samples (quantile)
Candidates per sample	1
Compute	
Training framework	Tinker API (Thinking Machines)
Reward computation	MacBook + NVIDIA RTX A5000 GPUs
Offline evaluation	MacBook + NVIDIA RTX A5000 GPUs
Seed	42

Table 9: Complete hyperparameters and configuration for reproducibility.

D Per-Detector Results with Confidence Intervals

Table 10 provides the complete per-detector, per-method results with 95% bootstrap confidence intervals (500 iterations) for all four detectors: RoBERTa, Fast-DetectGPT, Binoculars, and MAGE.

Detector	Method	AUROC [95% CI]	TPR@1%FPR [95% CI]	ASR [95% CI]
RoBERTa	M0 No Attack	0.806 [0.801, 0.810]	0.203 [0.196, 0.209]	0.797 [0.791, 0.804]
	M1 Simple Para.	0.778 [0.773, 0.783]	0.111 [0.106, 0.116]	0.889 [0.884, 0.894]
	M2 StealthRL (Ours)	0.691 [0.685, 0.697]	0.002 [0.002, 0.003]	0.998 [0.997, 0.998]
	M3 Adv. Para.	0.651 [0.645, 0.657]	0.058 [0.055, 0.062]	0.942 [0.938, 0.945]
	M4 AuthorMist	0.627 [0.620, 0.633]	0.056 [0.052, 0.059]	0.944 [0.941, 0.948]
	M5 Homoglyph	0.630 [0.624, 0.636]	0.001 [0.000, 0.001]	0.999 [0.999, 1.000]
Fast-DetectGPT	M0 No Attack	0.661 [0.655, 0.668]	0.388 [0.380, 0.396]	0.612 [0.604, 0.620]
	M1 Simple Para.	0.588 [0.582, 0.595]	0.148 [0.143, 0.154]	0.852 [0.846, 0.857]
	M2 StealthRL (Ours)	0.089 [0.086, 0.092]	0.002 [0.001, 0.002]	0.998 [0.998, 0.999]
	M3 Adv. Para.	0.536 [0.530, 0.543]	0.092 [0.087, 0.097]	0.908 [0.903, 0.913]
	M4 AuthorMist	0.518 [0.511, 0.524]	0.067 [0.064, 0.072]	0.933 [0.928, 0.936]
	M5 Homoglyph	0.080 [0.078, 0.083]	0.000 [0.000, 0.000]	1.000 [1.000, 1.000]
Binoculars	M0 No Attack	0.705 [0.699, 0.712]	0.367 [0.360, 0.375]	0.633 [0.625, 0.640]
	M1 Simple Para.	0.593 [0.587, 0.599]	0.158 [0.152, 0.163]	0.842 [0.837, 0.848]
	M2 StealthRL (Ours)	0.055 [0.052, 0.058]	0.002 [0.001, 0.003]	0.998 [0.997, 0.999]
	M3 Adv. Para.	0.511 [0.504, 0.517]	0.051 [0.048, 0.055]	0.949 [0.945, 0.952]
	M4 AuthorMist	0.559 [0.553, 0.566]	0.036 [0.033, 0.038]	0.964 [0.962, 0.967]
	M5 Homoglyph	0.593 [0.587, 0.599]	0.000 [0.000, 0.000]	1.000 [1.000, 1.000]
MAGE	M0 No Attack	0.983 [0.981, 0.984]	0.843 [0.837, 0.849]	0.157 [0.151, 0.163]
	M1 Simple Para.	0.973 [0.972, 0.975]	0.720 [0.713, 0.727]	0.280 [0.273, 0.287]
	M2 StealthRL (Ours)	0.891 [0.888, 0.895]	0.089 [0.084, 0.093]	0.911 [0.907, 0.916]
	M3 Adv. Para.	0.967 [0.965, 0.969]	0.666 [0.658, 0.674]	0.334 [0.326, 0.342]
	M4 AuthorMist	0.969 [0.967, 0.971]	0.651 [0.644, 0.658]	0.349 [0.342, 0.356]
	M5 Homoglyph	0.772 [0.767, 0.777]	0.136 [0.130, 0.141]	0.864 [0.859, 0.870]

Table 10: Complete per-detector results with 95% bootstrap confidence intervals for all four detectors: RoBERTa, Fast-DetectGPT, Binoculars, and MAGE. Bold indicates the best value per metric. StealthRL (M2) achieves near-zero TPR@1%FPR on three of the four detectors.

E LLM Judge Prompt Templates

We use separate gpt-5-nano prompts for quality and semantic similarity. Method labels are never shown to the judge. The exact quality-rating system prompt is:

You are an expert linguist and paraphrase evaluator. Your task is to assess the overall writing quality of a paraphrased text compared to the original source text.

Judge the paraphrase as real writing, not as an attack artifact. Reward unusual sentence structure only when it still reads naturally. Penalize awkward clause order, stilted transitions, filler phrases, obvious prompt leakage, parenthetical meta-comments, detector-evasion artifacts, and phrasing that feels unnatural even if the meaning is preserved.

Be strict about naturalness. Use the full 1-5 scale and avoid defaulting to 3 unless it truly fits.

Scoring criteria: 5 - Excellent: Fluent, grammatical, and natural throughout; reads like polished human writing. 4 - Good: Clear and mostly natural with only minor awkwardness. 3

- Acceptable: Understandable, but noticeably stiff, awkward, or uneven. 2 - Poor: Readably degraded; unnatural syntax or phrasing frequently distracts. 1 - Unusable: Severely broken, incoherent, or clearly unnatural.

Provide your final output as a JSON object in this format: {"score": <score from 1 to 5>, "justification": "<brief explanation>"}

The quality-rating user prompt template is:

Evaluate the following paraphrase using the criteria above (focus on fluency and overall writing quality):

Original Text: """{original_text}"""

Paraphrased Text: """{paraphrased_text}"""

What score (1 to 5) would you assign to the paraphrase’s quality, and why? Do not give extra credit for sounding evasive or unusual if the prose becomes less natural.

The exact semantic-similarity system prompt is:

You are an expert linguist and paraphrase evaluator. Your task is to assess how well the paraphrased text preserves the meaning of the original source text.

Be generous when meaning is substantially preserved. Use the full 1-5 scale and avoid defaulting to 3 unless it truly fits. If the paraphrase keeps the core meaning with only minor changes, prefer 4 or 5. Use 2 or 1 only for clear meaning loss or topic drift.

Scoring criteria: 5 - Approximately equivalent: Meaning preserved; only wording/structure changes. 4 - Nearly equivalent: Meaning mostly preserved; small factual or emphasis shifts. 3 - Somewhat equivalent: Partial meaning preserved; important details differ. 2 - Topically related: Same topic but most meaning lost. 1 - Not related: Different topic or meaning.

Provide your final output as a JSON object in this format: {"score": <score from 1 to 5>, "justification": "<brief explanation>"}

The semantic-similarity user prompt template is:

Evaluate the following paraphrase using the criteria above:

Original Text: """{original_text}"""

Paraphrased Text: """{paraphrased_text}"""

What score (1 to 5) would you assign for semantic similarity, and why?

F Dataset Statistics

Stage	Purpose	Human Samples	AI Samples
Train	RL fine-tuning (GRPO)	0	10,000
Test	Detection evaluation	15,310	14,656
Likert eval	Quality scoring (per method)	0	500
Token range		100–500 tokens	
Source		MAGE benchmark [15]	
Domains		Multiple (essays, Q&A, creative writing)	

Table 11: Dataset statistics for training and evaluation. The Likert evaluation uses 500 AI samples per attack method (M1–M5) with matched sample IDs.