

Table 3-2. Basic RDD transformations on an RDD containing {1, 2, 3, 3}

Function name	Purpose	Example	Result
<code>map()</code>	Apply a function to each element in the RDD and return an RDD of the result.	<code>rdd.map(x => x + 1)</code>	{2, 3, 4, 4}
<code>flatMap()</code>	Apply a function to each element in the RDD and return an RDD of the contents of the iterators returned. Often used to extract words.	<code>rdd.flatMap(x => x.to(3))</code>	{1, 2, 3, 2, 3, 3, 3}
<code>filter()</code>	Return an RDD consisting of only elements that pass the condition passed to <code>filter()</code> .	<code>rdd.filter(x => x != 1)</code>	{2, 3, 3}
<code>distinct()</code>	Remove duplicates.	<code>rdd.distinct()</code>	{1, 2, 3}
<code>sample(withReplacement, fraction, [seed])</code>	Sample an RDD, with or without replacement.	<code>rdd.sample(false, 0.5)</code>	Nondeterministic

Table 3-3. Two-RDD transformations on RDDs containing {1, 2, 3} and {3, 4, 5}

Function name	Purpose	Example	Result
<code>union()</code>	Produce an RDD containing elements from both RDDs.	<code>rdd.union(other)</code>	{1, 2, 3, 3, 4, 5}
<code>intersection()</code>	RDD containing only elements found in both RDDs.	<code>rdd.intersection(other)</code>	{3}
<code>subtract()</code>	Remove the contents of one RDD (e.g., remove training data).	<code>rdd.subtract(other)</code>	{1, 2}
<code>cartesian()</code>	Cartesian product with the other RDD.	<code>rdd.cartesian(other)</code>	{(1, 3), (1, 4), ... (3,5)}

Table 3-4. Basic actions on an RDD containing {1, 2, 3, 3}

Function name	Purpose	Example	Result
<code>collect()</code>	Return all elements from the RDD.	<code>rdd.collect()</code>	{1, 2, 3, 3}
<code>count()</code>	Number of elements in the RDD.	<code>rdd.count()</code>	4
<code>countByValue()</code>	Number of times each element occurs in the RDD.	<code>rdd.countByValue()</code>	{(1, 1), (2, 1), (3, 2)}

Function name	Purpose	Example	Result
<code>take(num)</code>	Return num elements from the RDD.	<code>rdd.take(2)</code>	{1, 2}
<code>top(num)</code>	Return the top num elements the RDD.	<code>rdd.top(2)</code>	{3, 3}
<code>takeOrdered(num)(ordering)</code>	Return num elements based on provided ordering.	<code>rdd.takeOrdered(2)(myOrdering)</code>	{3, 3}
<code>takeSample(withReplacement, num, [seed])</code>	Return num elements at random.	<code>rdd.takeSample(false, 1)</code>	Nondeterministic
<code>reduce(func)</code>	Combine the elements of the RDD together in parallel (e.g., sum).	<code>rdd.reduce((x, y) => x + y)</code>	9
<code>fold(zero)(func)</code>	Same as <code>reduce()</code> but with the provided zero value.	<code>rdd.fold(0)((x, y) => x + y)</code>	9
<code>aggregate(zeroValue)(seqOp, combOp)</code>	Similar to <code>reduce()</code> but used to return a different type.	<code>rdd.aggregate((0, 0)) ((x, y) => (x._1 + y, x._2 + 1), (x, y) => (x._1 + y._1, x._2 + y._2))</code>	(9, 4)
<code>foreach(func)</code>	Apply the provided function to each element of the RDD.	<code>rdd.foreach(func)</code>	Nothing