

Subquery

- Query within another query is called Subquery/ nested query.
- Subquery is used to retrieve data from single or multiple tables by using more than one step.

Types of Sub Query

1. Non correlated Subquery
 - In non correlated subqueries child query is executed first then the parent query is executed.
2. Correlated Sub query
 - In correlated subqueries parent query is executed first then the child query is executed.

Non correlated Subquery

- Child Query
 - A query which provides value to another query is called child query/ inner query.
- Parent Query
 - A query which receives values from another query is called parent query / outer query.

Types of Non correlated Subquery

1. Single row sub query
2. Multiple row sub query
3. Multiple column sub query
4. Inline view sub query

Single row sub query

- In single row sub query, child query returns a single value (i.e. Single row having single column).
- We can use =, <, >, <=, >=, <>, between and operators.

Multiple row sub query

- In multiple row sub query, child query returns multiple value (i.e. multiple row having single column).
- In multiple row sub query we are using in operator.

Multiple column sub query

- In multiple column sub query, child query returns more than one column.

Inline view sub query

- In inline views we are using Subquery in place of table with in parent query.

Example#1

Write a query to display the employees who are getting more salary than the average salary from employee table.

ename	salary
Ram	30000.00
Raj	35000.00
Rahul	40000.00
Alok	60000.00
Sunil	35000.00
Tushar	50000.00

Requirement

ename	salary
Alok	60000.00
Tushar	50000.00

```
CREATE TABLE employee(  
    ename varchar(20),  
    salary decimal(8,2)  
);
```

```
INSERT INTO employee VALUES  
( 'Ram', 30000), ( 'Raj', 35000), ( 'Rahul', 40000),  
( 'Alok', 60000), ( 'Sunil', 35000), ( 'Tushar', 50000);
```

```
SELECT * FROM employee;  
SELECT avg(salary) FROM employee;  
SELECT * FROM employee WHERE salary > (SELECT avg(salary) FROM employee);
```

Example#2

Write a query to display the employees who are working in IT department from employee, department tables by using sub query.

department_id	department_name	employee_id	employee_name	department_id
1	IT	101	Raj	1
2	HT	102	Alok	2
3	Finance	103	Sunil	1
		104	Ram	3
		105	Tushar	2

Requirements

employee_id	employee_name	department_id
101	Raj	1
103	Sunil	1

```
CREATE TABLE departments (  
    department_id INT,  
    department_name VARCHAR(50)  
);
```

```
CREATE TABLE employees (  
    employee_id INT,  
    employee_name VARCHAR(100),  
    department_id INT  
);
```

```
INSERT INTO departments (department_id, department_name)  
VALUES  
    (1, 'IT'),  
    (2, 'HT'),  
    (3, 'Finance');
```

```
INSERT INTO employees (employee_id, employee_name, department_id)  
VALUES  
    (101, 'Raj', 1),  
    (102, 'Alok', 2),  
    (103, 'Sunil', 1),
```

(104, 'Ram', 3),
(105, 'Tushar', 2);

SELECT * FROM employees WHERE department_id =

(SELECT department_id FROM departments WHERE department_name='IT');

Example#3

Write a query to display the employees who are getting more salary than the highest paid employee in '1' department.

employee_id	employee_name	salary	department_id
101	Raj	30000.00	1
102	Alok	40000.00	2
103	Sunil	35000.00	1
104	Ram	45000.00	3
105	Tushar	30000.00	2

Requirements

employee_id	employee_name	salary	department_id
102	Alok	40000.00	2
104	Ram	45000.00	3

```
CREATE TABLE departments (  
    department_id INT,  
    department_name VARCHAR(50)  
);
```

```
CREATE TABLE employees (  
    employee_id INT,  
    employee_name VARCHAR(100),  
    salary decimal(8,2),  
    department_id INT  
);
```

```
INSERT INTO departments (department_id, department_name)  
VALUES  
(1, 'IT'),
```

```
(2, 'HR'),  
(3, 'Finance');
```

```
INSERT INTO employees VALUES
```

```
(101, 'Raj', 30000, 1),  
(102, 'Alok', 40000, 2),  
(103, 'Sunil', 35000, 1),  
(104, 'Ram', 45000, 3),  
(105, 'Tushar', 30000, 2);
```

```
SELECT max(salary) FROM employees WHERE department_id=1;
```

```
SELECT * FROM employees
```

```
WHERE salary > (SELECT max(salary) FROM employees WHERE department_id=1);
```

Example#4

Write a query to display the employees who are getting more salary than the highest paid employee in 'IT' department.

```
SELECT * FROM employees WHERE salary >  
(SELECT max(salary) FROM employees WHERE department_id=  
(SELECT department_id FROM departments WHERE department_name='IT'));
```

Example#5

Write a query to display the employees who are getting more salary than 'Sunil' and work in the department where 'Tushar' works.

```
SELECT * FROM employees  
WHERE salary > (SELECT salary FROM employees WHERE employee_name='Sunil')  
AND department_id = (SELECT department_id FROM employees WHERE  
employee_name='Tushar');
```

Example#6

Write a query to display the second highest salary from employee table.

```
SELECT max(salary) FROM employees  
WHERE salary < (SELECT max(salary) FROM employees);
```

Example#7

Write a query to display the employee details who is getting second highest salary from employee table.

```
SELECT * FROM employees where salary = (  
SELECT max(salary) FROM employees  
WHERE salary < (SELECT max(salary) FROM employees));
```

Multiple row sub query

Example#1

Write a query to display employee details those are getting maximum salary in each departments.

```
SELECT * FROM employees WHERE (department_id, salary) IN (  
    SELECT department_id, max(salary) FROM employees GROUP BY department_id  
);
```

Example#2

Write a query to display employees who are working in either IT or HR departments.

```
SELECT * FROM employees
WHERE department_id in (SELECT department_id FROM departments
WHERE department_name in ('IT','HR'));
```

Example#3

Write a query to list the department names which have no employee.

```
SELECT * FROM departments
WHERE department_id not in (SELECT department_id FROM employees);
```

Multiple Column Sub Query

Example#1

Write a query to find the employees whose department_id and salary are same as 'Alok'.

```
SELECT * FROM employees WHERE (department_id, salary) IN (SELECT department_id, salary
FROM employees WHERE employee_name='Alok');
```

Inline Views/ Derived Table

- In inline views we are using Subquery in place of table with in parent query.
- Syntax:

```
select * from (subquery)
```

Example#1

Write a query to display employee those are getting more than 420000 annual salaries.

```
SELECT * FROM (
SELECT employee_name, salary, salary*12 as total_sal FROM employees ) AS emp
WHERE total_sal > 420000;
```

Example#2

Write a query to display employee those are getting minimum annual salaries.

#Write a query to display employee those are getting minimum annual salaries.

#step1: find anual salary

```
SELECT salary*12 as annual_salary FROM employees
```

#step2: find minimum anual salary

```
SELECT min(annual_salary) FROM (
```

```
SELECT salary*12 as annual_salary FROM employees) as emp)
```

#step3: find employee who is getting minimum anual salary

```
SELECT salary*12 as annual_salary FROM employees;
```

```
SELECT *,salary*12 FROM employees WHERE salary*12 = (SELECT min(annual_salary) FROM (
SELECT salary*12 as annual_salary FROM employees) as emp);
```

Example#3

Write a query to display lowest average salary based on department from employee table.

```
SELECT min(avg_salary) FROM
```

```
(SELECT department_id,avg(salary) as avg_salary FROM employees GROUP BY department_id)
as emp;
```


Example#4

Write a query to display department having maximum number of employees.

```
SELECT department_id, count(*) FROM employees  
GROUP BY department_id  
HAVING count(*) = (SELECT max(emp_count) FROM  
( SELECT count(*) as emp_count FROM employees group by department_id) as table1);
```