

Mandatory

- Vs Code
 - Node Js - v22.2.0 or greater
-

Deploying locally using vs code

1. Open the folder in vs code.
 2. next open the vs code terminal by clicking (...) above top left side.
 3. Make sure the path is `PS C:\your_path\..\cuk-homepage>`
 4. Then use command `cd frontend` to go inside frontend directory.
 5. use command `npm init -y`.
 6. Then use command `npm install` to install all the dependencies.
 7. After completion of installation use command `npm run dev` to run the frontend server(locally).
 8. You can see `http://localhost:5173/` in terminal click `ctrl + click` to open.
 9. To stop in terminal press `ctrl + c`.
 10. For backend similarly open new terminal.
 11. If path is `PS C:\your_path\..\cuk-homepage>` then use command `cd backend` to change directory to backend.
 12. Then use command `npm init -y`
 13. Then use command `npm install` to install all dependencies in backend.
 14. After installation use command `node server.js` to run backend.
-

Note

- Backend and Frontend should run simultaneously.
 - first run backend then take new terminal and run frontend.
-

Error handling

- If you get any error similar to module not found then in terminal install the particular dependency using command `npm install module_name` ex:- `npm install express`, `npm install jsonwebtoken ..` etc.
-

Step-by-Step Deployment Guide on Plesk for Subdomain (`iqac.cuk.ac.in`)

- ◇ Step 1: Prepare Your Project

Vue.js Frontend (Vite build)

```
cd your-vue-frontend
npm install
npm run build
```

This will create a `dist/` folder with static files.

Node.js Backend

Ensure your backend uses environment variables (like `.env`) and listens on a port (like 3000 or 8080).

◇ Step 2: Create a Subdomain in Plesk

1. **Login to your Plesk dashboard.**
2. Go to **Websites & Domains**.
3. Click **"Add Subdomain"**.
 - **Subdomain name:** `iqac`
 - **Parent domain:** `cuk.ac.in`
 - **Document root:** Something like `iqac.cuk.ac.in` or `/httpdocs/iqac`

This will create a directory like: `/var/www/vhosts/cuk.ac.in/iqac.cuk.ac.in/httpdocs`

◇ Step 3: Upload Vue Frontend

1. Go to **File Manager** in Plesk.
2. Navigate to the subdomain folder: `iqac.cuk.ac.in > httpdocs`
3. Upload the contents of your `dist/` folder (from `npm run build`) into this directory.

☒ You may need to delete the default `index.html` file before uploading.

◇ Step 4: Setup Node.js Backend

1. In Plesk, go to **Node.js** (you'll see it if your hosting supports it).
2. Select your subdomain (`iqac.cuk.ac.in`) → **Enable Node.js**.
3. Set the following:
 - **Application root:** Create a folder like `/httpdocs/backend`
 - Upload your **Node.js app** into this folder
 - **Application startup file:** usually `index.js` or `app.js`
 - **Document root:** keep it separate, like `/httpdocs` (for frontend)
4. Add your `.env` file with production values (e.g., DB credentials, port).
5. Use the **Terminal** or **SSH** from Plesk to install dependencies:

```
cd /httpdocs/backend
npm install
```

◇ Step 5: Configure Reverse Proxy (Optional but Recommended)

If your backend runs on port 3000, but you want `iqac.cuk.ac.in/api` to access it:

- 1. In Plesk, go to **Apache & nginx Settings** for your subdomain.
- 2. Add a **proxy rule** like:

```
location /api/ {
    proxy_pass http://127.0.0.1:3000/;
    proxy_http_version 1.1;
    proxy_set_header Upgrade $http_upgrade;
    proxy_set_header Connection 'upgrade';
    proxy_set_header Host $host;
    proxy_cache_bypass $http_upgrade;
}
```

- 3. Restart services or use **Restart Node.js App** in Plesk.

◇ Step 6: Configure MySQL

- Use Plesk's **Databases** tab to:
 - Create a new MySQL database
 - Create a user and assign it to the DB
- Add these credentials to your `.env` file in your Node.js backend.

◇ Step 7: Test Everything

- Test `iqac.cuk.ac.in` → should load your Vue frontend.
- Test `/api` routes → should hit your backend (e.g., `iqac.cuk.ac.in/api/notices`)
- Make sure uploads, DB connections, and admin login all work.

 Summary

Part	Tool	Directory/File
Subdomain	Plesk	<code>iqac.cuk.ac.in</code>
Frontend	Vue.js	Upload <code>dist/</code> to <code>/httpdocs</code>

Part	Tool	Directory/File
Backend	Node.js	<code>/httpdocs/backend</code> with <code>app.js</code>
Database	MySQL	Create via Plesk, connect in <code>.env</code>
API Proxy	nginx/Apache	Reverse proxy <code>/api</code> to port <code>3000</code>
SSL	Let's Encrypt	Enable via Plesk UI