## **NET Module 2 Test**

: The basic unit of concurrency in .NET is a	
a) process	
b) task	

(c) task ✓

2: Under .NET the managed id of main thread is always \_\_\_\_\_.

(a) 1 ✓ (b) 2 (c) 3

3: Give threads x and y such that thread x invokes y.Join() then \_\_\_\_\_.

(a) y will wait for x to exit

(b) x will wait for y to exit ✓ (c) x will wait for x to exit

4: The value of static field of a class is \_\_\_\_\_.

(a) shared by all the threads ✓
(b) assigned separately to each thread
(c) only visible to main thread
5: A thread that owns the monitor assigned to object x, temporarily releases this monitor using expression
(a) Monitor.Exit(x)
(b) Monitor.Wait(x) ✓
(c) Monitor.Pulse(x)
6: An async qualified method yields a task to its caller using statement.
(a) return
(b) await ✓
(c) yield
7: System.IO can be used to obtain size of the file without opening it.
(a) File
(b) FileStream
(c) FileInfo ✓
(5)

8: Creating a file-stream with FileMode.Create will cause exception if the target file		
(a) does not exist		
(b) exists		
(c) exists but is read-only ✓		
9: The XML serializer gathers serialization data from the of the target object.		

(a) instance fields

(b) public instance fields and properties ✓(c) instance properties

(a) TcpClient ✓(b) TcpListener

10: System.Net.Sockets.\_\_\_\_\_ opens a socket for streaming data between two endpoints.

- (c) UdpClient
- 11: In IPv4, \_\_\_\_\_ address is reserved for listening on all addresses available on local machine (a) 255.255.255

(b) 127.0.0.1
(c) 0.0.0.0 \square
12: The address 127.0.0.1 is also called address.  (a) broadcast  (b) loopback ✓  (c) any
<ul> <li>13: Only class address can be used for multicasting data-grams.</li> <li>(a) A</li> <li>(b) C</li> <li>(c) D ✓</li> </ul>
14: The default port used by HTTP server is
(a) 80 ✓
(b) 25
(c) 110

15: Under HTTP, a response status code beginning with digit 5 indicates			
(a) success			
(b) server error ✓			
(c) client error			
16: HTTP verb is used for updating a resource on the server.			
(a) GET			
(b) POST			
(c) PUT ✓			
17: Named pipes are commonly used for cross communication.			
(a) thread			
(b) process ✓			
(c) machine			
18: Under .NET data-provider, the connection object handles			
(a) communication session ✓			
(b) execution of SQL commands			

(c) fetching of rows of a table			
19: Execute method of command object should be used for executing following SQL SELECT COUNT(*) FROM Suppliers (a) Reader (b) NonQuery (c) Scalar ✓			
20: The data-provider for SQL server used as a prefix for each parameter name.  (a) ◎ ✓  (b):  (c) ?			
21: The default parameter direction is  (a) Input ✓  (b) Output  (c) InputOutput			

<ul><li>22: A transaction is</li><li>(a) atomic</li><li>(b) durable ✓</li><li>(c) consistent</li></ul>	_ if it always ends with either commit or rollback.
<ul><li>23: In entity framework,</li><li>(a) DbSet</li><li>(b) DbContext ✓</li><li>(c) DbConnection</li></ul>	connects entity classes to database.
<ul><li>24: Supplier is a parent en</li><li>(a) Id</li><li>(b) ItemId</li><li>(c) SupplierId ✓</li></ul>	tity of Item entity, according to conventional mapping property of Item represents foreign key.
<ul><li>25: Composite primary key</li><li>(a) Fluent API ✓</li><li>(b) Data Annotations</li></ul>	can only be mapped using

(c) Mapping Conventions
26: gRPC uses for transport between server and client.  (a) TCP  (b) HTTP/1  (c) HTTP/2 ✓
<ul> <li>27: In N-tier architecture, the UI is implemented by tier.</li> <li>(a) data</li> <li>(b) middle</li> <li>(c) presentation ✓</li> </ul>
<ul> <li>28: In ASP.NET core a request is passed through a chain of</li> <li>(a) middlewares ✓</li> <li>(b) services</li> <li>(c) controllers</li> </ul>
29: A service added using method has the shortest life-time

<ul><li>(a) AddScoped</li><li>(b) AddTransient ✓</li><li>(c) AddSingleton</li></ul>
<ul><li>30: In MVC pattern, receives users commands and passes them to other two.</li><li>(a) model</li><li>(b) view</li><li>(c) controller ✓</li></ul>
<ul> <li>31: Razor pages use to publish dynamic web content.</li> <li>(a) model and view ✓</li> <li>(b) model and controller</li> <li>(c) view and controller</li> </ul>
<ul> <li>32: In razor syntax, value of server-side variable x can be emitted using</li> <li>(a) {x}</li> <li>(b) @x ✓</li> <li>(c) \${x}</li> </ul>

33: MapDefaultControllerRoute method sets the default controller name to			
(a) Index			
(b) Welcome			
(c) Home ✓			
24. Feels COM interferes systemate the eternal and interferes			
34: Each COM interface extends the standard interface.			
(a) IUnknown ✓			
(b) IDispatch			
(c) IClassFactory			
35: The life-time of a COM object is managed by the			
(a) garbage collector			
(b) COM runtime			
(c) object itself ✓			
26. In COM interent analysis managed code to consume COM interfaces of a native component chiest			
36: In COM interop enables managed code to consume COM interfaces of a native component object.			
(a) RCW ✓			

(b) CCW
(c) PCW
37: In Windows Forms output is rendered as graphics.
(a) scalar
(b) vector
(c) raster ✓
38: In WPF, layout of the UI is specified using a markup language known as
(a) XML
(b) XAML ✓
(c) SGML
39: Windows Forms control only supports simple data binding.
(a) TextBox ✓
(b) ComboBox
(c) DataGridView

40: In MVVM pattern (a) Model (b) View ✓ (c) ViewModel	receives user's input.	