Difference between abstract class and interface

Abstract class and interface both are used to achieve abstraction where we can declare the abstract methods. Abstract class and interface both can't be instantiated.

But there are many differences between abstract class and interface that are given below.

Abstract class	Interface
1) Abstract class can **have abstract and non-abstract** methods.	Interface can have **only abstract** methods. Since Java 8, it can have **default and static methods** also.
2) Abstract class **doesn't support multiple inheritance**.	Interface **supports multiple inheritance**.
3) Abstract class **can have final, non-final, static and non-static variables**.	Interface has **only static and final variables**.
4) Abstract class **can provide the implementation of interface**.	Interface **can't provide the implementation of abstract class**.
5) The **abstract keyword** is used to declare abstract class.	The **interface keyword** is used to declare interface.
6) An **abstract class** can extend another Java class and implement multiple Java interfaces.	An **interface** can extend another Java interface only.
7) An **abstract class** can be extended using keyword "extends".	An **interface** can be implemented using keyword "implements".
8) A Java **abstract class** can have class members like private, protected, etc.	Members of a Java interface are public by default.

9)**Example:**
public abstract class Shape{
public abstract void draw();
}
	Example:
	public interface Drawable{
	void draw();
	}

Simply, abstract class achieves partial abstraction (0 to 100%) whereas interface achieves fully abstraction (100%).

Example of abstract class and interface in Java

Let's see a simple example where we are using interface and abstract class both.

```
//Creating interface that has 4 methods
interface A{
void a();//bydefault, public and abstract
void b();
void c();
void d();
}

//Creating abstract class that provides the implementation of one method of A interface
abstract class B implements A{
public void c(){System.out.println("I am C");}
}

//Creating subclass of abstract class, now we need to provide the implementation of rest of the methods
class M extends B{
public void a(){System.out.println("I am a");}
public void b(){System.out.println("I am b");}
public void d(){System.out.println("I am d");}
}

//Creating a test class that calls the methods of A interface
class Test5{
public static void main(String args[]){
A a=new M();
a.a();
a.b();
a.c();
a.d();
}}
```

Test it Now

Output:

```
I am a
I am b
I am c
I am d
```

← Prev Next →

Feedback

- Send your Feedback to feedback@javatpoint.com

Help Others, Please Share

Learn Latest Tutorials


React tutorial
ReactJS


Regex tutorial
Regex


Reinforcement learning tutorial
Reinforcement Learning


R Programming tutorial
R Programming


RxJS tutorial
RxJS


React Native tutorial
React Native


Python Design Patterns
Python Design Patterns


Python Pillow tutorial
Python Pillow


Python Turtle tutorial
Python Turtle


Keras tutorial
Keras

Preparation


Aptitude
Aptitude


Logical Reasoning
Reasoning


Verbal Ability
Verbal Ability


Interview Questions
Interview Questions


Company Interview Questions
Company Questions

Trending Technologies


Artificial Intelligence Tutorial
Artificial Intelligence


AWS Tutorial
AWS


Selenium tutorial
Selenium


Cloud Computing tutorial
Cloud Computing


Hadoop tutorial
Hadoop


ReactJS Tutorial
ReactJS


Data Science Tutorial
Data Science


Angular 7 Tutorial
Angular 7


Blockchain Tutorial
Blockchain


Git Tutorial
Git


Machine Learning Tutorial
Machine Learning


DevOps Tutorial
DevOps

B.Tech / MCA