

[Home](#) [Java](#) [Programs](#) [OOps](#) [String](#) [Exception](#) [Multithreading](#) [Collections](#)


Java Arrays

Normally, an array is a collection of similar type of elements which has contiguous memory location.

Java array is an object which contains elements of a similar data type. Additionally, The elements of an array are stored in a contiguous memory location. It is a data structure where we store similar elements. We can store only a fixed set of elements in a Java array.


Array in Java is index-based, the first element of the array is stored at the 0th index, 2nd element is stored on 1st index and so on.

Unlike C/C++, we can get the length of the array using the length member. In C/C++, we need to use the sizeof operator.



In Java, array is an object of a dynamically generated class. Java array inherits the Object class, and implements the Serializable as well as Cloneable interfaces. We can store primitive values or objects in an array in Java. Like C/C++, we can also create single dimensional or multidimensional arrays in Java.

Moreover, Java provides the feature of anonymous arrays which is not available in C/C++.



Advantages

- **Code Optimization:** It makes the code optimized, we can retrieve or sort the data efficiently.
- **Random access:** We can get any data located at an index position.

Disadvantages

- **Size Limit:** We can store only the fixed size of elements in the array. It doesn't grow its size at runtime. To solve this problem, collection framework is used in Java which grows automatically.



Jobs in Germany

Make it in Germany

Types of Array in java

There are two types of array.

- Single Dimensional Array
- Multidimensional Array

Single Dimensional Array in Java

Syntax to Declare an Array in Java

```
dataType[] arr; (or)  
dataType []arr; (or)  
dataType arr[];
```

Instantiation of an Array in Java

```
arrayRefVar=new datatype[size];
```

Example of Java Array

Let's see the simple example of java array, where we are going to declare, instantiate, initialize and traverse an array.

```
//Java Program to illustrate how to declare, instantiate, initialize  
//and traverse the Java array.  
class Testarray{  
  public static void main(String args[]){  
    int a[]=new int[5];//declaration and instantiation  
    a[0]=10;//initialization  
    a[1]=20;  
    a[2]=70;  
    a[3]=40;  
    a[4]=50;
```

↑ SCROLL TO TOP

```
for(int i=0;i<a.length;i++)//length is the property of array
System.out.println(a[i]);
}}
```

Test it Now

Output:

```
10
20
70
40
50
```

Declaration, Instantiation and Initialization of Java Array

We can declare, instantiate and initialize the java array together by:

```
int a[]={33,3,4,5};//declaration, instantiation and initialization
```

Let's see the simple example to print this array.

```
//Java Program to illustrate the use of declaration, instantiation
//and initialization of Java array in a single line
class Testarray1{
public static void main(String args[]){
int a[]={33,3,4,5};//declaration, instantiation and initialization
//printing array
for(int i=0;i<a.length;i++)//length is the property of array
System.out.println(a[i]);
}}
```

Test it Now

Output:

↑ SCROLL TO TOP

```
33
3
4
5
```

For-each Loop for Java Array

We can also print the Java array using **for-each loop**. The Java for-each loop prints the array elements one by one. It holds an array element in a variable, then executes the body of the loop.

The syntax of the for-each loop is given below:

```
for(data_type variable:array){
    //body of the loop
}
```

Let us see the example of print the elements of Java array using the for-each loop.

```
//Java Program to print the array elements using for-each loop
class Testarray1{
    public static void main(String args[]){
        int arr[]={33,3,4,5};
        //printing array using for-each loop
        for(int i:arr)
            System.out.println(i);
    }
}
```

Output:

```
33
3
4
5
```

↑ SCROLL TO TOP

Passing Array to a Method in Java

We can pass the java array to method so that we can reuse the same logic on any array.

Let's see the simple example to get the minimum number of an array using a method.

```
//Java Program to demonstrate the way of passing an array
//to method.
class Testarray2{
//creating a method which receives an array as a parameter
static void min(int arr[]){
int min=arr[0];
for(int i=1;i<arr.length;i++)
if(min>arr[i])
min=arr[i];

System.out.println(min);
}

public static void main(String args[]){
int a[]={33,3,4,5};//declaring and initializing an array
min(a);//passing array to method
}}
```

Test it Now

Output:

3

Anonymous Array in Java

Java supports the feature of an anonymous array, so you don't need to declare the array while passing an array to the method.

```
//Java Program to demonstrate the way of passing an anonymous array
//to method.
public class TestAnonymousArray{
//creating a method which receives an array as a parameter
static void printArray(int arr[]){
for(int i=1;i<arr.length;i++)
if(arr[i]<arr[0])
arr[i];
}
```

↑ SCROLL TO TOP

```
}

public static void main(String args[]){
    printArray(new int[]{10,22,44,66}); //passing anonymous array to method
}
```

Test it Now

Output:

```
10
22
44
66
```

Returning Array from the Method

We can also return an array from the method in Java.

```
//Java Program to return an array from the method
class TestReturnArray{
    //creating method which returns an array
    static int[] get(){
        return new int[]{10,30,50,90,60};
    }

    public static void main(String args[]){
        //calling method which returns an array
        int arr[]=get();
        //printing the values of an array
        for(int i=0;i<arr.length;i++)
            System.out.println(arr[i]);
    }
}
```

Test it Now

Output:

```
10
30
50
90
60
```

The Java Virtual Machine (JVM) throws an `ArrayIndexOutOfBoundsException` if length of the array is negative, equal to the array size or greater than the array size while traversing the array.

```
//Java Program to demonstrate the case of  
//ArrayIndexOutOfBoundsException in a Java Array.  
public class TestArrayException{  
public static void main(String args[]){  
int arr[]={50,60,70,80};  
for(int i=0;i<=arr.length;i++){  
    System.out.println(arr[i]);  
}  
}}
```

Test it Now

Output:

```
Exception in thread "main" java.lang.ArrayIndexOutOfBoundsException: 4  
    at TestArrayException.main(TestArrayException.java:5)  
50  
60  
70  
80
```

Multidimensional Array in Java

In such case, data is stored in row and column based index (also known as matrix form).

Syntax to Declare Multidimensional Array in Java

```
dataType[][] arrayRefVar; (or)  
dataType [][]arrayRefVar; (or)  
dataType arrayRefVar[][]; (or)  
dataType [][]arrayRefVar[];
```

↑ SCROLL TO TOP

Example to instantiate Multidimensional Array in Java

```
int[][] arr=new int[3][3]; //3 row and 3 column
```

Example to initialize Multidimensional Array in Java

```
arr[0][0]=1;  
arr[0][1]=2;  
arr[0][2]=3;  
arr[1][0]=4;  
arr[1][1]=5;  
arr[1][2]=6;  
arr[2][0]=7;  
arr[2][1]=8;  
arr[2][2]=9;
```

Example of Multidimensional Java Array

Let's see the simple example to declare, instantiate, initialize and print the 2Dimensional array.

```
//Java Program to illustrate the use of multidimensional array  
class Testarray3{  
    public static void main(String args[]){  
        //declaring and initializing 2D array  
        int arr[][]={{1,2,3},{2,4,5},{4,4,5}};  
        //printing 2D array  
        for(int i=0;i<3;i++){  
            for(int j=0;j<3;j++){  
                System.out.print(arr[i][j]+" ");  
            }  
            System.out.println();  
        }  
    }  
}
```

Test it Now

Output:

```
1 2 3  
2 4 5  
4 4 5
```

Jagged Array in Java

↑ SCROLL TO TOP | number of columns in a 2D array, it is known as a jagged array. In other words, it is an array of arrays with different number of columns.

```
//Java Program to illustrate the jagged array
class TestJaggedArray{
    public static void main(String[] args){
        //declaring a 2D array with odd columns
        int arr[][] = new int[3][];
        arr[0] = new int[3];
        arr[1] = new int[4];
        arr[2] = new int[2];
        //initializing a jagged array
        int count = 0;
        for (int i=0; i<arr.length; i++){
            for(int j=0; j<arr[i].length; j++){
                arr[i][j] = count++;
            }
        }

        //printing the data of a jagged array
        for (int i=0; i<arr.length; i++){
            for (int j=0; j<arr[i].length; j++){
                System.out.print(arr[i][j]+ " ");
            }
            System.out.println();//new line
        }
    }
}
```

Test it Now

Output:

```
0 1 2
3 4 5 6
7 8
```

What is the class name of Java array?

In Java, an array is an object. For array object, a proxy class is created whose name can be obtained by `getClass().getName()` method on the object.

```
//Java Program to get the class name of array in Java
class Testarray4{
    public static void main(String args[]){
        //declaration and initialization of array
        int arr[]={4,4,5};
        //getting the class name of Java array
        System.out.println(arr.getClass().getName());
    }
}
```

↑ SCROLL TO TOP

```
String name=c.getName();  
//printing the class name of Java array  
System.out.println(name);  
  
}}
```

Test it Now

Output:

I

Copying a Java Array

We can copy an array to another by the arraycopy() method of System class.

Syntax of arraycopy method

```
public static void arraycopy(  
Object src, int srcPos, Object dest, int destPos, int length  
)
```

Example of Copying an Array in Java

```
//Java Program to copy a source array into a destination array in Java  
class TestArrayCopyDemo {  
    public static void main(String[] args) {  
        //declaring a source array  
        char[] copyFrom = { 'd', 'e', 'c', 'a', 'f', 'f', 'e',  
                             'i', 'n', 'a', 't', 'e', 'd' };  
        //declaring a destination array  
        char[] copyTo = new char[7];  
        //copying array using System.arraycopy() method  
        System.arraycopy(copyFrom, 2, copyTo, 0, 7);  
        //printing the destination array  
        System.out.println(String.valueOf(copyTo));  
    }  
}
```

Test it Now

Output:

caffein

↑ SCROLL TO TOP

Cloning an Array in Java

Since, Java array implements the Cloneable interface, we can create the clone of the Java array. If we create the clone of a single-dimensional array, it creates the deep copy of the Java array. It means, it will copy the actual value. But, if we create the clone of a multidimensional array, it creates the shallow copy of the Java array which means it copies the references.

```
//Java Program to clone the array
class Testarray1{
    public static void main(String args[]){
        int arr[]={33,3,4,5};
        System.out.println("Printing original array:");
        for(int i:arr)
            System.out.println(i);

        System.out.println("Printing clone of the array:");
        int carr[]=arr.clone();
        for(int i:carr)
            System.out.println(i);

        System.out.println("Are both equal?");
        System.out.println(arr==carr);

    }
}
```

Output:

```
Printing original array:
33
3
4
5
Printing clone of the array:
33
3
4
5
Are both equal?
false
```

Addition of 2 Matrices in Java

Let's see a simple example that adds two matrices.

↑ SCROLL TO TOP

//Java Program to demonstrate the addition of two matrices in Java

```
class Testarray5{
public static void main(String args[]){
//creating two matrices
int a[][]={{1,3,4},{3,4,5}};
int b[][]={{1,3,4},{3,4,5}};

//creating another matrix to store the sum of two matrices
int c[][]=new int[2][3];

//adding and printing addition of 2 matrices
for(int i=0;i<2;i++){
for(int j=0;j<3;j++){
c[i][j]=a[i][j]+b[i][j];
System.out.print(c[i][j]+ " ");
}
System.out.println();//new line
}
}}
```

Test it Now

Output:

```
2 6 8
6 8 10
```

Multiplication of 2 Matrices in Java

In the case of matrix multiplication, a one-row element of the first matrix is multiplied by all the columns of the second matrix which can be understood by the image given below.

↑ SCROLL TO TOP

$$\text{Matrix 1} \begin{Bmatrix} 1 & 1 & 1 \\ 2 & 2 & 2 \\ 3 & 3 & 3 \end{Bmatrix} \quad \text{Matrix 2} \begin{Bmatrix} 1 & 1 & 1 \\ 2 & 2 & 2 \\ 3 & 3 & 3 \end{Bmatrix}$$

$$\text{Matrix 1} \times \text{Matrix 2} \begin{Bmatrix} 1*1+1*2+1*3 & 1*1+1*2+1*3 & 1*1+1*2+1*3 \\ 2*1+2*2+2*3 & 2*1+2*2+2*3 & 2*1+2*2+2*3 \\ 3*1+3*2+3*3 & 3*1+3*2+3*3 & 3*1+3*2+3*3 \end{Bmatrix}$$

$$\text{Matrix 1} \times \text{Matrix 2} \begin{Bmatrix} 6 & 6 & 6 \\ 12 & 12 & 12 \\ 18 & 18 & 18 \end{Bmatrix} \quad \text{JavaTpoint}$$

Let's see a simple example to multiply two matrices of 3 rows and 3 columns.

```
//Java Program to multiply two matrices
public class MatrixMultiplicationExample{
    public static void main(String args[]){
        //creating two matrices
        int a[][]={{1,1,1},{2,2,2},{3,3,3}};
        int b[][]={{1,1,1},{2,2,2},{3,3,3}};

        //creating another matrix to store the multiplication of two matrices
        int c[][]=new int[3][3]; //3 rows and 3 columns

        //multiplying and printing multiplication of 2 matrices
        for(int i=0;i<3;i++){
            for(int j=0;j<3;j++){
                c[i][j]=0;
                for(int k=0;k<3;k++){
                    {
                        c[i][j]+=a[i][k]*b[k][j];
                    }//end of k loop
                }
                System.out.print(c[i][j]+" "); //printing matrix element
            }//end of j loop
            System.out.println();//new line
        }
    }
}
```

Test it Now

Output:

↑ SCROLL TO TOP

Related Topics

- 1) Java Program to copy all elements of one array into another array
 - 2) Java Program to find the frequency of each element in the array
 - 3) Java Program to left rotate the elements of an array
 - 4) Java Program to print the duplicate elements of an array
 - 5) Java Program to print the elements of an array
 - 6) Java Program to print the elements of an array in reverse order
 - 7) Java Program to print the elements of an array present on even position
 - 8) Java Program to print the elements of an array present on odd position
 - 9) Java Program to print the largest element in an array
 - 10) Java Program to print the smallest element in an array
 - 11) Java Program to print the number of elements present in an array
 - 12) Java Program to print the sum of all the items of the array
 - 13) Java Program to right rotate the elements of an array
 - 14) Java Program to sort the elements of an array in ascending order
 - 15) Java Program to sort the elements of an array in descending order
 - 16) Find 3rd Largest Number in an Array
 - 17) Find 2nd Largest Number in an Array
 - 18) Find Largest Number in an Array
 - 19) Find 2nd Smallest Number in an Array
 - 20) Find Smallest Number in an Array
 - 21) Remove Duplicate Element in an Array
 - 22) Add Two Matrices
 - 23) Multiply Two Matrices
 - 24) Print Odd and Even Number from an Array
 - 25) Transpose matrix
 - 26) Java Program to subtract the two matrices
 - 27) Java Program to determine whether a given matrix is an identity matrix
 - 28) Java Program to determine whether a given matrix is a sparse matrix
 - 29) Java Program to determine whether two matrices are equal
 - 30) Java Program to display the lower triangular matrix
 - 31) Java Program to display the upper triangular matrix
- ↑ [SCROLL TO TOP](#) , find the frequency of odd & even numbers in the given matrix

33) Java Program to find the product of two matrices

34) Java Program to find the sum of each row and each column of a matrix

35) Java Program to find the transpose of a given matrix

[< Prev](#)[Next >](#)

 [For Videos Join Our Youtube Channel: Join Now](#)

Feedback


- Send your Feedback to feedback@javatpoint.com

Help Others, Please Share




Learn Latest Tutorials

↑ [SCROLL TO TOP](#)

 [SPSS tutorial](#)
SPSS






 [Swagger tutorial](#)

 [T-SQL tutorial](#)
Transact-SQL













 [Tumblr tutorial](#)
Tumblr

		Swagger		
 React tutorial ReactJS	 Regex tutorial Regex	 Reinforcement learning tutorial Reinforcement Learning	 R Programming tutorial R Programming	 RxJS tutorial RxJS
 React Native tutorial React Native	 Python Design Patterns Python Design Patterns	 Python Pillow tutorial Python Pillow	 Python Turtle tutorial Python Turtle	 Keras tutorial Keras


Preparation

 Aptitude Aptitude	 Logical Reasoning Reasoning	 Verbal Ability Verbal Ability	 Interview Questions Interview Questions	 Company Interview Questions Company Questions
--	--	--	--	--

Trending Technologies

 Artificial Intelligence Tutorial Artificial Intelligence	 AWS Tutorial AWS	 Selenium tutorial Selenium	 Cloud Computing tutorial Cloud Computing	 Hadoop tutorial Hadoop
 ReactJS Tutorial ReactJS	 Data Science Tutorial Data Science	 Angular 7 Tutorial Angular 7	 Blockchain Tutorial Blockchain	 Git Tutorial Git
 Machine Learning Tutorial Machine Learning	 DevOps Tutorial DevOps			

B.Tech / MCA

 DBMS tutorial DBMS	 Data Structures tutorial Data Structures	 DAA tutorial DAA	 Operating System tutorial Operating System	 Computer Network tutorial Computer Network
 Compiler Design tutorial Compiler Design	 Computer Organization and Architecture Computer Organization	 Discrete Mathematics Tutorial Discrete Mathematics	 Ethical Hacking Tutorial Ethical Hacking	 Computer Graphics Tutorial Computer Graphics
 Software Engineering Tutorial Software Engineering	 html tutorial Web Technology	 Cyber Security tutorial Cyber Security	 Automata Tutorial Automata	 C Language tutorial C Programming
 C++ tutorial C++	 Java tutorial Java	 .Net Framework tutorial .Net	 Python tutorial Python	 List of Programs Programs
 Control Systems tutorial Control System	 Data Mining Tutorial Data Mining	 Data Warehouse Tutorial Data Warehouse		

