




Java main() method

The main() is the starting point for JVM to start execution of a Java program. Without the main() method, JVM will not execute the program. The syntax of the main() method is:



public: It is an access specifier. We should use a public keyword before the main() method so that JVM can identify the execution point of the program. If we use private, protected, and default before the main() method, it will not be visible to JVM.

static: You can make a method static by using the keyword static. We should call the main() method without creating an object. Static methods are the method which invokes without creating the objects, so we do not need any object to call the main() method.

void: In Java, every method has the return type. Void keyword acknowledges the compiler that main() method does not return any value.

❗

MAJOR POINTS OF

main(): It is a default signature which is predefined in the JVM. It is called by JVM to execute a program line by line and end the execution after completion of this method. We can also overload the main() method.

String args[]: The main() method also accepts some data from the user. It accepts a group of strings, which is called a string array. It is used to hold the command line arguments in the form of string values.

```
main(String args[])
```

Here, args[] is the array name, and it is of String type. It means that it can store a group of string. Remember, this array can also store a group of numbers but in the form of string only. Values passed to the main() method is called arguments. These arguments are stored into args[] array, so the name args[] is generally used for it.

What happens if the main() method is written without String args[]?

It will compile, but not run, because JVM will not recognize the main() method. Remember JVM always looks for a method with a string type array as a parameter.

Execution Process

First, JVM executes the static block, then it executes static methods, and then it creates the object needed by the program. Finally, it executes the instance methods. JVM executes a static block on the highest priority basis. It means JVM first goes to static block even before it looks for the main() method in the program.

Example

```
class Demo
{
    static          //static block
    {
        System.out.println("Static block");
    }
    public static void main(String args[]) //static method
    {
        System.out.println("Static method");
    }
}
```

Output:

```
Static block
Static method
```

We observe that JVM first executes the static block, if it is present in the program. After that it searches for the main() method. If the main() method is not found, it gives error.

Example

A program that does not have the main() method gives an error at run time.

```
class DemoStaticBlock
{
    Static          //static block
    {
        System.out.println("Static block");
    }
}
```

↑ SCROLL TO TOP

```
}
```

Output:

```
Error: Main method not found in the class Demo, please define the main method as:  
public static void main(String[] args)  
or a JavaFX application class must extend javafx.application.Application
```

So the main() method should always be written as:

```
public static void main(String args[])
```

We can interchange public and static and write it as follows:

```
static public void main(String args[])
```

We can also use the different name for the String type array and write it as:

```
static public void main(String[] x)
```

Different ways of writing main() method are:

```
static public void main(String []x)  
static public void main(String...args)
```

String...args: It allows the method to accept zero or multiple arguments. There should be exactly three dots between String and array; otherwise, it gives an error.

Example

A program that has no main() method, but compile and runs successfully.

```
abstract class DemoNoMain extends javafx.application.Application  
{  
    static    //static block  
    {  
        System.out.println("Java");  
    }  
}
```

↑ SCROLL TO TOP

```
}  
}
```

Output:

```
Java
```

Overloading of main() method

We can also overload the main() method. We can define any number of main() method in the class, but the method signature must be different.


Example

```
class OverloadMain  
{  
    public static void main(int a) //overloaded main method  
    {  
        System.out.println(a);  
    }  
    public static void main(String args[])  
    {  
        System.out.println("main method incoked");  
        main(6);  
    }  
}
```

Output:

```
main method invoked  
6
```

[< Prev](#)[Next >](#)



 For Videos Join Our Youtube Channel: [Join Now](#)

Feedback

- Send your Feedback to feedback@javatpoint.com

Help Others, Please Share





Program by IIT Roorkee EICT


Learn from IIT Professors & Industry Practitioners. Adva Career Now!


Intellipaat


Learn Latest Tutorials



Splunk



SPSS



Swagger



Transact-SQL



Tumblr



ReactJS



Regex



Reinforcement Learning


R Programming



RxJS


React Native


Python Design Patterns


Python Pillow


Python Turtle



Keras


↑ SCROLL TO TOP

Python Design
Patterns

Preparation

 Aptitude
Aptitude

 Logical
Reasoning
Reasoning

 Verbal Ability
Verbal Ability


 Interview
Questions
Interview Questions

 Company
Interview
Questions
Company Questions


Trending Technologies

 Artificial
Intelligence
Tutorial
Artificial
Intelligence

 AWS Tutorial
AWS

 Selenium
tutorial
Selenium

 Cloud
Computing
tutorial
Cloud Computing

 Hadoop tutorial
Hadoop


 ReactJS
Tutorial
ReactJS

 Data Science
Tutorial
Data Science

 Angular 7
Tutorial
Angular 7

 Blockchain
Tutorial
Blockchain


 Git Tutorial
Git


 Machine
Learning Tutorial
Machine Learning


 DevOps
Tutorial
DevOps


B.Tech / MCA

 DBMS tutorial
DBMS

 Data Structures
tutorial
Data Structures

 DAA tutorial
DAA

 Operating
System tutorial
Operating System

 Computer
Network tutorial
Computer Network

↑ SCROLL TO TOP

 <div>Compiler Design tutorial Compiler Design</div>	 <div>Computer Organization and Architecture Computer Organization</div>	 <div>Discrete Mathematics Tutorial Discrete Mathematics</div>	 <div>Ethical Hacking Tutorial Ethical Hacking</div>	 <div>Computer Graphics Tutorial Computer Graphics</div>
 <div>Software Engineering Tutorial Software Engineering</div>	 <div>html tutorial Web Technology</div>	 <div>Cyber Security tutorial Cyber Security</div>	 <div>Automata Tutorial Automata</div>	 <div>C Language tutorial C Programming</div>
 <div>C++ tutorial C++</div>	 <div>Java tutorial Java</div>	 <div>.Net Framework tutorial .Net</div>	 <div>Python tutorial Python</div>	 <div>List of Programs Programs</div>
 <div>Control Systems tutorial Control System</div>	 <div>Data Mining Tutorial Data Mining</div>	 <div>Data Warehouse Tutorial Data Warehouse</div>		