

TABULATION:

MODEL PART NO.

R0920USG 9390000 (M4) 12972700 (M4A1) R0921USG

GET RIFLE FROM GUN RACK AND COLLAPSE THE BUTTSTOCK. DBTAIN LABEL FROM TARGET TAG. VERIFY SERIAL NUMBER ON RIFLE TO MATCH LABEL ON TARGET TAG. SCAN RFID TAG AND UID ON WEAPON, INSERT RIFLE INTO VCI BAG PER ARDEC DWG. 13027484 AND HEAT SEALED SEAM TO CLOSE. ATTACH/TAPE LABELS (SERIAL NUMBER, BARCODE/CONTRACT LABOR) TO BAG. ASIDE TO GUN RACK.

DO NOT SCALE


FINISH REO'D 125 7 UNLESS OTHERWISE


SPECIFIED


LOCATE

REFERENCE PACKING INSTRUCTION SHEET F-6010 FOR MATERIALS

REFERENCE: MACHINE SETTINGS








NOTE: PLACE EACH MAGAZINE, SLING & TECHNICAL MANUAL IN SEPARATE HEAT SEALED BAGS.

SETUP: PERFORM ONCE PER DAY

PERFORM SEAL STRENGTH TEST PER MIL-STD-3010 Method 2024 Reference: Form F6032 for INSTRUCTION.

SETUP: PERFORM ONCE PER LOT

PERFORM LEAK TEST PER MIL-STD-3010 METHOD 5009 Reference: Form F6033 for INSTRUCTION.



TOOL NO	TOOL NAME	SYMBOL

_	12-8-16	(RE-COMPETE) INITIAL RELEASE/ECO 52818	GC	
SYM	DATE	CHANGE RECORD	BY	
F-6004 Rev. 11-13				