

Symmetric Computations

Suraj Kumar

Inria & ENS Lyon

Email: *suraj.kumar@inria.fr*

CR12: September 2023

<https://surakuma.github.io/courses/daamtc.html>

Symmetric Rank-K (SYRK) update


$C = A \cdot A^T$, where A is an $n_1 \times n_2$ matrix and C is an $n_1 \times n_1$ symmetric matrix.

- It multiplies a matrix with its transpose
- It requires roughly half of the computation of general matrix multiplication due to symmetry
- $C_{ij} = \sum_{k=0}^{n_2-1} A_{ik} A_{jk}$ for $0 \leq j \leq i \leq n_1$

SYRK pseudo code:

```
for  $i = 0:n_1 - 1$ 
  for  $j = 0:i$ 
    for  $k = 0:n_2 - 1$ 
       $C[i][j] += A[i][k] * A[j][k]$ 
```


SYRK iteration space:



Here we assume that each $C[i][j]$ is initialized to 0 in the beginning.

Loomis-Whitney inequality

- For the 2d object G , $\text{Area}(G) \leq \phi_x \phi_y$
- For the 3d object H , $\text{Volume}(H) \leq \sqrt{\phi_{xy} \phi_{yz} \phi_{xz}}$



Lemma

Let $V \in \mathbb{Z}^3$ and $\phi_{ij}(V)$ be the projection of V on the $i - j$ plane, i.e.,
 $\phi_{ij}(V) = \{(i, j) : \exists k, (i, j, k) \in V\}$. Similarly $\phi_{jk}(V)$ and $\phi_{ik}(V)$ are defined.
Then

$$|V| \leq |\phi_{ij}(V)|^{\frac{1}{2}} |\phi_{jk}(V)|^{\frac{1}{2}} |\phi_{ik}(V)|^{\frac{1}{2}}.$$

Extension of Loomis-Whitney inequality

Theorem (Lemma 3, Ballard et al., SPAA 2023.)

Let $V = \{(i, j, k) \in \mathbb{Z}^3 : j < i\}$ and $\phi_{ij}(V)$ be the projection of V on the $i - j$ plane, i.e., $\phi_{ij}(V) = \{(i, j) : \exists k, (i, j, k) \in V\}$. Similarly $\phi_{jk}(V)$ and $\phi_{ik}(V)$ are defined. Then


$$2|V| \leq |\phi_{jk}(V) \cup \phi_{ik}(V)| (2|\phi_{ij}(V)|)^{\frac{1}{2}}.$$

Proof: Let $\tilde{V} = \{(i, j, k) \in \mathbb{Z}^3 : (j, i, k) \in V\}$.

$$|V| = |\tilde{V}| \text{ and } |V \cup \tilde{V}| = 2|V|$$

$$\phi_{ij}(\tilde{V}) = \{(i, j) : (j, i) \in \phi_{ij}(V)\} \text{ and } |\phi_{ij}(V) \cup \phi_{ij}(\tilde{V})| = 2|\phi_{ij}(V)|$$

$$\phi_{jk}(\tilde{V}) = \phi_{ik}(V), \phi_{ik}(\tilde{V}) = \phi_{jk}(V) \text{ and } \phi_{ik}(V \cup \tilde{V}) = \phi_{jk}(V \cup \tilde{V}) = \phi_{jk}(V) \cup \phi_{ik}(V)$$



Applying the previous lemma (Loomis-Whitney inequality) on $V \cup \tilde{V}$ yields the mentioned inequality.

Parallel memory-independent communication lower bounds for SYRK

We focus on the computation of the entries below the diagonal of C .

```
for  $i = 0:n_1 - 1$ 
  for  $j = 0:i - 1$ 
    for  $k = 0:n_2 - 1$ 
       $C[i][j] += A[i][k] * A[j][k]$ 
```

- The computation is load balanced – each processor performs $\frac{n_1(n_1-1)n_2}{2P}$ loop iterations
- One copy of data is in the system – there exists a processor whose input data at the start plus output data at the end must be at most $\frac{n_1(n_1-1)/2 + n_1n_2}{P}$ words
 - Will analyze data transfers for this processor
 - F be the set of indices (i, j, k) associated with loop iterations performed on this processor

Optimization problem to compute communication lower bound

$$\begin{aligned} & \text{Minimize } |\phi_{ik}(F) \cup \phi_{jk}(F)| + |\phi_{ij}(F)| \quad \text{s.t.} \\ & (2|\phi_{ij}(F)|)^{\frac{1}{2}} |\phi_{ik}(F) \cup \phi_{jk}(F)| \geq 2|F| = \frac{n_1(n_1 - 1)n_2}{P} \end{aligned}$$

$|\phi_{ik}(F) \cup \phi_{jk}(F)|$: number of accessed entries of A

$|\phi_{ij}(F)|$: number of accessed entries of C

- Using Lagrange multipliers, optimal value obtained when

$$|\phi_{ik}(F) \cup \phi_{jk}(F)| = 2|\phi_{ij}(F)| = \left(\frac{n_1(n_1-1)n_2}{P} \right)^{\frac{2}{3}}$$

- Lower bound = $|\phi_{ik}(F) \cup \phi_{jk}(F)| + |\phi_{ij}(F)| - \text{data owned by the processor}$
$$= \frac{3}{2} \left(\frac{n_1(n_1-1)n_2}{P} \right)^{\frac{2}{3}} - \frac{n_1(n_1-1)/2 + n_1 n_2}{P}$$

Symmetric Rank-2k (SYR2K) update

$C = A \cdot B^T + B \cdot A^T$, where A and B are $n_1 \times n_2$ matrices. C is an $n_1 \times n_1$ symmetric matrix.

SYR2K pseudo code:

for $i = 0:n_1 - 1$

for $j = 0:i$

for $k = 0:n_2 - 1$

$C[i][j] += A[i][k] * B[j][k] + A[j][k] * B[i][k]$

Assignment 3 – deadline Oct 5

Question: Obtain memory-independent communication lower bound for SYR2K. Assume that all the operations of each loop iteration are performed on the same processor, i.e, $A[i][k] * B[j][k]$ and $A[j][k] * B[i][k]$ are computed on one processor.