

Create Database Connection

- **Mongoose** is used to establish a secure connection between the **Node.js backend** and the **MongoDB database**.
- The **dotenv** package loads environment variables from the **.env** file, including the **MONGO_URI** connection string.
- The **mongoose.connect(mongoUri)** method connects the application to the **HouseHunt** database.
- A **success message** is displayed in the console after the database connection is established successfully.
- **Error handling** is implemented using a **try-catch** block to detect and display connection errors.
- The application uses the **default local MongoDB URI** (**mongodb://127.0.0.1:27017/househunt**) if **MONGO_URI** is not available.
- This connection enables seamless interaction with **User**, **Property**, **Booking**, **Review**, and **Wishlist** collections in **MongoDB**.

```
const mongoose = require('mongoose');
const dotenv = require('dotenv');

dotenv.config({ path: path.join(__dirname, '../backend/.env') });

const User = require('../backend/models/User');
const Property = require('../backend/models/Property');
const Booking = require('../backend/models/Booking');
const Review = require('../backend/models/Review');
const Wishlist = require('../backend/models/Wishlist');

const sampleProperties = JSON.parse(
  fs.readFileSync(path.join(__dirname, 'sampleProperties.json'), 'utf-8')
);

const seedData = async () => {
  try {
    const mongoUri = process.env.MONGO_URI || 'mongodb://127.0.0.1:27017/';
    console.log(`Connecting to database: ${mongoUri}`);
    await mongoose.connect(mongoUri);
    console.log('Database connection successful!');
  } catch (error) {
    console.error('Database connection failed:', error);
  }
}
```

WORKFLOW

