(a) Parts of a CONSTRUCT query

```
PREFIX table:  <http://csv2rdf.qlever.dev/table/>
PREFIX title:  <http://csv2rdf.qlever.dev/title/>
PREFIX imdb:  <https://www.imdb.com/>
CONSTRUCT {
  ?movie a imdb:Movie ;
         rdfs:label ?name ;
         imdb:startYear ?year .
}
WHERE {
  ?row a table:title ;
       title:tconst ?id ;
       title:primaryTitle ?name .
  BIND(IRI(CONCAT(STR(imdb:), "title/", ?id))
       AS ?movie)
  OPTIONAL { ?row title:startYear ?y .
             BIND(xsd:int(?y) AS ?year) }
}
```

Prefixes Short names for long IRIs.

Template The triples to produce. It is filled in once for every solution.

WHERE clause Its triple patterns are matched against the input graph. Every match is one *solution*.

BIND Computes a value: the movie IRI.

OPTIONAL Matches only if a year exists; otherwise `?year` stays unbound.

(b) What happens when the query is executed

1 Match: one row per solution

?id	?name	?movie	?year
"tt0113277"	"Heat"	title:tt0113277	1995
"tt1234567"	"Example"	title:tt1234567	

2 Fill in: the template, per solution

solution 1:

```
title:tt0113277 a imdb:Movie .
title:tt0113277 rdfs:label "Heat" .
title:tt0113277 imdb:startYear "1995"^^xsd:int .
```

solution 2:

```
title:tt1234567 a imdb:Movie .
title:tt1234567 rdfs:label "Example" .
~~title:tt1234567 imdb:startYear ?year .~~
```

skipped: `?year` is unbound

3 Combine: the output graph

All produced triples are combined into **one RDF graph** by set union; skipped triples are not part of it.