EXPERIMENT – 16
CLONE A VIRTUAL MACHINE IN VMWARE WORKSTATION

AIM

To create a clone of an existing virtual machine using VMware Workstation.

REQUIREMENTS

1. A computer with VMware Workstation installed.
2. An existing virtual machine that has at least one saved snapshot.
3. Enough free disk space on the host drive to store the cloned virtual machine.

PROCEDURE

1. Open VMware Workstation and select the virtual machine that has to be cloned from the library.
2. Make sure the virtual machine is powered off or is in a supported snapshot state.
3. Right-click the virtual machine (or open the VM menu) and choose Manage → Clone. The Clone Virtual Machine Wizard opens.
4. Read the welcome page and click Next.
5. Choose the clone source: an existing snapshot (for example Snapshot 1) or the current state of the virtual machine, and click Next.
6. Select Create a linked clone or Create a full clone, depending on the lab requirement, and click Next.
7. Enter a name for the cloned virtual machine and choose the folder where it will be stored.
8. Review the settings and click Finish to start the cloning process.
9. Wait until the clone is complete, then click Close.
10. Check that the cloned virtual machine appears in the library on the left side.
11. Select the cloned virtual machine and check its name, hardware summary and the "Clone of" entry in the Virtual Machine Details before powering it on.

IMPLEMENTATION INPUT

An existing Ubuntu 64-bit virtual machine and a clone created from Snapshot 1.

OUTPUT

The screenshot shows the cloned virtual machine displayed in VMware Workstation.



Figure 1: VMware Workstation displays "Clone of Ubuntu 64-bit (2)" as a separate virtual machine. The details identify the source VM configuration and show Snapshot 1.

RESULT

A cloned virtual machine is visible in VMware Workstation under the name "Clone of Ubuntu 64-bit (2)". The screenshot shows the clone and its configuration summary. The VM is powered off, so it can be started after the clone settings are confirmed.