Ex. No.: 12

## MITM ATTACK WITH ETTERCAP

## Aim:

To initiate a MITM attack using ICMP redirect with Ettercap tool.

## **Algorithm:**


- 1. Install ettercap if not done already using the
  - command-dnf install ettercap
- 2. Open etter.conf file and change the values of ec\_uid and ec\_gid to zero from default.
  - vi /etc/ettercap/etter.conf
- 3. Next start ettercap in GTK
  - ettercap -G
- 4. Click sniff, followed by unified sniffing.
- 5. Select the interface connected to the network.
- 6. Next ettercap should load into attack mode by clicking Hosts followed by Scan for Hosts
- 7. Click Host List and choose the IP address for ICMP redirect
- 8. Now all traffic to that particular IP address is redirected to some other IP address.
- 9. Click MITM and followed by Stop to close the attack.


## **Output:**

[root@localhost security lab]# dnf install ettercap

[root@localhost security lab]# vi /etc/ettercap/etter.conf

[root@localhost security lab]# ettercap -G





```
root@fedora:/home/sudhashreemadhu# dnf install ettercap
                                2.3 kB/s | 2.9 kB
Copr repo for PyCharm owned by phracek
                                               00:01
google-chrome
                                2.2 kB/s | 1.7 kB
                                               00:00
RPM Fusion for Fedora 40 - Nonfree - NVIDIA Dri 1.7 kB/s | 7.0 kB
                                               00:04
RPM Fusion for Fedora 40 - Nonfree - Steam
                                               00:01
                                903 B/s | 1.4 kB
Dependencies resolved.
Package
           Architecture Version
                                        Repository
-----
Installing:
ettercap
           x86_64 0.8.3.1-14.fc40
                                        fedora
                                                  892 k
Transaction Summary
Install 1 Package
Fotal download size: 892 k
Installed size: 2.7 M
s this ok [y/N]: y
Downloading Packages:
00:04
```

