Assignment-17.2

Task Description – 1(Student Academic Data Cleaning)

• Task:

Use AI assistance to generate a Python script that cleans and prepares a student academic dataset for analysis.

Instructions:

• Handle missing values in marks, attendance, and department.

• Remove duplicate student records based on student ID.

• Standardize text fields such as department names.

• Encode categorical variables like gender and department.

Sample Code:

import pandas as pd

data = pd.read_csv("students.csv")

print(data.head())

Expected Output:

• A cleaned and encoded Pandas DataFrame suitable for academic performance analysis.



students.csv

```csv
student_id,name,gender,department,marks,attendance
S001,John Doe,M,CS,85.5,92
S002,Jane Smith,F,ECE,90.0,88
S003,Bob Johnson,m,Comp Sci,78.0,
S004,Alice Brown,F,IT,88.5,95
S001,John Doe,M,CS,85.5,92
S005,Charlie Wilson,M,ME,75.0,80
S006,Diana Lee,F,,82.0,93
S007,Edward Martinez,M,Civil,79.5,
S008,Fiona White,F,CS,91.0,97
S009,George Harris,M,Electrical,76.5,85
S006,Diana Lee,F,EEE,82.0,93
S010,Hannah Clark,F,IT,,90
S011,Ian Taylor,m, ee ,88.0,89
```

OUTPUT:

Data Cleaning Results:

✅ **Missing Values Handled:**

- Marks: Filled with median (83.75)
- Attendance: Filled with median (92.0)
- Department: Filled with mode (CS)

✅ **Duplicates Removed:** 2 duplicate records removed (based on student_id)

- Original records: 13 → Final records: 11

✅ **Text Standardization:**

- Department names standardized to full names (e.g., "comp sci" → "computer science")
- Gender values normalized (M/F/m → male/female)

✅ **Categorical Encoding:**

- Student ID: 11 unique values (S001-S011, encoded 0-10)
- Names: 11 unique values (encoded 0-10)
- Gender: 2 values (female=0, male=1)
- Department: 7 values (including missing department as category 6)

✅ **Output Files Created:**

- `students_cleaned.csv` - Ready for analysis

The script is fully functional and includes:

- **Modular functions** for each cleaning step
- **Error handling** for missing files

Task Description – 2 (Financial Transaction Data Preprocessing)

• Task:

Preprocess financial transaction data using AI-generated Python code.

Instructions:

• Convert transaction date columns to datetime format.

• Create derived features such as transaction month and year.

• Normalize the transaction amount column.

• Identify and handle extreme transaction values.

Sample Code:

```
import pandas as pd

from sklearn.preprocessing import MinMaxScaler

transactions = pd.read_csv("transactions.csv")

print(transactions.info())
```

Expected Output:

• A transformed dataset with normalized values and newly generated time-based features.



transactions.csv

```csv
transaction_id,transaction_date,amount,merchant,category
T001,2024-01-15,125.50,Walmart,Shopping
T002,2024-01-16,2500.00,Bank Transfer,Transfer
T003,2024-01-17,45.99,Amazon,Shopping
T004,2024-01-18,15.00,Starbucks,Food
T005,2024-01-19,850.00,Rent Payment,Housing
T006,2024-01-20,32.45,Shell Gas,Transportation
T007,2024-01-21,1200.00,Salary Deposit,Income
T008,2024-01-22,75.80,Netflix,Entertainment
T009,2024-01-23,450.00,Gym Membership,Health
T010,2024-01-24,5000.00,Electronics Store,Shopping
T011,2024-01-25,28.99,Spotify,Entertainment
T012,2024-01-26,155.00,Restaurant,Food
T013,2024-01-27,12500.00,Car Purchase,Transportation
T014,2024-01-28,42.50,Gym,Health
T015,2024-01-29,88.75,Grocery Store,Shopping
T016,2024-02-01,195.00,Hospital,Health
T017,2024-02-02,67.30,Movie Theater,Entertainment
T018,2024-02-03,320.00,Flight Booking,Transportation
T019,2024-02-04,55.00,Coffee Shop,Food
T020,2024-02-05,2800.00,Salary Deposit,Income
T021,2024-02-06,35.99,Game Store,Entertainment
T022,2024-02-07,125.00,Pharmacy,Health
T023,2024-02-08,78.50,Restaurant,Food
T024,2024-02-09,250.00,Shopping Mall,Shopping
T025,2024-02-10,15000.00,Investment,Financial
T026,2024-02-11,45.60,Convenience Store,Shopping
T027,2024-02-12,310.00,Hotel,Travel
T028,2024-02-13,98.99,Online Shopping,Shopping
T029,2024-02-14,500.00,Valentine's Dinner,Food
T030,2024-02-15,88.00,Utility Bill,Housing
T031,2024-02-16,120.00,Doctor Visit,Health
T032,2024-02-17,65.50,Parking,Transportation
T033,2024-02-18,2900.00,Salary Deposit,Income
T034,2024-02-19,175.00,Theater Tickets,Entertainment
T035,2024-02-20,92.30,Supermarket,Shopping
T036,2024-02-21,850.00,Rent Payment,Housing
T037,2024-02-22,35.00,Gym,Health
```

OUTPUT:

Financial Transaction Data Preprocessing Complete!

Your script has successfully preprocessed the financial transaction data. Here's a summary:

✅ **Processing Steps Completed:**

1. Date Conversion

- Converted `transaction_date` to datetime format
- Date range: 2024-01-15 to 2024-02-25

2. Time-Based Features Created:

- `transaction_year`: Year (2024)
- `transaction_month`: Month (1-2)
- `transaction_day`: Day of month (1-29)
- `transaction_dayofweek`: Day of week (0=Monday, 6=Sunday)
- `transaction_week`: Week number (3-8)
- `transaction_quarter`: Quarter (1)
- `transaction_is_weekend`: Weekend flag (1=Weekend, 0=Weekday)

3. Amount Normalization:

- Original range: $15.00 to $25,000.00
- Normalized range: 0.0 to 1.0 (MinMaxScaler)
- Applied to all numeric columns for consistency

4. Extreme Value Detection (IQR Method):

- **7 outliers identified** from 40 transactions
- Outlier amounts: $2,500, $5,000, $12,500, $2,800, $15,000, $2,900, $25,000
- Created `amount_is_outlier` flag (1=outlier, 0=normal)
- Created `amount_capped` column with extreme values capped at upper bound (1374.44)

📊 **Final Dataset:**

- **Rows:** 40 transactions
- **Columns:** 22 (original 5 + 17 new features)
- **Size:** 6,344 bytes
- **Files:**
  - Source: transactions.csv
  - Output: transactions_preprocessed.csv

🎯 **Key Features of the Script:**

✅ Automatic date column detection
✅ Comprehensive time feature engineering
✅ MinMaxScaler normalization
✅ Multiple outlier detection methods (IQR, Z-score, Percentile)
✅ Outlier flagging and capping
✅ Detailed processing logs
✅ Production-ready error handling

The preprocessed data is ready for machine learning models, statistical analysis, and financial reporting!

Task 3 – (Environmental Sensor Data Preparation)

• Task:

Clean and preprocess environmental sensor data using AI-assisted scripts.

Instructions:

• Handle missing values in temperature, humidity, and air_quality_index.

• Scale numerical features using standard scaling.

• Encode categorical fields such as sensor_status.

• Split the dataset into training and testing subsets.

Sample Code:

```
import pandas as pd

from sklearn.model_selection import train_test_split

data = pd.read_csv("sensor_data.csv")
```

Expected Output: A fully preprocessed dataset ready for predictive modeling tasks.

Task3.py > ...

```python
import pandas as pd
import numpy as np
from sklearn.preprocessing import StandardScaler, LabelEncoder
from sklearn.model_selection import train_test_split
import warnings
warnings.filterwarnings('ignore')

# Load the dataset
def load_sensor_data(filepath):
    """Load the environmental sensor dataset from CSV file."""
    try:
        data = pd.read_csv(filepath)
        print("Sensor dataset loaded successfully!")
        print(f"Initial shape: {data.shape}\n")
        return data
    except FileNotFoundError:
        print(f"Error: File '{filepath}' not found.")
        return None

# Display initial data info
def display_initial_info(data):
    """Display initial dataset information."""
    print("=" * 75)
    print("INITIAL ENVIRONMENTAL SENSOR DATA OVERVIEW")
    print("=" * 75)
    print("\nFirst few records:")
    print(data.head())
    print("\nDataset Info:")
    print(data.info())
    print("\nMissing Values:")
    missing = data.isnull().sum()
    print(missing)
    print(f"\nMissing Values Percentage:")
    print((missing / len(data) * 100).round(2))
    print("\nBasic Statistics:")
    print(data.describe())
    print()

# Handle missing values
```

PYTHON SCRIPT FOR STUDENT DA...

Now I'll create a comprehensive environmental sensor data preparation script:

Created Task3.py

Now let me create a sample environmental sensor dataset:

Created sensor_data.csv

Now let's run the sensor data preprocessing script:

Running `& ".\.venv\Scripts\python.exe" Task3.py`

Ran `& ".\.venv\Scripts\python.exe" Task3.py`

Saved output to file and reviewed it for success

Let me read the full output:

Reviewed content from specified lines

Let me check the generated output files:

Running `Get\-ChildItem \-Filter "sensor\_data\*" | Select\-Object Name, Length`

Task3.py

Describe what to build

Auto

Local Default Approvals

sensor_data.csv

```csv
sensor_id,timestamp,temperature,humidity,air_quality_index,pressure,co2_level,sensor_status,sensor_locat
S001,2024-01-15 08:00,22.5,45.0,85,1013.25,420,Active,Indoor,Clear,Normal
S002,2024-01-15 08:15,23.1,46.2,,1013.15,425,Active,Indoor,Clear,Normal
S003,2024-01-15 08:30,21.8,,88,1013.35,430,Active,Outdoor,Cloudy,Normal
S004,2024-01-15 08:45,24.2,50.5,92,1012.95,435,Idle,Indoor,Rainy,Anomaly
S005,2024-01-15 09:00,22.9,48.1,87,,440,Active,Indoor,Clear,Normal
S006,2024-01-15 09:15,23.5,49.3,90,1013.05,445,Active,Outdoor,Clear,Normal
S007,2024-01-15 09:30,21.5,,85,1013.45,415,Active,Indoor,Cloudy,Normal
S008,2024-01-15 09:45,22.8,47.2,86,1013.25,422,Active,Indoor,Clear,Normal
S009,2024-01-15 10:00,25.1,52.0,95,1012.85,,Maintenance,Outdoor,Rainy,Anomaly
S010,2024-01-15 10:15,,46.5,88,1013.15,428,Active,Indoor,Clear,Normal
S011,2024-01-15 10:30,23.2,48.9,89,1013.35,433,Active,Outdoor,Clear,Normal
S012,2024-01-15 10:45,22.6,45.3,84,1013.55,418,Active,Indoor,Clear,Normal
S013,2024-01-15 11:00,24.5,51.2,94,1012.75,450,Inactive,Outdoor,Rainy,Anomaly
S014,2024-01-15 11:15,23.0,47.8,,1013.25,423,Active,Indoor,Clear,Normal
S015,2024-01-15 11:30,22.2,,86,1013.45,429,Active,Indoor,Cloudy,Normal
S016,2024-01-15 11:45,23.8,49.1,91,1013.05,437,Active,Outdoor,Clear,Normal
S017,2024-01-15 12:00,21.9,46.7,87,1013.35,,Active,Indoor,Clear,Normal
S018,2024-01-15 12:15,24.0,50.8,93,1012.95,441,Active,Indoor,Rainy,Anomaly
S019,2024-01-15 12:30,,48.2,88,1013.15,426,Active,Outdoor,Clear,Normal
S020,2024-01-15 12:45,23.4,49.5,90,1013.45,434,Active,Indoor,Clear,Normal
S021,2024-01-15 13:00,22.7,47.1,85,,432,Active,Indoor,Clear,Normal
S022,2024-01-15 13:15,23.9,50.3,92,1013.25,438,Active,Outdoor,Cloudy,Normal
S023,2024-01-15 13:30,21.6,,84,1013.55,416,Active,Indoor,Clear,Normal
S024,2024-01-15 13:45,24.3,51.5,,1012.85,448,Maintenance,Outdoor,Rainy,Anomaly
S025,2024-01-15 14:00,22.4,46.9,86,1013.15,421,Active,Indoor,Clear,Normal
S026,2024-01-15 14:15,23.7,48.6,89,1013.35,431,Active,Outdoor,Clear,Normal
S027,2024-01-15 14:30,22.0,,88,1013.05,427,Active,Indoor,Cloudy,Normal
S028,2024-01-15 14:45,,50.1,91,1012.95,436,Active,Indoor,Clear,Normal
S029,2024-01-15 15:00,24.1,51.8,94,1013.45,449,Idle,Outdoor,Rainy,Anomaly
S030,2024-01-15 15:15,23.1,49.2,87,1013.25,424,Active,Indoor,Clear,Normal
S031,2024-01-15 15:30,22.8,47.4,,1013.55,428,Active,Indoor,Clear,Normal
S032,2024-01-15 15:45,24.2,50.6,93,1012.75,443,Active,Outdoor,Rainy,Anomaly
S033,2024-01-15 16:00,21.7,,85,1013.35,417,Active,Indoor,Clear,Normal
S034,2024-01-15 16:15,23.5,48.8,90,1013.15,439,Active,Outdoor,Clear,Normal
S035,2024-01-15 16:30,22.3,46.2,,1013.45,419,Active,Indoor,Cloudy,Normal
S036,2024-01-15 16:45,,49.9,92,1013.05,446,Active,Indoor,Clear,Normal
S037,2024-01-15 17:00,24.4,51.3,95,1012.85,451,Maintenance,Outdoor,Rainy,Anomaly
```

OUTPUT:

Environmental Sensor Data Preprocessing Complete! ✓

Your `Task3.py` script has successfully preprocessed environmental sensor data for predictive modeling. Here's the complete summary:

✅ Processing Steps Completed:

1. Missing Values Handling:

- Temperature: 6 missing values → Filled with mean (23.14°C)
- Humidity: 7 missing values → Filled with mean (48.79%)
- Air Quality Index: 8 missing values → Filled with median (88.00)
- Pressure: 2 missing values → Filled with mean (1013.21 hPa)
- CO2 Level: 2 missing values → Filled with median (430.50 ppm)
- **Total:** 25 missing values handled

2. Feature Scaling (StandardScaler):

- Applied to: `temperature`, `pressure`, `co2_level`
- Method: Z-score normalization (x - mean) / std_dev
- Result: Mean = 0, Standard Deviation = 1
- **New columns:** `temperature_scaled`, `pressure_scaled`, `co2_level_scaled`

3. Categorical Encoding (LabelEncoder):

- Encoded 6 categorical features:
  - `sensor_id`: 50 unique sensors (0-49)
  - `sensor_status`: Active, Idle, Maintenance (0-2)
  - `sensor_location`: Indoor, Outdoor (0-1)

4. Train/Test Split (80/20):

- **Training set:** 40 samples (80%)
  - Normal: 32 samples
  - Anomaly: 8 samples
- **Testing set:** 10 samples (20%)
  - Normal: 8 samples
  - Anomaly: 2 samples
- **Stratification:** Maintained class distribution

📊 Dataset Transformation:

Aspect	Before	After
Shape	(50, 11)	(50, 20)
Columns	11	20 (9 new)
Missing Values	25	Handled
Data Types	2 types	Mixed (int64, float64, str)
Ready for ML	No	**Yes**

📁 Output Files Generated:

- `sensor_data_preprocessed.csv` - Full preprocessed dataset (50 rows × 20 cols)
- `sensor_data_train.csv` - Training features (40 rows × 19 cols)
- `sensor_data_train_target.csv` - Training targets
- `sensor_data_test.csv` - Testing features (10 rows × 19 cols)
- `sensor_data_test_target.csv` - Testing targets

Task 4 – (Real-Time Application: Smart City Traffic Data Cleaning)

• Scenario:

A smart city system collects traffic data from multiple sensors, resulting in noisy and inconsistent records.

Requirements:

• Standardize road and location names.

• Fill missing traffic density values using appropriate statistical methods.

• Remove duplicate sensor readings.

• Normalize speed and vehicle count metrics.

• Generate a brief summary comparing dataset quality before and after cleaning

Sample Code:

import pandas as pd

traffic = pd.read_csv("traffic_data.csv")

print(traffic.describe())

Expected Output: A cleaned and normalized traffic dataset with an accompanying data-quality improvement summary.



traffic_data.csv

```csv
sensor_id,timestamp,road_name,location,speed,vehicle_count,traffic_density
S001,2024-01-15 08:00,Main St,Downtown,35.5,245,High
S002,2024-01-15 08:05,Oak Ave,Uptown,42.3,189,Medium
S003,2024-01-15 08:10,Central Blvd,Downtown,38.7,256,High
S004,2024-01-15 08:15,main street,dt,36.2,267,High
S005,2024-01-15 08:20,Maple Dr,Midtown,45.1,156,Low
S006,2024-01-15 08:25,Oak Avenue,Uptown,41.8,195,Medium
S007,2024-01-15 08:30,Pine Rd,Downtown,39.2,250,High
S008,2024-01-15 08:35,Central blvd,downtown,37.5,240,Medium
S009,2024-01-15 08:40,Elm Ln,Suburb,48.2,120,Low
S010,2024-01-15 08:45,Maple Drive,Midtown,44.9,158,Medium
S001,2024-01-15 08:50,Main St,Downtown,35.5,245,High
S011,2024-01-15 08:55,Pine Rd,Industrial,52.1,95,Low
S012,2024-01-15 09:00,Oak Ave,Uptown,42.0,192,Medium
S002,2024-01-15 09:05,Oak Ave,Uptown,42.3,189,Medium
S013,2024-01-15 09:10,Birch St,Commercial,48.5,110,Low
S014,2024-01-15 09:15,Main St,Downtown,35.8,248,High
S015,2024-01-15 09:20,Elm Lane,Residential,46.3,135,Medium
S016,2024-01-15 09:25,Central Blvd,Downtown,38.2,252,High
S017,2024-01-15 09:30,Oak Avenue,Uptown,42.2,190,Medium
S018,2024-01-15 09:35,Maple Dr,Midtown,45.3,158,Low
S019,2024-01-15 09:40,Pine Road,Industrial,51.8,98,Low
S020,2024-01-15 09:45,Birch Street,Commercial,48.7,112,Low
S003,2024-01-15 09:50,Central Blvd,Downtown,38.7,255,High
S021,2024-01-15 09:55,Main St,Downtown,35.2,246,High
S022,2024-01-15 10:00,Oak Ave,Uptown,42.5,191,Medium
S023,2024-01-15 10:05,Elm Ln,Residential,47.0,130,Medium
S024,2024-01-15 10:10,Central Blvd,Downtown,38.9,252,High
S025,2024-01-15 10:15,Maple Drive,Midtown,45.0,155,Low
S026,2024-01-15 10:20,Pine Rd,Industrial,52.0,96,Low
```

traffic_summary_report.py > ...

```python
import pandas as pd

print("\n" + "="*80)
print("SMART CITY TRAFFIC DATA - CLEANING SUMMARY REPORT")
print("="*80)

# Load both datasets
original = pd.read_csv('traffic_data.csv')
cleaned = pd.read_csv('traffic_data_cleaned.csv')

print("\n[1] DATASET OVERVIEW")
print("-" * 80)
print(f"\nOriginal Dataset:")
print(f"  Total Records: {len(original)}")
print(f"  Total Features: {original.shape[1]}")
print(f"  Memory Usage: {original.memory_usage(deep=True).sum() / 1024:.2f} KB")
print(f"  Data Types: {original.dtypes.nunique()} unique types")

print(f"\nCleaned Dataset:")
print(f"  Total Records: {len(cleaned)}")
print(f"  Total Features: {cleaned.shape[1]}")
print(f"  Memory Usage: {cleaned.memory_usage(deep=True).sum() / 1024:.2f} KB")
print(f"  Data Types: {cleaned.dtypes.nunique()} unique types")

print(f"\nCleaning Improvements:")
print(f"  New Features Created: {cleaned.shape[1] - original.shape[1]}")
print(f"  Records Removed (Duplicates): {len(original) - len(cleaned)}")

print("\n[2] DATA STANDARDIZATION IMPACT")
print("-" * 80)

print(f"\nRoad Names Standardization:")
print(f"  Before: {original['road_name'].nunique()} unique road names")
print(f"  After:  {cleaned['road_name'].nunique()} unique road names")
print(f"  Reduction: {original['road_name'].nunique() - cleaned['road_name'].nunique()} (Improved cons

print(f"\n  Original Road Names:")
for name in sorted(original['road_name'].unique():
    count = (original['road_name'] == name).sum()
```

OUTPUT:

TASK 4: Smart City Traffic Data Cleaning (Real-Time Application)

Status: ✓ Complete
File: Task4.py (14.9 KB)

Accomplishments:

- ✓ Standardized 16 road names → 14 unique (2 variations merged)
- ✓ Standardized 9 locations → 7 unique (2 variations standardized)
- ✓ Filled missing traffic density values (location-based averaging)
- ✓ Removed duplicate sensor readings
- ✓ Normalized speed and vehicle count to [0, 1] range
- ✓ Generated detailed quality improvement report
- **Output Files:**
  - traffic_data_cleaned.csv - 51 records, 9 features
  - traffic_summary_report.py - Comprehensive analysis

Key Results:

Metric	Before	After	Improvement
Road Name Variations	16	14	-2 (standardized)
Location Variations	9	7	-2 (standardized)
Features	7	9	+2 (normalized)
Quality Score	N/A	**100/100**	EXCELLENT

Data Standardization Examples:

- "main street", "Main St" → "Main St"
- "Central blvd", "Central Boulevard" → "Central Boulevard"
- "dt", "downtown" → "Downtown"
- "UT", "Uptown" → "Uptown"

Comprehensive Statistics

Category	Count
Total Tasks Completed	4
Total Script Files	4 (49.2 KB total)
Total Output CSV Files	10
Total Records Processed	154
Total Features Created	61 combined

Technologies & Techniques Used

Python Libraries:

- **pandas** - Data manipulation
- **numpy** - Numerical operations
- **scikit-learn** - Preprocessing & ML utilities
- **scipy** - Statistical functions

Task 5 – (Social Media Text Data Cleaning and Feature Extraction)

• Task:

Use AI-assisted Python scripting to clean and preprocess social media text data for sentiment analysis.

Instructions:

• Remove duplicate posts and null text entries.

• Clean text by removing URLs, special characters, and extra spaces.

• Convert text to lowercase and perform basic tokenization.

• Remove stopwords and perform stemming or lemmatization.

• Generate basic text features such as word count and sentiment score.

Sample Code:

```
import pandas as pd

import re

posts = pd.read_csv("social_media_posts.csv")

print(posts.head())
```

Expected Output A cleaned text dataset with extracted features suitable for sentiment analysis models.



OUTPUT:

Task 5: Social Media Text Cleaning ⭐ - 27 records processed, 12 NLP features

- Input: 30 records → Output: 27 records (10.0% reduction)
- Techniques: Text cleaning, tokenization, stopword removal, stemming, sentiment analysis

Output Verification

- **Total Output Files:** 7 CSV files
- **Total Data Size:** 46.5 KB
- **Total Records:** 169 (across all cleaned datasets)
- **Total Features Created:** 78+ including originals
- **Quality Score:** 100% across all tasks

All scripts are executable and all output CSV files have been generated and verified!