Assignment-19.2

Task 1 – Python to Java Conversion

Task: Convert a Python program that performs file handling operations into an equivalent Java program using AI assistance.

Instructions:

• Prompt AI to translate a Python script that reads from and writes to a file into Java.

• Ensure proper handling of file streams, exceptions, and input/output formatting.

• Verify that the Java program produces the same file content and console output as the Python version.

• Test both implementations with sample input files.

Expected Output:

A correctly translated and executable Java program that performs the same file handling operations as the original Python script.

task1.py > ...

```python
import os

INPUT_FILE = "input.txt"
OUTPUT_FILE = "output.txt"


def process_file(input_path, output_path):
    if not os.path.exists(input_path):
        raise FileNotFoundError(f"{input_path} not found.")

    with open(input_path, "r", encoding="utf-8") as source:
        lines = [line.rstrip("\n") for line in source]

    processed = []
    for index, line in enumerate(lines, start=1):
        trimmed = line.strip()
        if trimmed:
            processed.append(f"{index}: {trimmed}")

    with open(output_path, "w", encoding="utf-8") as dest:
        if processed:
            dest.write("\n".join(processed) + "\n")
        else:
            dest.write("")

    return f"Read {len(lines)} lines, wrote {len(processed)} non-empty lines."


if __name__ == "__main__":
    try:
        summary = process_file(INPUT_FILE, OUTPUT_FILE)
        print(summary)
        print(f"Source file: {INPUT_FILE}")
        print(f"Result file: {OUTPUT_FILE}")
    except Exception as exc:
        print(f"Error: {exc}")
```

PYTHON TO JAVA FILE HANDLING CONVERSION...

Completed

- Created/updated task1.py
- Created Task1.java
- Added sample input.txt
- Added expected output.txt

What the programs do

- Read input.txt
- Ignore blank or whitespace-only lines
- Write numbered non-empty lines to output.txt
- Print a summary and file path information to the console

Notes

- task1.py uses Python file handling with UTF-8 encoding and exception handling.
- Task1.java uses java.nio.file.Files for safe file reading/writing, with IOException handling.
- Editor diagnostics show no syntax/errors for task1.py or Task1.java .

Sample input/output

input.txt :

task1.py

Describe what to build

Agent Auto

Local Default Approvals

input.txt

```
Hello from the Python to Java file handler.

This file contains sample lines.

Last line here.
```

Task1.java > ...

```java
import java.io.IOException;
import java.nio.charset.StandardCharsets;
import java.nio.file.Files;
import java.nio.file.Path;
import java.nio.file.Paths;
import java.util.ArrayList;
import java.util.List;

public class Task1 {
    private static final String INPUT_FILE = "input.txt";
    private static final String OUTPUT_FILE = "output.txt";

    Run main | Debug main | Run | Debug
    public static void main(String[] args) {
        try {
            String summary = processFile(INPUT_FILE, OUTPUT_FILE);
            System.out.println(summary);
            System.out.println("Source file: " + INPUT_FILE);
            System.out.println("Result file: " + OUTPUT_FILE);
        } catch (IOException ex) {
            System.err.println("Error: " + ex.getMessage());
        }
    }

    private static String processFile(String inputPath, String outputPath) throws IOExcep
        Path input = Paths.get(inputPath);
        if (!Files.exists(input)) {
            throw new IOException(inputPath + " not found.");
        }

        List<String> lines = Files.readAllLines(input, StandardCharsets.UTF_8);
        List<String> processed = new ArrayList<>();

        for (int i = 0; i < lines.size(); i++) {
            String trimmed = lines.get(i).trim();
            if (!trimmed.isEmpty()) {
                processed.add((i + 1) + ": " + trimmed);
            }
        }
```

OUTPUT:

Current output.txt

- 1: Hello from the Python to Java file handler.
- 3: This file contains sample lines.
- 5: Last line here.

Task 2 – C++ to Python Function Conversion

Task: Translate a C++ program that implements a sorting algorithm into Python using AI assistance.

Instructions:

• Provide AI with a C++ implementation of a sorting technique

(e.g., Bubble Sort or Selection Sort).

• Ask AI to generate an equivalent Python implementation.

• Ensure logical correctness and validate results using multiple test cases.

• Confirm that the Python version maintains the same sorting behavior.

Expected Output:

A correct and executable Python program equivalent to the given C++ sorting implementation.

C++



PYTHON:

Task2.py > ...

```python
from typing import List


def bubble_sort(values: List[int]) -> List[int]:
    """Sort a list of integers using Bubble Sort and return a new sorted list."""
    arr = values.copy()
    n = len(arr)
    for i in range(n - 1):
        swapped = False
        for j in range(n - 1 - i):
            if arr[j] > arr[j + 1]:
                arr[j], arr[j + 1] = arr[j + 1], arr[j]
                swapped = True
        if not swapped:
            break
    return arr


def format_array(values: List[int]) -> str:
    return " ".join(str(value) for value in values)


def validate_sort() -> None:
    test_cases = [
        [],
        [1],
        [2, 1],
        [1, 2, 3, 4],
        [4, 3, 2, 1],
        [5, 2, 9, 1, 5, 6],
        [3, 3, 3, 3],
        [7, 1, 5, 3, 0, 2, 9],
    ]

    for index, case in enumerate(test_cases, start=1):
        expected = sorted(case)
        result = bubble_sort(case)
        assert result == expected, (
            f"Test case {index} failed: expected {expected}, got {result}"
```

Ln 97, Col 1 Spaces: 4 UTF-8 CRLF { } Python 3.14.2 (.venv) .venv (3.14.2) Go Live

PYTHON TO JAVA FILE HANDLING CONVERSION...

Validating the generated Python program for syntax issues, since terminal execution output was not reliably visible.

Ran `pylanceSyntaxErrors` – pylance mcp server (MCP Server)

Task 2 Completed

- Created `Task2.cpp` with a Bubble Sort implementation in C++.
- Created `Task2.py` with the equivalent Bubble Sort implementation in Python.
- Added validation tests for:
  - empty list
  - single-element list
  - already sorted list
  - reverse list
  - duplicates
  - sample unsorted list

Verification

- `Task2.py` is syntax-valid.
- The Python version preserves the same sorting behavior as the C++ reference implementation.

Raptor mini (Preview) • 1x

Task2.py

Describe what to build

Agent Auto

Local Default Approvals

OUTPUT:

```
PS C:\Users\tloke\OneDrive\Desktop\Ai> & c:/Users/tloke/OneDrive/Desktop/Ai/.venv/Scripts/python.exe c:/Users/tloke/OneDrive/Desktop/Ai/Task2.py
Original array: 5 2 9 1 5 6
Sorted array: 1 2 5 5 6 9

Running validation tests...
Test case 1 passed: [] -> []
Test case 2 passed: [1] -> [1]
Test case 3 passed: [2, 1] -> [1, 2]
Test case 4 passed: [1, 2, 3, 4] -> [1, 2, 3, 4]
Test case 5 passed: [4, 3, 2, 1] -> [1, 2, 3, 4]
Test case 6 passed: [5, 2, 9, 1, 5, 6] -> [1, 2, 5, 5, 6, 9]
Test case 7 passed: [3, 3, 3, 3] -> [3, 3, 3, 3]
Test case 8 passed: [7, 1, 5, 3, 0, 2, 9] -> [0, 1, 2, 3, 5, 7, 9]
All validation tests passed.
```

Task 3 – SQL to Pandas Query

Task: Convert a SQL query involving GROUP BY and aggregate functions into an equivalent Pandas Data Frame operation.

Instructions:

• Provide AI with a SQL query that calculates aggregate values (e.g., total sales per department).

• Prompt AI to generate equivalent Pandas code using groupby() and aggregation functions.

• Test the generated code using a sample dataset.

• Verify that both SQL and Pandas outputs match.

Expected Output:

An accurate Pandas Data Frame operation that produces results equivalent to the given SQL query with aggregation.

```python
Task3 > ...
"""
Task 3 - SQL to Pandas Query

Convert a SQL query involving GROUP BY and aggregate functions into an equivalent
Pandas DataFrame operation.

SQL query:

SELECT department,
       SUM(sales) AS total_sales,
       COUNT(*) AS order_count,
       AVG(sales) AS avg_sales
FROM sales_data
GROUP BY department
HAVING SUM(sales) > 1000
ORDER BY total_sales DESC;

Equivalent Pandas operations are implemented below using groupby and agg.
"""

import pandas as pd


def build_sample_data() -> pd.DataFrame:
    data = [
        {"department": "Electronics", "sales": 450, "order_id": 1},
        {"department": "Electronics", "sales": 300, "order_id": 2},
        {"department": "Electronics", "sales": 350, "order_id": 3},
        {"department": "Furniture", "sales": 200, "order_id": 4},
        {"department": "Furniture", "sales": 850, "order_id": 5},
        {"department": "Clothing", "sales": 120, "order_id": 6},
        {"department": "Clothing", "sales": 220, "order_id": 7},
        {"department": "Clothing", "sales": 175, "order_id": 8},
        {"department": "Outdoors", "sales": 75, "order_id": 9},
        {"department": "Outdoors", "sales": 50, "order_id": 10},
    ]
    return pd.DataFrame(data)
```

Sample SQL

```sql
SELECT department,
       SUM(sales) AS total_sales,
       COUNT(*) AS order_count,
       AVG(sales) AS avg_sales
FROM sales_data
GROUP BY department
HAVING SUM(sales) > 1000
ORDER BY total_sales DESC;
```

OUTPUT:

```
department sales order_id
Electronics 450 1
Electronics 300 2
Electronics 350 3
Furniture 200 4
Furniture 850 5
Clothing 120 6
Clothing 220 7
Clothing 175 8
Outdoors 75 9
Outdoors 50 10
```

```
department total_sales order_count avg
Electronics 1100 3 366.666667
Furniture 1050 2 525.0
```

Task 4 – Real-Time Application: Multi-Language Snippet Converter

Scenario: Students will select a practical real-world application requiring the same logic in two different programming languages.

Example:

• Converting a REST API implementation from Python (Flask) to Java (Spring Boot).

• Translating a data processing script from Python to C++ for performance optimization.

Instructions:

• Provide AI with source code in one programming language.

• Prompt AI to convert the code into another chosen language.

• Execute and test both versions to ensure identical functionality.

• Document differences observed in syntax, libraries, and execution behavior.

Expected Output:

Functionally equivalent and executable code snippets implemented in two different programming languages, along with documented observations.

```python
"""
Task 4 – Real-Time Application: Multi-Language Snippet Converter

Scenario: Converting a REST API implementation from Python (Flask) to Java (Spring Boot).

This file contains:
- Python Flask implementation (task4.py)
- Java Spring Boot implementation (Task4.java)
- Documentation of differences

Example REST API: A simple GET endpoint that returns a JSON message.
"""

# Python Flask Implementation (task4.py)
"""
from flask import Flask, jsonify

app = Flask(__name__)

@app.route('/hello', methods=['GET'])
def hello():
    return jsonify(message="Hello, World!")

if __name__ == '__main__':
    app.run(debug=True)
"""

# Java Spring Boot Implementation (Task4.java)
"""
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.RestController;

@SpringBootApplication
@RestController
public class Task4Application {

    public static void main(String[] args) {
```

Testing Results

- **Python**: Runs successfully (tested: starts server on `http://127.0.0.1:5000`, debug mode active).
- **Java**: Requires Spring Boot dependencies (Maven/Gradle setup); code snippet provided but not executable without full project.

Documented Differences

1. **Syntax**:
   - Python: Concise decorators (`@app.route`) for routing.
   - Java: Annotations (`@GetMapping`), class-based structure.
2. **Libraries/Frameworks**:
   - Python: Flask (lightweight, `pip install flask`).
   - Java: Spring Boot (requires Maven/Gradle, multiple JARs).
3. **Execution Behavior**:
   - Python: Interpreted, runs directly (`python task4.py`).
   - Java: Compiled, needs build tools (`mvn spring-boot:run`).
4. **Code Structure**:
   - Python: Functional, single file.
   - Java: OOP, main class + controller.
5. **JSON Handling**:

task4

Describe what to build

Agent Auto

Local Default Approvals

Ln 94, Col 1 Spaces: 4 UTF-8 CRLF { } Plain Text Go Live

task4.py > ...

```python
from flask import Flask, jsonify

app = Flask(__name__)

@app.route('/hello', methods=['GET'])
def hello():
    return jsonify(message="Hello, World!")

if __name__ == '__main__':
    app.run(debug=True)
```

OUTPUT:

```
* Serving Flask app 'task4'
* Debug mode: on
WARNING: This is a development server.
* Running on http://127.0.0.1:5000
Press CTRL+C to quit
* Restarting with stat
* Debugger is active!
* Debugger PIN: 137-801-274
```

API Response: `GET http://127.0.0.1:5000/hello`

returns:

```
{"message": "Hello, World!"}
```

Task -5: (Basic Function Translation (Python to C++)

Translate a simple Python function that checks whether a number is even or odd into C++ using AI assistance.

Instructions:

• Provide AI with a basic Python function that determines if a number is even or odd.

• Prompt AI to generate equivalent C++ code.

• Ensure correct syntax, input handling, and output formatting.

• Compile and run the C++ program to verify it produces the same result as the Python version.

• Test with at least three different input values.

Expected Output:

A simple and executable C++ program equivalent to the given Python function, correctly identifying whether a number is even or odd for all test cases.

Python:

Task5.py > ...

```python
"""
Task 5: Basic Function Translation (Python to C++)

Translate a simple Python function that checks whether a number is even or odd into C++.
"""

def is_even_or_odd(n):
    """Return 'even' if n is even, 'odd' otherwise."""
    if n % 2 == 0:
        return "even"
    else:
        return "odd"


def main():
    test_cases = [4, 7, 0, -2, -5]
    for num in test_cases:
        result = is_even_or_odd(num)
        print(f"{num} is {result}")


if __name__ == "__main__":
    main()
```

C++:

Task5.cpp

```cpp
#include <iostream>
#include <string>

/**
 * Task 5: Basic Function Translation (Python to C++)
 *
 * Equivalent C++ function to check if a number is even or odd.
 */

std::string is_even_or_odd(int n) {
    if (n % 2 == 0) {
        return "even";
    } else {
        return "odd";
    }
}

int main() {
    int test_cases[] = {4, 7, 0, -2, -5};
    int num_tests = sizeof(test_cases) / sizeof(test_cases[0]);

    for (int i = 0; i < num_tests; ++i) {
        int num = test_cases[i];
        std::string result = is_even_or_odd(num);
        std::cout << num << " is " << result << std::endl;
    }

    return 0;
}
```

OUTPUT:

```
4 is even
7 is odd
0 is even
-2 is even
-5 is odd
```