

```
In [1]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
```

```
In [2]: df = pd.read_csv(r"C:\Users\user\Downloads\C10_air\csvs_per_year\csvs_per_year\
df
```

Out[2]:

	date	BEN	CO	EBE	NMHC	NO	NO_2	O_3	PM10	PM25	SO_2	TCH	TOL	
0	2012-09-01 01:00:00	NaN	0.2	NaN	NaN	7.0	18.0	NaN	NaN	NaN	2.0	NaN	NaN	28
1	2012-09-01 01:00:00	0.3	0.3	0.7	NaN	3.0	18.0	55.0	10.0	9.0	1.0	NaN	2.4	28
2	2012-09-01 01:00:00	0.4	NaN	0.7	NaN	2.0	10.0	NaN	NaN	NaN	NaN	NaN	1.5	28
3	2012-09-01 01:00:00	NaN	0.2	NaN	NaN	1.0	6.0	50.0	NaN	NaN	NaN	NaN	NaN	28
4	2012-09-01 01:00:00	NaN	NaN	NaN	NaN	1.0	13.0	54.0	NaN	NaN	3.0	NaN	NaN	28
...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
210715	2012-03-01 00:00:00	NaN	0.6	NaN	NaN	37.0	84.0	14.0	NaN	NaN	NaN	NaN	NaN	28
210716	2012-03-01 00:00:00	NaN	0.4	NaN	NaN	5.0	76.0	NaN	17.0	NaN	7.0	NaN	NaN	28
210717	2012-03-01 00:00:00	NaN	NaN	NaN	0.34	3.0	41.0	24.0	NaN	NaN	NaN	1.34	NaN	28
210718	2012-03-01 00:00:00	NaN	NaN	NaN	NaN	2.0	44.0	36.0	NaN	NaN	NaN	NaN	NaN	28
210719	2012-03-01 00:00:00	NaN	NaN	NaN	NaN	2.0	56.0	40.0	18.0	NaN	NaN	NaN	NaN	28

210720 rows × 14 columns



```
In [3]: df1 = df.fillna(0)
df1
```

Out[3]:

	date	BEN	CO	EBE	NMHC	NO	NO_2	O_3	PM10	PM25	SO_2	TCH	TOL	s
0	2012-09-01 01:00:00	0.0	0.2	0.0	0.00	7.0	18.0	0.0	0.0	0.0	2.0	0.00	0.0	280
1	2012-09-01 01:00:00	0.3	0.3	0.7	0.00	3.0	18.0	55.0	10.0	9.0	1.0	0.00	2.4	280
2	2012-09-01 01:00:00	0.4	0.0	0.7	0.00	2.0	10.0	0.0	0.0	0.0	0.0	0.00	1.5	280
3	2012-09-01 01:00:00	0.0	0.2	0.0	0.00	1.0	6.0	50.0	0.0	0.0	0.0	0.00	0.0	280
4	2012-09-01 01:00:00	0.0	0.0	0.0	0.00	1.0	13.0	54.0	0.0	0.0	3.0	0.00	0.0	280
...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
210715	2012-03-01 00:00:00	0.0	0.6	0.0	0.00	37.0	84.0	14.0	0.0	0.0	0.0	0.00	0.0	280
210716	2012-03-01 00:00:00	0.0	0.4	0.0	0.00	5.0	76.0	0.0	17.0	0.0	7.0	0.00	0.0	280
210717	2012-03-01 00:00:00	0.0	0.0	0.0	0.34	3.0	41.0	24.0	0.0	0.0	0.0	1.34	0.0	280
210718	2012-03-01 00:00:00	0.0	0.0	0.0	0.00	2.0	44.0	36.0	0.0	0.0	0.0	0.00	0.0	280
210719	2012-03-01 00:00:00	0.0	0.0	0.0	0.00	2.0	56.0	40.0	18.0	0.0	0.0	0.00	0.0	280

210720 rows × 14 columns

```
In [4]: df1.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 210720 entries, 0 to 210719
Data columns (total 14 columns):
 #   Column      Non-Null Count  Dtype
---  -
 0   date        210720 non-null  object
 1   BEN         210720 non-null  float64
 2   CO          210720 non-null  float64
 3   EBE         210720 non-null  float64
 4   NMHC        210720 non-null  float64
 5   NO          210720 non-null  float64
 6   NO_2        210720 non-null  float64
 7   O_3         210720 non-null  float64
 8   PM10        210720 non-null  float64
 9   PM25        210720 non-null  float64
10   SO_2        210720 non-null  float64
11   TCH         210720 non-null  float64
12   TOL         210720 non-null  float64
13   station     210720 non-null  int64
dtypes: float64(12), int64(1), object(1)
memory usage: 22.5+ MB
```


```
In [5]: df1.columns
```

```
Out[5]: Index(['date', 'BEN', 'CO', 'EBE', 'NMHC', 'NO', 'NO_2', 'O_3', 'PM10', 'PM2
5',
              'SO_2', 'TCH', 'TOL', 'station'],
              dtype='object')
```

```
In [6]: df2 = df1[['BEN', 'CO', 'EBE', 'NMHC', 'NO_2', 'O_3',
                  'PM10', 'SO_2', 'TCH', 'TOL', 'station']]
```

```
In [7]: sns.pairplot(df2)
```

```
Out[7]: <seaborn.axisgrid.PairGrid at 0x1b39356c7c0>
```




```
In [8]: sns.distplot(df2['station'])
```

C:\ProgramData\Anaconda3\lib\site-packages\seaborn\distributions.py:2557: FutureWarning: `distplot` is a deprecated function and will be removed in a future version. Please adapt your code to use either `displot` (a figure-level function with similar flexibility) or `histplot` (an axes-level function for histograms).


```
warnings.warn(msg, FutureWarning)
```

```
Out[8]: <AxesSubplot:xlabel='station', ylabel='Density'>
```



```
In [9]: sns.heatmap(df2.corr())
```

```
Out[9]: <AxesSubplot:>
```



## Linear Regression

```
In [10]: x = df2[['BEN', 'CO', 'EBE', 'NMHC', 'NO_2', 'O_3',  
               'PM10', 'SO_2', 'TCH']]  
y = df2['TOL']
```

```
In [11]: from sklearn.model_selection import train_test_split  
x_train,x_test,y_train,y_test = train_test_split(x,y,test_size=0.30)
```

```
In [12]: from sklearn.linear_model import LinearRegression  
  
lr = LinearRegression()  
lr.fit(x_train,y_train)
```

Out[12]: LinearRegression()

```
In [13]: print(lr.intercept_)  
  
-0.14997184840010114
```


```
In [14]: coeff = pd.DataFrame(lr.coef_,x.columns,columns=['Co-efficient'])  
coeff
```

Out[14]:

Co-efficient	
<b>BEN</b>	2.519797
<b>CO</b>	-0.321403
<b>EBE</b>	1.122704
<b>NMHC</b>	-0.645097
<b>NO_2</b>	0.004734
<b>O_3</b>	-0.000088
<b>PM10</b>	0.005698
<b>SO_2</b>	0.023465
<b>TCH</b>	-0.071214

```
In [15]: prediction = lr.predict(x_test)
plt.scatter(y_test, prediction)
```

Out[15]: <matplotlib.collections.PathCollection at 0x1b3a31502b0>



```
In [16]: print(lr.score(x_test,y_test))
```

0.8096303763473245

```
In [17]: lr.score(x_train,y_train)
```

Out[17]: 0.8038041251750647

## Ridge and Lasso

```
In [18]: from sklearn.linear_model import Ridge,Lasso
```

```
In [19]: rr = Ridge(alpha=10)
rr.fit(x_train,y_train)
rr.score(x_train,y_train)
```

Out[19]: 0.8038037485901953

```
In [20]: rr.score(x_test,y_test)
```

Out[20]: 0.8096250636845652

## Lasso Regression

```
In [21]: ls = Lasso(alpha=10)
ls.fit(x_train,y_train)
ls.score(x_train,y_train)
```

Out[21]: 0.05748860555150703

```
In [22]: ls.score(x_test,y_test)
```

```
Out[22]: 0.06126149795278113
```

## ElasticNET regression

```
In [23]: from sklearn.linear_model import ElasticNet  
es = ElasticNet()  
es.fit(x_train,y_train)
```

```
Out[23]: ElasticNet()
```

```
In [24]: print(es.coef_)
```

```
[ 5.12759826e-01 -0.00000000e+00  3.81971997e-01  0.00000000e+00  
 1.51187513e-02 -3.34048862e-04  1.31388355e-02  2.23265435e-02  
 0.00000000e+00]
```

```
In [25]: print(es.intercept_)
```

```
-0.12831485667759546
```

```
In [26]: print(es.score(x_test,y_test))
```

```
0.41574702273645137
```

```
In [27]: print(es.score(x_train,y_train))
```

```
0.40987952955773743
```

## LogisticRegression

```
In [28]: from sklearn.linear_model import LogisticRegression
```

```
In [29]: feature_matrix = df2.iloc[:,0:15]  
target_vector = df2.iloc[:,-1]
```

```
In [30]: feature_matrix.shape
```

```
Out[30]: (210720, 11)
```

```
In [31]: from sklearn.preprocessing import StandardScaler
```

```
In [32]: fs = StandardScaler().fit_transform(feature_matrix)
```



```
In [33]: logs = LogisticRegression()
logs.fit(fs,target_vector)
```

C:\ProgramData\Anaconda3\lib\site-packages\sklearn\linear\_model\\_logistic.py: 763: ConvergenceWarning: lbfgs failed to converge (status=1):  
STOP: TOTAL NO. of ITERATIONS REACHED LIMIT.

Increase the number of iterations (max\_iter) or scale the data as shown in:  
<https://scikit-learn.org/stable/modules/preprocessing.html> (<https://scikit-learn.org/stable/modules/preprocessing.html>)  
Please also refer to the documentation for alternative solver options:  
[https://scikit-learn.org/stable/modules/linear\\_model.html#logistic-regression](https://scikit-learn.org/stable/modules/linear_model.html#logistic-regression) ([https://scikit-learn.org/stable/modules/linear\\_model.html#logistic-regression](https://scikit-learn.org/stable/modules/linear_model.html#logistic-regression))  
n\_iter\_i = \_check\_optimize\_result(

```
Out[33]: LogisticRegression()
```

```
In [34]: observation = [[1.4,1.5,1.6,2.7,2.3,3.3,2.3,4.1,2.3,4.2,1.2]]
prediction = logs.predict(observation)
```

```
In [35]: print(prediction)

[28079059]
```

```
In [36]: logs.classes_
```

```
Out[36]: array([28079004, 28079008, 28079011, 28079016, 28079017, 28079018,
                28079024, 28079027, 28079035, 28079036, 28079038, 28079039,
                28079040, 28079047, 28079048, 28079049, 28079050, 28079054,
                28079055, 28079056, 28079057, 28079058, 28079059, 28079060],
                dtype=int64)
```

```
In [37]: from sklearn.model_selection import train_test_split

x_train,x_test,y_train,y_test = train_test_split(feature_matrix,target_vector,t
```

```
In [38]: print(logs.score(x_test,y_test))

0.04120792204505189
```

```
In [39]: print(logs.score(x_train,y_train))

0.04189038941316846
```

## Conclusion

linear regression is bestfit model

linear regression is best fit model for dataset madrid\_2001. The score of x\_train,y\_train is 0.8038041251750647 and x\_test and y\_test score is 0.8096303763473245.

In [ ]: