

CRUD Operations

Suresh L. Paul

2026-03-31

CREATE

- Single row

```
INSERT INTO names ( student_id , first_name , last_name ) VALUES
( 123456 , 'Tom' , 'Hardy' ) ;
```

- Multiple rows

```
INSERT INTO names ( student_id , first_name , last_name ) VALUES
( 234567 , 'Tom' , 'Cruise' ) ,
( 345678 , 'Tom' , 'Brady' ) ,
( 456789 , 'Tom' , 'Holland' ) ;
```

- From another table

```
INSERT INTO names_backup SELECT * FROM names ;
```

- From a csv file

```
-- Set mode to csv
.mode csv

-- import
.import /path/to/file.csv names
```

READ

- All

```
SELECT * FROM names ;
```

- Specific columns only

```
SELECT first_name , last_name FROM names ;
```

- Limited rows

```
SELECT * FROM names LIMIT 5 ;
```

- Produce Count

```
SELECT COUNT(*) FROM names ;
```

UPDATE

- Update specific rows

```
UPDATE names SET first_name = 'Timothy' WHERE student_id = 456789 ;
```

- Update multiple columns

```
UPDATE names SET first_name = 'Timmy' , last_name = 'Hollow' WHERE student_id = 456789 ;
```

- Update all rows – if there is a column named *enrollment_status*

```
UPDATE names SET enrollment_status = 'active' ;
```

otherwise , create a new variable and then update it!

```
-- 1. Add the column
ALTER TABLE names ADD COLUMN enrollment_status TEXT ;

-- 2. Then set the value
UPDATE names SET enrollment_status = 'active' ;
```

(or)

do it one go ...

```
ALTER TABLE names ADD COLUMN enrollment_status TEXT DEFAULT 'active' ;
```

DELETE

- Delete specific rows

```
-- delete Tom Hardy entry
DELETE FROM names WHERE last_name = 'Hardy' ;
```

- Delete all rows (use with caution)

```
DELETE FROM names_backup;
```

- Drop entire table

```
DROP TABLE names_backup;
```