

Conditionals using WHERE statement

Suresh L. Paul

2026-03-31

Logical Operators

- AND: both conditions must be true

```
WHERE
  student_id > 200000 AND
  first_name = 'Michael' ;
```

- OR: at least one condition must be true

```
WHERE
  first_name = 'Lauren' OR
  first_name = 'Michael' ;
```

Comparison Operators

- Equals / Not equals

```
WHERE student_id = 563701
WHERE group_id <> 5
```

- Greater than / Less than

```
WHERE student_id > 500000
WHERE student_id < 200000
WHERE group_id >= 3
WHERE group_id <= 2
```

Range and Lists

- BETWEEN: within a range (inclusive)

```
WHERE group_id BETWEEN 1 AND 3
```

- IN: matches any value in a list

```
WHERE first_name IN ('Jim', 'James', 'Jacob', 'Joe', 'John')
```

- NOT: reverses a condition

```
WHERE NOT group_id = 1 ;
```

- NOT IN: excludes values in a list

```
WHERE group_id NOT IN ( 1, 2, 3 )
```

(or)

```
WHERE NOT group_id IN ( 1, 2, 3 )
```

NULL Checks

- IS NULL

```
WHERE email_address IS NULL
```

- IS NOT NULL

```
WHERE email_address IS NOT NULL
```

Pattern Matching

- LIKE: pattern matching

```
WHERE first_name LIKE 'J%'      -- starts with J
WHERE last_name LIKE 'J____'    -- J followed by exactly 4 characters
```

- GLOB: case-sensitive pattern matching

```
WHERE last_name GLOB 'J*'       -- starts with J (case-sensitive)
```