

HTML -5 Test

NAME: SARJITH. S

Batch : F.E. -16th batch

Date : 29.08.26

1) HTML stands for hypertext Markup language.

H - hyper → Connection.

T - Text → data or information.

M → Markup → It does not use memory but uses built-in elements called as 'tags'.

L - Language → Language used for communication between browser and user.

HTML is a markup language used to connect text, images and links into a single webpage and connects these webpages to form a website for the browser in its understandable way. And structures them for easy understanding.

2) HTML is a Markup language:

It is called as markup language because unlike programming languages, HTML does not contain memory for compilation. The browser has built-in tags which will be used to structure and design the behaviour of the content.

only browser will store the data, not HTML.

3) HTML tag vs HTML element:

Tags :

tags are predefined keywords provided to assign a behaviour to the content. They are enclosed with angular brackets. Ex: `<html>`, `<head>`, `<body>`, etc.

Elements:

Full fledged tags are called as elements. The process of opening the tag, entering element contents and closing the tag is called as elements.

Ex: `<html> <head> </head> <body> content </body> </html>`

4. !DOCTYPE html tag:

The tag `<!DOCTYPE html>` is a declaration tag used as a declaration for the browser to show that the html file uses HTML 5 (latest version). If not used, the browser will start the older html where the new tools will not be executed.

5. Basic Structure of HTML Document:

A basic html tag starts with `<html>` tag and opens a `<head>` tag to provide a title and its properties, then the `<body>` tag is used [after closing `</head>` tag] to provide all the contents.

<html>: It is the universal tag used at the top of the file and at the very end of the file (**</html>**). Every operations should be done inside this tag so that, these contents will be classified as the markup language.

<head>: Here, the data about the html document will be declared along with its title (**<title>** tag).

<body>: Every contents, lists, tables, forms will be created inside this tag which will be visible to the user on the website. links and images are also added in this tag.
</body>
</html>

6) HTML Attributes:

Attributes are special functions used inside the tags to create additional functionality to the tags. Also used to implement Programming languages inside the HTML file. It consists of two types. Global attributes: used on all the tags, ex: id, class, style, and Local attributes: can only use on specified attribute tags like **<a>**, ****, etc. Ex: href, src, alt.

7) Src (vs) href:

Src : It is used inside image tag (`<img>`) to provide the directory of the image in the folder.

href : It is used inside `<a>` tag to provide URL or directory to another file or webpages.

8) alt attribute:

alt attribute is used inside `<img>` tag just in case, if the image does not load, the text provided in the alt attribute will be visible on the webpage.

Ex: ``

9) Block level elements:

When block level elements are used, the content will cover the entire width of the webpage. This means that block level tags cannot be used inside another block level tag.

Ex: title, address, main, header, etc.,

Inline elements:

They are called as helper tags or optional tags that can be used even inside the block level tags. It only covers the width of the content. Most of the inline tags are self-closing tags.

Ex: `span`, `strong`, `i`, `img`, etc.,

10) Semantic HTML:

HTML webpages that are meaningful and understandable to both users and browsers are called as Semantic HTML. The HTML code contains tags that break the body part to number of chunks which will be easily understood by the user and the browser.

Semantic tags:

Meaningful tags that are used to arrange the web page in an understandable manner to both browser and developer. Ex: a, header, footer, section, main, etc..

Non-Semantic tags:

These tags do not have any meaning, but it can be used for wrapping or grouping. Ex: 'div' and 'span'.

11) div (vs) span:

div: div tag is a non-semantic tag used for wrapping and grouping at block level. It is a block level tag that takes the whole width.

Span:

It is also a non-semantic tag but it is an inline tag. It only groups a small content.

12) HTML List:

ul tag : ul tag is used to create list in bullet points like dots.

- html
- head
- body

ol tag : It is used to create list in numbered points. used for steps definition.

1. open VS code
2. create a file
3. save the file

dl tag : It is used to create list along with its definition or explanation.

ul
unordered list

ol
ordered list

13. Explain the tags:

<table> : main tag used to create a table

<tr> : It creates and adds rows to the table.

<th> : It provides information in block letters, usually used at the beginning to easily understand the classification.

<td> : adds information to the rows in normal text

thead : creates heading section for the table.
This is the place where `<th>` tag is used to display classification in bold colour.

tbody : data section where `<td>` tags are used to add normal data.

tfoot : values like total, average and other will be displayed.

14) `<meta charset="UTF-8">` :

meta - used to provide data about the website

charset - character set that shows the type of characters used.

UTF - Unicode Transformation format.

It allows website to represent different kinds of text from different systems.

UTF-8 → the 8 represents 8 bits. all the english alphabets, special characters and emojis will be 8 bit under.

the value will ~~be~~ can be increased to 16, 32, or even 64, but the execution time also increases.

15. Open graph:

It provides a short information to the browser such that these data can be used by the search engine for filtering.

Here we can decide a title, description, etc. that can be viewed by the browser.

The issue is that, these `OG` tags are executed only if the webpage is deployed on the internet.

`og:title`: one of the main use the `og` tags have is that how the webpage links will be viewed while sharing in the social media.

`og:title`: title of the webpage during sharing.

`og:type`: shows the type of link, ex: webpage or videos.

`og:image`: It provides thumbnails to the links that pop up when the link is in the draft.

`og:url`: shows other web site's url ~~link~~ link.

`og:description`: a single line summary about the webpage.