Process Name Standard parameters Fixture No.	S	ANDHAR	Fixture Verification check sheet	heet Mag/FVCS/01 REV 00
Process Name Standard parameters Condition of Clamps Condition of Clamps Condition of Locating Blocks Should firmly hold the workpiece. Should not Condition of Locating Blocks Should be free from wear out, Check the flatness Condition of Locating Pins of Check dia and pin dia should not be more than 0.5mm Locating positions Should be free from uneven surface. High Part resting surface Chieck dia and pin dia should not be more than 0.5mm Coct Bolt and screw Tightness Should be free from uneven surface. High Part resting surface Chied part resting blocks Free from loose fitment Free from loose fitment Free from loose fitment Free from loose fitment Chied part resting blocks Free from loose fitment				
Frocess Name Standard parameters Frocess Name Standard parameters Condition of Clamps Condition of Clamps Condition of Clamps Condition of Locating Blocks Should firmly hold the workpiece.Should not Condition of Locating Blocks Should be free from wear out. Check the flatness Condition of Locating Blocks Should be as per drawing Locating positions Should be as per drawing Fart resting surface Should be free from uneven surface.High Part resting surface Child part resting blocks Free from loose fitment Frixture to be levelled check using sprit level Frixture lookers should have No. Description and added in Frixture should have No. OK/Contionally accepted / Rejected OK/Contionally				Crintion:
Ition of Clamps Should firmly hold the workpiece, Should not Create marks on the surface Should be free from wear out, Check the flatness Should be free from wear out, Check the flatness Should be free from wear out, Check the flatness OC The conting Pins or Check dia and record, Clearance between Hole Gland pin dia should not be more than 0.5mm OC Should be free from uneven surface, High points (Projections), sticking of foreign particles. Should be uniform, the differnace Brown Tightness Free from loose fitment Height should be uniform, the differnace Coc Tresting of child parts without taper. Fixure to be levelled, check using sprit level ace levelling Trubo. Coc Coc Fixure to be levelled, check using sprit level Trubo. Brown Conveneint Fixure to be levelled, check using sprit level Fixure should have No, Description and added in Coc Ergonics, Basyness for part foration. Fixure should have No, Description and added in Coc Ergonics, Basyness for part Fixure should have No, Description and added in The Fixure Ist Fixure should have No, Description and added in The Fixure Ist Fixure should have No, Description and added in The Fixure Ist Fixure should have No, Description and added in The Fixure Ist Fixure should have No, Description and added in The Fixure Ist Fixure should have No, Description and added in The Fixure Ist Fixure should have No, Description and added in The Fixure Ist Fixure should have No, Description and added in The Fixure Ist Fixure Shalus, Remarks OK/Contionally accepted / Rejected Due: 27 [3] \cdot 23	SI No.		Standard parameters	Voly 00
Itition of Clamps Should firmly hold the workpiece, Should not Create marks on the surface Blocks Should be free from wear out, Check the flatness of dia and plot dia and record, Clearance between Hole dia ting positions Check dia and profit as hould not be more than 0.5 mm ting positions Should be as per drawing ting positions Should be free from uneven surface, High points(Projections), sticking of foreign particles. Should be tree from uneven surface, High points(Projections), sticking of foreign particles. The from loose fitment Apart resting blocks Bree from loose fitment Apart resting blocks Free from loose fitment Beight should be uniform, the differnace Height should be uniform, the differnace Free from loose fitment Coc Britter to be levelled check using sprit level The and Grouting/Levelling of fixture in its Broomies. Easyness for part Grozelion Fricture should have No. Description and added in The Fixture should have No. Description and added in The Part made out of the Fixture to be checked and The Part made out of the Fixture to be detecked and The part resport to be attached The part resport to be attached The part resport to be attached The part made out of the Fixture to be detecked and The part made out of the Fixture to be detecked and The part made out of the Fixture to be detecked and The part made out of the Fixture to be detecked and The part made out of the Fixture to be detecked and The part made out of the Fixture to be detecked and The part made out of the Fixture to be detecked and The part made out of the Fixture to be detecked and The part made out of the Fixture to be detecked and The part made out of the Fixture to be detecked and The part made out of the Fixture to be detecked and The part made out of the Fixture to be detecked and The part made out of the Fixture to be detecked and The part made out of the Fixture to be detecked and The part made out of the Fixture to be detecked and The part made out of the Fixture to be detecked and The part made out of the Fixture to be d				Frank PH A
Itition of Clamps Should firmly hold the workpiece, Should not feeter marks on the surface should not Locating Blocks Should be surface and principle of the flatness of dia and principle of dia and screw Tightness Free from loose fitment Height should be uniform, the differnace of the dia parts without taper. Fixture to blevelled, check using sprit level Trube and Grouting/Levelling of fixture in its location. Fixture should have No.Description and added in of continuation of the Fixture be diatached of the Fixture to be checked and of chicked and response of the dia				Volvo F
Itition of Locating Blocks Itition of Block B	1	Condition of Clamps	Should firmly hold the workpiece,Should not create marks on the surface	OIC
ting positions Check dia and record.Clearance between Hole dia and pin dia should not be more than 0.5mm ting positions Should be as per drawing Cresting surface points(Projections), sticking of foreign particles. Should be free from uneven surface, High Colc. Should be free from uneven surface, High Colc. Should be free from uneven surface, High Colc. Height should be uniform, the differnace Colc. Fixture to be levelling of fixture in its Colc. Fixture should have No, Description and added in Colc. Fixture should have No, Description and added	2	Condition of Locating Blocks	Should be free from wear out, Check the flatness using steel rule	ok
ting positions Should be as per drawing resting surface Should be free from uneven surface, High points(Projections), sticking of foreign particles. The from loose fitment Height should be uniform, the differnace between block should not exceed 0.2 mm, Proper resting of child parts without taper. Fixture to be levelled, check using sprit level resting of child parts without taper. Fixture to be levelled, check using sprit level Trube and Grouting/Levelling of fixture in its location. Ergonics, Easyness for part fitment, removal, rotation etc. Ergonics, Easyness for part fitment, removal, rotation etc. Fixture should have No, Description and added in the Fixture list report to be attached OK/Contionally accepted / Rejected	ю	Condition of Locating Pins or Hole dia	Check dia and record,Clearance between Hole dia and pin dia should not be more than 0.5mm	D)(C
Inspection report Should be free from uneven surface, High points (Projections), sticking of foreign particles. The from loose fitment Height should be uniform, the differnace between block should not exceed 0.2mm, Proper resting of child parts without taper. Fixture to be levelled, check using sprit level fixture to be levelled, check using sprit level fixture and Grouting/Levelling of fixture in its location. Ergonics, Easyness for part fitment, removal, rotation etc. Fixture should have No, Description and added in colc fixture list framed e out of the Fixture to be checked and report to be attached report to be attached report to be attached from the fixture list from a discontinually accepted / Rejected of CK OK/Contionally accepted / Rejected of CK Date: 31 2 1.3	4	Locating positions		0 K
and screw Tightness Free from loose fitment Height should be uniform, the differnace between block should not exceed 0.2mm, Proper resting of child parts without taper. Fixure to be levelled, check using sprit level Trube and Grouting/Levelling of fixture in its location. Ergomics, Easyness for part fitment, removal, rotation etc. Fixure should have No, Description and added in the Fixture list Part made out of the Fixture to be checked and Inspection report The Bart made out of the Fixture to be checked and Tre Status / Remarks OK/Contionally accepted / Rejected	Ŋ	Part resting surface	Should be free from uneven surface, High points (Projections), sticking of foreign particles.	710
Height should be uniform,the differnace between block should not exceed 0.2mm, Proper resting blocks resting of child parts without taper. Fixture to be levelled, check using sprit level / Tube and Grouting/Levelling of fixture in its location. Fixture should have No, Description and added in fitment, removal, rotation etc. Fixture should have No, Description and added in the Fixture list Part made out of the Fixture to be checked and report to be attached report to be attached report to be attached / Poly (Contionally accepted / Rejected /	9	Bolt and screw Tightness	Free from loose fitment	06
ace levelling Tube and Grouting/Levelling of fixture in its OK Tube and Grouting/Levelling of fixture in its OK Incation.	7	Child part resting blocks	Height should be uniform,the differnace between block should not exceed 0.2mm,Proper resting of child parts without taper.	0K
Ergomics, Easyness for part fitment, removal, rotation etc. OC Ire Identification Fixture should have No, Description and added in the Fixture list OC Inspection report Part made out of the Fixture to be checked and report to be attached OC Inc Status / Remarks OK/Contionally accepted / Rejected CC OR/Contionally accepted / Rejected CC Date: 21/3/23 Date: 21/3/23	8	Surface levelling	Fixture to be levelled, check using sprit level /Tube and Grouting/Levelling of fixture in its location.	OK
re Identification the Fixture should have No,Description and added in the Fixture list Part made out of the Fixture to be checked and report to be attached report to be attached OK/Contionally accepted /Rejected OK/Contionally accepted /Rejected OK/Configure Status /Remarks OK/Configure Neighbor Status OK/Configure Neighbor Stat	6	Operator Conveneint	Ergomics,Easyness for part fitment,removal,rotation etc.	
Inspection report report to be attached repo	10	Fixture Identification	Fixture should have No,Description and added in the Fixture list	OIC
re Status / Remarks OK/Contionally accepted / Rejected OK/Contionally accepted / Rejected OK/Contionally accepted / Rejected OK/Contionally accepted / Rejected	11	Part Inspection report	Part made out of the Fixture to be checked and report to be attached	Olc
Date: 21 (2) 12		Fixture Status /Remarks	OK/Contionally accepted /Rejected	CK ,
Date: 21/3/2	hecke	id By O		21/3/2
	/erifie	d By		7 18 12
		,		

FK	2A/03		A VIIJAUO	Aag Er Aussur				T	S	AN	DHAF
						The same of the sa					
Dark	Number - Fren	14 WA	INSPECTION REPORT						Sample Qty : (no		
Part Number: Forme TH WA Port Name: LAD 20466			Engg. Change Level:						Date : 2/3/23		
	and the same against the same of the same		PROD. PROTO OTHERS								
Reas	and for Submission									-	
	Dimensional	Material	Appeara	nce	Engineer Specifical Testing	tion _	Others				
St.	Characteristic	Specification	Instrument			Observ	ation			rmance	Remark
No.			Used	1 (00	2	3	4	5	OK	Not OK	-
2	Din	1.583 -	MIT	288					-		
3	(D) (1)	1-904	MIT	109				,	_	-	
4	0/11	176 T	DVC.	76.2					-		
5	Dia	184	DYC	124.3		-					
-	Dim	598	M.T	596.0			-		-	-	
6	Dio	588.5	DVC	032.18					-	1	
8	man a third and many and the said	the sale of the sa	Mit	589	,	-	1. 11		-	-	
9	Dion :	434.5	MIT	351					-	1	
10	Dia Dia	0,19 TI	DUC	242.15		-	-	-		1	.94)
11	Dia	118:t1	Duc	118.2			1	-		1	
12	Dhi	28071	DVC	080.2			,		-		
13	Dia	810	MIT	810			-	<u> </u>	-		
14	D'M	4351	m.T.	135	-	-	1		-		
15	Din	35571	M.T	355			1		2	1	
16		23331		25.2		<u> </u>			1	1	•
17	A COLUMN TO SERVICE STATE OF THE SERVICE STATE STATE OF THE SERVICE STATE OF THE SERVICE STATE STATE STATE OF THE SERVICE STATE S	-					1	 	1	1	
18						1	1 2 7		1	1 - 7	
19					٠.,	1		2			Maria 1 1
20				25° 41	1				,		
21	ALLEGE AVERAGE AND ALLEGE AND ALL		1		46.0			11.			
22	To be a superior to the control of t	As a substitution of the state		1				7.1			
23				100			100				
24						7				, ,	
25							,				17. 1
26	COLUMN TO STATE OF THE STATE OF					1					
.27								. 5		,	
28	12-14-NV Taranto Control Taran						4.7				
29					£						1
30					1			* I			
31											
32						14.		7	14		1
33							1 3	.1			
34							استراض			• ,	
35	(0)									1	
Ins	pected By :					Appro	ved By	. k	~		

Approved By:

