
	ANDĤAR	Fixture Verification check s	sheet Mag/Fvcs/01 REV 00
Sl No.	Process Name	Standard parameters	Date: 22/04/8023  Fixture No: MAG THCM FCMD F-01  Fixture Description: FLONT DIA HO PIPE  Customer: THCM  Part Name: Ex 200 Cabin  Location: THCM Fabrication
1	Condition of Clamps	Should firmly hold the workpiece, Should not create marks on the surface	found ok
2	Condition of Locating Blocks	Should be free from wear out, Check the flatness using steel rule	found ou
3	Condition of Locating Pins or Hole dia	Check dia and record, Clearance between Hole dia and pin dia should not be more than 0.5mm	found ok
4	Locating positions	Should be as per drawing	
5	Part resting surface	Should be free from uneven surface, High points (Projections), sticking of foreign particles.	found ox
6	Bolt and screw Tightness	Free from loose fitment	found ox
7	Child part resting blocks	Height should be uniform, the differnace between block should not exceed 0.2mm, Proper resting of child parts without taper.	Checked and found ole
8	Surface levelling	Fixture to be levelled, check using sprit level /Tube and Grouting/Levelling of fixture in its location.	verified and found ok
9	Operator Conveneint	Ergomics,Easyness for part fitment,removal,rotation etc.	verified and found OK
10	Fixture Identification	Fixture should have No,Description and added in the Fixture list	1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
11	Part Inspection report	Part made out of the Fixture to be checked and report to be attached	port Chuleid and attached
	Fixture Status /Remarks	OK/Contionally accepted /Rejected	OK
Check	ed By Count		Date: 99 /04/9073
/erifie	ed By		Date: 20104 12023
	-0-		



-			DUALITY			PORT			(	<u> </u>	DHA
Dart	Number: TD	na sal	me: TATA HITAHCI					Sample Qty. : 5			
Part Number: TD09894  Part Name: Front Tube			Engg. Change Level:						Date: 10/04/2023		
_	on for Submission	1	PROD.	PROTO	ОТІ	ERS	77.4			709	120.05
Reas			100		and the second	17.77	Others			-	
	Dimensional Mate		al Appearance		Testing						
SI. No.	Characteristic	Specification	Instrument Used	- X	2	Observa 3	tion 4	5	OK	Not OK	Rem
1	Dia .	d12 -	DUC	12.4	12.5	123	12.4	1205	W	7	
2	O'm	5041.6	MI	48	49	H8	48	49	سا	<u>'</u> '	
3	Thick	4 ±1.6	Dre	3.5	3.6	3.0	3.	3.2	V		y 12 K
Ą	Dim	50 ± 1.6	MT	48	49	Aq	48	49	V	17 10	
5	Dim .	817.6 土4.0	MT	825	826	825	826	825	1.2	V.	40.7
6	RH Dim	20+1.6	DVC	19.5	19.2	18.9	19.0	19.5	1		* v
7	Ltt nim	20.±1.6	DVC	21 00	2000	20,5	208	21	L		1.8.01
8							- 3		1		
9				7.5	لسبنا			19-5 S	0		100
10										100	75
11		i		-					-	-	
13	<u> </u>			11. [2]			4.5.44		1		1 7 7
14									+-	1-	
15		10	1 11				4-1		-		
16				1				1000	8 2 2		
17							7	1 43	3 2 3 5		4.
18			11.11	77. 17. 77	7 .	1775	1000	1 2	214	15.55	1
19	1. 2. 1.			m edial de	San L	100				1925	
20				la l	2.5						
21					4.17	F".4.3-1		farte.	2		14.50
22				- i.				ti di			
23.			.3	/ 5,	3.3.3	i ta		27.9		10.00	
24					1 17	1.5	0		7	1 10	
25					370			a de	4	1 4 4	5.0
26							100	1 2		2	1
27											
28								1	7.5		1
29				10	i i		, š	1			
30			-		1	1	he"	1	1		1
31	√ ±				1		-				
32			Liferina	1. 1. 1		15.	1				N- PV
33:					1-1-		7 x		1	-	-
34 35	CONTRACTOR		\$0' . I'-	-	-		1000				17, 142,