

Catch every strip defect where it is born, not where it is shipped

AI surface inspection that finds, grades and routes every stainless strip defect to the process that caused it.

90%

of defects caught on real mill strip it had never seen

4.7%

of clean strip wrongly flagged, fewer than 1 in 20


~₹6.7 cr

a year at stake per line, at a 1% downgrade rate

7 months

to shadow mode on one line, go / no-go at month 7

REAL OUTPUT FROM OUR SYSTEM, ON STEEL IMAGES IT HAD NEVER SEEN



TEAM Futuristic | Krishna Kanta Mondal · Prathmesh Walimbe | IIT Bombay



TRY THE LIVE DEMO

surface-vision.github.io

Runs in your browser. Nothing leaves the page.

A defect born at the caster is paid for at every later stage, but today it is found only at the end

Where stainless surface defects are born, and where they are seen today

VALUE ADDED KEEPS RISING →



Melt & cast

SMS

Inclusions, slivers

NOT SEEN



Hot rolling

HSM

Scale, pits, edge cracks

NOT SEEN



Anneal & pickle

HRAP

Pickling patches

SPOT CHECK



Cold rolling

CRM

Scratches, roll marks

SPOT CHECK



Final anneal / BA

CRAP / BA

Stains, BA marks

SAMPLED



Finish & despatch

Slit, cut

Found here, or by the customer

CLAIMS

Why it hurts more on stainless



300 m/min

too fast for the eye to see



₹126k-165k

of nickel in a tonne of 304




No repair

2B/BA damage can't be polished out

Why now

India demand, Mt **+84% in 5 yrs**



FY21 FY22 FY23 FY24 FY25 FY30F



1.73 Mt imports

FY25; anti-dumping probe on cold-rolled 300/400, Sep 2025



IS 6911 mandatory

BIS certification for sheet and strip, since Aug 2024



2.67 MTPA

JSL cold rolling by FY28, up from 2.05

Cost of quality: where AI moves the money

← spend moves from failure to prevention

Prevention

defect sent to its owner in minutes

Appraisal

100% of the surface, every coil

Internal failure

caught before more value is added

External failure

fewer escapes to customers


Poor quality costs ~15% of sales in manufacturing (IISE).

Sources: AMETEK/Ternium; ASSDA; IISE; ASTM A240; LME nickel USD 16,402/t at INR 95.8 (22 Sep 2026); ISSDA; DGTR (Sep 2025); BIS QCO 2024. Photos: Wikimedia Commons (notes).


The problem is not that defects exist. They are found late, by sampling, and nobody is told which process caused them.

On stainless the surface is the product, so every defect type must reach the process that caused it


Six defect families, each traced to the process that caused it (real output from our system)




Born: **Caster**
Owner: **SMS**
Fix: Tundish level, mould flux




Born: **Reheat, hot rolling**
Owner: **HSM**
Fix: Reheat and coiling temperature




Born: **Hot rolling**
Owner: **HSM**
Fix: Decalcer pressure, nozzles



Born: **Reheat, pickling**
Owner: **HSM / pickling**
Fix: Furnace atmosphere, over-pickling



Born: **Anneal & pickle**
Owner: **Pickling line**
Fix: Acid strength, line speed



Born: **Cold rolling, handling**
Owner: **CRM / logistics**
Fix: Guides, rolls, coil handling

Stainless-only types to add with JSL data:

Roping

Ridging (ferritic 430)

Orange peel

Anneal colour

BA stains

Lamination

Precedent: who already does this, and what we copy




Outokumpu AI inspection live since 2024

Copy: offline, multi-site



Tata Steel video analytics, cold-rolled strip

Copy: in-house team owns it



Parsytec bright + dark-field light on stainless

Copy: optics spec

Grade-by-defect risk: which defects to train for first

Grade	Slivers	Scale	Scratches	Edge cracks	Ridging
200 series (Cr-Mn)	M	M	H	M	L
300 series (304, 316)	H	M	H	L	L
400 series (409, 430)	H	M	M	M	H
Duplex (2205)	M	H	M	H	L




Images: our system on held-out frames. Sources: Nortal/Outokumpu 2024; Tata Steel; Parsytec; Leão 2021; Steel in Translation. Photos: Commons (notes). Owners: team hypothesis. Grade risks: team hypothesis.


Classify, don't just alarm: a typed defect becomes a work order for a named owner. The pilot belongs on 300-series cold-rolled strip.

Four design choices that make the system work on a real line

1 Alarms you can act on



of defects caught
258 of 288 defective mill
images



of clean strip flagged
14 of 300 clean mill
images

So we: prove it on JSL's own clean and defective strip before any alarm is trusted.

2 One verdict per coil, not a stream of alarms




All defects on a coil roll up into one decision, using limits set per grade and finish. **Example: a light scratch can pass on 2B for tubes but downgrade BA for appliance panels.**

So we: agree accept, downgrade and hold limits per grade and finish with JSL Quality in P0.

3 Image detail sets what is seen, and the hardware bill

0.2 mm per pixel



~18 processors

sees defects from ~0.5 mm

0.5 mm per pixel



~3 processors

sees defects from ~1.3 mm

1.28 mm per pixel



1 processor

fine scratches vanish (~3 mm)

1.28 m strip at 250 m/min. Processors scale with pixels; a defect needs 2-3 pixels.

So we: fix the image resolution with JSL first, then size the hardware.

4 Operators act only on alarms they can trust



Every alarm shows its evidence

photo, defect type, severity and position on the coil



Four weeks of shadow mode first

it only advises; automatic holds start at ≥ 90% operator agreement



Every override is reviewed

weekly with the line and quality; the system improves from it


So we: earn trust on the shift floor before the system is allowed to act.

Results measured by us on public steel data the system had never seen. Hardware sizing derived from our line-speed benchmark.


Success is decided on the line, not in the lab: JSL's own strip, the right image detail, coil-level rules and operator trust.

Detect on the strip, decide at the coil, route to the owner, and learn from every correction

How it works: six stages from camera to corrective action



Running today



Upload a strip image, get:

- box on the defect
- defect type
- confidence
- severity score

16 samples built in, including clean mill strip. Or drop your own photo.

surface-vision.github.io runs in the browser

What JSL gets that a standard system does not



Alarms you can act on

4.7% false alarms



Root-cause routing

a work order per alarm



One verdict per coil

accept · downgrade · hold



JSL owns the system

no vendor lock-in

Build vs buy

	Cost per line	Proven at speed	Tuned to JSL grades	JSL owns the system
Commercial proven; the vendor owns it	●	●	●	●
Fully in-house JSL owns it; slow to prove	●	●	●	●
Hybrid (recommended) vendor cameras, JSL software	●	●	●	●

● strong
● partial
● weak


Output: hybrid is never weak.

BUILT = working in our prototype today, live at surface-vision.github.io.

Buy proven cameras, own the software: vendor-grade capture, tuned to JSL's grades and wired to JSL's process owners.

It already works on public steel data; the pilot's job is to prove it on JSL's own strip

Tested on three public steel datasets



NEU-DET

1,800 images, 6 types


University benchmark, hot-rolled strip



Severstal

12,568 real mill frames

Production strip from a steel mill




GC10-DET

2,294 frames, 10 types

Full-width line-scan camera frames (roll marks shown)

How well it finds each defect type (accuracy, held-out images)



Headline results



178 of 180

test images: the right defect type named




Live

anyone can test it now at surface-vision.github.io



~10,100



Known weak spots, and the fix for each





Weak spot	Today (0-1)	Fix in the pilot
Low-contrast texture: crazing, rolled-in scale	0.58-0.60	Angled lighting; JSL labels in P1
Real mill frames are harder than the lab benchmark	0.57 vs 0.75	Prove it on JSL's own strip in P1
Roll marks and edge cracks: few examples	0.20	Edge cameras; targeted labelling with JSL

Datasets: NEU-DET (Northeastern Univ.); Severstal steel defects (Kaggle); GC10-DET (Lv et al. 2020, CC BY 4.0). All scores on held-out images the system had never seen.

Strong on four of six defect families today. Every weak spot is known, and each has a fix in the pilot plan.

Seven months to shadow mode on one line, and nothing touches the mill until trust is earned

IMPLEMENTATION · ROADMAP · RISK



Pragati: JSL's digitalisation programme; Phase 2 brings Level-2 process data at Jajpur. KPI targets to be agreed with JSL Quality in P0.

Commit one line for seven months. The month-7 go/no-go is decided on JSL's own alarm and recall numbers.

At a conservative 1% downgrade rate, each line has ~₹6.7 cr a year at stake; ~₹43 cr across the fleet


Loss pool per line, ₹ cr a year

$0.4 \text{ Mt} \times \text{downgrade rate} \times \text{price discount} \times ₹167,407/\text{t}$

Downgraded	10% off	15% off	20% off
0.5% of volume	3.3	5.0	6.7
1.0% of volume	6.7	10.0	13.4
2.0% of volume	13.4	20.1	26.8

Base case (dark): ₹6.7 cr a year per line; ~₹43 cr across JSL's 2.57 Mt. Non-prime coil sells 10-30% below prime, so these discounts are conservative.

Where the value comes from, and how the pilot measures it



Impact beyond the P&L

Coverage 100% of both faces, every coil today: spot checks	Customers Defect map per coil for rail, metro, auto buyers Vande Bharat supplier	Process Defects tied to heat and coil IDs 6 families, each owned	Safety Severe-defect holds prevent strip breaks Ternium's business case	Sustainability Less rework and remelt; backs net zero JSL: 1.76 tCO2e/t, FY26	People Inspectors move to decisions HR AI: 95% self-served
---	---	---	--	--	---

WHAT WE ASK OF JSL

- One 300-series cold-rolled line, 7 months
- Vendor quotes for cameras and lighting in P0
- Downgrade rate by line and grade
- A metallurgist at 20% for root causes

In return: the measured downgrade rate, the value captured, and a go / no-go at month 7.

Inputs: JSL FY26 (INR 167,407/t; 2,565,902 t sold). Base case: a 0.4 Mt line, 1% downgraded at a 10% discount. Value at stake, not a savings forecast: JSL's own data sets the real figure.

Recommendation: approve a 7-month pilot on one 300-series cold-rolled line. JSL's own downgrade rate decides fleet rollout.