

Reference Guide

Pegboard

Version 6.50

Learn how to set up outlines the pegboard skintags, properties and values used for inserting pegboard functionality.

to be used by designers and
web builders

Document Purpose

Audience: Web Designers, Web builders

Document Version: 6.50

Written by Support

Purpose

This document is aimed at designers who need help with setting up templates and outlines of skin tags, properties and values that can be used for inserting pegboard functionality. Furthermore, this document provides an explanation of all the skin tags and properties. For assistance with using Pegboard please refer to the Pegboard Designer Guide.

Relevant documents

The following guides can also be viewed on the Manuals and Tutorials sections of the Pegboard's partners' area.

- Designer guide: assists designers who need help with setting up templates and understanding the pegboard architecture.
- Pegboard User Manual: assistance with using the pegboard console
- Menu Controls guide: setting up menus and applying css
- WYSIWYG manual: using the rich text editor
- Module Companion: information on pegboard modules, features and functionalities, to be used for selling pegboard and project scoping

Table of Contents

Sections

Page 1 – Template
Page 2 – Advanced
Page 23 – General
Page 45 – Navigation
Page 59 – Content
Page 61 – Images
Page 73 – Forms
Page 91 – Search
Page 96 – RSS
Page 98 – Settings
Page 100 – Banner Ads
Page 102 – Blogs
Page 110 – Bookmarks
Page 113 – Broadcasting
Page 114 – Datalist
Page 120 – Documents
Page 126 – Donations
Page 130 – Ecommerce
Page 148 – Emarketing
Page 156 – Events
Page 169 – Forums
Page 173 – Gallery
Page 174 – Jobs
Page 182 – Members
Page 201 – Links
Page 202 – News
Page 204 – Polls
Page 206 – Products
Page 231 – Template Email Tags

Template

Skintags

Skin Tags	Description	Use	Properties	Value	Default	Notes
pbTemplate	Must be included in a layout template as the placeholder for the page template.	In all layout template files.				



Advanced Collection

Skintags

Skin Tags	Description	Use	Properties	Value	Default	Notes
pbAdvPageSummary	Dynamically list webpages underneath the current page or, if there are none, pages at the same level. You can fix the pages listed by specifying a StartPage.		StartPage	String		Specify a page to start the summary, will list pages beneath the current one
			ShowInactive	True False	False	If 'True' will show pages set to invisible
			ShowInvisible	True False	False	If 'True' will show pages that are set to inactive
			OnlyShowChildPages	True False	False	If 'True' will only show child pages
			IncludeMenuItems	True False	True	If 'True' will include Menu items
			IncludeMemberContent	True False	False	If 'True' will include members content
			MemberContentOnly	True False	False	If 'True' will display members content only



ApprovedMemberContentOnly	True False	True	If 'True' will display approved members content only
CurrentMemberOnly	True False	False	If 'True' will display for current members only
SandboxMode	True False		
Member	String		Specify a member ID or name
Templates			
HeaderTemplate			
ItemTemplate			
AlternatingItemTemplate			
SelectedItemTemplate			
SelectedAlternatingItemTemplate			
SeparatorTemplate			
FooterTemplate			
NoDataTemplate			
pbAdvCollection pbAdvBasicSearchResults pbAdvCategory	Lists items within any collection, using an unordered list. By default this will dynamically pick up items underneath the current collection page. You can override this by setting the Collection property. This cover a Collection List and Summary.	http://rsb.org.au/Publications Collection	String
	A list control similar to the [pbAdvCollection], required to list search results from a [pbAdvBasicSearch].		Specify the collection. If left empty, if will automatically pick up the current collection the skin tag is on
	Lists items within any category, using inline templates for rendering. This	ShowInvisible	True False
			False
			If 'True' will show pages set to invisible



covers both a Category Summary and List

ShowInactive	True False	False	If 'True' will show pages that are set to inactive
IncludeMemberContent	True False	False	If 'True' will include members content
MemberContentOnly	True False	False	If 'True' will display members content only
ApprovedMemberContentOnly	True False	True	If 'True' will display approved members content only
CurrentMemberOnly	True False	False	If 'True' will display for current members only
Member	String		Specify a member ID or name
EditForm	String		Specify the location of the Edit Form
InsertForm	String		Specify the location of the Insert Form
DetailPage	String		Specify the location of the detail page
DataIdField	String		N/A
Category	String		Specify a category of items to display



MasterKeyField	String		Determines the field on which to filter by
DetailKeyField	String		Determines the value of the field to filter on
Sort	String		Specify a sort order (eg. Sort="SortOrder StartDate ArticleDate" etc)
RandomSort	True False	False	If 'True' will sort items randomly
Filter	String		Specify a filter (eg Featured='True')
MaxItems	Int32	0	Specify the max amount of items to display
PageSize	Int32	0	Specify the max items per page
Mode	CollectionMode	Standard	Standard,Category,Search,Page,Related,RelatedCategories
PageMethod	PagingMethod	QueryString	PostBack,QueryString
HideCurrentItem	True False	False	If 'True' then hide the current item



DisableItemScheduling	True False	False	If 'True' then disable item scheduling
ShowBookmarksOnly	True False	False	if True, the control will list bookmarks only
HideOldItems	True False	False	Hides items based on their start or end date
OldItemAsStartDate	True False	True	Set how an item is considered to be old. If true, old items are based on the start date. If false, old items are based on the end date.
UrlFilterMode	AND OR	AND	Determines which type of logic to append the URL filter and the skintag filter with
FilterParameter	String	filter	Determines which URL parameter to filter this collection with



CacheTime	Integer	900	Time to store the data set in the application cache
EnableCache	True False	TRUE	Enables caching the data set
HidePublicItems	True False	FALSE	Hides non-secured items from the result set

Templates

- HeaderTemplate
- FirstItemTemplate
- ItemTemplate
- AlternatingItemTemplate
- LastItemTemplate
- LastAlternatingItemTemplate
- SeparatorTemplate
- FooterTemplate
- NoDataTemplate



pbAdvBasicSearch	Provides a simple keyword-style search on all website content. Search results are displayed by any pbCollectionList or pbCollectionGrid control. Please note that need to use the skintag [ContentTemplate] instead of [ItemTemplate] to setup this inline control.	http://www.rsb.org.au/	ResultsPage	String		Specify a page to display results, results page should use the [pbAdvBasicSearchResults]
			PartialMatch	True False	True	Include results that are partial match
pbTextBox	This can used in conjunction with the skintags advanced member login and basic search to display a textbox.	http://www.brainboost.com.au/ http://www.wcaa.com.au/South-Australia-NT/Membership-Application-SA-NT.aspx	Id	String	""	Required
			ControlType	Text Password Multiline Numeric Masked	""	Type of the textbox entry
			CssClass	String	""	Set a CSS class for the textbox
			Columns	Integer	"0"	Set the textbox number of columns
			Rows	Integer	"0"	Set the number of rows in the textbox
			MaxLength	Integer	"0"	Set a maximum length of input for the textbox
			Width	Unit	""	Set the width of the textbox
			Height	Unit	""	Set the height of the textbox
			Mask	String	""	



		EmptyMessage	String	""	Insert a message into the textbox when empty
		DefaultButtonId	String	""	ID of the button to click when the return key is pressed inside the textbox
		CompareMessage	String		Message to display if the control set with the ControlToCompare property is not set to the same value as this textbox.
		ControlToCompare	String		
		EmailMessage	String		
		IsEmail	true false		
		IsRequired	true false		
		RequiredMessage	String		
		Text	String		
		ValidationGroup	String		
		value	object		
pbLabel	This can be used in conjunction with the skintags advanced member login and basic search to display a label.	http://www.brainboost.com.au/	Id	String	Required
		http://www.wcaa.com.au/South-Australia-NT/Membership-Application-SA-NT.aspx	CssClass	String	Specify a CSS class
			Text	String	Set the text for the label



pbButton	This can be used in conjunction with the skintags advanced member login and basic search to display a button.	http://www.brainboost.com.au/	Id	String	""	Required
		http://www.wcaa.com.au/South-Australia-NT/Membership-Application-SA-NT.aspx	ControlType	Button Image Link	""	Required
			Text	String	""	Set the text for the button
			ImageUrl	String	""	If ControlType="Image", set the image path here
			CommandName	String		The command name to assign to the button
			CommandArgument	String		The command arguments to assign to the button
			ConfirmMessage	String		The confirmation message to display when submitting
			Tooltip	String		The tooltip text to display for the button
			IsBackButton	True False	False	If 'True' then the button is set to be a Back button



			EnableCustomEvents	True False	False	If 'True' then custom events are enabled on the button
			ValidationGroup	String		The validation group to link the button to
			CssClass	String		The CSS class to apply to the button
pbAdvMemberLogin	In-line templatable member login control	http://www.brainboost.com.au	FailedUrl	String		Set the URL for the fail page
			SuccessUrl	String		Set the URL for the success page
			LogoutUrl	String		Set the redirect page after logout
			ForgotUrl	String		Specify a forgot details URL page
			LoginRoles	String		Allows you to limit the tag to only allow login for members who have access to the specified role(s)
			FailedMessage	String	login failed	Edit the failed login message



pbAdvPager	Can be used in the Header or Footer Template of a pbAdvCollection control to provide paging control	ShowFailedMessageBox				True False	False	If 'True' displays a failed message box
		Templates				AnonymousTemplate		
		MemberTemplate						
		EnableFirstLast				True False	"False"	Enables the First and Last page navigation buttons
		EnableSmartShortCuts				True False	"False"	
		SmartShortCutRatio				Integer	"3"	
		MaxSmartShortCutCount				Integer	"6"	
		SmartShortCutThreshold				Integer	"30"	
		CompactModePageCount				Integer	"10"	
		NormalModePageCount				Integer	"10"	
pbPageNav	pbPageNav provides a button, link, or image control allowing you to navigate a collection of items or a group of pages (pages at the same level) with a next/previous button. This tag can be used on Page, Collection, Collection_Item, and Category Templates.	EnableTooltips				True False	"False"	Buttons will show explanitive tooltips when hovered
		EnableInfo				True False	"True"	
		Text				String		Text displayed on link eg "Next"
		ImageUrl				String		Image URL for button image
		CssClass				String	pbPageNav	Specify a differnt CSS class
		DisabledCssClass				String	disabled	CSS class when link is disabled



ControlType	ButtonControlType	Button	Button,Image,Link
Mode	NavigationDirection	Next	Next,Previous
NavigateChildPages	True False	False	If 'True' then navigating will cascade down to child pages
ParentStartPage	String		If NavigateChildPages is 'True' then this property indicates the name of the page whose siblings are not included in the navigation when using cascading navigation

pbAdvItemCategorySummary	Inline templatable category summary control which can be used to display the category image.	http://www.davey.com.au	ShowInactive	True False	False	If 'True' then show inactive categories
			ShowInvisible	True False	False	If 'True' then show invisible categories
			IncludeMemberContent	True False	False	If 'True' then include member content



MemberContentOnly	True False	False	If 'True' then only include member content
ApprovedMemberContentOnly	True False	False	If 'True' then only include approved member content
CurrentMemberOnly	True False	False	If 'True' then only include the current member's content
Member	String		The name of the member whose content should be included
MaxLevels	Int32		The maximum level of categories to include
MaxItems	Int32	0	Specify the max amount of items to display
HideCurrentItem	True False	False	If 'True' then hide the current item
Templates			
HeaderTemplate			
ItemTemplate			
AlternatingItemTemplate			
SeparatorTemplate			
FooterTemplate			



pbctAdvItemCategorySummary	Inline templatable category summary control which can be used to display the category image. This control is used in a control template.	http://www.davey.com.au	ShowInactive	True False	False	If 'True' then show inactive categories
			ShowInvisible	True False	False	If 'True' then show invisible categories
			IncludeMemberContent	True False	False	If 'True' then include member content
			MemberContentOnly	True False	False	If 'True' then only include member content
			ApprovedMemberContentOnly	True False	False	If 'True' then only include approved member content
			CurrentMemberOnly	True False	False	If 'True' then only include the current member's content
			Member	String		The name of the member whose content should be included
			MaxLevels	Int32		The maximum level of categories to include
			MaxItems	Int32	0	Specify the max amount of items to display



		HideCurrentItem	True False	False	If 'True' then hide the current item
Templates					
HeaderTemplate					
ItemTemplate					
AlternatingItemTemplate					
SeparatorTemplate					
FooterTemplate					
pbAdvBrowserPanel	Inline control which can be used to switch content based on the client browser device				
Templates					
DefaultTemplate					
IeTemplate					
FirefoxTemplate					
SafariTemplate					
MobileTemplate					
IPadTemplate					
IPhoneTemplate					
AndroidTemplate					
SymbianTemplate					
BlackberryTemplate					
pbAdvItemImageGallery	Inline templatable version of the PBItemImageGallery. To be used with the PbAdvItemImageGalleryImage	GroupName	String	default	Binds multiple sets of pbAdvItemGal leryImage controls by setting a common group name
Maxitem					Maximum number of items to display
Templates					
MainImageTemplate					
ItemTemplate					
AlternatingItemTemplate					
SeparatorTemplate					



		HeaderTemplate			
		NoDataTemplate			
		FooterTemplate			
pbAdvItemImageGalleryImage	Image to be used inside a pbAdvItemImageGallery inline control	GroupName	String	default	Binds multiple sets of pbAdvItemImageGalleryImage controls by setting a common group name
		FileNameOnly	True False	False	If true, will output the imageUrl as plain text. Note that this will disable the default click functionality, requiring it to be manually implemented via client-side scripting
		Width	String	48	Width of the image
		Height	String	48	Height of the image
		ImageUrl	String		If specified, a fixed image will be used for the thumbnail



pbDataRepeaterPager	Templatable pager control for use with pbAdvCollection control	ShrinkOnly	True False	False	If 'True' do not enlarge the image if it is bigger than the specified size
		Format	String		JPEG or GIF
		JpgQuality	Int32	0	0 - 100
		GifColors	Int32	0	max colors
		GifColorBits	Int32	0	Color bits
		AltText	String		Alt text for the image
		Tooltip	String		Tooltip for the image
		CssClass	String		CssClass for the image
		Mode	QueryString PostBack	QueryString	Determines whether to postback the page to perform pagination or work solely off URL string values
		GotoCommandName	String	gotopage	
		ParameterName	String		URL parameter to use to determine pagination
		MinPageItems	Int32	5	Minimum page items to show
		MaxPageItems	Int32	5	Maximum number of page items to show
		PageSize	Int32	10	Size of items per page



FirstPlaceholderID	String	FirstPlaceholder	ID of the ASP Placeholder for the FirstTemplate
PreviousPlaceholderID	String	PreviousPlaceholder	ID of the ASP Placeholder for the FirstTemplate
MorePreviousPlaceholderID	String	MorePreviousPlaceholder	ID of the ASP Placeholder for the MorePreviousTemplate
PagePlaceholderID	String	PagePlaceholder	ID of the ASP Placeholder for the PageTemplate
MoreNextPlaceholderID	String	MoreNextPlaceholder	ID of the ASP Placeholder for the MoreNextTemplate
NextPlaceholderID	String	NextPlaceholder	ID of the ASP Placeholder for the NextTemplate
LastPlaceholderID	String	LastPlaceholder	ID of the ASP Placeholder for the LastTemplate



	Info1PlaceHolderID	String	Info1PlaceHolder	ID of the ASP PlaceHolder for the Info1Template
	Info2PlaceHolderID	String	Info2PlaceHolder	ID of the ASP PlaceHolder for the Info2Template
	Templates			
	LayoutTemplate			
	FirstTemplate			
	PreviousTemplate			
	MorePreviousTemplate			
	PageTemplate			
	MoreNextTemplate			
	NextTemplate			
	LastTemplate			
	Info1Template			
	Info2Template			
pbWizard	Creates a multi-page stepped wizard control. (There are no properties for this control)		pbWizardPage	

Inline Template skintags

The following are skintags specifically for Inline templating. These new skintags can be used as a subsitute the standard control templates. The builder to define the control template with the page elimating the need to create



additional control templates. The new skintag are prefixed wiht pbAdv and act like html tags where is there is opening and closing tags. For example, here is a how the new skintags works together to create a collection list.

Collection List -

```
[pbAdvCollection Collection="News" PageSize="6"]
[HeaderTemplate]
<ul class="list">
  <li class="header"><div class="header"><h3>News Summary</h3></div></li>
[/HeaderTemplate]
[ItemTemplate]
<li class="item">
  <table class="item" cellpadding="0" cellspacing="0" border="0">
    <tr><td>[News.ArticleDate("dd-MM-yy")]</td>
      <td width="10">&nbsp;</td>
      <td><a href="[Item.PageURL]">[Item.Name]</a></td>
    </tr></table>
</li>
[/ItemTemplate]
[AltItemTemplate]
<li class="altitem">
  <table class="altitem" cellpadding="0" cellspacing="0" border="0">
    <tr><td>[News.ArticleDate("dd-MM-yy")]</td>
      <td width="10">&nbsp;</td>
      <td><a href="[Item.PageURL]">[Item.Name]</a></td>
    </tr></table>
</li>
[/AltItemTemplate]
[FooterTemplate]
</ul>
[/FooterTemplate]
[/pbAdvCollection]
```

It is important to note that the skintags need to be on their own lines to work and that the standard pbForm skintags can be used.

The following example shows how to implement a stepped form using pbWizard



Reference Guide

[nbWizard]



General:

Skintags

Skin Tag

Collection

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbCollection	Lists items within any collection, using supplied templates for rendering. (no additional markup is generated by this control). Goes to a folder '/controls/collection'.	http://www.pegboardcms.com	Collection	String		Sets the control to pick up items from the collection specified. Leave off to pick up the current collection
			Template	String		Allows you to select a different folder for the control templates
			ShowInactive	True False	False	If true the control will also list inactive items
			ShowInvisible	True False	False	if True, the control will also list invisible items
			ObjectType	String		Set the type of Grid list, eg. collection/category and so on
			MaxRows	Int32	0	Sets the maximum number of items
			Category	String		Filter the collection by the specified category
			Filter	String		Filter the collection (eg. if True, the control will list
			ShowBookmarksOnly	True False	False	bookmarks only
			Sort	String		Sort the collection
			RandomSort	True False	False	if true, items in the list are randomly ordered
			SortField	String		Orders the list by the field specified
			SortDirection	String	ASC	Switches the order of the list ascending or descending
			IncludeMemberContent	True False	False	if True, include member's content
			MemberContentOnly	True False	False	if True, display member's content only
			ApprovedMemberContentOnly	True False	True	If True, display approved member's content only
			CurrentMemberOnly	True False	False	if True, display current login member's content only



Member	String		set up the member's ID or username
TopPagerVisible	True False	False	If 'True' will display a top pager above the item list
BottomPagerVisible	True False	True	Displays a pager below the list
TopPagerCssClass	String		Allows you to override the CSS class on the top pager
BottomPagerCssClass	String		Allows you to override the CSS class on the bottom pager
PageSize	Int32	10	Sets the number of items per page. Setting this to 0 disables paging
EnableAjax	True False	False	Enable Ajax
CategoryParameter	String		Parameter name which pass in the URL
TopPagerCssClass	String		Allows you to override the CSS class on the top pager
BottomPagerCssClass	String		Allows you to override the CSS class on the bottom pager
CurrentItemNameAsCategory	True False	False	n/a
HideOldItems	True False	False	Hides items (events) based on their start or end date
HideCurrentItem	True False	True	If displayed on detail page, the current item will be hidden
OldItemAsStartDate	True False	True	Set how an item is considered to be old. If true, old items are based on the start date. If false, old items are based on the end date.
MaxAge	Int32	0	n/a
MinAge	Int32	0	n/a
ItemCount	Int32		n/a
Templates			
HeaderTemplate			
ItemTemplate			
AlternatingItemTemplate			
SeparatorTemplate			
FooterTemplate			

pbCollectionGrid pbAdvCollectionGrid	Lists items within any collection, using a grid/table-based layout. By default this will dynamically pick up	http://www.macromeats.com.au/Recipes.aspx http://www.wildo.com.au/R	CssClass	String	pbGrid	Allows you to override the CSS class on the control
			Columns	Int32	1	Number of columns in the grid



items underneath the current collection page. You can override this by setting the Collection property.

ecipes.aspx

Collection	String		Sets the control to pick up items from the collection specified. Leave off to pick up the current collection
Template	String		Allows you to select a different folder for the control templates
ShowInactive	True False	False	If true the control will also list inactive items
ShowInvisible	True False	False	if True, the control will also list invisible item
ObjectType	String		Set the type of Grid list, eg. collection/category and so on
MaxRows	Int32	0	Unlimited row if it's 0
Category	String		Filter the collection by the specified category
Filter	String		Filter the collection
ShowBookmarksOnly	True False	False	if True, the control will list bookmarks only
Sort	String		Sort the collection
RandomSort	True False	False	If true, items in the list are randomly ordered
SortField	String		Orders the grid by the field specified
SortDirection	String	ASC	Switches the order of the grid ascending or descending
IncludeMemberContent	True False	False	if True, include member's content
MemberContentOnly	True False	False	if True, display member's content only
ApprovedMemberContentOnly	True False	True	If True, display approved member's content only
CurrentMemberOnly	True False	False	if True, display current login member's content only
Member	String		set up the member's ID or username
TopPagerVisible	True False	False	Displays a pager above the list
BottomPagerVisible	True False	True	Displays a pager below the list
TopPagerCssClass	String		Allows you to override the CSS class on the top pager
BottomPagerCssClass	String		Allows you to override the CSS class on the bottom pager
PageSize	Int32	10	Sets the number of items per page. Setting this to 0 disables paging



EnableAjax	True False	False	if True, Enable Ajax
CategoryParameter	String		Parameter name which pass in the URL
TopPagerCssClass	String		Allows you to override the CSS class on the top pager
BottomPagerCssClass	String		Allows you to override the CSS class on the bottom pager
CurrentItemNameAsCategory	True False	False	n/a
HideOldItems	True False	False	Hides items (events) based on their start or end date
HideCurrentItem	True False	True	If displayed on detail page, the current item will be hidden
OldItemAsStartDate	True False	True	Set how an item is considered to be old. If true, old items are based on the start date. If false, old items are based on the end date.
MaxAge	Int32	0	n/a
MinAge	Int32	0	n/a
ItemCount	Int32		n/a
Direction	RepeatDirection	Horizontal	Horizontal,Vertical
GridLines	GridLines	None	None,Horizontal,Vertical,Both
Layout	RepeatLayout	Table	Table,Flow
ListCssClass	String	list	Allows you to override the css class on the inner UL tag
CssClass	String	pbList	Allows you to override the CSS class on the control
Collection	String		Sets the control to pick up items from the collection specified. Leave off to pick up the current collection
Template	String		Allows you to select a different folder for the control templates
ShowInactive	True False	False	If true the control will also list inactive items
ShowInvisible	True False	False	if True, the control will also list invisible item
ObjectType	String		Set the type of Grid list, eg. collection/category and so on
MaxRows	Int32	0	Unlimited row if it's 0
Category	String		Filter the collection by the specified category
Filter	String		Filter the collection



ShowBookmarksOnly	True False	False	if True, the control will list bookmarks only
Sort	String		Sort the collection
RandomSort	True False	False	If true, items in the list are randomly ordered
SortField	String		Orders the list by the field specified
SortDirection	String	ASC	Switches the order of the list ascending or descending
IncludeMemberContent	True False	False	if True, include member's content
MemberContentOnly	True False	False	if True, display member's content only
ApprovedMemberContentOnly	True False	True	If True, display approved member's content only
CurrentMemberOnly	True False	False	if True, display current login member's content only
Member	String		set up the member's ID or username
TopPagerVisible	True False	False	Displays a pager above the list
TopPagerCssClass	String		Allows you to override the CSS class on the top pager
TopPagerCssClass	String		Allows you to override the CSS class on the top pager
BottomPagerCssClass	String		Allows you to override the CSS class on the bottom pager
PageSize	Int32	10	Sets the number of items per page. Setting this to 0 disables paging
EnableAjax	True False	False	Enable Ajax
CategoryParameter	String		Parameter name which pass in the URL
TopPagerCssClass	String		Allows you to override the CSS class on the top pager
BottomPagerCssClass	String		Allows you to override the CSS class on the bottom pager
CurrentItemNameAsCategory	True False	False	n/a
HideOldItems	True False	False	Hides items (events) based on their start or end date
HideCurrentItem	True False	True	If displayed on detail page, the current item will be hidden



pbCollectionSummary	Lists items within any collection, using an unordered list. By default this will dynamically pick up items underneath the current collection page. You can override this by setting the Collection property. Unlike the CollectionList, this control picks up only a set number of items specified by the MaxRows property.	http://www.nickdube.com/ http://www.pegboardcms.com/default.aspx http://www.vlga.org.au/default.aspx	OldItemAsStartDate	True False	True	Set how an item is considered to be old. If true, old items are based on the start date. If false, old items are based on the end date.
			MaxAge	Int32	0	n/a
			MinAge	Int32	0	n/a
			ItemCount	Int32		n/a
			Templates			
			HeaderTemplate			
			ItemTemplate			
			AlternatingItemTemplate			
			SeparatorTemplate			
			FooterTemplate			
			ListCssClass	String	list	Allows you to override the css class on the inner UL tag
			CssClass	String	pbSummary	Allows you to override the CSS class on the control
			Collection	String		Sets the control to pick up items from the collection specified. Leave off to pick up the current collection
			Template	String		Allows you to select a different folder for the control templates
			ShowInactive	True False	False	If true the control will also list inactive items
			ShowInvisible	True False	False	If 'True' will show pages that are set to invisible
			ObjectType	String		collection/category and so on
			MaxRows	Int32	0	The maximum number of items to display in the summary
			StartingRow	Int32	0	n/a
			Category	String		Filter the collection by the specified category
			Filter	String		Filter the collection
			ShowBookmarksOnly	True False	False	If 'True' will only show items that are bookmarked
			Sort	String		Sort the collection
			RandomSort	True False	False	If true, items in the list are randomly ordered
			SortField	String		Orders the summary by the field specified



SortDirection	String	ASC	Switches the order of the summary between ascending or descending
IncludeMemberContent	True False	False	if True, include member's content
MemberContentOnly	True False	False	if True, display member's content only
ApprovedMemberContentOnly	True False	True	If True, display approved member's content only
CurrentMemberOnly	True False	False	if True, display current login member's content only
Member	String		set up the member's ID or username
CategoryParameter	String		Parameter name which pass in the URL
HideOldItems	True False	False	Hides items (events) based on their start or end date
HideCurrentItem	True False	True	If displayed on detail page, the current item will be hidden
OldItemAsStartDate	True False	True	Set how an item is considered to be old. If true, old items are based on the start date. If false, old items are based on the end date.
ItemCount	Int32		n/a

Category

pbCategory	Lists items within any category, using supplied templates for rendering. (no additional markup is generated by this control). Goes to the folder '/controls/category'	http://www.pegboardcms.com/default.aspx	ObjectType Collection	String String	collection/category and so on Sets the control to pick up items from the collection specified. Leave off to pick up the current collection
Template				String	Allows you to select a different folder for the control templates
ShowInactive				True False	False If true the control will also list inactive items
ShowInvisible				True False	False If true the control will also list invisible categories
Sort				String	SortOrder Sort the collection
SortField				String	Orders the summary by the field specified
SortDirection				String	ASC Switches the order of the summary between ascending or descending



RandomSort	True False	False	If true, items in the list are randomly ordered
MaxRows	Int32	0	The maximum number of items to display in the summary. Note: use "0" for all items
IncludeMemberContent	True False	False	if True, include member's content
MemberContentOnly	True False	False	if True, display member's content only
ApprovedMemberContentOnly	True False	True	If True, display approved member's content only
CurrentMemberOnly	True False	False	if True, display current login member's content only
Member	String		set up the member's ID or username
Filter	String		Filter the collection
TopPagerVisible	True False	False	Displays a pager above the list
BottomPagerVisible	True False	True	Displays a pager below the list
TopPagerCssClass	String	pbPager	Allows you to override the CSS class on the top pager
BottomPagerCssClass	String	pbPager	Allows you to override the CSS class on the bottom pager
PageSize	Int32	10	Sets the number of items per page. Setting this to 0 disables paging
EnableAjax	True False	False	If 'True' will display an ajax on load
Category	String		Filter the collection by the specified category
CategoryParameter	String		Parameter name which pass in the URL
HideIfNoItems	True False	False	Only shows category if it or a sub category contains an item
HideIfNoSubCats	True False	False	If 'True' will hide if no sub-categories exist
MaxAge	Int32	0	n/a
MinAge	Int32	0	n/a
pbCategoryGrid pbAdvCategoryGrid	Lists items within any collection, using a grid/table-based layout. By default this will dynamically pick up items underneath the current	http://www.wcaa.com.au/South-Australia-NT/Retail-Outlets-SA-NT.aspx	
CssClass	String	pbGrid	Allows you to override the CSS class on the control
Columns	Int32	1	Number of columns in the grid
ObjectType	String		collection/category and so on



collection page. You can override this by setting the Collection property.

Collection	String		Sets the control to pick up items from the collection specified. Leave off to pick up the current collection
Template	String		Allows you to select a different folder for the control templates
ShowInactive	True False	False	If true the control will also list inactive items
ShowInvisible	True False	False	If true the control will also list invisible categories
Sort	String	SortOrder	Sort the collection
SortField	String		Orders the grid by the field specified
SortDirection	String	ASC	Switches the order of the grid ascending or descending
RandomSort	True False	False	If true, items in the list are randomly ordered
MaxRows	Int32	0	The maximum number of items to display in the summary. Note: use "0" for all items
IncludeMemberContent	True False	False	if True, include member's content
MemberContentOnly	True False	False	if True, display member's content only
ApprovedMemberContentOnly	True False	True	If True, display approved member's content only
CurrentMemberOnly	True False	False	if True, display current login member's content only
Member	String		set up the member's ID or username
Filter	String		Filter the collection
TopPagerVisible	True False	False	Displays a pager above the list
BottomPagerVisible	True False	True	Displays a pager below the list
TopPagerCssClass	String		Allows you to override the CSS class on the top pager
BottomPagerCssClass	String		Allows you to override the CSS class on the bottom pager
PageSize	Int32	10	Sets the number of items per page. Setting this to 0 disables paging
EnableAjax	True False	False	If 'True' will display an ajax on load



Category	String		Filter the collection by the specified category
CategoryParameter	String		Parameter name which pass in the URL
HideIfNoItems	True False	False	Only shows category if it or a sub category contains an item
HideIfNoSubCats	True False	False	If 'True' will hide if no sub-categories exist
MaxAge	Int32	0	n/a
MinAge	Int32	0	n/a
Direction	RepeatDirection	Horizontal	Horizontal,Vertical
GridLines	GridLines	None	None,Horizontal,Vertical,Both
Layout	RepeatLayout	Table	Table,Flow
Templates			
HeaderTemplate			
ItemTemplate			
AlternatingItemTemplate			
SeparatorTemplate			
FooterTemplate			

pbCategoryList	Lists items within any category, using supplied templates for rendering. (no additional markup is generated by this control). Templates source from the folder '/controls/category'	http://www.nickdube.com/Web-Design-Gallery.aspx http://www.mobiletherapists.com.au/Browse-Therapists.aspx	ListCssClass	String	list	Allows you to override the css class on the inner UI tag
			CssClass	String	pbList	Allows you to override the CSS class on the control
			ObjectType	String		collection/category and so on
			Collection	String		Sets the control to pick up items from the collection specified. Leave off to pick up the current collection
			Template	String		Allows you to select a different folder for the control templates
			ShowInactive	True False	False	If true the control will also list inactive items
			ShowInvisible	True False	False	If true the control will also list invisible categories
			Sort	String	SortOrder	Sort the collection
			SortField	String		Orders the summary by the field specified
			SortDirection	String	ASC	Switches the order of the summary between ascending or descending
			RandomSort	True False	False	If true, items in the list are randomly ordered



override this by setting the Collection property. Unlike the CategoryList, this control picks up only a set number of categories specified by the MaxRows property.

Collection	String		Sets the control to pick up categories from the collection specified. Leave off to pick up the current collection
Template	String		Allows you to select a different folder for the control templates
ShowInactive	True False	False	If true the control will also list inactive categories
ShowInvisible	True False	False	If true the control will also list invisible categories
Sort	String	SortOrder	Sort the collection
SortField	String		Orders the summary by the field specified
SortDirection	String	ASC	Switches the order of the summary between ascending or descending
RandomSort	True False	False	If true, items in the list are randomly ordered
MaxRows	Int32	0	The maximum number of categories to display in the summary
IncludeMemberContent	True False	False	if True, include member's content
MemberContentOnly	True False	False	if True, display member's content only
ApprovedMemberContentOnly	True False	True	If True, display approved member's content only
CurrentMemberOnly	True False	False	if True, display current login member's content only
Member	String		set up the member's ID or username
Filter	String		Filter the collection
Category	String		Filter the collection by the specified category
CategoryParameter	String		Parameter name which pass in the URL
HideIfNoItems	True False	False	Only shows category if it or a sub category contains an item
HideIfNoSubCats	True False	False	If 'True' will hide if no sub-categories exist

pbPager	Use inside a pbAdvProductSearch template to define a custom pager	http://www.gerardmccabe.com.au	DisableLeftButton	True False	False	Remove the "Previous" page button
---------	---	---	-------------------	------------	-------	-----------------------------------



within the search results

ccape.com.au

		DisableNumbers	True False	False	Set to "True" to hide the page numbers
		DisableRightButton	True False	False	Remove the "Next" page button
		PreviousImageUrl	String		The URL of the image to display for the "Navigate Previous" button. This button is disabled if the user is on the first page.
		PreviousImageDisabledUrl	String		The URL of the image to display for the disabled "Navigate Previous" button. This button is disabled if the user is on the first page.
		NextImageUrl	String		The URL of the image to display for the "Navigate Next" button
		NextImageDisabledUrl	String		The URL of the image to display for the disabled "Navigate Next" button. This button is disabled if the user is on the last page.
pbHeadContent	Use on a page or layout template to render content in the <head> of the page	DisableAllText	True False	False	Set to "true" if only images need to be displayed for the pager. This is equivalent in setting "DisableLeftButton", "DisableNumbers" and "DisableRightButton" to "True".
pbDeviceSkinSwitcher	Used with Device skins to allow a mobile user to switch between browsing the site using the mobile device skin or the default site skin	DefaultSkinText	String	"Main Site"	[pbHeadContent] This is the head content [/pbHeadContent] The text to render as the link to switch back to the main default site skin
		DeviceSkinText	String	"Mobile Site"	The text to render as the link to switch back to the device site skin
pbConditional	Allows the control of content	DisplayForMember	Ignore False True	Ignore	Determines whether to evaluate if a
		Operator	Equals NotEquals GreaterThan	Equals	Determines what kind of logic to
		FieldValueType	String Date Decimal Integer	String	Determines what type of field to
		BrowserMatch	MatchAll MatchAny	MatchAny	Determines whether to evaluate any
		IgnoreCase	True False	FALSE	Determines whether to ignore



Roles	String	Roles to check a member against
FieldName	String	Name of the field to compare
FieldValue	String	Value to compare against
Browser	String	Value to determine browser against
Templates		
TrueContentTemplate		
FalseContentTemplate		

Control Tags

Skin Tag

Collection

	Description	Use	Properties	Value	Default	Notes
pbCollectionGrid	Lists items within any collection, using a grid/table-based layout. By default this will dynamically pick up items underneath the current collection page. You can override this by setting the Collection property..		CssClass	String	pbGrid	Allows you to override the CSS class on the control
			Columns	Int32	1	Number of columns in the grid
			Template	String		Allows you to select a different folder for the control templates
			ShowInactive	True False	False	If true the control will also list inactive items
			ShowInvisible	True False	False	If True, the control will also list invisible item
			ObjectType	String		Set the type of Grid list, eg. collection/category and so on
			MaxRows	Int32	0	Unlimited row if it's 0
			Category	String		Filter the collection by the specified category
			Filter	String		Filter the collection
			ShowBookmarksOnly	True False	False	If True, the control will list bookmarks only
			Sort	String		Sort the collection
			RandomSort	True False	False	Allow the items to be sorted randomly
			SortField	String		Orders the summary by the field specified
			SortDirection	String	ASC	Switches the order of the summary between ascending or descending
			IncludeMemberContent	True False	False	If True, include member's content
			MemberContentOnly	True False	False	If True, display member's content only
			ApprovedMemberContentOnly	True False	True	If True, display approved member's content only



pbCollectionList	Lists items within any collection, using an unordered list. By default this will dynamically pick up items underneath the current collection page. You can override this by setting the Collection property.	CurrentMemberOnly	True False	False	if True, display current login member's content only
		Member	String		if True, display current login member's content only
		TopPagerVisible	True False	False	set up the member's ID or username
		BottomPagerVisible	True False	True	Displays a pager below the list
		PageSize	Int32	10	Sets the number of items per page. Setting this to 0 disables paging
		EnableAjax	True False	False	If 'True' will display an ajax on load
		Direction	RepeatDirection	Horizontal	Horizontal, Vertical
		GridLines	GridLines	None	None, Horizontal, Vertical, Both
		Layout	RepeatLayout	Table	Table, Flow
		Templates			
		HeaderTemplate			
		ItemTemplate			
		AlternatingItemTemplate			
		SeparatorTemplate			
		FooterTemplate			
		Template	String		Allows you to select a different folder for the control templates
		ShowInactive	True False	False	If true the control will also list inactive items
		ShowInvisible	True False	False	if True, the control will also list invisible item
		ObjectType	String		Set the type of Grid list, eg. collection/category and so on
		MaxRows	Int32	0	Unlimited row if it's 0
		Category	String		Filter the collection by the specified category
		Filter	String		Filter the collection
		ShowBookmarksOnly	True False	False	if True, the control will list bookmarks only
		Sort	String		Sort the collection
		RandomSort	True False	False	Allow the items to be sorted randomly
		SortField	String		Orders the summary by the field specified
		SortDirection	String	ASC	Switches the order of the summary between ascending or descending



IncludeMemberContent	True False	False	if True, include member's content
MemberContentOnly	True False	False	if True, display member's content only
ApprovedMemberContentOnly	True False	True	if True, display approved member's content only
CurrentMemberOnly	True False	False	if True, display current login member's content only
Member	String		if True, display current login member's content only
TopPagerVisible	True False	False	set up the member's ID or username
BottomPagerVisible	True False	True	Displays a pager below the list
PageSize	Int32	10	Sets the number of items per page. Setting this to 0 disables paging
EnableAjax	True False	False	If 'True' will display an ajax on load
ListCssClass	String	list	Allows you to override the css class on the inner UL tag
CssClass	String	pbList	Allows you to override the CSS class on the control
Templates			
HeaderTemplate			
ItemTemplate			
AlternatingItemTemplate			
SeparatorTemplate			
FooterTemplate			
ListCssClass	String	list	Allows you to override the css class on the inner UL tag
CssClass	String	pbSummary	Allows you to override the CSS class on the control
Template	String		Allows you to select a different folder for the control templates
ShowInactive	True False	False	If true the control will also list inactive items
ShowInvisible	True False	False	If 'True' will show pages that are set to invisible
ObjectType	String		collection/category and so on
MaxRows	Int32	0	The maximum number of items to display in the summary
StartingRow	Int32	0	n/a



Category	String		Filter the collection by the specified category
Filter	String		Filter the collection
Sort	String		Sort the collection
RandomSort	True False	False	If true, items in the list are randomly ordered
SortField	String		Orders the summary by the field specified
SortDirection	String	ASC	Switches the order of the summary between ascending or descending
IncludeMemberContent	True False	False	if True, include member's content
MemberContentOnly	True False	False	if True, display member's content only
ApprovedMemberContentOnly	True False	True	If True, display approved member's content only
CurrentMemberOnly	True False	False	if True, display current login member's content only
Member	String		set up the member's ID or username

pbAdvContentPanel	allows show and hide items based on condition.	[pbAdvCollection collection="test"] [ItemTemplate] [pbAdvContentPanel DisplayForMember="True" FieldName="post" FieldValue="True"] [Item.Name] [/pbAdvContentPanel] [/ItemTemplate] [FooterTemplate][FooterTemplate] plate] [/pbAdvCollection]	DisplayForMember	True/FALSE	FALSE	If true the control will only display contents for members.
			Roles			specify role name of member
			FieldName			field name that needs to be checked against field value
			FieldValue			Value to compare against



		ComparisonOperator	Equals NotEquals GreaterThan LessThan	Equals	Specifies the type of logic to use in the evaluation of the parameters.
		FieldValueType	StringType DateType DecimalType IntegerType		Type of the field, specifies what type of comparison to use to evaluate.
pbAjaxPanel	Adds an ajax conditional update				
pbBrowserPanel	Allows a designer to show or hide content based on the browser in use.	IsIE	True False Ignore	Ignore	Allows browser-targeting.
		IsFirefox			Ignore will not cause any evaluation.
	This control is superceded by the pbConditional control.	IsSafari			True requires the browser to match.
		IsMobile			False requires the browser not to match.
		IsIPad			
		IsiPhone			
		IsAndroid			
		IsSymbian			
		IsBlackBerry			
		Browser	String		Set a Browser to evaluate against
		UserAgentContains	String		Performs a contains comparison
		UserAgentRegEx	String		Performs regex validation against
pbRequiredValidator	Adds a validator onto a page.	Mode	Required Email Compare RegEx	Required	Determines what logic to use when validating
		ControlToValidate	String		ID of the control to validate against
		ErrorMessage	String		Message to show on unsuccessful validation
		InitialValue	String		Initial value of the control (to determine if a change was made in Required mode)
		ControlToCompare	String		ID of the control to compare to when in Compare mode
		Expression	String		Regular Expression to use when validating in RegEx mode
		ValidationGroup	String		Identifier for what group to attach this validator to
		ValueToCompare	String		Value to compare against in Compare mode



ValueTags

pbRequestValue	Displays the value of the Request	Key	name of the request	n/a
----------------	-----------------------------------	-----	---------------------	-----

Item:

Item.Active	Item.AccessMode
Item.Alias	Item.AccessRoles
Item.AliasPath	Item.Active
Item.BodyTag	Item.AdditionalPageFooterContent
Item.BodyTagAttributes	Item.AdditionalPageHeaderContent
Item.Category	Item.Alias
Item.CheckedOut	Item.AliasPath
Item.CheckedOutBy	Item.BodyTagAttr
Item.CheckedOutById	Item.CacheMaxAge
Item.CheckedOutDateTime	Item.CacheMode
Item.CreatedBy	Item.Category
Item.CreatedById	Item.CategoryPaths
Item.CreatedDate	Item.CheckedOut
Item.CreatedDateTime	Item.CheckedOutBy
Item.CssFiles	Item.CheckedOutDateTime
Item.Deleted	Item.CheckedOutTimestamp
Item.DeletedBy	Item.CheckedOutUserId
Item.DeletedById	Item.CollectionId
Item.DeletedDateTime	Item.CreatedBy
Item.Description	Item.CreatedTimestamp
Item.DocType	Item.CreatedUserId
Item.ForceSSL	Item.CssFiles
Item.ForeignKey	Item.Deleted
Item.ForgeignKey	Item.DeletedBy
Item.HtmlTitle	Item.DeletedDateTime
Item.Id	Item.DeletedTimestamp
Item.ImageGalleryURL	Item.DeletedUserId
Item.ImageUrl	Item.Description
Item.IntId	Item.DocType
Item.JsFiles	Item.ForceSSL
Item.Keywords	Item.ForeignKey
Item.Layout	Item.GooglePriority
Item.MenuCssClass	Item.GoogleUpdateFrequency
Item.ModifiedBy	Item.Id
Item.ModifiedById	Item.ImageUrl
Item.ModifiedDateTime	Item.IntId
Item.Name	Item.IsScheduled

Item.<FieldName>



Item.PageUrl
Item.ParentId
Item.Robots
Item.Searchable
Item.SiteId
Item.SiteObjectType
Item.Skin
Item.SortOrder
Item.Summary
Item.Target
Item.Template
Item.Title
Item.RatingTypeId
Item.CommentCount
Item.AvgRating1
Item.AvgRating2
Item.AvgRating3
Item.AvgRating4
Item.AvgRating5
Item.AvgRating6
Item.AvgRating7
Item.AvgRating8
Item.AvgRating9
Item.AvgRating10

Item.JsFiles
Item.Keywords
Item.Layout
Item.McApprovedBy
Item.McApprovedTimestamp
Item.McApprovedUserId
Item.McCreatedBy
Item.McCreatedTimestamp
Item.McCreatedUserId
Item.McIsApproved
Item.McIsMemberContent
Item.MenuCssClass
Item.MenuDisabledCssClass
Item.MenuHoverCssClass
Item.MenuHoverImageUrl
Item.MenuHoverImageUrl
Item.MenuHoverImageUrl
Item.MenuHoverImageUrl
Item.MenuImageUrl
Item.MenuSelectedCssClass
Item.ModifiedBy
Item.ModifiedDateTime
Item.ModifiedTimestamp
Item.ModifiedUserId
Item.Name
Item.PageUrl
Item.ParentId
Item.Robots
Item.ScheduleEnd
Item.ScheduleStart
Item.Searchable
Item.SiteId
Item.SiteObjectType
Item.Skin
Item.SortOrder
Item.Staged
Item.Summary
Item.Template
Item.TitleItem
Item.Visible
Item.XuaCompatible

ThisRequest:



ThisRequest.Alias
ThisRequest.AliasPath
ThisRequest.BrowserIsFirefox
ThisRequest.BrowserIsIE
ThisRequest.BrowserIsSafari
ThisRequest.BrowserMajorVersion

ThisRequest.BrowserMinorVersion

ThisRequest.Description
ThisRequest.HostHeader
ThisRequest.IsEnabled
ThisRequest.IsFuturePreview
ThisRequest.IsPreview
ThisRequest.IsSearchable
ThisRequest.IsSecure
ThisRequest.IsVisible
ThisRequest.Keywords
ThisRequest.Layout
ThisRequest.Name
ThisRequest.ParentSiteObjectId

ThisRequest.ParentURL
ThisRequest.PreviewDateTime

ThisRequest.RequestUrl
ThisRequest.SiteAlias
ThisRequest.SiteAliasPath
ThisRequest.SiteId
ThisRequest.SiteObjectId
ThisRequest.SiteRoot
ThisRequest.Skin
ThisRequest.SkinFolder
ThisRequest.Template
ThisRequest.TemplateFolder
ThisRequest.Title
ThisRequest.BrowserIsiPhone
ThisRequest.BrowserIsiPad
ThisRequest.BrowserIsSymbian
ThisRequest.BrowserIsAndroid
ThisRequest.BrowserIsBlackberry
ThisRequest.Browser
ThisRequest.MemberProfileId
ThisRequest.MemberProfileUrl

ThisRequest.[Alias]
ThisRequest.act
ThisRequest.AdminLanguage
ThisRequest.AdminTheme
ThisRequest.AliasPath
ThisRequest.BodyAttribs
ThisRequest.BrowserIsFireFox

ThisRequest.BrowserIsIE

ThisRequest.BrowserIsSafari
ThisRequest.BrowserMajorVersion
ThisRequest.BrowserMinorVersion
ThisRequest.CacheMaxAge
ThisRequest.CacheMode
ThisRequest.CollectionType
ThisRequest.Content
ThisRequest.CurrencySymbol
ThisRequest.DataDate
ThisRequest.Description
ThisRequest.DocType
ThisRequest.DontCache

ThisRequest.hid
ThisRequest.HostHeader

ThisRequest.HostHeaderSiteId
ThisRequest.id
ThisRequest.IsEnabled
ThisRequest.IsFuturePreview
ThisRequest.IsInConsole
ThisRequest.IsInSite
ThisRequest.IsInstalling
ThisRequest.IsInSystem
ThisRequest.IsPreview
ThisRequest.IsSearchable
ThisRequest.IsSecure
ThisRequest.IsStagedObject
ThisRequest.IsUpgrading
ThisRequest.IsVisible
ThisRequest.Keywords
ThisRequest.LastModified
ThisRequest.Layout
ThisRequest.MemberId
ThisRequest.MembersValid



ThisRequest.MemberName
ThisRequest.Name
ThisRequest.oid
ThisRequest.ParentSiteObjectID
ThisRequest.ParentURL
ThisRequest.pid
ThisRequest.PreviewDateTime
ThisRequest.PrintMode
ThisRequest.RequestUrl
ThisRequest.Robots
ThisRequest.sid
ThisRequest.SiteAlias
ThisRequest.SiteAliasPath
ThisRequest.SiteID
ThisRequest.SiteObjectID
ThisRequest.SiteObjectType
ThisRequest.SiteRoot
ThisRequest.Skin
ThisRequest.SkinFolder
ThisRequest.StagingEnabled
ThisRequest.Template
ThisRequest.TemplateFolder
ThisRequest.Title
ThisRequest.UserID
ThisRequest.Values

ValueTag formats

The following prefixes to valuetags can be used to perform special logic against any given value

itemCss.	This tag will strip any CSS-invalid tags from the value and convert them to _s
itemLookup.	This tag will any ID value or comma-separated ID values and return their associated names
DataItemCss.	These tags work like the above however will work inside of repeaters off the current repeater item
DataItemLookup.	



Menus and Navigation

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbCssSiteMenu	Inserts a site navigation menu that displays with fly-out menus for subpages when the user hovers over the menu.		Width	Unit		The overall width of the
			Height	Unit		The overall
			StartPage	String		Sets the site menu to only show pages under the
			EnableShadows	True False	False	Enable drop shadows
			MaxLevels	Int32	3	Sets the maximum number of
			CssClass	String	pbCssSiteMenu	Allows you to override the
			ShowCategories	True False	False	If true, displays
			CategoryDepth	Int32	1	Sets the maximum
			ShowItems	True False	False	Displays individual
			GutterWidth	Unit	0px	n/a
			DisableInactive	True False	False	If 'True' disables pages
			ItemSpacing	Unit	0px	The spacing
			SeparatorWidth	Unit	0px	Width of
			SeparatorHeight	Unit	0px	Height of
			SeparatorPaddingLeft	Unit	0px	Left padding
			SeparatorPaddingTop	Unit	0px	Top padding
			SeparatorPaddingRight	Unit	0px	Right padding
			SeparatorPaddingBottom	Unit	0px	Bottom
			SeparatorBgImage	String		Separator
			IncludeMemberContent	True False	False	If 'True' will display
			MemberContentOnly	True False	False	If 'True' will display
			ApprovedMemberContentOnly	True False	True	If 'True' will only display
			CurrentMemberOnly	True False	False	If 'True' will only display



			Member	String		set up the member's ID
			NoImages	True False	False	Stops the menu from rendering any
			ShowPopoutImages	DefaultBoolean	1	True,False,Def
			AutoSeparators	AutoSeparatorMode	None	All,RootOnly,N
			SeparatorBgRepeat	BackgroundImageRepeat	Repeat	Repeat,NoRepeat,RepeatX,R
pbPanelMenu	Inserts a vertical navigation menu that displays with expanding and collapsing panels. As the user navigates through the site, the area they are currently in expands on the menu, showing the available subpages	http://www.wcombudsmansa.com.au/ http://www.cfmvic.com.au/Products/Catering-Equipment/General-Cooking-	StartPage	String		Sets the panel menu to only show pages under the
			Width	Unit		The overall width of the
			Height	Unit		The overall height of the
			CurrentNode	String		n/a
			MaxLevels	Int32	3	Sets the maximum number of
			CssClass	String	pbPanelMenu	Allows you to override the
			TopImagesOnly	True False	False	n/a
			SubImagesOnly	True False	False	n/a
			UseLevelCss	True False	False	n/a
			CollapseAnimationDuration	Int32	100	Duration of animation for
			ExpandAnimationDuration	Int32	200	Duration of animation for
			ExpandAll	True False	False	Expands all levels of the
			ExpandLevels	Int32	0	Sets the maximum number of
			DisableInactive	True False	False	If 'True' disables pages
			ShowCategories	True False	False	If true, displays
			CategoryDepth	Int32	1	Sets the maximum
			ShowItems	True False	False	Displays individual



			IncludeMemberContent	True False	False	If 'True' will display
			IncludeStartPageInMenu	True False	FALSE	If 'True' and 'StartPage' property
			MemberContentOnly	True False	False	If 'True' will display
			ApprovedMemberContentOnly	True False	True	If 'True' will only display
			CurrentMemberOnly	True False	False	If 'True' will only display
			Member	String		set up the member's ID
			ShowInvisible	True False	False	If 'True' will display pages
			CollapseAnimationType	PanelbarAnimationType	InQuint	None,Linear,InQuad,OutQuad,InOutQuad,InCubic,OutCubic,InOutCubic,InQuart,OutQuart,InOutQuart,InQuint,OutQuint,InOutQuint
			ExpandAnimationType	PanelbarAnimationType	InQuint	None,Linear,InQuad,OutQuad,InOutQuad,InCubic,OutCubic,InOutCubic,InQuart,OutQuart,InOutQuart,InQuint,OutQuint,InOutQuint
			ExpandMode	PanelbarExpandMode	MultipleExpandedItems	MultipleExpandedItems,SingleExpandedItem
pbSiteMenu	Inserts a site navigation menu that displays with fly-out menus for subpages when the user hovers over the menu. The site menu can either display horizontally (with vertical fly-outs), or vertically (with horizontal	http://www.dvanda.com.au/ http://www.zinkmineralcosmetics.com/	StartPage	String		Sets the site menu to only show pages under the
			Width	Unit		The overall width of the



fly-outs).

MaxLevels	Int32	3	Sets the maximum number of
ShowCategories	True False	False	If true, displays
CategoryDepth	Int32	1	Sets the maximum
ShowItems	True False	False	Displays individual
EnableAutoScroll	True False	False	Enables automatic
EnableScreenBoundryDetection	True False	False	" "
EnableScreenBoundaryDetection	True False	False	Enables screen
MaxSubMenuWidth	Unit		Sets the maximum
MaxSubMenuHeight	Unit		Sets the maximum
CollapseAnimDuration	Int32	100	Sets the duration of for
CollapseAnimDelay	Int32	500	Sets the delay before a sub
ExpandAnimDuration	Int32	200	Sets the duration of
ExpandAnimDelay	Int32	0	Sets the delay before a sub
CssClass	String	pbMenu	Allows you to override the
OffsetX	Int32	0	Sets a horizontal offset of child
OffsetY	Int32	0	Sets a vertical offset of child menu items
DisableInactive	True False	False	If 'True'
DisableHoverOnSelected	True False	True	n/a
TopImagesOnly	True False	False	Display the top level items
SubImagesOnly	True False	False	Display the sub menus as
IncludeMemberContent	True False	False	If 'True' will display
MemberContentOnly	True False	False	If 'True' will display



ApprovedMemberContentOnly	True False	True	If 'True' will display
CurrentMemberOnly	True False	False	If 'True' will display for
Member	String		set up the member's ID
TopLevelSeparators	True False	False	If 'True' includes a top
TopLevelSeparatorText	String		If 'True' includes a
SelectParents	True False	False	If 'True' will class the
NoImages	True False	False	Stops the menu from
Level1OffsetX	Int32	0	rendering any Sets the offset
Level1OffsetY	Int32	0	from the
Level2OffsetX	Int32	0	" "
Level2OffsetY	Int32	0	" "
Level3OffsetX	Int32	0	" "
Level3OffsetY	Int32	0	" "
Level4OffsetX	Int32	0	" "
Level4OffsetY	Int32	0	" "
Level5OffsetX	Int32	0	" "
Level5OffsetY	Int32	0	" "
ShowMemberPages	True False	False	If "True" will show member
ShowMemberPagesForRoles	String		Specify which member
Direction	ItemFlow	Horizontal	Vertical, Horizo
SubMenuDirection	ItemFlow	Vertical	Vertical, Horizo
CollapseAnimType	AnimationType	InQuint	None, Linear, InQuad, OutQuad, InOutQuad, InCubic, OutCubic, InOutCubic, InQuart, OutQuart, InOutQuart, InQuint, OutQuint, InOutQ



			ExpandAnimType	AnimationType	OutQuint	None,Linear,InQuad,OutQuad,InOutQuad,InCubic,OutCubic,InOutCubic,InQuart,OutQuart,InOutQuart,InQuint,OutQuint,InOutQuint
			ExpandDirection	ExpandDirection	Auto	Auto,Up,Down
pbBreadcrumb	Provides a dynamic 'breadcrumb trail' of where the user currently is in the website	http://www.cityofliberty.org/About/City_Hall.aspx http://www.cfmvc.com.au/Products/Catering-Equipment/General-Cooking-Equipment.aspx	CssClass	String	pbBreadcrumb	Allows you to override the
			Separator	String	 > 	Sets the separator character
			ShowInvisible	True False	False	if True, Show
			IncludeFolders	True False	False	if True, Include
			IncludeMenuItems	True False	False	if True, Include Menu
			IncludeCategories	True False	False	If 'True' will display
			UseLastVisitedCategory	True False	False	n/a
pbPageSummary	Lists website pages in an unordered list. By default it will dynamically list pages underneath the current page or, if there are none, pages at the same level. You can fix the pages listed by specifying a StartPage.	http://www.dvanda.com.au/Whoweare/OurCompany.aspx http://endeavourliving.com.au/homes.aspx	StartPage	String		The control will only list pages underneath
			CssClass	String	pbSummary	Allows you to override the
			Template	String		Allows you to select a
			ShowInactive	True False	False	If true the control will
			ShowInvisible	True False	False	if true, the control will
			OnlyShowChildPages	True False	False	Disables the listing of
			IncludeMenuItems	True False	True	Include menu items in page
			IncludeMemberContent	True False	False	if True, include
			MemberContentOnly	True False	False	if True, display member's



			ApprovedMemberContentOnly	True False	True	If True, display approved
			CurrentMemberOnly	True False	False	if True, display current login
			Member	String		if set up the member's ID or username,
pbSiteMap	Build the site map control.	http://www.pegboardcms.com/Sub/Sitemap.aspx http://endeavourliving.com.au/sitemap.aspx	StartPage	String		Specify the start page for
			StartPagelsRoot	True False	True	True' by default.
			TreeWidth	Unit		Specify the width of the
			TreeHeight	Unit		Specify the height of the
			TreeSkinID	String	Sitemap	Available skin Ids: SitemapVista, SitemapInox,S
			TreeLevels	Int32	0	Max level of
			TreeExpandAll	True False	True	Set to 'True' by default,
			IncludeMemberContent	True False	False	If 'True' displays
			MemberContentOnly	True False	False	If 'True' displays
			ApprovedMemberContentOnly	True False	True	If 'True' displays only
			CurrentMemberOnly	True False	False	If 'True' displays to
			Member	String		set up the member's ID
			ShowCategories	True False	False	If 'True' will display
			ShowItems	True False	False	If 'True' will display
			ShowInvisible	True False	False	If 'True' will show pages
			SiteMapType	SiteMapTypes	Tree	Tree,List,Adva
pbSiteMap2	Build the site map control.		StartPage	String		Specify the start page for
			StartPagelsRoot	True False	True	True' by default.



level) with a next/previous button.
This tag can be used on Page,
Collection, Collection_Item, and
Category Templates.

ControlType	ButtonControlType	Button	Button,Image
SortField	String	SortOrder	Sets the collection sort field to use
Mode	NavigationDirection	Next	Next,Previous
EnableWrapAround	True False	False	When true, allows the first and last pages to connect to

pbGoogleAnalytics	This controls generates the javascript for Google Analytics Page Tracking and Ecommerce Tracking	http://www.greatdanefurniture.com/	AccountNumber	String		The Google Analytics
			DomainName	String		Enter the domain name to enable sub-
			SetAllowLink	String	true	The value to set for the "_setAllowLink" option. This
			SetAllowHash	String	false	The value to set for the "_setAllowHash" option. This
			EcommerceTrackingMode	True False	False	If 'False' then the control generates Page Tracking javascript. If
			EcommerceAffiliation	String		The "Affiliation"
			EcommerceUseSuburbAsCity	True False	True	If 'True' then set the Ecommerce

pbMenu	Basic unordered list site menu. Allows full control over the appearance (css) and operation (js) of the menu	caju.com.au	RootPath	String		The url path that is treated as the starting point for the menu.



This skincontrol is only available in Pegboard versions 6.5 and greater

IncludeCategories ShowCategories	True False	FALSE	Enable the inclusion of Collection Item Categories in the menu.
IncludeItems ShowItems	True False	FALSE	Enable the inclusion of Collection Items in the menu.
MaxDepth	Integer	0	The maximum depth to recurse the site map when building the menu.
TooltipField	String		The SiteObject field used to populate the title attribute of the menu item. (eg. Name/Summary)
ShowMemberPages	True False	FALSE	Enable the inclusion of Member Content pages in the menu.



ShowMemberPagesForRole	String		Gives the ability to filter the Member Content pages that are included based on the Member's Role.
ContainerTagName	String		The HTML tag name used to wrap the menu control. Leaving this blank will exclude the wrapping element.
RenderContainerID	String		Optionally include an ID on the wrapping container element.
EnableLevelCss	True False	FALSE	Enable the generation of level specific css class to be render in the menu.
LevelCssPrefix	String	level	The prefix that will be added to the level css classes.



		EnableAliasCss	True False	FALSE	Enable the generation of css classes based on the alias of each item in the menu.
		AliasPathCssPrefix	string		The prefix to use when generating css classes based on alias paths.
		EnableItemTypeCss	True False	FALSE	Enable the generation of css classes based on each items SiteObjectType property.
		ItemTypeCssPrefix	String	sot-	The prefix to use when generation TypeCss classes for each item.
		DisableMegaMenus		FALSE	Enable the generation of mega menu HTML rich items in the menu.
pbGoogleMapV3	Google map control representing a single address	GoogleKey	String		Key for use with Google Maps API v3
		DefaultZoom	Int32		15 Zoom ratio for default view



PopupInfoMaxWidth	Unit	300 Maximum width for popup infos on the map
Address	String	Address to show on the map
Name	String	Name of the location on the map
PopupContent	String	Content for the popup





Content

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbContent	Inserts an editable content region that is managed in the console with a WYSIWYG editor. This replaces the pbEditableRegion in PB4. All pbContent tags must have a 'region name' specified	http://www.pegboardcms.com	CssClass	String	content	Sets the CSS class that is applied to the container set by ContainerType (if any).
			RegionName	String		Each tag within a template must have a different RegionName. The RegionName is used as the label on the tab above the editor in the console
			StripHtml	True False	False	If true, removes all html markup from the content.
			Toolset	String		n/a
			ContainerType	None Span Div	None	content in
pbContentEx	Inserts content from another page	http://www.pegboardcms.com	CssClass	String	content	Sets the CSS class that is applied to the container set by ContainerType (if any).
			PageName	String		The Name or Alias of the page to extract content from
			RegionName	String		The Region to extract content from
			StripHtml	True False	False	If true, removes all html markup from the content.
			Toolset	String		n/a
			ContainerType	None Span Div	None	Type of container to wrap the content in

Control Tags

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbContent pbCtContent	Inserts an editable content region that is managed in the console with a WYSIWYG editor. This replaces the pbEditableRegion in PB4. All pbContent tags must have a 'region name' specified		RegionName	String		Each tag within a template must have a different RegionName. The RegionName is used as the label on the tab above the editor in the console
			StripHtml	True False	False	If true, removes all html markup from the content.



pbContentEx	Inserts content from another page	ContainerType	None Span Div	None	Type of container to wrap the content in
		Toolset	String		n/a
		CssClass	String	content	Sets the CSS class that is applied to the container set by ContainerType (if any).
		PageName	String		The Name or Alias of the page to extract content from
		RegionName	String		The Region to extract content from
		StripHtml	True False	False	If true, removes all html markup from the content.
		Toolset	String		n/a
		ContainerType	None Span Div	None	Type of container to wrap the content in



Images

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbImageThumbnail	Inserts a thumbnail image no bigger than the width and height supplied.		Height	Number	100	Max. Height in pixels
			ImagePath	Path to image	n/a	The relative path to the image (Required)
			NavigationTarget	Hyperlink Target	n/a	If specified with the URL, the supplied target is added to the link
			NavigationURL	Hyperlink URL	n/a	If specified, the thumbnail is wrapped in a hyperlink to the supplied URL
pbImage	Inserts an image that is manageable through the console. This is similar in principle to the pbContent tag but useful where a single image is desired. (The ImageName is required and follows the same rules as RegionName on the pbContent tag).		Width	Number	100	Max. Width in pixels
			Alt	String		Lets you override the alt text on the image tag
			Title	String		Lets you override the title property on the image tag.



ImageName	String		Each tag within a template must have a different ImageName. The ImageName is used as the label for the image in the console
CssClass	String	pbImage	Allows you to override the CSS class on the container.
Width	Unit		Width of the image (Required unless Thumbnail="False")
Height	Unit		Height of the image (Required unless Thumbnail="False")
Thumbnail	True False	True	If true, the image is passed through the thumbnail control, which will resample the image to the specified width and height



FilenameOnly	True False	False	Render the filename only, not the image.
AltTextOnly	True False	False	Render the alt text only.
Format	String		add the type
NoImageUrl	String		Specify a default image to display when no image is present
JpgQuality	Int32	90	Jpeg quality settings
GifColors	Int32	255	Color
GifColorBits	Int32	8	Color bits
ShrinkOnly	True False	False	When a image resized by the pegboard thumbnailer it will only down size.
ContainerType	None Span Div	None	Type of container to wrap the content in
pblmageEx	Inserts an image from another page. http://www.pegboardcms.com/Products1/PegboardCMSProductOverview.aspx	Alt	Lets you override the alt text on the image tag
	Title	String	Lets you override the title property on the image tag.



PageName	String		The Name or Alias of the page to extract image from
ImageName	String		The name of the region to extract the image from
CssClass	String	pblImage	Allows you to override the CSS class on the container.
Width	Unit		Width of the image (Required unless Thumbnail="False")
Height	Unit		Height of the image (Required unless Thumbnail="False")
Thumbnail	True False	True	If true, the image is passed through the thumbnail control, which will resample the image to the specified width and height
FilenameOnly	True False	False	Render the filename only, not the image.



AltTextOnly	True False	False	Render the alt text only.
Format	String		add the type
NoImageUrl	String		Specify a default image to display when no image is present
JpgQuality	Int32	90	Jpeg quality settings
GifColors	Int32	255	Color
GifColorBits	Int32	8	Color bits
ShrinkOnly	True False	False	When a image resized by the pegboard thumbnailer it will only down size.
ContainerType	None Span Div	None	Type of container to wrap the content in
UseAltTextAsTooltip	True False	False	If 'True' then set the Tooltip value to the AltText value
pbltemImageGallery	Displays an interactive mini gallery of images for the collection item. (This control is for use on item detail templates).	http://www.rosiesdollsclothes.com.au/Store/DoubleStrapShoe-White.aspx	CssClass
		String	pbltemImageGallery
			Allows you to override the CSS class on the control
ShowMain	True False	True	Show the main preview image



LinkMainImage	True False	True	Wrap the main with a link
ShowTooltips	True False	False	Show the image description as a tooltip
Width	Unit		Set the width of the gallery
Height	Unit		Set the height of the gallery
ImageWidth	Int32	240	Set the width of the main preview image
ImageHeight	Int32	200	Set the height of the main preview image
ThumbWidth	Int32	120	Set the width of the thumbnail images
ThumbHeight	Int32	120	Set the height of the thumbnail images
RepeatColumns	Int32	2	Set the number of columns per row
Align	HorizontalAlign	NotSet	NotSet, Left, Center, Right, Justify
RepeatDir	RepeatDirection	Horizontal	Horizontal, Vertical
RepeatLayout	RepeatLayout	Table	Table, Flow



	Sort	String		Orders the Gallery by the field specified. Can also specify the direction - "ASC DESC"	
	RandomSort	True False	False	If true, items in the Gallery are randomly ordered	
pbltemImageGalleryMain	Displays an interactive mini gallery of images for the collection item. (this control is for use on item detail templates)	http://www.rosiesdollsclothes.com.au/Store/DoubleStrapShoe-White.aspx	Alt	String	Lets you override the alt text on the image tag
	Title	String			Lets you override the title property on the image tag.
	CssClass	String	pblImageGalleryMain		Allows you to override the CSS class on the control
	Width	Unit			Set the width of the gallery
	Height	Unit			Set the height of the gallery



		Thumbnail	True False	True	If true, the image is passed through the thumbnail control, which will resample the image to the specified width and height
		FilenameOnly	True False	False	Render the filename only, not the image.
		ContainerType	None Span Div	None	Type of container to wrap the content in
pbitemImageGalleryThumb	Inserts a thumbnail image no bigger than the width and height supplied.	CssClass	String	pbitemImageGalleryThumb	Allows you to override the CSS class on the control
		Template	String		Allows you to select a different control template folder (always under the "imagegallery" folder)
		SortField	String		Orders the Gallery by the field specified



SortDirection	String	ASC	Switches the order of the Gallery between ascending or descending
MaxRows	Int32	0	The maximum number of items to display in the gallery
Filter	String		Filter the gallery
RandomSort	True False	False	If true, items in the Gallery are randomly ordered

Item Image:

pbImage pbCtlImage	Inserts an image that is managable through the console. This is similar in principle to the pbContent tag but useful where a single image is desired. (The ImageName is required and follows the same rules as RegionName on the pbContent tag).	http://aprilmarieswimwear.com.au/Products/KenDuncanPresents.aspx	Alt	String	Lets you override the alt text on the image tag
			Title	String	Lets you override the title property on the image tag.



ImageName	String		Each tag within a template must have a different ImageName. The ImageName is used as the name for the image region in the console
CssClass	String	pblImage	Allows you to override the CSS class on the container.
Width	Unit		Width of the image (If thumbnailed)
Height	Unit		Height of the image (If thumbnailed)
MinWidth	Int32		MinWidth of image (can't be used with Width)
MinHeight	Int32		MinHeight of image (can't be used with Height)



Thumbnail	True False	True	If true, the image is passed through the thumbnail control, which will resample the image to the specified width and height
FilenameOnly	True False	False	Render the filename only, not the image.
AltTextOnly	True False	False	Render the alt text only.
Format	String		add the type
NoImageUrl	String		Specify a default image to display when no image is present
JpgQuality	Int32	90	Jpeg quality settings
GifColors	Int32	255	Color
GifColorBits	Int32	8	Color bits
ShrinkOnly	True False	False	When a image resized by the pegboard thumbnailer it will only down size.



ContainerType	None Span Div	None	Type of container to wrap the content in
UseAltTextAsTooltip	True False	False	If 'True' then set the Tooltip value to the AltText value



Forms Module

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbForm	This tag acts as a placeholder for any form. When used on a form template it will simply insert the form belonging to the current page. You can also use it on other templates by specifying the Form property	http://www.jumpfirst.com.au/Contact_Us.aspx http://www.emergencyteachers.com.au/TeacherandChildcareStaffProfile/TeachersForms/TeacherRegistration.aspx?gclidCollection=VIC1&Profile_State=VIC&Profile_SD=12/07/2010	Action	String		target URL for the form post (use when posting to external pages)
			Method	String	post	Specify a form method
			SendEmail	True False	True	If ture the control will force sending form email when does Action
			EnableAjax	True False	False	Enables Ajax overlay while form is submitting
			RedirectTo	String		Makes the form redirect to the specified URL after the user submits it
			PasswordFieldName	String	Password	Specify the password field name
			EmailFromFieldName	String	EmailFrom	Specify the email from field name
			EmailSubjectFieldName	String	EmailSubject	Specify the email subject field name
			UserEmailAddressFieldName	String	EmailAddress	Specify the email address field name
			AdminEmailAddressFieldName	String	AdminEmailAddress	Specify the administrator email address
			Form	String		Allows you to override the form being displayed. By default the current form page is used (if applicable)
			SubmitButtonText	String	Submit	Lets you override the text on the submit button
			CssClass	String	pbForm	Allows you to override the CSS class on the form
			ReceivedText	String	Thankyou, your enquiry has been submitted	Set the recieved text upon submission
			UserSMSFieldName	String	UserSMS	Specify the user sms field name
			AdminSMSFieldName	String	AdminSMS	Specify the administrator sms field name
			Publication	String		Publication in EMarketing to signup
			PublicationsFieldName	String	Campaigns	EmailAddress to Form field with Campaign values (please use the form field attribute DataSource to auto-populate this field)



EnableEmSignup	True False	False	If 'True' will add the form values as an EMarketing subscriber
ConfirmMessage	String		Specify a confirmation message (causes a confirmation popup)
EmailDelayHours	Int32	0	Number of hours to delay the sending of user emails
EmailDelayMinutes	Int32	0	Number of minutes to delay the sending of user emails
AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of administrator emails
AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the sending of administrator emails
AdminAttachUploads	True False	False	Will cause all FileUpload field values to be attached to the administrator email when sent out
UserAttachUploads	True False	False	Will cause all FileUpload field values to be attached to the user email when sent out
UserSMSCountry	Int32	61	Country code that the user SMS is to be sent to
AdminSMSCountry	Int32	61	Country code that the admin SMS is to be sent to
MaxUserSMS	Int32	10	Max number of SMS messages that a number can receive
MaxUserSMSText	String	Maximum number of SMS already sent to this number	Message displayed when max number of SMS messages reached
OnClientClick	String		JavaScript to attach to the Form Submit Button's OnClick event
UserSMSExpiryHours	Int32	0	SMS messages, used as part of the "MaxUserSMS" property can expire after the specified number of hours. A value of 0 means it never expires
ValidationGroup	String		Sets the form validation group (use this to separate multiple forms on a single page)

Advanced Forms

pbFormField	Displays the individual form fields on a page. This skintag will only	http://www.elixia.com.au/Sig_n_Up.aspx	FormGroup	String	Default	Used if there are more than one advanced forms on one page
-------------	---	---	-----------	--------	---------	--



render the specified field.

<http://www.wcaa.com.au/Victoria/Membership-Application-VIC.aspx>

Field	String		Each form field must have it's own field name
EnableUsernameValidation	True False	False	If 'True' will check whether the username entered is valid
FieldType	String		Specify the field type eg. Text
FilenameOnly	True False	False	n/a
EnableEmailTest	True False	False	Enable email address validation
EnablePrepopulate	True False	True	If 'False' then the form field will not be prepopulated with url parameters
ValidationGroup	String		The form validation group to link the form field to
ReadOnly	True False	False	If 'True' then the form field will be read-only

pbFormFieldList

Displays all form fields on a page inside an unordered list

FormGroup	String	Default	Used if there are more than one advanced forms on one page
RenderTable	True False	False	If True renders fields in a table. If False renders fields in an unordered list.
ValidationGroup	String		Separates validation between multiple forms on a single page

pbFormSubmit

Displays the submit button and works in conjunction with the pbFormField skintag.

<http://www.elixia.com.au/Sign Up.aspx>
<http://www.wcaa.com.au/Victoria/Membership-Application-VIC.aspx>

Action	String		Set the action for the form
Method	String	post	Set the method for the form
FormGroup	String	Default	Used if there are more than one advanced forms on one page
FormName	String		Specify which form to use from the console
ButtonText	String	Submit	Set the submit button text
ImageUrl	String		Set an image for the button if the ControlType="Image"
SendEmail	True False	False	If 'True' will send the user a confirmation email
EmailFromFieldName	String	EmailFrom	Specify the email from field name
EmailSubjectFieldName	String	EmailSubject	Specify the email subject field name
UserEmailAddressFieldName	String	EmailAddress	Specify the email address field name



AdminEmailAddressFieldName	String	AdminEmailAddress	Specify the administrator email address
PasswordFieldName	String	Password	Specify the password field name
ReceivedText	String	Thankyou, your enquiry has been submitted	Allows you to override the CSS class on the form
UserSMSFieldName	String	UserSMS	Specify the user sms field name
AdminSMSFieldName	String	AdminSMS	Specify the administrator sms field name
UserSMSCountryFieldName	String	UserSMSCountry	Specify the user's sms country
AdminSMSCountryFieldName	String	AdminSMSCountry	Specify the administrator sms country
MaxUserSMSCountFieldName	String	MaxUserSMSCount	Set a maximum amount of SMS sent to each user
MaxUserSMSMessageFieldName	String	MaxUserSMSMessage	" "
UserSMSExpiryPeriodFieldName	String	UserSMSExpiryPeriod	n/a
RedirectTo	String		Set a redirect page after submission
ConfirmMessage	String		Set a confirmation message upon submission
EmailDelayHours	Int32	0	Set the email delay in hours
EmailDelayMinutes	Int32	0	Set the email delay in minutes
AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of administrator emails
AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the sending of administrator emails
AdminAttachUploads	True False	False	If 'True' allows the admin to attach uploads
UserAttachUploads	True False	False	N/A
ControlType	SubmitControlTypes	Button	Button,ImageButton,LinkButton
AllowMultipleMemberForms	True False	True	If 'False' then a member can only submit the form once
MultipleMemberFormsErrorText	String	You have submitted this form previously. This form cannot be submitted more than once.	Message to display if a member tries to submit the form more than once
ValidationGroup	String		The form validation group to apply to when submitting the form
UseRadButton	True False	FALSE	Renders the submit button as a Telerik RadButton which automatically disables during form processing.
pbDocumentUploadFormSubmit	Display a submit button to upload documents. This works in http://www.freshpictmedia.com.au	DocumentFieldName	Document
		String	Specify the document field name



conjunction with the pbFormField skintag.

NameFieldName	String	Name	Specify the documents name field name
Collection	String		Specify the collection to grab items from
FormGroup	String	Default	Select a form group
FormName	String		Specify the form to upload the document
ButtonText	String	Submit	Insert button text
ImageUrl	String		Use to select an image for the submit button
SendEmail	True False	False	If 'True' sends an email
EmailFromFieldName	String	EmailFrom	Specify the email from field name
EmailSubjectFieldName	String	EmailSubject	Specify the email subject field name
UserEmailAddressFieldName	String	EmailAddress	Specify the email address field name
AdminEmailAddressFieldName	String	AdminEmailAddress	Specify the administrator email address
PasswordFieldName	String	Password	Specify the password field name
ReceivedText	String	Thankyou, your enquiry has been submitted	Set the recieved text upon submission
UserSMSFieldName	String	UserSMS	Specify the user sms field name
AdminSMSFieldName	String	AdminSMS	Specify the administrator sms field name
UserSMSCountryFieldName	String	UserSMSCountry	Specify the user's sms country
AdminSMSCountryFieldName	String	AdminSMSCountry	Specify the administrator sms country
MaxUserSMSCountFieldName	String	MaxUserSMSCount	Set a maximum amount of SMS sent to each user
MaxUserSMSMessageFieldName	String	MaxUserSMSMessage	Allows the subscriber to limit the number of SMSs that may be sent to them from the system.
UserSMSExpiryPeriodFieldName	String	UserSMSExpiryPeriod	Allows the subscriber to limit the time period passed before the number of SMSs sent expires
RedirectTo	String		Set a redirect page after submission
ConfirmMessage	String		Set a confirmation message upon submission
EmailDelayHours	Int32	0	Set the email delay in hours
EmailDelayMinutes	Int32	0	Set the email delay in minutes
AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of administrator emails



			AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the sending of administrator emails
			AdminAttachUploads	True False	False	If 'True' allows the admin to attach uploads
			UserAttachUploads	True False	False	N/A
			ControlType	SubmitControlTypes	Button	Button,ImageButton,LinkButton
			AllowMultipleMemberForms	True False	True	If 'False' then a member can only submit the form once
			MultipleMemberFormsErrorText	String	You have submitted this form previously. This form cannot be submitted more than once.	Message to display if a member tries to submit the form more than once
			ValidationGroup	String		The form validation group to apply to when submitting the form
			UseRadButton	True False	FALSE	Renders the submit button as a Telerik RadButton which automatically disables during form processing.
			pbEmMemberSignupFormSubmit	Display a submit button to signup emarketing subscribers and members. This works in conjunction with the pbFormField skintag.	http://www.brainboost.com.au/Members_SignUp.aspx	
			AddMemberToRole	String		Specify member roles (separated by a ',') which new members will be added to by default upon signing up
			Publication	String		Specify a publication to assign the subscriber to
			NewMemberActive	True False	True	Specifies whether new members signing up will be active by default
			PublicationsFieldName	String	Campaigns	Form field to mutiple publications
			UsernameFieldName	String	Username	nominate the username field
			UsernameMaxLength	Int32	0	Set the username maximum length
			PasswordMaxLength	Int32	0	Set the password maximum length
			FormGroup	String	Default	Set the form group
			FormName	String		Set the form name, this is used when there are multiple forms on a page
			ButtonText	String	Submit	Change the text for the submit button, is set to 'Submit' by default
			ImageUrl	String		Specify the path for the image if using an image button



SendEmail	True False	False	If 'True' sends an email to the user
EmailFromFieldName	String	EmailFrom	Set the email subject field name
EmailSubjectFieldName	String	EmailSubject	Set the email subject field name
UserEmailAddressFieldName	String	EmailAddress	Set the user email address field name
AdminEmailAddressFieldName	String	AdminEmailAddress	Set the admin email address field name
PasswordFieldName	String	Password	Set the password field name
ReceivedText	String	Thankyou, your enquiry has been submitted	Use this property to change the recieved text
UserSMSFieldName	String	UserSMS	Set the user SMS field name
AdminSMSFieldName	String	AdminSMS	Set the administrator SMS field name
UserSMSCountryFieldName	String	UserSMSCountry	Set the user SMS country field name
AdminSMSCountryFieldName	String	AdminSMSCountry	Set the administrator SMS country field name
MaxUserSMSCountFieldName	String	MaxUserSMSCount	Set a maximum amount of SMS sent to each user
MaxUserSMSMessageFieldName	String	MaxUserSMSMessage	Allows the subscriber to limit the number of SMSs that may be sent to them from the system.
UserSMSExpiryPeriodFieldName	String	UserSMSExpiryPeriod	Allows the subscriber to limit the time period passed before the number of SMSs sent expires
RedirectTo	String		Set the redirect page upon submission
ConfirmMessage	String		Set the confirmation message
EmailDelayHours	Int32	0	Set the delay in hours for the user to recieve a confirmation email
EmailDelayMinutes	Int32	0	Set the delay in minutes for the user to recieve a confirmation email
AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of administrator emails
AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the sending of administrator emails
AdminAttachUploads	True False	False	If 'True' allow the administrator to attach uploads
UserAttachUploads	True False	False	If 'True' allow the user to attach uploads
ControlType	SubmitControlTypes	Button	Button,ImageButton,LinkButton



			AllowMultipleMemberForms	True False	True	If 'False' then a member can only submit the form once
			MultipleMemberFormsErrorText	String	You have submitted this form previously. This form cannot be submitted more than once.	Message to display if a member tries to submit the form more than once
			ValidationGroup	String		The form validation group to apply to when submitting the form
			UseRadButton	True False	FALSE	Renders the submit button as a Telerik RadButton which automatically disables during form processing.
pbEmSignupFormSubmit	Display a submit button to signup emarketing subscribers. This works in conjunction with the pbFormField skintag.	http://www.brainboost.com.au/forms/newsletter.aspx	Publication	String		Specify a publication to assign the subscriber to
			PublicationsFieldName	String	Campaigns	Form field to mutiple publications
			FormGroup	String	Default	Set the form group
			FormName	String		Set the form name, this is used when there are multiple forms on a page
			ButtonText	String	Submit	Change the text for the submit button, is set to 'Submit' by default
			ImageUrl	String		Specify the path for the image if using an image button
			SendEmail	True False	False	If 'True' sends an email to the user
			EmailFromFieldName	String	EmailFrom	Set the email subject field name
			EmailSubjectFieldName	String	EmailSubject	Set the email subject field name
			UserEmailAddressFieldName	String	EmailAddress	Set the user email address field name
			AdminEmailAddressFieldName	String	AdminEmailAddress	Set the admin email address field name
			PasswordFieldName	String	Password	Set the password field name
			ReceivedText	String	Thankyou, your enquiry has been submitted	Use this property to change the recieved text
			UserSMSFieldName	String	UserSMS	Set the user SMS field name
			AdminSMSFieldName	String	AdminSMS	Set the administrator SMS field name
			UserSMSCountryFieldName	String	UserSMSCountry	Set the user SMS country field name
	AdminSMSCountryFieldName	String	AdminSMSCountry	Set the administrator SMS country field name		



		MaxUserSMSCountFieldName	String	MaxUserSMSCount	Set a maximum amount of SMS sent to each user
		MaxUserSMSMessageFieldName	String	MaxUserSMSMessage	Allows the subscriber to limit the number of SMSs that may be sent to them from the system.
		UserSMSExpiryPeriodFieldName	String	UserSMSExpiryPeriod	Allows the subscriber to limit the time period passed before the number of SMSs sent expires
		RedirectTo	String		Set the redirect page upon submission
		ConfirmMessage	String		Set the confirmation message
		EmailDelayHours	Int32	0	Set the delay in hours for the user to receive a confirmation email
		EmailDelayMinutes	Int32	0	Set the delay in minutes for the user to receive a confirmation email
		AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of administrator emails
		AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the sending of administrator emails
		AdminAttachUploads	True False	False	If 'True' allow the administrator to attach uploads
		UserAttachUploads	True False	False	If 'True' allow the user to attach uploads
		ControlType	SubmitControlTypes	Button	Button,ImageButton,LinkButton
		AllowMultipleMemberForms	True False	True	If 'False' then a member can only submit the form once
		MultipleMemberFormsErrorText	String	You have submitted this form previously. This form cannot be submitted more than once.	Message to display if a member tries to submit the form more than once
		ValidationGroup	String		The form validation group to apply to when submitting the form
		UseRadButton	True False	FALSE	Renders the submit button as a Telerik RadButton which automatically disables during form processing.
pbEventRegistrationFormSubmit	Display a submit button to register users for events. This works in conjunction with the pbFormField skintag.	ConfirmByDefault	True False	False	If 'True' will confirm registration immediately
		NoSeatsMessage	String	There are no more seats available for this event	Display a message when there are no seats available
		NotEnoughSeatsMessage	String	There are not enough seats available to complete your purchase	Display a message when there are not enough seats available



FormGroup	String	Default	Used if there are more than one advanced form on a page. Apply this to each form field so that the form elements are grouped together.
FormName	String		Set the form name, this is used when there are multiple forms on a page
ButtonText	String	Submit	Set the text for the submit button
ImageUrl	String		Set an image URL if the submit button is to be an image
SendEmail	True False	False	If 'True' will send an email to the register
EmailFromFieldName	String	EmailFrom	Set the email subject field name
EmailSubjectFieldName	String	EmailSubject	Set the email subject field name
UserEmailAddressFieldName	String	EmailAddress	Set the user email address field name
AdminEmailAddressFieldName	String	AdminEmailAddress	Set the admin email address field name
PasswordFieldName	String	Password	Set the password field name
ReceivedText	String	Thankyou, your enquiry has been submitted	Use this property to change the recieved text
UserSMSFieldName	String	UserSMS	Set the user SMS field name
AdminSMSFieldName	String	AdminSMS	Set the administrator SMS field name
UserSMSCountryFieldName	String	UserSMSCountry	Set the user SMS country field name
AdminSMSCountryFieldName	String	AdminSMSCountry	Set the administrator SMS country field name
MaxUserSMSCountFieldName	String	MaxUserSMSCount	Set the max user sms count field name
MaxUserSMSMessageFieldName	String	MaxUserSMSMessage	Set the max user sms message field name
UserSMSExpiryPeriodFieldName	String	UserSMSExpiryPeriod	
RedirectTo	String		Set the redirect page upon submission
ConfirmMessage	String		Set the confirmation message
EmailDelayHours	Int32	0	Set the delay in hours for the user to recieve a confirmation email
EmailDelayMinutes	Int32	0	Set the delay in minutes for the user to recieve a confirmation email
AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of administrator emails



AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the sending of administrator emails
AdminAttachUploads	True False	False	If 'True' allow the administrator to attach uploads
UserAttachUploads	True False	False	If 'True' allow the user to attach uploads
ControlType	SubmitControlTypes	Button	Button,ImageButton,LinkButton
SeatsFieldName	String	Seats	Set the Seats field name
NameFieldName	String	ContactName	Set the ContactName field name
AddressFieldName	String	ContactAddress	Set the ContactAddress field name
Address2FieldName	String	ContactAddress2	Set the ContactAddress2 field name
SuburbFieldName	String	ContactSuburb	Set the ContactSuburb field name
StateFieldName	String	ContactState	Set the ContactState field name
PostcodeFieldName	String	ContactPostcode	Set the ContactPostcode field name
CountryFieldName	String	ContactCountry	Set the ContactCountry field name
PhoneFieldName	String	ContactPhone	Set the ContactPhone field name
FaxFieldName	String	ContactFax	Set the ContactFax field name
MobileFieldName	String	ContactMobile	Set the ContactMobile field name
EmailFieldName	String	ContactEmail	Set the ContactEmail field name
CompanyFieldName	String	Company	Set the Company field name
PositionFieldName	String	Position	Set the Position field name
DateOfBirthFieldName	String	DateOfBirth	Set the DateOfBirth field name
CommentsFieldName	String	Comments	Set the Comments field name
AttendeesFieldName	String	Attendees	Set the Attendees field name
HearAboutUsFieldName	String	HearAboutUs	Set the HearAboutUs field name
AllowMultipleMemberForms	True False	True	If 'False' then a member can only submit the form once
MultipleMemberFormsErrorText	String	You have submitted this form previously. This form cannot be submitted more than once.	Message to display if a member tries to submit the form more than once
ValidationGroup	String		The form validation group to apply to when submitting the form
UseRadButton	True False	FALSE	Renders the submit button as a Telerik RadButton which automatically disables during form processing.



pbJobApplicationFormSubmit	Display a submit button to upload jobs applications. This works in conjunction with the pbFormField skintag.	FormGroup	String	Default	Used if there are more than one advanced form on a page. Apply this to each form field so that the form elements are grouped together.
		FormName	String		Specify a form to use from the console
		ButtonText	String	Submit	Set the text for the submit button
		ImageUrl	String		If the control type is set to 'Image', set the path of the image to appear for the link
		SendEmail	True False	False	If 'True' will send an email to the user
		EmailFromFieldName	String	EmailFrom	Set the email subject field name
		EmailSubjectFieldName	String	EmailSubject	Set the email subject field name
		UserEmailAddressFieldName	String	EmailAddress	Set the user email address field name
		AdminEmailAddressFieldName	String	AdminEmailAddress	Set the admin email address field name
		PasswordFieldName	String	Password	Set the password field name
		ReceivedText	String	Thankyou, your enquiry has been submitted	Use this property to change the recieved text
		UserSMSFieldName	String	UserSMS	Set the user SMS field name
		AdminSMSFieldName	String	AdminSMS	Set the administrator SMS field name
		UserSMSCountryFieldName	String	UserSMSCountry	Set the user SMS country field name
		AdminSMSCountryFieldName	String	AdminSMSCountry	Set the administrator SMS country field name
		MaxUserSMSCountFieldName	String	MaxUserSMSCount	Set the max user sms count field name
		MaxUserSMSMessageFieldName	String	MaxUserSMSMessage	Set the max user sms message field name
		UserSMSExpiryPeriodFieldName	String	UserSMSExpiryPeriod	n/a
		RedirectTo	String		Set the redirect page upon submission
		ConfirmMessage	String		Set the confirmation message
		EmailDelayHours	Int32	0	Set the delay in hours for the user to receive a confirmation email
		EmailDelayMinutes	Int32	0	Set the delay in minutes for the user to receive a confirmation email
		AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of administrator emails



		AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the sending of administrator emails
		AdminAttachUploads	True False	False	If 'True' allow the administrator to attach uploads
		UserAttachUploads	True False	False	If 'True' allow the user to attach uploads
		ControlType	SubmitControlTypes	Button	Button,ImageButton,LinkButton
		AllowMultipleMemberForms	True False	True	If 'False' then a member can only submit the form once
		MultipleMemberFormsErrorText	String	You have submitted this form previously. This form cannot be submitted more than once.	Message to display if a member tries to submit the form more than once
		ValidationGroup	String		The form validation group to apply to when submitting the form
		UseRadButton	True False	FALSE	Renders the submit button as a Telerik RadButton which automatically disables during form processing.
pbMemberPaidSignupFormSubmit pbMemberSignupFormSubmit	Display a submit button to signup members. This works in conjunction with the pbFormField skintag.	http://www.sydneywomensnetwork.com.au/MembershipRegistration.aspx	AddMemberToRole	String	Specify member roles (separated by a ',') which new members will be added to by default upon signing up
		NewMemberActive	True False	True	Specifies whether new members signing up will be active by default
		UsernameFieldName	String	Username	nominate the username field
		RandomPassword	True False	False	Generate a random password for the member (emailtag [RandomPassword])
		AddProfileToCollection	True False	False	Gives the ability to enter the members details into a collection
		NewMemberContentActive	True False	False	If 'True' will make the member immediately active without administrator authorisation
		BillingProductFieldName	String	BillingProduct	Relate the member to a product
		SignupRequiresPayment	True False	False	If 'True' member must make payment for membership, goes through checkout process
		RequiresPayment	True False	False	
		ButtonTextOnUpdate	String	Update details	Specify the confirmation text
		UpdateConfirmText	String	Thankyou, your details have been updated	Change the update confirmation text



UsernameMaxLength	Int32	0	Set a max length for the username
PasswordMaxLength	Int32	0	Set a max length for the password
FormGroup	String	Default	Used if there are more than one advanced forms on the page
FormName	String		Specify a form from the console
ButtonText	String	Submit	Edit the button text
ImageUrl	String		Set the image URL if using an image control type
SendEmail	True False	False	If 'True' send the user an email
EmailFromFieldName	String	EmailFrom	Specify an email from field name
EmailSubjectFieldName	String	EmailSubject	Specify an email subject field name
UserEmailAddressFieldName	String	EmailAddress	Specify a user email address field name
AdminEmailAddressFieldName	String	AdminEmailAddress	Specify an administrator email address field name
PasswordFieldName	String	Password	Set a password field name
ReceivedText	String	Thankyou, your enquiry has been submitted	Set the text displayed upon submission
UserSMSFieldName	String	UserSMS	Set the user SMS field name
AdminSMSFieldName	String	AdminSMS	Set the administrator SMS field name
UserSMSCountryFieldName	String	UserSMSCountry	Set the user SMS country field name
AdminSMSCountryFieldName	String	AdminSMSCountry	Set the administrator SMS country field name
MaxUserSMSCountFieldName	String	MaxUserSMSCount	Set the max user sms count field name
MaxUserSMSMessageFieldName	String	MaxUserSMSMessage	Set the max user sms message field name
UserSMSExpiryPeriodFieldName	String	UserSMSExpiryPeriod	
RedirectTo	String		Page to redirect to after form submission
ConfirmMessage	String		Set the confirmation message
EmailDelayHours	Int32	0	Set the delay in hours for the user to receive a confirmation email
EmailDelayMinutes	Int32	0	Set the delay in minutes for the user to receive a confirmation email
AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of administrator emails



			AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the sending of administrator emails
			AdminAttachUploads	True False	False	If 'True' allow the administrator to attach uploads
			UserAttachUploads	True False	False	If 'True' allow the user to attach uploads
			ControlType	SubmitControlTypes	Button	Button,ImageButton,LinkButton
			NewMemberRequiresConfirmation	True False	False	If 'True' then the membership will not be activated until the member has confirmed their membership by navigating to a members confirmation page sent to them in the email.
			AllowMultipleMemberForms	True False	True	If 'False' then a member can only submit the form once
			MultipleMemberFormsErrorText	String	You have submitted this form previously. This form cannot be submitted more than once.	Message to display if a member tries to submit the form more than once
			ValidationGroup	String		The form validation group to apply to when submitting the form
			RoleFieldNames	String	"RoleName"	Comma separated list of field names that are used to capture the role names that the member is in / is to be associated with.
			AllowUsernameUpdate	True False	False	When 'True', allows a username to be updated
			UseRadButton	True False	FALSE	Renders the submit button as a Telerik RadButton which automatically disables during form processing.
pbMemberContentFormSubmit	Display a submit button so members can submit contents. This works in conjunction with the pbFormField skintag.	http://www.wcaa.com.au/Victoria/Membership-Application-VIC.aspx	ContentParent	String		Specify the collection parent of the item
			ObjectType	String		Product, Datalist, News etc
			BillingProduct	String		Path to product item
			GoToCart	True False	False	If 'True' redirects to shopping cart
			GoToCheckout	True False	False	If 'True' redirects to checkout page
			LogActionText	String		N/A
			LogSummaryText	String	{Summary}	N/A
			FormGroup	String	Default	N/A
			FormName	String		Specify the name of the console form to use



ButtonText	String	Submit	Specify the text displayed on submit button
ImageUrl	String		The path to the image if an image is used for the button
SendEmail	True False	False	If 'True' sends the user an email after submission
EmailFromFieldName	String	EmailFrom	The form field for the from email address
EmailSubjectFieldName	String	EmailSubject	The form field for the email subject
UserEmailAddressFieldName	String	EmailAddress	The form field for the user email address
AdminEmailAddressFieldName	String	AdminEmailAddress	The form field for the admins email address
PasswordFieldName	String	Password	The form field for the users password
ReceivedText	String	Thankyou, your enquiry has been submitted	The text displayed after the form is submitted
UserSMSFieldName	String	UserSMS	Set the user SMS field name
AdminSMSFieldName	String	AdminSMS	Set the administrator SMS field name
UserSMSCountryFieldName	String	UserSMSCountry	Set the user SMS country field name
AdminSMSCountryFieldName	String	AdminSMSCountry	Set the administrator SMS country field name
MaxUserSMSCountFieldName	String	MaxUserSMSCount	Set the max user sms count field name
MaxUserSMSMessageFieldName	String	MaxUserSMSMessage	Set the max user sms message field name
UserSMSExpiryPeriodFieldName	String	UserSMSExpiryPeriod	N/A
RedirectTo	String		Page to redirect to after form submission
ConfirmMessage	String		Set the confirmation message
EmailDelayHours	Int32	0	Set the delay in hours for the user to receive a confirmation email
EmailDelayMinutes	Int32	0	Set the delay in minutes for the user to receive a confirmation email
AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of administrator emails
AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the sending of administrator emails
AdminAttachUploads	True False	False	If 'True' allow the administrator to attach uploads



UserAttachUploads	True False	False	If 'True' allow the user to attach uploads
ControlType	SubmitControlTypes	Button	Button,ImageButton,LinkButton
AllowMultipleMemberForms	True False	True	If 'False' then a member can only submit the form once
MultipleMemberFormsErrorText	String	You have submitted this form previously. This form cannot be submitted more than once.	Message to display if a member tries to submit the form more than once
ValidationGroup	String		The form validation group to apply to when submitting the form
NewMemberContentActive	True False	False	If 'True' will make new content active without needing authorisation
RemoveExistingRoles	True False	False	If 'True' will delete the existing roles that the associated member is in.
IsUpgrade	True False	False	Should be set to 'True' when the form is used to update content and BillingProduct has been set
PendingMembersContentActive	True False	False	If IsUpgrade is 'True', when 'True' this will allow the upgraded content to be active when the order has been completed
PendingMembersContentVisible	True False	False	If IsUpgrade is 'True', when 'True' this will allow the upgraded content to be visible when the order has been completed
CopyCategories	True False	False	If 'True' the categories that the content is associate with are copied over to the pending content. This is only relevant when IsUpgrade is 'True'
UseRadButton	True False	FALSE	Renders the submit button as a Telerik RadButton which automatically disables during form processing.
pbFormHiddenCaptcha	Place the hidden the captcha on a form page	http://www.wcaa.com.au/Victoria/Membership-Application-VIC.aspx	FormGroup
		String	"Default"
			The FormGroup property is used when there is more than one free form on a page.



pbFormErrors	Display the submission errors for forms. E.g. Required field	http://www.wcaa.com.au/Victoria/Membership-Application-VIC.aspx	FormGroup	String	"Default"	The FormGroup property is used when there is more than one free form on a page
			CssClass	String	-	Apply a CSS class to the errors
			DisplayMode	BulletList List SingleParagraph	"BulletList"	Select how to display the errors BulletList List SingleParagraph
			HeaderText	String	-	Specify a header text
			ShowMessageBox	True False	"False"	If 'True' will show a message box
			Width	Unit	-	Set the width of the error box
			Height	Unit	-	Set the height of the error box
			BackColor	Color	-	Set the back colour of the error box
			BorderColor	Color	-	Apply a border colour to the error box
			BorderStyle	BorderStyle	"None"	Set a border style
			BorderWidth	Unit	"1px"	Set the border width. By default set to 1px thick
			ForeColor	Color	"Red"	Set the forecolour
			RenderInUpdatePanel	True False	"False"	Render the validation errors in an AJAX panel (this is required to be "True" for Checkout pages when using pbAdvCustomerDetails)
pbAdditionalFieldLookupValue	Display a field value from related lookup data.		Field	String	-	Name of the additional field
			LookupField	String	-	Name of the field to retrieve from the related lookup record



Basic Search

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbBasicSearch	Provides a simple keyword-style search on all website content. Search results are displayed by any pbCollectionList or pbCollectionGrid control	http://www.star21.com.au http://www.redscooter.com.au/	ResultsPage	String		Specifies the page that the search will redirect to, to display results. The results page should contain a [pbCollectionList] or [pbCollectionGrid] tag to list the results. If unspecified, the same page will be used (no redirect)
			LabelText	String		Sets the label for the search field
			ButtonText	String	Search	The text for the search button
			PartialMatch	True False	True	If true, partial matches will be returned, otherwise the whole word must be matched
			TextboxWidth	Unit	90px	The width of the search field
			EmptyMessage	String		n/a
			UseStdInput	True False	False	n/a
pbBasicSearchResults	A list control similar to the [pbCollectionList], required to list search results from a [pbBasicSearch].	http://www.star21.com.au/Search-Results.aspx http://www.redscooter.com.au/searchresults.aspx	TopPagerVisible	True False	False	Shows a pager above the list
			BottomPagerVisible	True False	True	Shows a pager below the list
			CssClass	String	pbList	Allows you to override the css class on the UL tag
			ListCssClass	String	list	Allows you to override the CSS class on the li tags
			Template	String		Allows you to select a different control template folder (always under the "list" folder)
			CurrentPage	Int32	0	n/a
			PageSize	Int32	10	Sets the number of items per page. Setting this to 0 disables paging
			IncludeMemberContent	True False	False	If 'True' will display members content
			MemberContentOnly	True False	False	If 'True' will display members content only



ApprovedMemberContentOnly	True False	True	If 'True' will display only members content that has been approved by the administrator
CurrentMemberOnly	True False	False	Will display only for current members
Member	String		set up the member's ID or username
EnableAjax	True False	False	If 'True' will display an ajax on load
Templates			
HeaderTemplate			
ItemTemplate			
AlternatingItemTemplate			
SeparatorTemplate			
FooterTemplate			

pbBasicSearchSummary	Used in conjunction with pbBasicSearch, this provides a brief text summary of the term searched for and the number of results. It should be placed on your results page.	http://www.star21.com.au/Section/Message	String	Your search for {Keyword} returned {Count} results. Lets you override the text displayed - use the placeholders [Keyword] and [Count] in the string to insert the appropriate value	
		IncludeMemberContent	True False	False	If 'True' will display members content
		MemberContentOnly	True False	False	If 'True' will display members content only
		ApprovedMemberContentOnly	True False	True	If 'True' will display only members content that has been approved by the administrator
		CurrentMemberOnly	True False	False	Will display only for current members
		Member	String		set up the member's ID or username

Advanced Search

pbAdvBasicSearch	Provides a simple keyword-style search on all website content. Search results are displayed by any pbCollectionList or pbCollectionGrid control. Please note that need to use the skintag [ContentTemplate] instead of [ItemTemplate] to setup	http://www.brainboost.com.au/Section/ResultsPage	String	""	Usage Example: [pbAdvBasicSearch] [ContentTemplate] [pbTextbox ID="SearchText" ControlType="Text"] [pbButton ID="SearchButton" ControlType="Link"]
		http://www.pegboardcms.com/Section/PartialMatch	PartialMatch	True False	"True"
		Templates			
		ContentTemplate			



this inline control.

[/Contenttemplate]
[/pbAdvBasicSearch]

pbAdvBasicSearchResults	A list control similar to the [pbAdvCollection], required to list search results from a [pbAdvBasicSearch].	http://www.brainboost.com.au/Search_Results.aspx http://www.pegboardcms.com/SearchResults.aspx	Collection	String	""	Limit search results to within a certain Collection or Collections
			ItemType	String	""	Limit search results to a certain type of item
			ShowInvisible	True False	"False"	Show invisible items in the search results
			ShowInactive	True False	"False"	Show inactive items in the search results
			IncludeMemberContent	True False	"False"	Show members content in the search results
			MemberContentOnly	True False	"False"	Show only member content in the search results
			ApprovedMemberContentOnly	True False	"True"	Only show members content that is approved (only used when members content results are enabled)
			CurrentMemberOnly	True False	"False"	Shows content only for the currently logged-in member
			Member	String	""	Allows the search results to show members content for a specific member
			MasterKeyField	String	""	Filter the search results on this field name
			DetailKeyField	String	""	Filter the search results on this field value ((Value Of MasterKeyField) = DetailKeyField)
			Sort	String	""	Sorts the search results on this parameter (eg DocumentDate DESC for sorting by document dates newest first)
			Filter	String	""	Filters the search results based on a string (eg. "Name = 'SearchResult'")



		MaxItems	Integer	"0"	Maximum items to show in the search results
		PageSize	Integer	"0"	Size for each page in the results
		PageParameter	String	Controls Id	URL parameter to use to determine current page for this control
pbAdvSearchSortSelector	A dynamic sort selector, which is rendered as a dropdown, which posts back when the user selects a new sort value	SortField	String	""	e.g. "SearchScore"
		SortFields	String	""	e.g. "SearchScore,DateAdded"
		SortFieldLabels	String	"False"	e.g. "Search Score,Date Added"
pbSearchResultsGoogleMapV3	Google map which shows all search results on a single map using the search results as a data source	GoogleKey	String		Key to use for Google Maps API v3
		DefaultZoom	Int32		15 Default zoom ratio to use for the map
		PopupInfoMaxWidth	Int32		300 Maximum width for the popups on the map
		AddressFields	String		Fields to use to source address data from the search results
		SearchResultsGroup	String		Group name of the search results control to pull data from
		MaxLocations	Int32		0 Maximum locations to attach to the map
		PopupInfoFormat	String	<div>{Name} {Address} {Suburb} {State} {Postcode}</div>	Formatting to use for the popup contents
pbAdvValueSearchResultsFilter	Adds an optional filter selector to any search results page. Renders a checkbox list of filter options.	FieldNames	String		Names of the fields to filter
		FieldLabels	String		Labels to show on the checkboxlist items for the associated field name
		FieldValue	String		Value to filter to
		HideEmptyRows	True False	FALSE	Hides rows with no associated search result values
pbAdvCategorySearchResultsFilter	Adds an optional filter selector to any search results page to filter out certain categories.	CollectionID	String		ID of the collection to source categories from



pbAdvCollectionFieldSearchResultsFilter	Adds an optional filter selector to any search results page to filter out certain field values		HideEmptyRows	True False	FALSE	Hides rows with no associated search result values
			CollectionID	String		ID of the collection to source categories from
pbAdvDateCompareSearchResultsFilter	Adds an optional filter selector to any search results page to filter by certain dates.		HideEmptyRows	True False	FALSE	Hides rows with no associated search result values
			FieldName	String		Name of the field to filter out
			NumberOfDays	String		Comma-separated list of options for days to filter by
			FieldName	String		Name of the date field to filter by
			LessThan	True False	TRUE	Determines whether to filter future or past
			Suffix	String	" Days"	suffix to append to filter options
pbAdvPostalDistanceSearchResultsFilter	Adds an optional filter selector to any search results page to filter by distances.		HideEmptyRows	True False	FALSE	Hides rows with no associated search result values
			LessThan	True False	TRUE	Determines whether to filter distances less than or greater than
			Distances	String		Comma-separated list of options for distances to filter by
			FieldName	String		Name of the date field to filter by
			HideEmptyRows	True False	FALSE	Hides rows with no associated search result values
			Suffix	String	" Kms"	suffix to append to filter options



RSS Module:

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbRssList pbAdvRssList	Display an external RSS Feed as a templatable collection list/summary	http://www.holleynerthercote.com.au/ http://waihekewine.co.nz/Island_of_Wine_News/WaihekeWineintheNews.aspx http://www.managementliabilityinsurance.com.au/	Url	String		URL Source of RSS Feed
			CssClass	String	pbRssList	Specify an alternative CSS class
			ListCssClass	String	list	Specify a CSS class for the list element
			MaxRows	Int32	0	Set the maximum
			PageSize	Int32	0	Set the maximum
			TopPagerVisible	True False	False	If 'True' will
			BottomPagerVisible	True False	True	If 'True' will
						display a
			Filter	String		N/A
			Sort	String		Specify a sort
			Template	String		Specify a list
			CacheTime	Int32	5	Time to cache
			CurrentPage	Int32	0	
			NoDataText	String		Text do display if
			Templates			
			HeaderTemplate			
			ItemTemplate			
			AlternatingItemTemplate			
			SeparatorTemplate			
			FooterTemplate			
pbRssFeed	Generates a link to an RSS feed for a specified collection.	http://www.emblaustralia.org/About_Us/news_and_communication.aspx	Collection	String		Sets the collection to generate the feed for.
		http://discoverme.com.au/News.aspx	ShowImage	True False		Leave this off Shows the RSS icon image.
		http://www.oakridgewines.com.au/News_Events/News1.aspx	ShowText	True False		Shows the hyperlinked text.



ImageUrl	String	If ShowImage is true, this sets the image
Text	String	If ShowText is true, this sets the text that is displayed. If
Tooltip	String	Sets the hover tooltip displayed when the user hovers on the
MaxRows	Int32	Set the maximum
Sort	String	Specify a sort
AdditionalFields	String	Additional
ImageRegions	String	Image regions
ContentRegions	String	Content
DefaultImageRegion	String	Default image
DefaultImageHeight	Int32	Default image
DefaultImageWidth	Int32	Default image
DescriptionContentRegion	String	Description



Site Settings and Configuration:

Skintags

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbConfigValue	Displays the value of the application configuration setting specified	http://pegboardcms.com	Key	A config setting	n/a	e.g. "SiteURL", "ProductKey", etc.
pbPartnerValue	Displays a setting from the partner configuration		Key	A partner setting	n/a	e.g. "Name", "Logo", etc.
pbSiteValue	Displays a setting from the site configuration	http://pegboardcms.com	Key	A site setting	n/a	See below for values.

pbSiteValue Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
'Name"						
'OwnerName"						
"OwnerAddress"						
"OwnerSuburb"						
"OwnerState"						
"OwnerCountry"						
"OwnerPostcode"						
"OwnerABN"						
"OwnerEmail"						
"OwnerPhone"						
"OwnerFax"						
"PostalAddress"						
"PostalSuburb"						
"PostalState"						
"PostalCountry"						



Reference Guide

"PostalPostcode"

"Url"

"SecureUrl"

"Domain"

"SecureDomain"



Banner Ads Module:

Skintags

Skin Tags	Description	Use	Properties	Value	Default	Notes
pbBannerAd	Inserts a banner ad 'slot' - i.e. A placeholder for the banner ad to be displayed	http://www.dlish.co.nz/ http://www.andrewsairportpa	Collection	String		Specify the banner ad collection to
			Height	Unit		Sets the height of the
			Width	Unit		Sets the width of the banner
			UseWeighting	True False	True	Lets you set whether or not this slot should use the
			IncludeMemberContent	True False	False	If 'True' will display
			MemberContentOnly	True False	False	If 'True' will display
			ApprovedMemberContentOnly	True False	True	If 'True' will display approved
			CurrentMemberOnly	True False	False	If 'True' will display for
			Member	String		set up the member's ID
			ShowName	True False	False	If 'True' will display name
			ShowSummary	True False	False	If 'True' will display
			ShowInactive	True False	False	If 'True' then display
			ShowInvisible	True False	False	If 'True' then display
			Target	String	_blank	Set the url target

Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
<no tags>						



Emailtags

Value Tags	Description	Use	Properties	Value	Default	Notes
<no tags>						



Blogs Module:

Skin tags

Skin Tags	Description	Use	Properties	Value	Default	Notes
pbBlogCommentForm	Provides an entry form for users to post new Blog comments. This will usually go on an item details page to post comments on that item.	http://www.brainboost.com.au/About_Us/BrainBoostBlog/theBrainBoostLearningSystem.aspx http://www.dlish.co.nz/blog/Nanas_crepes.aspx	UseHtmlEditor AuthorLabelText EmailLabelText CommentLabelText SubmitButtonText EditorWidth EditorHeight ReceivedText SkinID AllowMultipleVotes RatingImageHover RatingImageHoverSelected RatingImageHeight RatingImageWidth RatingImageYesNoHeight RatingImageYesNoWidth ShowTitle TitleLabelText RatingImage	True False String String String String Unit Unit String String True False String String Int32 Int32 Int32 Int32 True False String String	False Author Email Comment Submit 100% 200px Thank you, your comment was received True False Title Title	If set to 'true' will display a Overrides the Overrides the Overrides the Comment Overrides the text on the Sets the width Sets the Lets you set the message that is displayed to Allows you to override the True by default, will Url of the image to display for the rating control Url of the image to display for the The rating image height The rating The Yes/No rating image The Yes/No rating image If 'True' then Overrides the Url of the image to



RatingImageHighlighted	String		Url of the image to
RatingImageYes	String		Url of the image to display for an
RatingImageYesHighlighted	String		Url of the image to display for a
RatingImageNo	String		Url of the image to display for an
RatingImageNoHighlighted	String		Url of the image to display for a
ShowInfoIcons	True False	False	If 'True' then show an information
InfoIconUrl	String		Url of the image to
InfoPopupOffsetX	Int32	30	X offset of the popup for the
InfoPopupOffsetY	Int32	10	Y offset of the popup for the
InfoPopupTrackMouse	True False	TRUE	If 'True' then the info icon popup will
DisableInfoPopup	True False	FALSE	If 'True' then the info icon
RedirectTo	String		Set a redirect page after
TopPagerVisible	True False	False	Displays a
BottomPagerVisible	True False	True	Displays a
CssClass	String	pbBlogCommentList	Allows you to override the
Template	String		Allows you to select a
Filter	String		Allows you to set filter
CurrentPage	Int32	0	n/a
PageSize	Int32	10	Sets the number of items per



SortDirection	String	ASC	Switches the order of the comments
EnableAjax	True False	False	If 'True' will display an ajax
RatingAsText	True False	False	If 'True' will display
NumberOfRatings	Int32	0	Specify the number of
Templates			
HeaderTemplate			
ItemTemplate			
AlternatingItemTemplate			
SeparatorTemplate			
FooterTemplate			
NoDataTemplate			
SubmitButtonText	String	Submit	Text to show
ReceivedText	String	Thank you, your comment was received	Text to show
NoAvatarUrl	String	~/system/images/avatars/noavatar.jpg	Avatar to use
AvatarWidth	Unit		Avatar width
AvatarHeight	Unit		Avatar Height
MemberNameField	MemberNameFields	Username	Username,First name,Fullname
CaptchaTextboxLabel	String	Type the code from the image	Label to show
RatingImageHeight	Int32	0	The rating image height
RatingImageWidth	Int32	0	The rating image width
RatingImageYesNoHeight	Int32	0	Set the height of the yes/no
RatingImageYesNoWidth	Int32	0	Set the width of the yes/no
RatingImage	String		Set the path to the image
RatingImageHighlighted	String		Url of the image to
RatingImageYes	String	/system/images/ratings/up.png	Url of the image to display for an
RatingImageYesHighlighted	String	/system/images/ratings/uph.png	Url of the image to display for a
RatingImageNo	String	/system/images/ratings/down.png	Url of the image to display for an



				RatingImageNoHighlighted	String	/system/images/ratings/downh.png	Url of the image to display for a
				AllowMultipleVotes	True False	True	If 'True' allows multiple votes
				ShowInfoIcons	True False	False	If 'True' then show an information
				InfoIconUrl	String		Url of the image to
				InfoPopupOffsetX	Int32	30	X offset of the popup for the
				InfoPopupOffsetY	Int32	10	Y offset of the popup for the
				InfoPopupTrackMouse	True False	True	If 'True' then the info icon popup will
				DisableInfoPopup	True False	False	If 'True' then the info icon
				SendEmail	True False	False	If 'True' then an email will
				UseRadButton	True False	FALSE	Renders the
pbMemberBlogCommentList	Lists blog comments from members only. Using this on an item details page will list the comments that belong to that item, if Blog Comments have been	http://www.saltmedia.co.nz		TopPagerVisible	True False	False	If 'True' will display the
pbAdvMemberBlogCommentList				BottomPagerVisible	True False	True	If 'True' will display the
				CssClass	String	pbMemberBlogCommentList	Specify a CSS
				Template	String		Allows you to select a
				CurrentPage	Int32	0	
				PageSize	Int32	10	Specify the amount of
				Filter	String		Allows you to set filter
				SortDirection	String	ASC	Specify the sort direction,
				EnableAjax	True False	True	If 'True' will display an ajax
				AvatarWidth	Unit		Specify the width of the
				AvatarHeight	Unit		Specify the height of the



			MemberNameField	MemberNameFields	Username	Username, Firstname, Fullname, Nickname
			AvatarRegionName	String		The name of the image region that
			AvatarDefaultImageUrl	String		The default image to use if
pbBlogCommentRatingSummaryValue	Displays a summary of all ratings for a site object	http://www.powderhounds.com	RatingImage	String		Url of the image to
			RatingImageHighlighted	String		Url of the image to
			RatingImageHeight	Int32		The rating image height
			RatingImageWidth	Int32		The rating
			RatingImageYes	String		Url of the image to display for an
			RatingImageYesHighlighted	String		Url of the image to display for a
			RatingImageNo	String		Url of the image to display for an
			RatingImageNoHighlighted	String		Url of the image to display for a
			RatingImageYesNoHeight	Int32		The Yes/No rating image
			RatingImageYesNoWidth	Int32		The Yes/No rating image



		FilterByRatingGroup	String	all	Specify which ratings summary information to display. Can be one of the following values: * "all" – Show all ratings and additional rating fields (default) * "reviewcount" – Show the total number of reviews for this collection item only * "overall" – Show the
pbBlogCommentValue pbControlTemplateBlogCommentValue	When displaying historical blog comments in a blog comment list, include this control in a template to display the rating information	http://www.powderhounds.com	RatingImage	String	Url of the image to
			RatingImageHighlighted	String	Url of the image to
			RatingImageHeight	Int32	The rating image height
			RatingImageWidth	Int32	The rating
			LabelText_OverallRating	String	Overall Rating Overrides the
			LabelText_ReviewCount	String	Reviews Overrides the Review Count



FilterByRatingGroup	String	all	Specify which rating information to display. Can be one of the following values: * "all" – Show all ratings and additional rating fields (default) * "additionaldata" – Show additional data values only * "overall" – Show the overall rating
---------------------	--------	-----	---

Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
Blog.Author	These are applicable to Blog collections only					
Blog.BlogDate						
pbBlogCommentList tags:						
BlogComment.Author	Control template only					
BlogComment.Content						
BlogComment.Timestamp						
BlogComment.Email						
BlogComment.Rating1						
BlogComment.Rating2						
BlogComment.Rating3						
BlogComment.Rating4						
BlogComment.Rating5						
BlogComment.LabelRating1						
BlogComment.LabelRating2						



BlogComment.LabelRating3
BlogComment.LabelRating4
BlogComment.LabelRating5

Emailtags

Value Tags	Description	Use	Properties	Value	Default	Notes
<No tags>						



Bookmarks Module:

Skin tags

Skin Tags	Description	Use	Properties	Value	Default	Notes
pbBookmark	Generates a link (with optional image) that allows a user to bookmark/shortlist any collection item. The item is added to a list of bookmarks that belong to the current user. This tag can be used on an item details page (such as the default_item template) or in a pbCollectionList control template. This same tag will remove the item if it has already been bookmarked.	http://www.rosiesdollsclothes.com.au/Store/Nightie-PinkFrog.aspx	BookmarkText	String		Sets the text on the link to add a bookmark
			BookmarkImage	String		Sets the image to use on the add bookmark link
		http://www.vhhe.com.au/ProductCatalogue/Bedroom.aspx	BookmarkTooltip	String		Sets the hover text (tooltip) on the link to add a bookmark
			RemoveText	String		Sets the text on the link to remove a bookmark
			RemoveImage	String		Sets the image to use on the remove bookmark link
			RemoveTooltip	String		Sets the hover text (tooltip) on the link to remove a bookmark
			ShowImage	True False		Display an image on the link
			ShowText	True False		Display the text on the link
			ShowAlert	True False		Displays a javascript alert to the user when they bookmark or remove an item
			BookmarkAlert	String		If ShowAlert is true, sets the alert text that appears when the user bookmarks an item
			RemoveAlert	String		If ShowAlert is true, sets the alert text that appears when the user removes a bookmarked item
pbBookmarkCount	Displays the current count of items that have been bookmarked	http://www.actionsdh.com/	-			
pbBookmarkRemoveAll	Generates a link that allows a user to clear all items from their bookmarks list.	http://www.rosiesdollsclothes.com.au/Myaccount/Wishlist.aspx	ImageUrl	String		Sets the image to use on the link
			Text	String		Sets the text on the link



		http://www.vhhe.com.au/bookmarks.aspx	Tooltip	String		Sets the hover text (tooltip) that appears when the user hovers on the link
			AlertText	String		Sets the confirmation message that appears when the user clicks the link
			ShowImage	True False		Display the image on the link
			ShowText	True False		Display the text on the link
pbCollectionSummary	Lists items within any collection, using an unordered list. By default this will dynamically pick up items underneath the current collection page. You can override this by setting the Collection property. Unlike the CollectionList, this control picks up only a set number of items specified by the MaxRows property.	<i>Please refer to the general section for all the properties</i>	ShowBookmarksOnly	True/False	"False"	True: The control will list bookmarked items only.
pbBookmarkItemCount	Shows the number of currently bookmarked items		EmptyText	String		Text to show if there are no bookmarks.

Control Tags

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbBookmark pbCtBookmark	Generates a link (with optional image) that allows a user to bookmark/shortlist any collection item. The item is added to a list of bookmarks that belong to the current user. This tag can be used on an item details page (such as the default_item template) or in a pbCollectionList control template.	http://www.rosiesdollsclothes.com.au/Store/Nightie-PinkFrog.aspx	BookmarkText	String		Sets the text on the link to add a bookmark
			BookmarkImage	String		Sets the image to use on the add bookmark link
		http://www.vhhe.com.au/ProductCatalogue/Bedroom.aspx	BookmarkTooltip	String		Sets the hover text (tooltip) on the link to add a bookmark
			RemoveText	String		Sets the text on the link to remove a bookmark



This same tag will remove the item if it has already been bookmarked.

RemoveImage	String	Sets the image to use on the remove bookmark link
RemoveTooltip	String	Sets the hover text (tooltip) on the link to remove a bookmark
ShowImage	True False	Display an image on the link
ShowText	True False	Display the text on the link
ShowAlert	True False	Displays a javascript alert to the user when they bookmark or remove an item
BookmarkAlert	String	If ShowAlert is true, sets the alert text that appears when the user bookmarks an item
RemoveAlert	String	If ShowAlert is true, sets the alert text that appears when the user removes a bookmarked item

Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
<no tags>						

Emailtags

Value Tags	Description	Use	Properties	Value	Default	Notes
member.bookmarks	 separated list of bookmarks for the form submitter (does not necessarily require a member)					
member.bookmarkswithcode	 separated list of bookmark links with link text 'item.code - item.name'					



Podcast Module

Skintags

Skin Tags	Description	Use	Properties	Value	Default	Notes
-----------	-------------	-----	------------	-------	---------	-------

Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
------------	-------------	-----	------------	-------	---------	-------

[Podcast.MediaURL]
[Podcast.AltMediaURL]
[Podcast.PubDate]
[Podcast.AuthorEmail]

Emailtags

Value Tags	Description	Use	Properties	Value	Default	Notes
------------	-------------	-----	------------	-------	---------	-------

<no tags>



Datalists Module:

Skintags

Skin Tags	Description	Use	Properties	Value	Default	Notes
pbDatalistSearch	Provides an advanced search control for searching through Datalist collections. Note this search will only ever return Datalist items.	http://www.mobiletherapists.com.au/	Collection	String		Specify the collection to display items
		http://www.davey.com.au/DaveyDealers.aspx	CollectionType	String	Datalist	Specify the type of collection to search within, E.g. "Product"
		http://clubs.swimming.org.au/	ResultsPage	String		Sets the results page that the user will be redirected to upon submitting a search. This page should contain a [pbDatalistSearchResults] to display the results. You can leave this off to use the current page.
			SearchFields	String	keyword,collection,category	Specifies the fields that the search control should provide. The default is "keyword,collection,category", which provides a keywords field, a collection dropdown and a category dropdown, in that order. Category is a special field in that you include "category" only once regardless of how many category levels you want, and set the CategoryLevels to determine the number of category drop-downs. Note any datalist field can be searched on, including additional fields you add.



FieldLabels	String		This list works similar to the SearchFields property, and should match up with the fields specified on that property. It overrides the labels given to each field (by default they will use the field name as the label). E.g. "Keywords,Collection,Group" would correspond with the example in the above property, changing each related label such as "category" to "Group" etc. Note that categories work differently in this case if you have more than 1, you need to include the label for each category in order.
CategoryLevels	Int32	1	The number of category search fields to include - these will be different category levels. E.g. Specifying 3 will create a field for the first 3 levels of your category structure. Only applicable when "category" is included in the SearchFields property.
ShowAllOption	True False	True	If true, dropdowns contain a "show all" item at the top of the list, otherwise one item will always be selected.
ShowAllFields	String		N/A
ShowLabelInsideField	True False	False	If 'True' will display a label within the field
Dependency	String		Lets you set up field dependencies, so that field B is disabled until field A has been selected. You don't have to do this for categories as it is done automatically where this is more than 1 category level. Contact support for more details!



ButtonText	String	Search	Lets you override the text on the search button.
UseDropDownFields	True False	False	If true, the fields are generated as dropdown lists where possible. Otherwise, textboxes are used.
AllOptionText	String	[all]	When ShowAllOption="true", sets the text for that item.
PostcodeField	String		Nominate the postcode field from the form
PostcodeFieldRequired	True False	False	If 'True' will require the postcode field to be completed
PostcodeDistance	Int32	0	Radius that the search will look within given the specified postcode
StateField	String		Specify the form field for the 'State'
CountryField	String		Specify the form field for the 'Country'
ForceTextboxFields	String		Fields to force to render as
CategoryCheckBoxList	True False	False	Show categories as checkbox list
EnableAutoComplete	True False	False	Enables the premptive search dropdown for suburb/postcode. Enables the premptive search textbox for site object field ie. Name, Summary etc. Requires ForceDropDownList to not equal True
AutoCompleteMinChars	Int32	3	the client typing 3 charactors then start loading the auto complete list
AutoCompleteMaxHeight	Unit		Maximum height of the
DisableAutoCompleteFilter	True False	False	Disable the Country and State filter auto complete by select a postcode/suburb
CategorySortOrder	True False	False	
ForceDropDownFields	String		List of fields that must be rendered as dropdown fields
ForceCheckBoxListFields	String		List of fields that must be rendered as checkboxlist fields



	ForceToFromFields	String		List of fields that must be rendered as to / from fields		
	ForceCheckboxFields	String		List of fields that must be rendered as checkbox fields		
	CategoryCheckBoxListForceSelection	True False	False	If 'True' then at least one item must be selected in the Category CheckBoxList		
	SuburbField	String	Suburb	Specify the form field for the 'Suburb'		
	CheckBoxListColumns	Int32	3	Specify the number of columns the checkboxlists will use		
	CheckBoxListRepeatDirection	String	Horizontal	Specify the direction the collection lists uses		
	FromLabel	String	From	Specify the label that the "From" field uses		
	ToLabel	String	To	Specify the label that the "To" field uses		
	FromToDecimalPlaces	String	0'	Specify the number of decimal places used in the "To" and "From" fields		
	PostCodeFieldEmptyMessage	String		Message to show if the postcode filter datalist search result.		
	Filter	String				
	DistanceByPostCodeOnly	True False	False	If 'True' then selecting suburb from dropdown list will choose the postcode rather than suburb name		
	SortAdditionalFields	True False	FALSE	Sorts the additional field values		
	WholePhrase	True False	TRUE	Matches the entire phrase entered in keywords as a continuous string (splits search strings on commas)		
	MatchAllFieldValues	True False	TRUE	Performs an AND logic between		
	MatchAllAdditionalFields	True False	FALSE	Performs an AND logic between		
pbDatalistSearchResults pbAdvDatalistSearchResults	A list control similar to the [pbCollectionList], required to list search results from a [pbDatalistSearch].	http://www.davey.com.au/DaveyDealers.aspx http://clubs.swimming.org.au/	Sort	String	SortOrder	Specify the sort order
			Collection	String		Sets the control to pick up items from the collection specified. Leave off to pick up the current collection
			CollectionType	String	Datalist	Specify the type of collection to search within, E.g. "Product"
			TopPagerVisible	True False	False	Shows a pager above the list



BottomPagerVisible	True False	True	Shows a pager below the list
CssClass	String	pbList	Allows you to override the css class on the UL tag
Template	String		Allows you to select a different control template folder (always under the "list" folder)
CurrentPage	Int32	0	
PageSize	Int32	10	Sets the number of items per page. Setting this to 0 disables paging
ShowInactive	True False	False	If true will also list inactive items
IncludeMemberContent	True False	False	If 'True' will display members content
MemberContentOnly	True False	False	If 'True' will display members content only
ApprovedMemberContentOnly	True False	True	If 'True' will display approved members content only. Set to 'True' by default.
CurrentMemberOnly	True False	False	If 'True' will display for current members only
Member	String		set up the member's ID or username
EnableAjax	True False	False	If 'True' will display an ajax on load
NoSearchResultsText	String		Display a message if there are no search results
MaxRows	Int32	0	Unlimited row if it's 0
MatchAllCategories	True False	True	Item must match all selected categories
IncludeDistance	True False	False	Include an estimated distance for postcode distance search. Fieldname for distance is "PostalDistance"
ItemCount	Int32	0	
RandomSort	True False	False	If 'True' then randomly sort results
RedirectOnSingleResult	True False	False	If 'True' then the search results will automatically redirect to the item detail page if only one item is returned in the search result.
SearchResultsGroup	String		Used with GoogleMap to show multiple search results on a map



Templates
HeaderTemplate
ItemTemplate
AlternatingItemTemplate
SeparatorTemplate
FooterTemplate

pbDatalistSearchSummary	Used in conjunction with [pbDatalistSearchResults]. This returns a summary of search results.	http://www.davey.com.au/DaveyDealers.aspx	Message	String	Your search for {Keyword} returned {Count} results
pbGoogleMap	Displays the Google map using the API provided by Google. It uses additional fields to parse in the address.	http://www.davey.com.au/DaveyDealers.aspx	Address	String	Static address for map
			Width	Unit	Width of map
			Height	Unit	Height of map
			GoogleKey	String	Google API Key
			AddressFields	String	Address fields to make full address to map for current item. ie: "address1,suburb,state,postcode,country"

Control Tags

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbGoogleMap pbCtGoogleMap	Displays the Google map using the API provided by Google. It uses additional fields to parse in the	http://www.davey.com.au/About_Davey1/Dealer_Results.aspx?dlSearchKey=RGF0YWxpY2h0YU00N0W4xcWR2dTQ1Z2thYWtrZTA= http://clubs.swimming.org.au/	Address	String		Static address for map
			Width	Unit		Width of map
			Height	Unit		Height of map
			GoogleKey	String		Google API Key
			AddressFields	String		Address fields to make full address to map for current item. ie: "address1,suburb,state,postcode,country"

Emailtags

Value Tags	Description	Use	Properties	Value	Default	Notes
<no tags>						



Documents Module:

Skintags

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbDocumentSearch	Provides a search that goes through document collections only. Search results are displayed in a [pbCollectionList] or [pbCollectionSummary].	http://dabpumpsaustralia.com.au/SideMenu/DABSpareParts.aspx	ResultsPage	String		Sets the page to which the user will be redirected to see the search results. This page must contain the [pbDocumentSearchResults] tag. Leave this off to use the current page.
			LabelText	String		Sets the text (if any) of the label before the search field.
			ButtonText	String	Search	Lets you override the text on the search button.
			PartialMatch	True False	True	If true, partial matches will be returned, otherwise the whole word must be matched
			TextboxWidth	Unit	90px	Lets you set the width on the search field textbox.
			Collection	String		Sets the control to pick up items from the collection specified. Leave off to pick up the current collection
			Category	String		Filter the collection by the specified category



SearchFields	String	keyword	Specifies the fields that the search control should provide. The default is "keyword,collection,category", which provides a keywords field, a collection dropdown and a category dropdown, in that order. Category is a special field in that you include "category" only once regardless of how many category levels you want, and set the CategoryLevels to determine the number of category drop-downs. Note any datalist field can be searched on, including additional fields you add.
FieldLabels	String		This list works similar to the SearchFields property, and should match up with the fields specified on that property. It overrides the labels given to each field (by default they will use the field name as the label). E.g. "Keywords,Collection,Group" would correspond with the example in the above property, changing each related label such as "category" to "Group" etc. Note that categories work differently in this case if you have more than 1, you need to include the label for each category in order.
CategoryLevels	Int32	1	The number of category search fields to include - these will be different category levels. E.g. Specifying 3 will create a field for the first 3 levels of your category structure. Only applicable when "category" is included in the SearchFields property.



ShowAllOption	True False	True	If true, dropdowns contain a "show all" item at the top of the list, otherwise one item will always be selected.
ShowLabelInsideField	True False	False	If 'True' will display label inside field
Dependency	String		Lets you set up field dependencies, so that field B is disabled until field A has been selected. You don't have to do this for categories as it is done automatically where this is more than 1 category level. Contact support for more details!
UseDropDownFields	True False	False	If true, the fields are generated as dropdown lists where possible. Otherwise, textboxes are used.
UseCheckBoxListFields	True False	False	If true, the fields are generated as checkbox lists where possible. Otherwise, textboxes are used.
AllOptionText	String	[all]	When ShowAllOption="true", sets the text for that item.
ForceTextboxFields	String		List of fields to force to render as
CategoryCheckBoxList	True False	False	Show categories as checkbox list

pbDocumentSearchResults pbAdvDocumentSearchResults	A list control similar to the [pbCollectionList], required to list results from the [pbDocumentSearch].	http://dabpumpsaustralia.com.au/SideMenu/DABSpares/SparesResults.aspx	Sort	String	SortOrder	Specify the sort order
		http://www.bsc.com.au/SearchResults.aspx	Collection	String		Lets you limit the document collection(s) to be searched
			TopPagerVisible	True False	False	Shows a pager above the list
			BottomPagerVisible	True False	True	Shows a pager below the list
			CssClass	String	pbList	Allows you to override the css class on the UL tag
			Template	String		Allows you to select a different control template folder (always under the "list" folder)
			CurrentPage	Int32	0	



PageSize	Int32	10	Sets the number of items per page. Setting this to 0 disables paging
ShowInactive	True False	False	If true will also list inactive items
IncludeMemberContent	True False	False	If 'True' will display members content
MemberContentOnly	True False	False	If 'True' will display members content only
ApprovedMemberContentOnly	True False	True	If 'True' will display approved members content only. Is set to 'True' by default
CurrentMemberOnly	True False	False	If 'True' will display for current members only
Member	String		set up the member's ID or username
EnableAjax	True False	False	If 'True' will display an ajax on load
NoSearchResultsText	String		Specify the text if there are no results to display
MaxRows	Int32	0	Specify the max amount of rows to display
MatchAllCategories	True False	True	If 'True' will match specified categories
Templates			
HeaderTemplate			
ItemTemplate			
AlternatingItemTemplate			
SeparatorTemplate			
FooterTemplate			

pbDocumentSearchSummary	Displays a message summarising the results of the search.	http://www.vlga.org.au/Resources/Library.aspx	Message	String	Your search for {Keyword} returned {Count} results	
pbDocumentUploadForm	This form allows a user to upload and submit their own documents to a document collection. In addition it provides all the functionality of a normal pbForm control.	http://freshpictmedia.com.au/	Collection	String	Specify the document collection to upload new documents to	
			DocumentFieldName	String	Document	Specify the form field name for the document
			RedirectTo	String	Makes the form redirect to the specified URL after the user submits it	



PasswordFieldName	String	Password	Specify the form field for the Password field. Set to 'Password' if left blank
EmailFromFieldName	String	EmailFrom	Specify the form field for Email From
EmailSubjectFieldName	String	EmailSubject	Specify the form field for Email Subject
UserEmailAddressFieldName	String	EmailAddress	Specify the email address field name
AdminEmailAddressFieldName	String	AdminEmailAddress	Specify the admin email address
Form	String		Allows you to override the form being displayed. By default the current form page is used (if applicable)
SubmitButtonText	String	Submit	Lets you override the text on the submit button
CssClass	String	pbForm	Allows you to override the CSS class on the form
ReceivedText	String	Thankyou, your enquiry has been subn	Confirmation text on submission
UserSMSFieldName	String	UserSMS	Field name to pull the users SMS #
AdminSMSFieldName	String	AdminSMS	Field name to pull the administrators
Publication	String		Publication to signup to
PublicationsFieldName	String	Campaigns	Form field to mutiple publications
EnableEmSignup	True False	False	If 'True' will add the user to emarketing subscribers
ConfirmMessage	String		Message upon confirmation
EmailDelayHours	Int32	0	Number of hours to delay the sending of customer emails
EmailDelayMinutes	Int32	0	Number of minutes to delay the sending of customer emails
AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of administrator emails
AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the sending of administrator emails
AdminAttachUploads	True False	False	Allows the administrator to attach files
UserAttachUploads	True False	False	N/A
UserSMSCountry	Int32	61	Specify the country code, by default 60



[pbDocumentUploadFormSubmit] See "Forms"

Value Tags

Description	Use	Properties	Value	Default	Notes
This field will mask the actual URL of the document on the server and will trigger member security.					

Donations Module:

Skintags

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbDonationFormSubmit	Displays a submit button to submit a donation form. This works in conjunction with the pbFormField skintag.	http://rsb.org.au/Support/Us/Give/Donations.aspx https://www.brightongrammar.vic.edu.au/BGS_Portal/ParentsStudentsandStaff/Givingto_BGS.aspx	ReceiptPage	String		Set a receipt page
			FormGroup	String	Default	Set a form group
			FormName	String		Select a form name
			ButtonText	String	Submit	Set the button text for submit, by default is 'Submit'
			ImageUrl	String		Set an image path for the button link
			SendEmail	True False	False	If 'True' will send an email to donator
			EmailFromFieldName	String	EmailFrom	Set the email from field name
			EmailSubjectFieldName	String	EmailSubject	Set the email subject field name
			UserEmailAddressFieldName	String	EmailAddress	Set the email address field name
			AdminEmailAddressFieldName	String	AdminEmailAddress	Set the administrator email address field name
			PasswordFieldName	String	Password	Set the password field name
			ReceivedText	String	Thankyou, your enquiry has been subn	Text that displayed upon submission
			UserSMSFieldName	String	UserSMS	Set the user SMS field name
			AdminSMSFieldName	String	AdminSMS	Set the administrator SMS field name
			UserSMSCountryFieldName	String	UserSMSCountry	Set the user SMS country
			AdminSMSCountryFieldName	String	AdminSMSCountry	Set the administrator SMS country
			MaxUserSMSCountFieldName	String	MaxUserSMSCount	Set max amount of
			MaxUserSMSMessageFieldName	String	MaxUserSMSMessage	Set the max user sms message
			UserSMSExpiryPeriodFieldName	String	UserSMSExpiryPeriod	Set the user SMS expiry period field name
			RedirectTo	String		Set a page to redirect to upon submission
			ConfirmMessage	String		Set a confirmation message upon submission
			EmailDelayHours	Int32	0	Set the hours for delay until email is sent to the user



EmailDelayMinutes	Int32	0	Set the minutes for delay until emails are sent to the users
AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of administrator emails
AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the sending of administrator emails
AdminAttachUploads	True False	False	If 'True' allow administrator to attach uploads
UserAttachUploads	True False	False	If 'True' allow user to attach uploads
ControlType	SubmitControlTypes	Button	Button,ImageButton,LinkButton
AllowMultipleMemberForms	True False	TRUE	If 'False' then a member can only submit the form once
MultipleMemberFormsErrorText	String	You have submitted this form previously. This form cannot be submitted more than once.	Message to display if a member tries to submit the form more than once
ValidationGroup	String		The form validation group to apply to when submitting the form

pbDonationFormErrors	Works in conjunction with [pbDonationFormSubmit] and [pbFormField] tags. This tag will display any errors that occur after submit.	http://rsb.org.au/Support_Us_-_Give/Donations.aspx https://www.brightongrammar.vic.edu.au/BGS_Portal/ParentsStudentsandStaff/Giving_to_BGS.aspx			
pbDonationReceiptField	This is the standard form field skin tag that is part of the Forms module. The “Field” parameter can be set to a standard or custom donation field.	https://www.brightongrammar.vic.edu.au/BGS_Portal/ParentsStudentsandStaff/Giving_to_BGS.aspx	Field	String	The donation field value to display
			RenderAsLiteral	True False	False
					If True then render the value as a string literal. If False then render the value as a Span
pbRegularDonationSelector	This skin tag is used to display the options to capture a single or regular payment. This skin tag can be omitted from the form if only single payments are required.	https://www.brightongrammar.vic.edu.au/BGS_Portal/ParentsStudentsandStaff/Giving_to_BGS.aspx	TitleText	String	Text to display in the title of the control
			SingleDonationText	String	Single Donation
			RegularDonationText	String	Regular Donation
			Period	String	Text to show on the selection for Text to show on the selection for Comma-separated list of values to display in the Period dropdown list. E.g. “Monthly,Quarterly”



		Frequency	String			Comma-separated list of values to display in the Frequency dropdown list. E.g. "1 Month,2 Months,1 Year"
pbDonationReceiptLoader	This skin control must be placed at the top of a donation receipt page in order to make the receipt fields available to the pbDonationReceiptField skin control.	https://www.brightongramm-ar.vic.edu.au/BGS_Portal/ParentsStudentsandStaff/GivingtoBGS.aspx	-			

Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
<no tags>						

Emailtags

Value Tags	Description	Use	Properties	Value	Default	Notes
id	Donation ID					
siteid	Site ID for the donation					
donationnumber	donation (similar to order number)					
donationdate	date of the donation					
paymentmethod	name of the payment method used					
memberid	member id of the donator					
surchargeate	% surcharge					
surchargeamount	total surcharge value					
total	total donation amount					
merchantgatewayid	the payment					
gatewayresponsecode	code returned from the gateway					
gatewayresponsetext	response text from the gateway					
gatewayresponsereference	reference number from the gateway					
creditcard	type of credit card and last 4 digits					



recurringdonation Whether the donation was recurring



Ecommerce Module:

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbCheckoutCustomerDetails	Displays the form for the customer to enter their billing/address details during the checkout process.	http://www.oakridgewines.com.au/PurchaseWine.aspx	Edit	True False		
			ReadOnly	True False	False	If True, the customer details will not be editable on the page
		http://www.rankinsdirect.com.au/shop.aspx	EnableShipTo	True False		* Moved to Ecommerce Settings in Console *
		http://www.printersupermarket.com.au	EnableComments	True False		If 'True' will display a comments box for user comments
		http://www.rsb.org.au/ShopOnline.aspx	EnableWhereDidYouHear	True False		If 'True' will enable a dropdown for users to choose an option. Options are specified in the console E-Commerce settings
		http://www.kristina.com.au/productsandServices.aspx	EnableMemberSignup	True False		If 'True' will force user to sign up as a member
			EnableRememberMe	True False	True	New from v5.34.6
			UseCompanyField	True False	False	If 'True' inserts an extra field for the user to enter their Company
			CompanyFieldLabelText	String	Company	Used to edit the company label text
			UseDateOfBirthField	True False	False	If 'True' then the Date of Birth field is displayed
			UseGenderField	True False	False	If 'True' then the Gender field is displayed
			GenderOptions	String	M;F	Semi-colon delimited list of options to display in the Gender dropdown
			PrintMode	True False	False	Retrieves customer details from order for printing purposes
			AllowEditOnShoppingCart	True False	False	Allows the control to be editable on /ShoppingCart.aspx
pbCheckoutFailed	Displays an error message when checkout has failed.	-				



pbCheckoutOrderDetails pbAdvCheckoutOrderDetails	Displays the final details of the customer's order, including their order/receipt number, on the receipt page of the Checkout process.	http://www.oakridgewines.com.au/PurchaseWine.aspx	ReceiptText	String	Your Order Number:	Lets you override the text before the order number at the beginning of the Order details.
		http://www.rankinsdirect.com.au/shop.aspx	Template	String		Allows you to select a different folder for the control templates (always under the "order" folder).
		http://www.printersupermarket.com.au	ShowReceiptContainer	True False		Set receipt container Visible or invisible
			Templates			
			HeaderTemplate			
pbCheckoutPaymentDetails	Displays the form for the customer to enter their payment details during the checkout process	http://www.oakridgewines.com.au/PurchaseWine.aspx	PaymentMethodDescription	String		Text displayed to describe payment methods
		http://www.rankinsdirect.com.au/shop.aspx	Edit	True False		See 'ReadOnly'
		http://www.printersupermarket.com.au	ReadOnly	True False	False	If True, the payment details will not be editable on the page
		http://www.rsb.org.au/ShopOnline.aspx	ValidateCreditCardNumber	True False	False	If 'True' the credit card field will
		http://www.kristina.com.au/ProductsandServices.aspx	ForcedPaymentType	String		N/A
			ExpiryMonthAsText	True False	True	If True, the expiry month dropdown will contain short month labels (Jan, Feb, etc.), otherwise the number of the month will be displayed
			CreditCardSurcharge	String	0	Specify credit card surcharge
			PrintMode	True False	False	Retrieves customer details from order for printing purposes
			ShowPublicPaymentOptionsForMembers	True False	True	If 'False' will hide payment options of type 'Public' when member is logged in
pbCheckoutPostage	Displays the list of postage options with a radio button list that the user must select during the Checkout	http://www.oakridgewines.com.au/PurchaseWine.aspx	RepeatColumns	Int32	1	Number of columns the radiobutton list should use.



process.		http://www.rankinsdirect.com.au/shop.aspx	ReadOnly	True False	False	If 'True' allows the user to edit details
		http://www.printersupermarket.com.au	ErrorMessage	String	Please select a postage method	Set an error message
		http://www.rsb.org.au/ShopOnline.aspx	DisplayAsDropDown	True False	False	If 'True' will display postage options in a dropdown format
		http://www.kristina.com.au/ProductsandServices.aspx	SelectText	String	Please Select	Specify alternative select text which appears at the top of the dropdown
			EnablePriceInfo	True False	True	If 'True' will display the price against each postage option
			ShowPublicPostageOptionsForMembers	True False	True	If 'False' will hide postage options of type 'Public' when member is logged in
			EnableDefault	True False	False	If 'True' the control will never load without a postage type selected (unless there are no types to display)
pbCheckoutProceed	Provides the button required to proceed to the next step in the Checkout process.		TitleLabel	String	Postage Method	The Title to display above the postage methods
		http://www.oakridgewines.com.au/PurchaseWine.aspx	ProceedButtonText	String		Specify the text for the proceed button
		http://www.rankinsdirect.com.au/shop.aspx	ImageUrl	String		the image URL for the button
			MinQtyErrorText	String	You do not have enough items in your shopping cart. You require at least {minqty} items to proceed	The message to display if the number of items in the shopping cart is less than the shopping cart minimum quantity
			MaxQtyErrorText	String	You have too many items in your shopping cart. You can have at most {maxqty} items in your cart	The message to display if the number of items in the shopping cart is greater than the shopping cart maximum quantity
		http://www.printersupermarket.com.au	UsePaymentPage	True False		If 'True' will include a payment process
		http://www.rsb.org.au/ShopOnline.aspx	UseConfirmPage	True False		If 'True' will include a confirmation page in the checkout process
			EnableAjax	True False	Varies	Enables ajax on the proceed



pbCheckoutPromocode	Used on the checkout template to provide an input field for the user to enter a Promotional Code	http://www.rosiesdollsclothes.com.au				
pbOrderSearch	Provides a search which works with the pbOrdersList, letting you filter orders by Order number or Account name	http://www.rosiesdollsclothes.com.au http://www.rankinsdirect.com.au/shop.aspx	SearchOrderNo	True False	True	Displays a field to search by order no.
			SearchOrderName	True False	False	Displays a field to search by order name
			ButtonText	String	Search	Overrides the text on the search button
			OrderNoLabel	String	Order no.	Overrides the label for the order no. field
			OrderNameLabel	String	Name	Overrides the label for the order name field
			ResultsPage	String		Sets the results page to redirect to on performing a search; this page should contain the [pbOrdersList] tag. Leave this blank to use the current page
pbOrdersList	Displays a list of past Orders for the currently logged in Member. If the user isn't logged the list is not displayed.	http://www.rosiesdollsclothes.com.au	Template	String		Allows you to select a different folder for the control templates (always under the "orderlist" folder).
			CssClass	String	pbOrdersList	Overrides the CSS class around the list
			EnableReorder	True False	True	Provides a link which copies the contents of the past order to the user's current shopping cart
			ReorderText	String	Reorder	Sets the text for the Reorder link
			ShowAllMembersOrders	True False	False	If True, it will displays everyone's orders, not just the current member
			Templates HeaderTemplate ItemTemplate AlternatingItemTemplate SeparatorTemplate FooterTemplate			



pbCart	Inserts the shopping cart view on the ShoppingCart page	http://www.oakridgewines.com.au/PurchaseWine.aspx	Edit	True False		If 'True' allows the user to edit the cart, such as delete items. If 'False' will display the items within the cart.
		http://www.printersupermarket.com.au	Template	String		Allows you to select a different folder for the control templates (always under the "cart" folder).
		http://www.rsb.org.au/ShopOnline.aspx	ReadOnly	True False	False	If True, the shopping cart will not be editable on the page
		http://www.kristina.com.au/ProductsandServices.aspx	MaxItemQuantity	String	9999	Setup the max item quantity which can be purchased
			UpdateButtonVisible	True False	True	Show the update button
			SortField	String		Orders the list by the field specified, for the default, sort by Timestamp Asc and then ItemName Asc
			SortDirection	String	ASC	Switches the order of the comments between Date ascending or descending
			CheckoutButtonVisible	True False	False	Show the Checkout button
			CheckoutButtonText	String	Checkout	Set the checkout button text
			UpdateButtonText	String	Update	Set the text for the update button
			AllowEditOnCheckoutDetails	True False	False	If 'True' then the cart can be edited during on the Checkout Details page
			IncludePostageOnShoppingCart	True False	False	If 'True' then the cart will display the postage amount on the shoppingcart page
			AccountNumber	String		The Google Analytics account number
			DomainName	String		Enter the domain name to enable sub-domain tracking (e.g. ".mydomain.com")
			SetAllowLink	String	true	The value to set for the "_setAllowLink" option. This defaults to "true". Set this to "" to skip this option.
			SetAllowHash	String	false	The value to set for the "_setAllowHash" option. This defaults to "false". Set this to "" to skip this option.



			EnableGoogleAnalyticsCartAdd	True False	False	If true, the shopping cart will process any previous add to cart clicks with related Google Analytics enabled.
			Templates			
			HeaderTemplate			
			ItemTemplate			
			AlternatingItemTemplate			
			SeparatorTemplate			
			FooterTemplate			
pbShoppingCartAdd	Refer to "[pbProductAddToCart]"	-				
pbCartMiniSummary	Displays a summary of the user's shopping cart, showing total quantity and price	http://www.oakridgewines.com.au/PurchaseWine.aspx http://www.rankinsdirect.com.au/shop.aspx	CartItemsLabelText	CartItemsLabelText	"Items in Cart: "	Lets you override the text displayed in the summary
pbCartSummary pbAdvCartSummary	Displays a summary of the user's shopping cart on any page, listing the items in the cart	http://www.oakridgewines.com.au/PurchaseWine.aspx http://www.rankinsdirect.com.au/shop.aspx http://www.printersupermarket.com.au	Template	String		Allows you to select a different folder for the control templates (always under the "cartsummary" folder).
			QuoteRedirectTo	String		n/a
			SaveQuoteText	String	save as quote | 	Change quote text
			ShowQuote	True False	False	If 'True' will show the quote
			Templates			
			HeaderTemplate			
			ItemTemplate			
			AlternatingItemTemplate			
			SeparatorTemplate			
			FooterTemplate			
pbCheckoutEmSubscribe	Allows a user to signup for e-marketing campaigns during the checkout process. This uses the information entered into the billing address and content for subscriber information.	http://www.mynextcareer.com.au/	Title	String	Email Subscriptions	The title to display on the field container
			ReadOnly	True False	False	If 'True' then the fiels are set to read-only
			AllCampaignsSelected	True False	False	if 'True' then each campaign will default as selected in the list



pbCheckoutMemberSignup	Allows a user to signup during the checkout process. This uses the billing address and contact details for members information.	http://www.mynextcareer.com.au/	NewMemberActive	True False	False	Specifies whether the new member is active immediately after the checkout process has been completed with a successful purchase
			PaidOnly	True False	False	Specifies that the control is only visible if there is a membership product in the cart, i.e.: a product with a "NewMemberRole" additional property with a value.
			Title	String	Membership	The title to display on the field container
			ReadOnly	True False	False	If 'True' then the fields are set to read-only
			EmailAsUsername	True False	False	If 'True' then set the user name to the email address
pbAdvCart	Use this control for advanced inline templating of the shopping cart in the checkout process		Templates			
			HeaderTemplate			
			ItemTemplate			
			AlternatingItemTemplate			
			SeparatorTemplate			
			SubTotalTemplate			
			TaxTotalTemplate			
			DiscountTotalTemplate			
			PostageTotalTemplate			
			TotalTemplate			
			FooterTemplate			
			NoDataTemplate			
			AccountNumber	String		The Google Analytics account number
			DomainName	String		Enter the domain name to enable sub-domain tracking (e.g. ".mydomain.com")
			SetAllowLink	String	true	The value to set for the "_setAllowLink" option. This defaults to "true". Set this to "" to skip this option.
			SetAllowHash	String	false	The value to set for the "_setAllowHash" option. This defaults to "false". Set this to "" to skip this option.



		EnableGoogleAnalyticsCartAdd	True False	False	If true, the shopping cart will process any previous add to cart clicks with related Google Analytics enabled.
pbAdvOrderItems	Use this control for advanced inline templating of the order items in the checkout process	Templates HeaderTemplate ItemTemplate AlternatingItemTemplate SeparatorTemplate SubTotalTemplate TaxTotalTemplate DiscountTotalTemplate PostageTotalTemplate SurchargeTotalTemplate TotalTemplate FooterTemplate NoDataTemplate			
pbAdvPaymentDetails	Use this control for advanced inline templating of the payment details in the checkout process	Templates CreditCardTemplate DirectDepositTemplate ChequeTemplate			
pbAdvCustomerDetails	Use this control for advanced inline templating of the customer details in the checkout process	ShippingDetails	True False	False	If 'True' then include shipping details
		FormGroup	String	Default	Used if there are more than one advanced forms on the page
		FormName	String		Specify a form from the console
		UseMemberDetails	True False	True	If 'True' then form fields will be prepopulated with member details
		ValidationGroup	String		The form validation group to apply to when submitting the form
		PrintMode	True False	False	Retrieves customer details from order for printing purposes



EnableChoicesAddressValidation	True False	False	For use with Australia Post Choices account. Will validate the address entered by the user and allow for automatically correcting the state, suburb and postcode values. Note: validation errors will be displayed in the pbFormErrors tag
ChoicesCanUpdateSuburb	True False	False	When EnableChoicesAddressValidation is True, will automatically replace the suburb with the suggestion from Australia Post
ChoicesCanUpdateState	True False	False	When EnableChoicesAddressValidation is True, will automatically replace the state with the suggestion from Australia Post
ChoicesCanUpdatePostcode	True False	False	When EnableChoicesAddressValidation is True, will automatically replace the postcode with the suggestion from Australia Post

Templates

ContentTemplate

pbAdvOrdersList	Use this control for advanced inline templating of order lists	StatusFilter	String		Comma separated set of order
		ShowDetailOnly	True False	FALSE	Only shows the detailtemplate
		DetailUrl	String		Adds a 'DetailUrl' property to each
		EnableConfirmationEmails	True False	FALSE	Sends confirmation emails to
		ShowAllMembersOrders	True False	FALSE	Shows all orders in the control
		EnableReorder	True False	FALSE	Enables the ability to re-order

Templates

HeaderTemplate

ItemTemplate

AlternatingItemTemplate

SeparatorTemplate

SubTotalTemplate

TaxTotalTemplate

DiscountTotalTemplate



		PostageTotalTemplate			
		SurchargeTotalTemplate			
		TotalTemplate			
		FooterTemplate			
		NoDataTemplate			
pbUseShippingCheckBox	Displays a "Use Billing Details as Shipping Details " check box. This control is meant to be used in conjunction with the pbAdvCustomerDetails	UseWhenChecked	True False	True	If 'True' then use billing details as shipping details when the check box is checked. If 'False' then use billing details as shipping details if the check box is unchecked.
		Default	True False	False	The default state of the check box
		Text	String		The text to display for the check box. E.g. "Same as Bill To Details"
pbCtCartEditButton	Edit button for editable fields in the cart item in the checkout process.				
pbCtCartEditUpdateButton	Button to submit the update for editable fields in the cart item in the				
pbCtCartEditCancelButton	Button to cancel the update for editable fields in the cart item in the				
pbCtCartEditCancelButton	Delete button for the cart item in the cart. Used with inline				
pbCtCartItemName	Used with inline templating. Cart Item Name				
pbCtCartItemName	Used with inline templating. Cart Item Quantity				
pbCtCartSubTotal	Used with inline templating. Cart Sub Total				
pbCtCartTax	Used with inline templating. Cart Tax Amount				



pbCtCartPostage	Used with inline templating. Cart Postage Amount				
pbCtCartTotal	Used with inline templating. Cart Total				
pbAdvCartItemQty	Used with inline templating. Cart Item Quantity				
pbAdvCartDeleteButton	Used with inline templating. Cart Delete Button				
pbCheckoutInsuranceOption	Gives the user the ability to opt in or out of postage insurance	RepeatColumns	Int32	1	Number of columns the radiobutton list should use.
		HeadingText	String	Postage Insurance	The text to display as the title for this control
		IncludeText	String	Include Insurance	The text to display for the Include Option
		ExcludeText	String	Excude Insurance	The text to display for the Exclude Option
		RenderMode	RadioButtonList DropDown CheckBox	RadioButtonList	Specifies how the control will render
		RepeatDirection	Horizontal Vertical	Horizontal	The direction to use when rendering multiple columns for RadioButtonList mode
		RepeatLayout	Table Flow	Table	The layout mode of the RadionButtonList
pbFreightCalculator	Displays a textbox for the user to enter in their postcode to have a freight calculation returned for the current product page	ButtonType	Button / Image / Link	Button	Customise the type of button used to submit the postcode by choosing either of these button types
		ButtonText		Empty	
		ButtonImageUrl		Empty	
		ButtonTooltip		Empty	
		PostageName		Empty	Set this to the name of one of the postage methods created in the ecommerce manage postage section
		ShowPublicPostageOptionsForMembers	True / False	True	Shows public postage options when members are logged in. Use
		PostageLabel		Please enter a postcode	
		PostageAmountLabel		Postage Price:	



	IncorrectPageError			pbFreightCalculator can only be used on a product details page
	PostageMethodNotFoundError			Postage method not found
	MultiplePostageMethodsFoundError			Multiple postage methods found
	CountryNotFoundForPostcodeError			Country not found for this postcode
	InvalidPostcodeError			Invalid postcode
	DeliveryPostCode		Empty	Set this value to a valid post code to allow the control to work without a post code being entered
pbAdvChoicesAvailableCollectionPoint: Displays a radio button list or dropdown selection for the user to select from a list of available Australia Post Collection Points for the specified postcode. Note: this tag required an Australia Post Choices account	DisplayAsDropDown	True / False	False	If True, will render as a drop down selection. If False, will render as a radion button list selection.
	DropDownWidth	Unit	Empty	The width of the drop down control
	DropDownWidth2	Unit	Empty	The width of the drop down when opened
	DropDownMaxHeight	Unit	Empty	The height of the drop down when opened
	RepeatDirection	Horizontal Vertical	Vertical	The direction of the radion button list options
	RepeatColumns	Numeric	0	The number of columns to use when rendering the radion button list options
	RepeatLayout	Table Flow	Table	Rendering mode of the radion button list options
	MaxDistance	Numeric	5	Specifies the distance from the specified postcode to return available collection point options
pbAdvChoicesCollectionPointOptionSe Displays a radio button list or dropdown selection for the user to select delivery address options. Note: This tag requires an Australia Post Choices account.	DisplayAsDropDown	True / False	False	If True, will render as a drop down selection. If False, will render as a radion button list selection.
	SpecifiedAddressOptionText	String	"A Specified Address"	The text to display as the specified address option.
	CollectionPointOptionText	String	"Australia Post Collection Point"	The text to display as the Australia Post Collection Point option.
	DropDownWidth	Unit	Empty	The width of the drop down control



			DropDownWidth2	Unit	Empty	The width of the drop down when opened
			DropDownMaxHeight	Unit	Empty	The height of the drop down when opened
			RepeatDirection	Horizontal Vertical	Vertical	The direction of the radion button list options
			RepeatColumns	Numeric	0	The number of columns to use when rendering the radion button list options
			RepeatLayout	Table Flow	Table	Rendering mode of the radion button list options
pbAdvChoicesParcelTracking	Display the tracking events for a parcel sent using Australia Post. This feature requires an Australia Post Choices account.	This tag can be used in a pbAdvOrdersList DetailTemplate to automatically show the tracking events for customer orders. This tag can also be used on a stand alone page, the user will be required to enter a	Templates HeaderTemplate ItemTemplate AlternatingItemTemplate SeparatorTemplate FooterTemplate NoDataTemplate ErrorTemplate InputTemplate NoTrackingTemplate			
pbAdvOrderDetails	Allows extended details from an		Templates ContentTemplate			

Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
CheckoutPageUrl	These are applicable to the eCommerce module					
ShoppingCartPageUrl						
pbCartMiniSummary tags:	OR					
MiniCart.ItemCount	pbMiniCartItemCount	Control template only				
MiniCart.TotalPrice	pbMiniCartTotalPrice					
pbCart tags:	OR					
Cart.DeleteButton	pbCartDeleteButton	Control template only				
Cart.EditButton	pbCartEditButton					
Cart.ItemCode						
Cart.ItemComments						
Cart.ItemDescription						



Cart.ItemName	pbCartItemName
Cart.ItemOptions	
Cart.ItemQty	pbCartItemQty
Cart.ItemTaxCode	
Cart.ItemTaxRate	
Cart.ItemTotal	
Cart.ItemType	
Cart.ItemUnitPrice	
Cart.Postage	pbCartPostage
Cart.QtyBox	
Cart.SubTotal	pbCartSubTotal
Cart.Tax	pbCartTax
Cart.Total	pbCartTotal
Cart.ItemCapped	
Cart.ItemWeight	
Cart.ItemHeight	
Cart.ItemWidth	
Cart.ItemDepth	

CartEdit tags:	OR	
CartEdit.CancelButton	pbCartEditCancelButton	Control template only
CartEdit.UpdateButton	pbCartEditUpdateButton	

pbCartSummary tags:	OR	
CartSummary.ItemCode		Control template only
CartSummary.ItemComments		
CartSummary.ItemDescription		
CartSummary.ItemName		
CartSummary.ItemQty		
CartSummary.ItemTaxCode		
CartSummary.ItemTaxRate		
CartSummary.ItemType		
CartSummary.ItemUnitPrice		
CartSummary.Total	pbCartSummaryTotal	



CartSummary.ItemCapped
CartSummary.ItemWeight
CartSummary.ItemHeight
CartSummary.ItemWidth
CartSummary.ItemDepth

pbOrdersList tags:	OR	
Order.Number	pbOrderNumber	Control template only
Order.Date		
Order.PayMethod		
Order.Status	pbOrderStatus	
Order.TotalQty	pbOrderTotalQty	
Order.Total		
Order.CustomerDetails	pbOrderCustomerDetails	
Order.PaymentDetails	pbOrderPaymentDetails	
Order.ItemDetails	pbOrderItemDetails	
Order.ReorderLink	pbOrderReOrderLink	
Order.Postage	pbOrderPostage	
Order.PurchaseOrderNo	pbPurchaseOrderNumber	

Emailtags

Skin Tags	Description	Use	Properties	Value	Default	Notes
-----------	-------------	-----	------------	-------	---------	-------

Order Confirmation Email:
The following tags are used in templating the emails that are sent to the customer or administrator when an order is placed through the eCommerce module. Email templates need to be html files and uploaded to the templates/email/ folder within your skin. Two standard templates are installed by default in this folder called order_admin.htm and order_customer.htm, which can be modified. The below values are always entered within square brackets, e.g. [ItemTable], [Order.Number]

Order.Number
Order.Date
Order.BillToName
Order.BillToDateOfBirth
Order.BillToGender
Order.BillToAddress
Order.BillToAddress2



Reference Guide

Order.BillToSuburb
Order.BillToState
Order.BillToPostcode
Order.BillToCountry
Order.BillToEmail
Order.BillToPhone
Order.BillToFax
Order.BillToMobile
Order.ShipToName
Order.ShipToDateOfBirth
Order.ShipToGender
Order.ShipToAddress
Order.ShipToAddress2
Order.ShipToSuburb
Order.ShipToState
Order.ShipToPostcode
Order.ShipToCountry
Order.ShipToEmail
Order.ShipToPhone
Order.ShipToFax
Order.ShipToMobile
Order.PayMethod
Order.PostageType
Order.PostageAmount
Order.TaxAmount
Order.SubTotal
Order.Total
Order.Comment
Order.SurchargeAmount
Order.SurchargeRate
Order.DiscountTotal
Order.Promocode
Order.HowDidYouHear



ItemTable Inserts a table listing each product/item that has been ordered

ItemTable tags

- Item.OrderId
- Item.SiteId
- Item.ItemType
- Item.ItemId
- Item.ItemCode
- Item.ItemNam
- Item.ItemDescription
- Item.ItemQty
- Item.ItemUnitPrice
- Item.ItemTaxCode
- Item.ItemTaxRate
- Item.ItemOptions
- Item.ItemComments
- Item.Comments
- Item.UsePoints
- Item.ItemCapped
- Item.IsDownload
- Item.DownloadUrl
- Item.MaxDownloads
- Item.DownloadCount
- Item.McObjectId
- Item.ItemWeight
- Item.ItemHeight
- Item.ItemWidth
- Item.ItemDepth
- Item.ItemMemberPoints
- Item.ItemPageUrl
- Item.ItemPageLink
- Item.ItemTax
- Item.ItemTotalTax
- Item.ItemTotal



Item.ItemUnitPriceIncTax
Item.ItemTotalIncTax
Item.PromoItemEntry
Item.PromoItemLinkedCartItemId
Item.PromoCodeApplied
Item.Timestamp
Item.SortOrder
Item.TieredRegistrationId
Item.PostageType
Item.PostageService
Item.PostageBoxTypeName
Item.PostageBoxCount
Item.PostageBoxWeight
Item.PostagePrice

In addition to the above values, you may use any calculated fields defined in the ECommerce settings or additional fields attached to the item(s)
Event-specific tags are available on event items.



eMarketing Module:

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbEMarketingSignUp pbEMarketingSignupForm	A form that will add a user as to emarketing campaigns.	http://www.mazedistribution.com.au/Maze_Club.aspx http://www.schoolgetaways.com.au/ http://www.emergencyteachers.com.au/eNewsSubscribe.aspx	RedirectTo	String		Select a page to redirect to after
			PasswordFieldName	String	Password	Set the password field
			EmailFromFieldName	String	EmailFrom	Set the email from field
			EmailSubjectFieldName	String	EmailSubject	Set the email subject field
			UserEmailAddressFieldName	String	EmailAddress	Set the user email address
			AdminEmailAddressFieldName	String	AdminEmailAddress	Set the administrator email address field name
			Form	String		Choose the
			SubmitButtonText	String	Submit	Set the submit button text.
			CssClass	String	pbForm	Specify a CSS class to apply
			ReceivedText	String	Thankyou, your enquiry has been subn	Text that displays after
			UserSMSFieldName	String	UserSMS	Set the user
			AdminSMSFieldName	String	AdminSMS	Set the administrator
			Publication	String		Choose a publication for
			PublicationsFieldName	String	Campaigns	To subscribe to multiple publications,
			EnableEmSignup	True False	False	N/A
			ConfirmMessage	String		Message that displays upon
			EmailDelayHours	Int32	0	Set the delay in hours for
			EmailDelayMinutes	Int32	0	Set the delay in minutes for



AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of
AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the
AdminAttachUploads	True False	False	If 'True' allow the
UserAttachUploads	True False	False	If 'True' allow the user to
UserSMSCountry	Int32	61	Set the user country code
AdminSMSCountry	Int32	61	Set the administrator
MaxUserSMS	Int32	10	Set the maximum
OnClientClick	String		JavaScript to attach to the
MaxUserSMSText	String	Maximum number of SMS already sent	N/A
UserSMSExpiryHours	Int32	0	Set the SMS
AdminEmailDelayHours	Int32	0	The number of hours to delay the
AdminEmailDelayMinutes	Int32	0	the number of minutes to delay the
UseRadButton	True False	FALSE	Renders the
pbEmUnsubscribeConfirm	This tag is used for the Unsubscribe page, it will appear as a form for the user to confirm their unsubscription. http://www.fiera.com.au/unsubscribe.aspx		
Text	String	Confirm	Text to display on
ImageUrl	String		Select an image to
Tooltip	String	Pointer Hand	
RedirectTo	String		Set the redirect page
ControlType	ButtonControlType	Button	Button,Image,
Field	String		eg.
FormatString	String		
pbEmReferFriendForm	Sending the refer materials to multi friends. http://www.fiera.com.au/ReferFriend.aspx http://www.dmzine.com.au/ReferFriend.aspx		
EmailFrom	String		Set the email from address
EmailSubject	String		Sets the email subject field
EmailTemplate	String		Sets the email



pbEMarketingSignupForm	Allow the user to signup to E-Marketing campaigns.	http://www.mazedistribution.com.au/Maze_Club.aspx http://www.schoolgetaways.com.au/ http://www.emergencyteachers.com.au/eNewsSubscribe.aspx	SuccessMessage	String	Thank you for using refer a friend	Used to specify a
			NoEmailMessage	String	Please enter a friend's email address	Message to
			AdminEmailAddressFieldName	String	"AdminEmailAddress"	Field name for
			CssClass	String	"pbForm"	Allows you to override the
			EmailFromFieldName	String	"EmailFrom"	Field name for
			EmailSubjectFieldName	String	"EmailSubject"	Field name for
			Form	String		Allows you to override the form being displayed. By
			PasswordFieldName	String	"Password"	Field name to
			Publication	String		Publication to
			PublicationsFieldName	String		Form field to allow multiple
			ReceivedText	String	"Thankyou, your enquiry has been submitted"	Message to show on
			RedirectTo	String	n/a	Makes the form redirect to the
			SubmitButtonText	String	"Submit"	Lets you override the Form field
			UserEmailAddressFieldName	String	"EmailAddress"	
			EmailDelayHours	Int32	0	Number of hours to delay
			EmailDelayMinutes	Int32	0	Number of minutes to
			AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of
			AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the
			UserSMSFieldName	String		Form field
			AdminSMSFieldName	String		Form field
			EnableEmSignup	True False	FALSE	Enables
			ConfirmMessage	String		Message to
			AdminAttachUploads	True False	FALSE	Attaches all



		UserAttachUploads	True False	FALSE	Attaches all
		UserSMSCountry	int32		61 Country code
		AdminSMSCountry	int32		61
		OnClientClick	String		JavaScript to attach to the
		MaxUserSMS	Int32		0 Maximum
		MaxUserSMSText	String		Message to
		UserSMSExpiryHours	Int32		0 Time in hours
[pbEMarketingSignupFormSubmit]	See "Forms"				
[pbEmSignupFormSubmit]	See "Forms"				
[pbAdvNewsletters]	List newsletters on the front-end of the site	Campaign	String		Filter the list
		ShowInvisible	True False	False	
		Sort	String	""	
		Filter	String	""	
		MaxItems	Integer	"0"	
		PageSize	Integer	"0"	
		Templates			
		HeaderTemplate			
		ItemTemplate			
		AlternatingItemTemplate			
		SelectedItemTemplate			
		SelectedAlternatingItemTemplate			
		SeparatorTemplate			
		FooterTemplate			

Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
<no tags>						

Emailtags

Skin Tags	Description	Use	Properties	Value	Default	Notes
[Campaign.Name]						
[Campaign.Description]						
[Campaign.Subject]						
[Newsletter.Name]						
[Newsletter.Description]						
[Newsletter.Subject]						



[Newsletter.IssueDate]

[pbCurrentDate]

[pbUnsubscribe] [pbUnsubscribeURL]	Inserts a link on the e-marketing newsletter that goes to "/Unsubscribe.aspx". This page needs a template applied with [pbEmUnsubscribeConfirm] tag			
[pbPreview] [pbPreviewURL]	Inserts a link on the e-marketing newsletter that directs to a page of the current newsletter viewed through a web browser.			
[pbReferFriend]	Inserts a link to the Refer a friend page. Page must be called Refer a Friend			See [pbEmReferFriendForm]
[pbContent]	Inserts an editable content region that is managed in the console with a WYSIWYG editor. All pbContent tags must have a 'region name' specified	RegionName	Any name eg. "Default"	Each tag within a template must have a different RegionName.
		Name	As "RegionName"	As
		ToolSet		
[pbImage]	Inserts an editable image region that is managed in the console. All pbImage tags must have a 'image name' specified	ImageName	Any name, e.g. "Default"	n/a
		RegionName	as "RegionName"	as "RegionName"
		Name	as "RegionName"	as "RegionName"
[pbItem]	Inserts an editable collection item that is managed in the console. All pbItem tags must have a 'name' specified	ItemName	Any name, eg. "Default"	n/a



		Link	True/False	"False"	Render the item name as a link to the
		RegionName	as "RegionName"	as "RegionName"	as
		Name	as "RegionName"	as "RegionName"	as
		Collection	n/a	n/a	
[pbItemField]	Inserts an Item field into the email	ItemName	Name of pbItem, eg. "Default"	n/a	The name of the pbItem
		Field	Field name, eg. "Name" or "Summary"	n/a	The field to display
		RegionName	as "RegionName"	as "RegionName"	as
		Name	as "RegionName"	as "RegionName"	as
		FieldName	as "Field"	as "Field"	as "Field"
		Format	String		Specify the format that
[pbSubscriber]	Inserts a field from the subscriber into the email	Key	A Subscriber value field	n/a	eg. "Firstname", "Lastname",
		Name	as "Key"	as "Key"	as "Key"
		Value	as "Key"	as "Key"	as "Key"
		Field	as "Key"	as "Key"	as "Key"
[pbPartnerValue]	Inserts a field from the partner into the email	Key	A Partner value field	n/a	eg. "Name", "Logo", etc.
		Name	as "Key"	as "Key"	as "Key"
		Value	as "Key"	as "Key"	as "Key"
[pbSiteValue]	Inserts a field from the site settings into the email	Key	A Site value field	n/a	e.g. "Name", "OwnerName", "OwnerAddress",
		Name	as "Key"	as "Key"	as "Key"
		Value	as "Key"	as "Key"	as "Key"

Refer a Friend Email Template

pbSubscriber	Key="Name" and Key="Email" only	eg. [pbSubscriber]
SignupURL		
Comment		







Events Module:

Skintags

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbEventAttendeeList pbAdvEventAttendeeList	Lists Attendees of the event registration.	N/A	TopPagerVisible BottomPagerVisible CssClass Template CurrentPage PageSize SortDirection EnableAjax Templates HeaderTemplate ItemTemplate AlternatingItemTemplate SeparatorTemplate FooterTemplate	True False True False String String Int32 Int32 String True False	False True pbEventAttendeeList 0 10 ASC False	Displays a Displays a Allows you to override the Allows you to select a Sets the number of items per Switches the order of the comments If 'True'
pbEventCalendar	Provides a Calendar view of Events for a Collection or for the whole site, which can be switched between month, week, or day views.	http://sydneywomensnetwork.com.au/Events.aspx http://www.brainboost.com.au/Calendars/InformationSessions.aspx	Collection CombineAllEvents Width Height StartInFullTime	String True False Unit Unit True False	False False	Sets the calendar to pick up Events from the If true, the Collection property is ignored and Calendar Calendar If true, the initial daily view shows 24 hours,



			DayStartHour	Int32	8	Sets the hour for the daily
			DayEndHour	Int32	18	Sets the hour for the daily
			FirstDayOfWeek	String	Sunday	Lets you set the first day of
			LastDayOfWeek	String	Saturday	Lets you set the first day of
			ShowViewTabs	True False	True	Shows the Day/Week/Mo
			ShowNavigation	True False	True	Shows the Next/Previous
			InitialView	String	MonthView	Sets the default view
			SkinID	String		Allows you to override the
			HideOldEvents	True False	False	If true, the calendar does
			OldEventAsStartDate	True False	True	
			IncludeMemberContent	True False	False	If 'True' will display
			MemberContentOnly	True False	False	If 'True' will display
			ApprovedMemberContentOnly	True False	True	Set to 'True' by default.
			CurrentMemberOnly	True False	False	Will display Will display only for
			EventsPerDay	Int32	2	Sets the number of events to show for each
			Member	String		set up the member's ID
			Culture	String	en-AU	Allows you to change the
pbEventFeedbackForm	Inserts a form that is used to collect feedback for an event. Feedback is stored in the backend.	N/A	Answer0FieldName	String	Answer0	Set the field name for the
			Answer1FieldName	String	Answer1	
			Answer2FieldName	String	Answer2	
			Answer3FieldName	String	Answer3	
			Answer4FieldName	String	Answer4	
			Answer5FieldName	String	Answer5	
			Answer6FieldName	String	Answer6	



Answer7FieldName	String	Answer7	
Answer8FieldName	String	Answer8	
Answer9FieldName	String	Answer9	
CommentsFieldName	String	Comments	Set the field name for the
IsPrivateFieldName	String	IsPrivate	Indicates whether the event
RedirectUrl	String		Makes the form redirect to the
RedirectTo	String		Choose a page to redirect to
PasswordFieldName	String	Password	Set the
EmailFromFieldName	String	EmailFrom	Set the email
EmailSubjectFieldName	String	EmailSubject	Set the email subject field
UserEmailAddressFieldName	String	EmailAddress	Set the user email address
AdminEmailAddressFieldName	String	AdminEmailAddress	Set the administrator
Form	String		Specify a form to use from the console. If left blank, this
SubmitButtonText	String	Submit	Set the submit
CssClass	String	pbForm	Specify a CSS class to apply
ReceivedText	String	Thankyou, your enquiry has	Set the text that is
UserSMSFieldName	String	UserSMS	Set the user
AdminSMSFieldName	String	AdminSMS	Set the administrator
Publication	String		Choose a campaign to
PublicationsFieldName	String	Campaigns	Set a publications field name to
EnableEmSignup	True False	False	If 'True' will subscribe the
ConfirmMessage	String		Set a confirm
EmailDelayHours	Int32	0	Set the delay in hours until a email



EmailDelayMinutes	Int32	0	Set the delay in minutes until an email
AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of
AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the
AdminAttachUploads	True False	False	If 'True' administrator
UserAttachUploads	True False	False	If 'True' user
UserSMSCountry	Int32	61	Specify the user sms
AdminSMSCountry	Int32	61	Specify the administrator
OnClientClick	String		JavaScript to attach to the
MaxUserSMS	Int32	10	Set the max amount of
MaxUserSMSText	String	Maximum number of SMS al	Specify a max
UserSMSExpiryHours	Int32	0	N/A
AdminEmailDelayHours	Int32	0	The number of hours to delay the
AdminEmailDelayMinutes	Int32	0	the number of minutes to delay the

pbEventMiniCalendar	Displays a small Calendar that highlights each day that contains an event. Clicking that day on the calendar links the user to the Events page and filters on that date.	http://www.exxtendedtraining.com.au/TrainingandEvents.aspx	Collection	String	Will display only items
			Width	Unit	Set the width
			Height	Unit	Set the height
			FirstDayOfWeek	String	Set the first day of the
			SkinID	String	Set a skin ID
	Displays the price of the event for the current user, when using role-based pricing.	http://www.aitoolkit.org/Home/Events.aspx	IncludeMemberContent	True False	If 'True' will display
			MemberContentOnly	True False	If 'True' will display only
			ApprovedMemberContentOnly	True False	Set to 'True' by default.
			CurrentMemberOnly	True False	Will display if 'True' will display for



		Member	String		Set the	
		HideOldEvents	True False	False	If 'True' old events will	
		OldEventAsStartDate	True False	False		
		Culture	String	en-AU	Allows you to change the	
pbEventPrice	Displays the price of an event.	CalcTax	True False	True	Show the price either	
		ShowTaxOnly	True False	False	Show the Tax Amount of the	
pbEventRegistrationForm	This form allows a user to register for an event. In addition it provides all the functionality of a normal pbForm control. It can be used on an event detail page, otherwise use pbEventRegistrationLink.	http://www.exxtendedtrainin g.com.au/TrainingandEvehnts /Another_Test_Event.aspx	ConfirmByDefault	True False	False	If true, new registrations will default to confirmed
			NoSeatsMessage	String	There are no more seats ava	There are no more seats
			NotEnoughSeatsMessage	String	There are not enough seats ;	There are not enough seats available to
			RedirectTo	String		Makes the form redirect to the
			PasswordFieldName	String	Password	Set the
			EmailFromFieldName	String	EmailFrom	Set the email
			EmailSubjectFieldName	String	EmailSubject	Set the email subject field
			UserEmailAddressFieldName	String	EmailAddress	Set the user email address
			AdminEmailAddressFieldName	String	AdminEmailAddress	Set the administrator
			Form	String		Allows you to override the form being displayed. By
			SubmitButtonText	String	Submit	Lets you override the
			CssClass	String	pbForm	Allows you to override the
			ReceivedText	String	Thankyou, your enquiry has	Set the text that is
			UserSMSFieldName	String	UserSMS	Set the user



AdminSMSFieldName	String	AdminSMS	Set the administrator
Publication	String	Publication	Publication to
PublicationsFieldName	String	Campaigns	Form field to multiple
SeatsFieldName	String	Seats	Set the Seats
NameFieldName	String	ContactName	Set the ContactName
AddressFieldName	String	ContactAddress	Set the ContactAddress
Address2FieldName	String	ContactAddress2	Set the ContactAddress
SuburbFieldName	String	ContactSuburb	Set the ContactSuburb
StateFieldName	String	ContactState	Set the
PostcodeFieldName	String	ContactPostcode	Set the
CountryFieldName	String	ContactCountry	Set the ContactCountry
PhoneFieldName	String	ContactPhone	Set the ContactPhone
FaxFieldName	String	ContactFax	Set the
MobileFieldName	String	ContactMobile	Set the ContactMobile
EmailFieldName	String	ContactEmail	Set the ContactEmail
CompanyFieldName	String	Company	Set the
PositionFieldName	String	Position	Set the
DateOfBirthFieldName	String	DateOfBirth	Set the
CommentsFieldName	String	Comments	Set the
AttendeesFieldName	String	Attendees	Set the
HearAboutUsFieldName	String	HearAboutUs	Set the HearAboutUs
EnableEmSignup	True False	False	Set a confirm
ConfirmMessage	String		Set the delay in hours until a email
EmailDelayHours	Int32	0	Number of hours to delay
EmailDelayMinutes	Int32	0	Number of minutes to
AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of



	AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the	
	AdminAttachUploads	True False	False	Attaches all fileupload	
	UserAttachUploads	True False	False	Attaches all	
	UserSMSCountry	Int32	61	Specify the user sms	
	AdminSMSCountry	Int32	61	Specify the administrator	
	MaxUserSMS	Int32	10	Set the max amount of	
	OnClientClick	String		JavaScript to attach to the	
	MaxUserSMSText	String	Maximum number of SMS al	Specify a max	
	UserSMSExpiryHours	Int32	0	Time before	
	OneCollectionMessage	String	Only events from one range	Error message to display when events	
	AdminEmailDelayHours	Int32	0	The number of hours to delay the	
	AdminEmailDelayMinutes	Int32	0	the number of minutes to delay the	
pbEventRegistrationLink	Allows you to have an Event Registration form on a different page to the event details. This tag provides a link from the event details page to a separate pbEventRegistrationForm.	http://www.exxtendedtrainin g.com.au/TrainingandEvehnts /Another_Test_Event.aspx	Form	String	Allows you to set the form to which the user will be redirected to
	Text	String	Register for this event		Sets the text displayed for
	Target	String			If specified the target value is
	CssClass	String	pbEventRegistrationLink		Allows you to override the
	NoRegisterText	String			Sets the text displayed for events that



pbEventSearch	Provides an advanced search control for searching through Event collections. Note this search will only ever return Event items.	ResultsPage	String	Sets the results page that the user will be redirected to upon submitting a search. This
		SearchFields	String	keyword,collection,category Specifies the fields that the search control should provide. The default is "keyword,collection,category,startdate,enddate", which provides a keywords field, a collection dropdown and a category dropdown, in that order.
		FieldLabels	String	This list works similar to the SearchFields property, and should match up with the fields specified on that property. It overrides the labels given to each field (by default they will use the field name as the label). E.g. "Keywords,Col



CategoryLevels	Int32	1	The number of category search fields to include - these will be different category levels. E.g. Specifying 3
ShowAllOption	True False	True	If true, dropdowns contain a "show all"
ShowLabelInsideField	True False	False	If 'True' will display the
Dependency	String		Lets you set up field dependencies, so that field B is disabled until field A has been selected. You don't have to
ButtonText	String	Search	Lets you override the
UseDropDownFields	True False	False	If true, the fields are generated as dropdown
AllOptionText	String	[all]	When ShowAllOptio
PostcodeField	String	Postcode	Nominate the postcode field
PostcodeDistance	Int32	0	Radius that the search will look within
MaxRows	Int32		0 limit the max number of
IncludeDistance	True False	FALSE	show a postcode
ShowInvisible	True False	FALSE	show invisible
pbEventSearchResults A list control similar to the	Sort	SortOrder	Field(s) on



pbAdvEventSearchResults

[pbCollectionList], required to list search results from a [pbEventSearch].

Collection	String		Sets the control to pick up items from the collection
TopPagerVisible	True False	False	Shows a pager
BottomPagerVisible	True False	True	Shows a pager
CssClass	String	pbList	Allows you to override the
Template	String		Allows you to select a different
CurrentPage	Int32	0	
PageSize	Int32	10	Sets the number of items per
ShowInactive	True False	False	If true will also list inactive
IncludeMemberContent	True False	False	If 'True' will display
MemberContentOnly	True False	False	If 'True' will display
ApprovedMemberContentOnly	True False	True	If 'True' will display will only display
CurrentMemberOnly	True False	False	Display only for current
Member	String		set up the member's ID
EnableAjax	True False	False	If 'True' will display an ajax
NoSearchResultsText	String		Display a message if
Templates			
HeaderTemplate			
ItemTemplate			
AlternatingItemTemplate			
SeparatorTemplate			
FooterTemplate			

[pbEventRegistrationFormSubmit]

See "Forms"

[pbEventRegistrationAttendeeNames]

Record event attendee names and email addresses for event tired pricing.

AttendeeNamesHeading

string

Please complete the attendee



AttendeeEmailTextboxLabel	string	EmailAddress
AttendeeNameTextboxLabel	string	Name
AttendeeNamesIncompleteMessage	string	Attendee

[PbEventSearchSummary]	Used in conjunction with pbEventsSearchResults, this provides a brief summary of the number of results. It should be placed on your results page.	Message	String	Your search returned {Count} Lets you override the text displayed - use the [Count] placeholder in
pbAdvEventRegistrationTieredPricing	Used to show a selector for tiered Please use pbEventTieredPrice to	QuantityControlType	Dropdown Textbox	Dropdown
		QuantityMinValue	Int32	Determines 0 Minimum
		QuantityMaxValue	Int32	10 Maximum
		UseTieredQuantity	True False	TRUE Uses the
		NoSeatsText	String	Unavailable Text to show if
		NoSeatsSelectedMessage	String	Please select a seat quantity Error message
		CalcTax	True False	TRUE Determines
		ShowTaxOnly	True False	FALSE Determines
		Templates		
		HeaderTemplate		
		ItemTemplate		
		AlternatingItemTemplate		
		SeparatorTemplate		
		FooterTemplate		
		NoDataTemplate		

Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
Event.Duration						
Event.EndDate						
Event.PricePerSeat						
Event.StartDate						
Event.TotalSeats						
Event.VenueAddressAddress						
Event.VenueAddressAddress2						
Event.VenueAddressCountry						



Event.VenueAddressSuburb
Event.VenueAddressState
Event.VenueAddressPostcode
Event.VenueContactName
Event.VenueContactEmail
Event.VenueContactFax
Event.VenueContactPhone
Event.VenueContactMobile
Event.Price0
Event.Price1
Event.Price2
Event.Price3
Event.Price4
Event.Price5
Event.Price6
Event.Price7
Event.Price8
Event.Price9
Event.EventColourID
Event.EnableAttendeeEmailBefore

Event.EnableAttendeeEmailAfter
Event.FeedbackFormID
Event.PreEventMailoutCount
Event.PostEventMailoutCount
Event.FeedbackQuestions
Event.DateOfBirth
Event.Comments
Event.AvailableSeats
Event.AvailableSeatsUnconfirmed
Event.AttendeeNames

Event Attendee Tags

Item.RegisteredTimeStamp
Item.ContactName
Item.Confirmed
Item.Seats
Item.ContactEmail
Item.ContactFax
Item.ContactMobile
Item.ContactPhone
Item.ContactAddress
Item.ContactAddress2
Item.ContactSuburb
Item.ContactState
Item.ContactCountry



Item.ContactPostcode
Item.Company
Item.Position
Item.DateOfBirth
Item.Comments
Item.AttendeeNames
Item.RequiresPurchase
Item.IsPaidFor
Item.TaxCode
Item.TaxRate
Item.HearAboutUs

Emailtags

Value Tags

Event.Duration
Event.EndDate
Event.PricePerSeat
Event.StartDate
Event.TotalSeats
Event.VenueAddressAddress
Event.VenueAddressAddress2
Event.VenueAddressCountry
Event.VenueAddressName
Event.VenueAddressSuburb
Event.VenueAddressState
Event.VenueAddressPostcode
Event.VenueContactEmail
Event.VenueContactFax
Event.VenueContactPhone
Event.VenueContactMobile

Description

Used for the
pbEventRegistrationForm email
template

Use

Properties

Value

Default

Notes



Forums Module:

Skintags

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbForumList	Displays a list of forum threads in a collection	http://obstetricexcellence.com.au/members-forum.aspx	Collection	String		Sets the control to pick up items from the collection
			CssClass	String	pbForumList	Allows you to override the CSS class on
			DateTimeFormat	String		Allows you to override the
pbForumPostList	Lists the posts for a forum collection.	http://obstetricexcellence.com.au/members-forum/General-Forum-Discussion/29.aspx	Collection	String		Sets the control to pick up items from the collection
			CssClass	String	pbForumPosts	Specify a CSS
			CurrentPage	Int32	N/A	N/A
			PageSize	Int32	10	Sets the number of list per page.
pbForumPostReply	Generates a comment box for replies.	http://obstetricexcellence.com.au/members-forum/General-Forum-Discussion/85.aspx?act=addpost	DateTimeFormat	String		Allows you to override the
			AllowSubscription	True False	False	If True, a checkbox will be displayed for logged in members
pbForumRecentPosts pbAdvForumRecentPosts	Generates a list of recent posts.		SubscriptionChecked	True False	False	Sets whether the
			Collection	String		Sets the control to pick up items from the collection



			CssClass	String	pbSummary	Sets the control to pick up items from the collection
			ListCssClass	String	summary	Applies a CSS class to the list
			Template	String		Allows you to select a
			RecordCount	Int32	0	n/a
			MaxRows	Int32	5	Set the
			Category	String		Select a
			Templates			
			HeaderTemplate			
			ItemTemplate			
			AlternatingItemTemplate			
			SeparatorTemplate			
			FooterTemplate			
pbForumSearch	A search that will only search through forum collections.	http://obstetricexcellence.com.au/members-forum.aspx	ButtonText	String	Search	Text to display on button
			UseImageButton	True False	False	Use image button in
			ImageButtonUrl	String		Url of image
			ForumUrl	String		Forum page
pbForumSearchResults	Outputs the results of the forum search.	http://obstetricexcellence.com.au/members-forum.aspx	Collection	String		Sets the control to pick up items from the collection
			Forum	String		Show results from a specific
			CssClass	String	pbForumSearchResults	Sets the control to pick up items from the collection
			CurrentPage	Int32		
			PageSize	Int32	10	Sets the number of list per page.
			DateTimeFormat	String		Allows you to override the



pbForumThreadList	Lists threads of the current collection or specify a collection to display.	http://www.actionsdh.com/web8.pbstaging.com/Forums/Healthyplaceshealthypeople.aspx http://obstetricexcellence.com.au/members-forum/General-Forum-Discussion.aspx	Collection	String		Sets the control to pick up items from the collection
			Forum	String		Show threads for a specific forum
			CssClass	String	pbForumList	Apply a class to the forum
			CurrentPage	Int32		
			PageSize	Int32	10	Sets the number of list per page.
			NewThreadButtonText	String	Write a New Post	Edit the button to
			DateTimeFormat	String		Allows you to override the
pbForumSubscribe	Displays a button allowing a logged in Member to subscribe/unsubscribe from forums or threads	http://www.asceptrg.org	ControlType	Button Image Link	Button	Sets which type of button to render:
			ForumUnsubImageUrl	String		The path for the forum
			ForumSubImageUrl	String		The path for the forum
			ThreadSubImageUrl	String		The path for the thread
			ThreadUnsubImageUrl	String		The path for the thread
			ForumUnsubMessage	String	Stop receiving notification emails for this Forum	Sets the forum unsubscribe
			ForumSubMessage	String	Start receiving notification emails for this Forum	Sets the forum subscribe
			ThreadSubMessage	String	Subscribe to this Thread	Sets the thread
			ThreadUnsubMessage	String	Unsubscribe from this Thread	Sets the thread
			Mode	Thread Forum	Thread	Sets the mode of the button. The mode "Thread" is only applicable



Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
ForumPost.Message	Use in the control template for Forum Post listed all the posts	http://obstetricexcellence.com.au/members-forum/General-Forum-Discussion/29.aspx				
ForumPost.PostedBy						
ForumPost.Subject						
ForumPost.Timestamp						

Emailtags

Value Tags	Description	Use	Properties	Value	Default	Notes
<no tags>						



Gallery Module:

Skintags

Skin Tags	Description	Use	Properties	Value	Default	Notes
pbGallerySlideShow	Inserts a Silverlight image gallery slideshow for presenting a gallery collection	http://www.arden.net.au/Projects/external-galvanised-custom-spiral-staircase.aspx http://pegboardcms.com/Gallery1.aspx	Collection	Name/Id of a collection		Lets you override the gallery collection to display. By default the

Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
Gallery.AltImageUrl	Inserts the image path for alt items	Used in gallery control templates				
Gallery.Author	Inserts the gallery image author					
Gallery.Date	Inserts the item image date					
Gallery.ImageUrl	Inserts the item image path url					

Emailtags

Value Tags	Description	Use	Properties	Value	Default	Notes
<no tags>						



Jobs Module

Skintags

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbJobApplicationForm	See "pbJobApplicationForm Form Fields" for relevant form field names. Accessible from the job application link. Gives the ability to post a reply to a job item.	http://www.worknoz.com.au	RedirectTo	String		Makes the form redirect to the
			PasswordFieldName	String	Password	Set the
			EmailFromFieldName	String	EmailFrom	Set the email
			EmailSubjectFieldName	String	EmailSubject	Set the email subject field
			UserEmailAddressFieldName	String	EmailAddress	Set the user email address
			AdminEmailAddressFieldName	String	AdminEmailAddress	Set the administrator
			Form	String		Allows you to override the form being displayed. By
			SubmitButtonText	String	Submit	Lets you override the
			CssClass	String	pbForm	Allows you to override the
			ReceivedText	String	Thankyou, your enquiry has been subn	Set the recieved text
			UserSMSFieldName	String	UserSMS	Set the user
			AdminSMSFieldName	String	AdminSMS	Set the administrator
			Publication	String		Publication to
			PublicationsFieldName	String	Campaigns	Form field to mutiple
			EnableEmSignup	True False	False	If 'True' will subscribe the
			ConfirmMessage	String		Specify a
			EmailDelayHours	Int32	0	Number of hours to delay
			EmailDelayMinutes	Int32	0	Number of minutes to



AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of
AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the
AdminAttachUploads	True False	False	If 'True' will allow the administrator
UserAttachUploads	True False	False	If 'True' will allow the user
UserSMSCountry	Int32	61	Set the SMS country code
AdminSMSCountry	Int32	61	Set the SMS country code
MaxUserSMS	Int32	10	Specify the maximum
OnClientClick	String		JavaScript to attach to the
MaxUserSMSGText	String	Maximum number of SMS already sent	Message to
UserSMSExpiryHours	Int32	0	Hours to pass
AdminEmailDelayHours	Int32	0	The number of hours to delay the
AdminEmailDelayMinutes	Int32	0	the number of minutes to delay the

pbJobApplicationLink	Inserts a link to a form application form. To be played on the Job item page.	http://www.worknoz.com.au	Form	String	Used to specify which form to
			Text	String	Apply for this job
			Target	String	If specified the target value is
			CssClass	String	Specify a CSS class to apply
			NoApplyText	String	Text applied if the job is not



pbJobSearch	Search for job collection items only. http://www.worknoz.com.au	ResultsPage	String	Sets the results page that the user will be redirected to upon submitting a
		SearchFields	String	keyword, collection, category
				Specifies the fields that the search control should provide. The default is "keyword, collection, category", which provides a keywords field, a collection dropdown and a category dropdown, in that order.
		FieldLabels	String	This list works similar to the SearchFields property, and should match up with the fields specified on that property. It overrides the labels given to each field (by default they will use the field name as the label). E.g. "Keywords, Col



		CategoryLevels	Int32	1	The number of category search fields to include - these will be different category levels. E.g. Specifying 3
		ShowAllOption	True False	True	If true, dropdowns contain a "show all"
		ShowLabelInsideField	True False	False	If 'True' the label will
		Dependency	String		Lets you set up field dependencies, so that field B is disabled until field A has been selected. You don't have to
		ButtonText	String	Search	Lets you override the
		UseDropDownFields	True False	False	If true, the fields are generated as dropdown
		AllOptionText	String	[all]	When ShowAllOptio
		ShowInactive	True False	True	If true will show all
		ShowInvisible	True False	True	If true will show all
pbJobSearchResults pbAdvJobSearchResults	Displays search results from the [pbJobSearch] in a list.	SortField	String	SortOrder	Orders the list by the field
		SortDirection	String	ASC	Switches the order of the
		TopPagerVisible	True False	False	Shows a pager
		BottomPagerVisible	True False	True	Shows a pager
		CssClass	String	pbList	Allows you to override the



Template		String	Allows you to select a different
CurrentPage	Int32	0	n/a
PageSize	Int32	10	Sets the number of items per
ShowInactive	True False	False	If true will also list inactive
IncludeMemberContent	True False	False	If 'True' will display
MemberContentOnly	True False	False	If 'True' will display only
ApprovedMemberContentOnly	True False	True	If 'True' will display only members content that
CurrentMemberOnly	True False	False	If 'True' will display only
Member	String		set up the member's ID
EnableAjax	True False	False	If 'True' a ajax will display on
Templates			
HeaderTemplate			
FirstItemTemplate			Only available in
ItemTemplate			
AlternatingItemTemplate			
LastItemTemplate			Only available in
LastAlternatingItemTemplate			Only available in
NoDataTemplate			Only available in
SeparatorTemplate			
FooterTemplate			
pbJobSearchHistory	Allows a user to see saved searches		
SaveLabel	String		Label to show
DeleteLabel	String		Label to show on the delete
StartEmailLabel	String		Label to show on the button
StopEmailLabel	String		Label to show on the button



		HideDisabled	True False	TRUE	Hides disabled buttons
		SaveCss	String	save-favourite	CssClass to apply to the
		DeleteCss	String	delete-favourite	Css class to apply to the
		StartEmailCss	String	email-favourite	Css class to apply to the
		StopEmailCss	String	email-favourite	Css class to apply to the
		DisabledCss	String		Css class to apply to
		SaveAsCss	String	save-search-as	CssClass to apply to the
		SaveAsValidationCss	String	save-search-as-validation	CssClass to apply to the
		SaveSearchAsEmptyText	String	Save search as	Text to show in the textbox
		SaveSearchAsRequiredText	String	Search name required	Error message to show if the
pbJobSearchHistoryList	Inline-template skin control used to list out a members job search	Templates			
		HeaderTemplate			
		ItemTemplate			
		AlternatingItemTemplate			
		SeparatorTemplate			
		FooterTemplate			
		NoDataTemplate			
[pbJobApplicationFormSubmit]	See 'Forms' under 'Advanced Forms'				

pbJobApplicationForm Form Fields



Field Name	Description	Use	Properties	Value	Default	Notes
ContactName	Use these form field names to parse the field data to the jobs collection					
ContactAddress						
ContactSuburb						
ContactState						
ContactPostcode						
ContactCountry						
ContactPhone						
ContactFax						
ContactMobile						
ContactEmail						
Comments						
CoverLetter						
CurriculumVitae						
JobType						
Salary						
Website						
Area						
CompanyName						
JobContactName						
JobContactAddress						
JobContactSuburb						
JobContactState						
JobContactPostcode						
JobContactCountry						
JobContactPhone						
JobContactFax						
JobContactMobile						
JobContactEmail						

Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
Job.JobType						
Job.ContactName						
Job.ContactPhone						
Job.ContactMobile						
Job.ContactFax						
Job.ContactEmail						
Job.Salary						
Job.Website						
Job.LocationAddress						



Job.LocationSuburb
Job.LocationState
Job.LocationCountry
Job.LocationPostcode
Job.Area
Job.CompanyName

Emailtags

Value Tags

<no tags>

Description	Use	Properties	Value	Default	Notes
-------------	-----	------------	-------	---------	-------



Members Module:

Skin tags

Skin Tags	Description	Use	Properties	Value	Default	Notes
pbCancelMembership	Inserts a form to delete a member.	http://www.emergencyteachers.com.au/endmembership.aspx	DeleteMember	True False	False	If 'True' member will be deteted from Members
			ConfirmMessage	String	Please confirm that you would like to c	Text displayed upon confirmation of cancellation
			CancelMessage	String	Your membership account has now be	Text displayed that confirms the cancellation
			SendAdminEmail	True False	False	If 'True' sends the administrator a notification email
			SendUserEmail	True False	False	If 'True' sends the user a confirmation email
			RedirectUrl	String		Specify a page to redirect to after submission
pbMemberActivitySummary	A summary of the current member activity. Will list current members online.	http://www.saltmedia.co.nz	MemberIdParam	String	mid	
			AvatarWidth	Int32	32	Set the width of the members avatar image
			AvatarHeight	Int32	32	Set the height of the members avatar image
			AvatarDefaultImageUrl	String	~\system\images\avatars\noavatar.jpg	Specify an alternative avatart default image path
			DatetimeFormat	String	dd-MMM-yyyy HH:mm	Edit the date format
			MemberActivityPageUrl	String		
			MaxResults	Int32		10 Max amount of results to display
			AvatarRegionName	String		The name of the image region that contains the member's avatar
			UseMemberProfile	True False	False	If 'True' uses the members profile page instead of the MemberActivityPageUrl
			RatingAsText	True False	True	Either uses images or text to display the rating
			RatingImageHeight	Int32	0	The rating image height in pixels
			RatingImageWidth	Int32	0	The rating image width in pixels



RatingImageYesNoHeight	Int32	0	Set the height of the yes/no rating
RatingImageYesNoWidth	Int32	0	Set the width of the yes/no rating
RatingImage	String		Set the path to the image that is to be used for the rating
RatingImageHighlighted	String		Url of the image to display for a selected rating
RatingImageYes	String	/system/images/ratings/up.png	Url of the image to display for an unselected Yes option of a Yes/No rating
RatingImageYesHighlighted	String	/system/images/ratings/uph.png	Url of the image to display for a selected Yes option of a Yes/No rating
RatingImageNo	String	/system/images/ratings/down.png	Url of the image to display for an unselected No option of a Yes/No rating
RatingImageNoHighlighted	String	/system/images/ratings/downh.png	Url of the image to display for a selected No option of a Yes/No rating
FilterByRatingGroup	String	all	Specify which rating information to display. Can be one of the following values: * "all" – Show all ratings and additional rating fields (default) * "additionaldata" – Show additional data values only * "overall" – Show the overall rating for this comment only (see below for an explanation of how this is calculated) * "graphical_multiple" – Show graphical ratings that are not graphical yes/no ratings (i.e. there are more than two rating options) only * "graphical_yesno" – Show graphical yes/no ratings only * "text" – Show text ratings (i.e. ratings containing a dropdown list) only
HideRatingLabelDiv	True False	False	Hide the label div for the ratings
ShowRatings	True False	False	If 'True' ratings will be displayed



pbMemberForgotPassword	Allows the user to retrieve a forgotten password.	http://www.fiera.com.au/retrieve-password.aspx	ResetPassword	True False	False	If resetting password, sends a link back to the page that contains the reset password control via the email template
			ResetPage	String		Page name that contains the pbMemberResetPasswordSubmit skintag
			ResetPasswordTime	Int32	1440	Number of minutes that the link to the reset page is valid
			ButtonText	String	Recover Password	
			ConfirmText	String	An email has been sent to you containing your login details	
			EmailTemplate	String		Name of the template used to send through the link to reset the members password. This should contain the skintag [Member.ResetPasswordURL] to provide the link back to the reset page
			SendToInactive	True False	True	Sends the password through to a member based on their active flag
			InactiveText	String		Error text displayed if the member is inactive
			ShowUserName	True False	FALSE	display user name along with email address
			BothFieldsRequired	True False	FALSE	makes both email address and username field require.
			EmailAddressLabelText	String	Your Email Address	allow you to set different label text for email address field name
			UserNameLabelText	String	Your User Name	allow you to set different label text for user name field name
			ConfirmPasswordField	String	ConfirmPassword	Name of the form field that is used to confirm the password
pbMemberResetPasswordSubmit	Allows the user to reset their password in conjunction with the pbMemberForgotPassword skintag. The minimum form fields for this skintag to work are: EmailAddress, Password, ConfirmPassword					



			ErrorPage	String		Name of the page that a user is redirected to if their reset password link has expired/does not exist
			InvalidEmailText	String	Password reset request not found for this member	The user must enter in their email address again as part of the password reset. If the email doesn't match the reset password link, the error is displayed using the pbFormErrors skintag
pbMemberInfo	Displays the currently logged in members details. e.g. Name, Avatar	http://www.saltmedia.co.nz	Field	String		the member field to display. The field names can be obtained from the member pages on the console.
			NonMemberText	String		the text when the members isnt logged in
			McMode	True False	False	When set to 'True', member information is retrieved from the current SiteObject's member content status
			DateFormat	String		If retrieving a date value from a member (such as the date of birth), this property will set the date format to be used
pbMemberLogin	Provides a control with which members can log in or out of the website. By default, while the member is not logged in, it acts as a login control where the member must enter a correct username and password. Once logged in, it displays the member's username and acts as a logout control so the member can click a button to logout	http://www.whiteint.com.au/ http://www.pegboardcms.com http://www.hamiltonhall.com.au/	LogoutRedirectUrl	String		the redirect URL after logout
			LoginRedirectUrl	String		the redirect URL after login successful
			FailRedirectUrl	String		fail login redirect to the URL
			UsernameLabel	String	Username	Lets you override the username label
			PasswordLabel	String	Password	Lets you override the password label
			LoginText	String	Login	Lets you override the text on the login button
			LogoutText	String	Logout	Lets you override the text on the logout button
			WelcomeMessage	String	Welcome {Username}	Allows you to specify a message that is shown once the member logs in



pbMemberPaidSignupForm	DEPRECATED! use MemberSignup requirespayment property	FailureMessage	String	Invalid Username or Password	Lets you override the error message is displays after a failed login attempt
		EnableLogin	True False	True	If false, the control can only be used to logout
		EnableLogout	True False	True	If false, the control can only be used to login
		EnableFailMessage	True False	False	If false, no message is displayed for failed logins
		LoginRoles	String		Allows you to limit the tag to only allow login for members who have access to the specified role(s)
		UsernameEmptyMessage	String		Lets you set the watermark text for the username textbox
		PasswordEmptyMessage	String		Lets you set the watermark text for the password textbox
		UsernameWidth	Unit	150px	Specifies the width of the username textbox
		PasswordWidth	Unit	150px	Specifies the width of the password textbox
		EnableForgotPassword	True False	False	Enable Forgot password link button
		ForgotPasswordText	String	Forgot Password	Set the text for the forgot password text
		ForgotPasswordPage	String		forgot password page name
		UsernameMaxLength	Int32	0	Set the maximum length of the username
		PasswordMaxLength	Int32	0	Set the maximum length of the password
		LockedMessage	String		Message to display if the members account has been locked
		LockedUrl	String		The url to redirect to if the member is locked
		AddMemberToRole	String		Specify member roles (separated by a ',') which new members will be added to by default upon signing up
		NewMemberActive	True False	False	Specifies whether new members signing up will be active by default
		UsernameFieldName	String	Username	Nominate the username field from the form



RandomPassword	True False	False	if Random Password is true, the submit button will appear whatever the password field existed or not. A random password will be generated if no password field or password field hasn't been filled out during new member signup.
BillingProductFieldName	String	BillingProduct	the dropdown list field name in the form. It contain the products which users will purchase
ForcePayment	True False	False	
EmptyCart	True False	True	
RedirectTo	String		Makes the form redirect to the specified URL after the user submits it
PasswordFieldName	String	Password	
EmailFromFieldName	String	EmailFrom	
EmailSubjectFieldName	String	EmailSubject	
UserEmailAddressFieldName	String	EmailAddress	
AdminEmailAddressFieldName	String	AdminEmailAddress	
Form	String		Allows you to override the form being displayed. By default the current form page is used (if applicable)
SubmitButtonText	String	Submit	Lets you override the text on the submit button
CssClass	String	pbForm	Allows you to override the CSS class on the form
ReceivedText	String	Thankyou, your enquiry has been submitted	
UserSMSFieldName	String	UserSMS	
AdminSMSFieldName	String	AdminSMS	
Publication	String		Publication to signup to
PublicationsFieldName	String	Campaigns	Form field to mutiple publications
EnableEmSignup	True False	False	
ConfirmMessage	String		
EmailDelayHours	Int32	0	Number of hours to delay the sending of customer emails
EmailDelayMinutes	Int32	0	Number of minutes to delay the sending of customer emails
AdminAttachUploads	True False	False	
UserAttachUploads	True False	False	



		UserSMSCountry	Int32	61	
		AdminSMSCountry	Int32	61	
		MaxUserSMS	Int32	10	
		MaxUserSMSText	String		Maximum number of SMS already sent to this number
		UserSMSExpiryHours	Int32	0	
		AdminEmailDelayHours	Int32	0	The number of hours to delay the admin email from being sent
		AdminEmailDelayMinutes	Int32	0	the number of minutes to delay the admin email from being sent
pbMemberSearch	Provides a search control to search for Members.	ResultsPage	String		Sets the results page that the user will be redirected to upon submitting a search. This page should contain a [pbMemberSearchResults] to display the results. Leave unspecified to use the current page.
		SearchFields	String	keyword	Specifies the fields that the search control should provide. The default "keyword" field searches any of the text fields on a member. Any members field can be searched on, including additional fields.
		FieldLabels	String		This list should match up with the fields specified on the SearchFields property. It overrides the labels given to each field (they default to match the field name).
		ButtonText	String	Search	Lets you override the text on the search button.
pbMemberSearchResults pbAdvMemberSearchResults	A list control similar to the [pbCollectionList], required to list search results from a [pbMemberSearch].	Sort	String	Username	Orders the list by the field specified
		TopPagerVisible	True False	False	Shows a pager above the list
		BottomPagerVisible	True False	True	Shows a pager below the list
		CssClass	String	pbList	Allows you to override the css class on the UL tag



pbMemberSignupForm pbMemberPaidSignupForm	This form allows a user to sign themselves up as a member. In addition it provides all the functionality of a normal pbForm control. The form can also be used to edit the members details.	http://www.fiera.com.au/Sign-Up.aspx http://www.sydneywomensnetwork.com.au/MembershipRegistration.aspx	AddMemberToRole	String		Used to add a member to a role
			NewMemberActive	True False	True	By default set to 'True', will make the new user active
			UsernameFieldName	String	Username	Set the username field name
			RandomPassword	True False	False	If 'True' will generate a random password (emailtag [RandomPassword])
			AddProfileToCollection	True False	False	If 'True' will add the new profile to a collection
			NewMemberContentActive	True False	False	If 'True' will make new content active without needing authorisation
			ButtonTextOnUpdate	String	Update details	If the user is logged in, the form will display an update button, set the text with the property
			BillingProductFieldName	String	BillingProduct	Select a product to bill to the subscriber
			SignupRequiresPayment	True False	False	If 'True', user must pay upon signup
			RequiresPayment	True False	False	" "

UpdateConfirmText	String	Thankyou, your details have been updt	Text displayed as confirmation on update
UsernameMaxLength	Int32	0	Specify a maximum user name length
PasswordMaxLength	Int32	0	Specify a maximum password length
ForcePayment	True False	False	If 'True' user must make payment
EmptyCart	True False	True	Set to 'True' by default. Empties cart.
PromotionCodeTemplate	String		Set a template for the promotion code
EnableEmailOnUpdate	True False	False	If 'True' will send an email upon update
RedirectTo	String		Set the redirect page after submission
PasswordFieldName	String	Password	Set the password field name
EmailFromFieldName	String	EmailFrom	Set the email from field name
EmailSubjectFieldName	String	EmailSubject	Set the email subject field name
UserEmailAddressFieldName	String	EmailAddress	Set the user email address field name
AdminEmailAddressFieldName	String	AdminEmailAddress	Set the administrator email address field name
Form	String		Specify the console form to use
SubmitButtonText	String	Submit	Specify the text for the submit button, set to 'Submit' by default
CssClass	String	pbForm	Specify a CSS class for the form
ReceivedText	String	Thankyou, your enquiry has been subn	Change the text displayed upon submission
UserSMSFieldName	String	UserSMS	Set the user SMS field name
AdminSMSFieldName	String	AdminSMS	Set the adminstrator SMS field name
Publication	String		Assign the user to an e-marketing publication
PublicationsFieldName	String	Campaigns	Specify a publications field name if user is to be subscribed to more than one publication
EnableEmSignup	True False	False	If 'True' assigns the user to e-marketing
ConfirmMessage	String		Set the confirmation message
EmailDelayHours	Int32	0	Set the delay in hours before user recieves email



			EmailDelayMinutes	Int32	0	Set the delay in minutes before the user receives email
			AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of administrator emails
			AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the sending of administrator emails
			AdminAttachUploads	True False	False	If 'True' allows the administrator to attach uploads
			UserAttachUploads	True False	False	If 'True' allows the user to attach uploads
			UserSMSCountry	Int32	61	Specify the user SMS country code
			AdminSMSCountry	Int32	61	Specify the administrator SMS country code
			OnClientClick	String		JavaScript to attach to the Form Submit Button's OnClick event
			MaxUserSMS	Int32	10	Set a maximum number of SMS to send per user
			MaxUserSMSText	String		Maximum number of SMS already sent Error message to show when
			UserSMSExpiryHours	Int32	0	Hours to pass until SMS count expires
			NewMemberRequiresConfirmation	True False	False	If 'True' then the membership will not be activated until the member has confirmed their membership by navigating to a members confirmation page sent to them in the email.
			AdminEmailDelayHours	Int32	0	The number of hours to delay the admin email from being sent
			AdminEmailDelayMinutes	Int32	0	the number of minutes to delay the admin email from being sent
pbMemberUpdateSummary	Displays a list of links to member profiles	http://www.saltmedia.co.nz	MaxResults	Int32	10	Limit the amount of profiles to display
pbMemberContentForm	A form that will enter the user as a new member and also submit the data to a collection. The collection must use additional fields and these fields need to be	http://www.wcaa.com.au/Victoria/Membership-Application-VIC.aspx	ContentParent	String		Specify whether the product has a parent collection.
			ObjectType	String		News,Datalist,Product,etc..
			BillingProduct	String		Specify a product item to attach the member content to.



labelled "Profile_fieldname".

GoToCart	True False	False	If true, the user is redirected to the Shopping Cart page upon clicking the button
GoToCheckout	True False	False	If true, the user is redirected to the first step of the Checkout process upon clicking the button.
RedirectTo	String		Makes the form redirect to the specified URL after the user submits it
PasswordFieldName	String	Password	The field name used to specify the members password
EmailFromFieldName	String	EmailFrom	The field name used to specify the members from email
EmailSubjectFieldName	String	EmailSubject	The field name used to specify the email subject sent to the user
UserEmailAddressFieldName	String	EmailAddress	The field name used to specify the email address that appears in the 'To' address when an email is sent out
AdminEmailAddressFieldName	String	AdminEmailAddress	The field name used to specify the email address that appears in the 'From' address when an email is sent out
Form	String		Allows you to override the form being displayed. By default the current form page is used (if applicable)
SubmitButtonText	String	Submit	Lets you override the text on the submit button
CssClass	String	pbForm	Allows you to override the CSS class on the form
ReceivedText	String	Thankyou, your enquiry has been sub	Text that displays after the form has been submitted
UserSMSFieldName	String	UserSMS	The field name in the form that specifies the users SMS name
AdminSMSFieldName	String	AdminSMS	The field name in the form that specifies the admin SMS name
Publication	String		Publication to signup to
PublicationsFieldName	String	Campaigns	Form field to mutiple publications
EnableEmSignup	True False	False	If 'True' adds the user as an e-marketing subscriber
ConfirmMessage	String		N/A



EmailDelayHours	Int32	0	Number of hours to delay the sending of customer emails
EmailDelayMinutes	Int32	0	Number of minutes to delay the sending of customer emails
AdminEmailDelayHours	Int32	0	Number of hours to delay the sending of administrator emails
AdminEmailDelayMinutes	Int32	0	Number of minutes to delay the sending of administrator emails
AdminAttachUploads	True False	False	N/A
UserAttachUploads	True False	False	N/A
UserSMSCountry	Int32	61	N/A
AdminSMSCountry	Int32	61	N/A
OnClientClick	String		JavaScript to attach to the Form Submit Button's OnClick event
MaxUserSMS	Int32	10	N/A
MaxUserSMSText	String	Maximum number of SMS already sent	N/A
UserSMSExpiryHours	Int32	0	N/A
AdminEmailDelayHours	Int32	0	The number of hours to delay the admin email from being sent
AdminEmailDelayMinutes	Int32	0	the number of minutes to delay the admin email from being sent
NewMemberContentActive	True False	False	If 'True' will make new content active without needing authorisation
pbAdvMembers	Generates a summary of current members.	http://www.saltmedia.co.nz	
ShowInactive	True False	False	If 'True' will display items that are inactive
AdminMode	True False	False	N/A
EditForm	String		Path to specify the location of the members edit form
InsertForm	String		Path to specify the location of members insert form
DetailPage	String		Specify the path of the detail page
MasterKeyField	String		N/A
DetailKeyField	String		N/A
Sort	String		Specifies how items are sorted
RandomSort	True False	False	If 'True' will display items in a random order
Filter	String		N/A



pbMemberSignupConfirm	This control must be included in a membership confirmation page. It controls how the membership state must be set when a member confirms their membership.	MaxItems	Int32	0	The max amount of items displayed.
		PageParameter	String		N/A
		PageSize	Int32	0	Max size of page items
		CurrentPageIndex	Int32	0	N/A
		PageCount	Int32		N/A
		RecordCount	Int32		N/A
		PageMethod	PagingMethod	QueryString	PostBack,QueryString
		Templates			
		HeaderTemplate			
		FirstItemTemplate			
		ItemTemplate			
		AlternatingItemTemplate			
		LastItemTemplate			
		LastAlternatingItemTemplate			
		SeparatorTemplate			
		FooterTemplate			
		NoDataTemplate			
		CssClass	String	content	The name of the CSS class to apply to the content of any messages
		RegionName_Success	String		The content region that contains the Success message
		RegionName_Failed	String		the content region that contains the Failed message
		ApproveMember	True False	True	If 'True' then the member is automatically approved and activated. If 'False' then the member is set to Confirmed and the administrator must manually approve the member in the Administration Console in order to activate the membership.
		SendAdminEmail	True False	True	If 'True' then an email will be sent to the administrator when the member confirmation page is hit
		EmailFrom	String		The "From" address for the admin email. This value will default to the site's administrator email address if the property is not specified.



		EmailTo	String		The "To" address for the admin email. This value will default to the site's administrator email address if the property is not specified.
		StripHtml	True False	False	If true, removes all html markup from the content.
		ContainerType	ContainerObjectType	None	None,Span,Div
[pbAdvMemberLogin]	Refer to "Advanced"				
[pbMemberSignupFormSubmit]	Refer to "Forms" under "Advanced"				
[pbAdvMemberRoles]	displays the role names that the member belongs to	Filter	String		filter role names using filter property
		[ItemTemplate]			
		[Item.name]			
		[/ItemTemplate]			
		[/pbAdvMemberRoles]			
		Sort	String		Specifies how items are sorted
		MaxItems	Int32	0	The max amout of items displayed.
pbMemberContentSubscribe	Allows a user to subscribe to a collection	ControlType	Button Image Link	Button	Determines how to render the button
		Collection	String		Determines which collection to subscribe to
		SubscribelImageUrl	String		Image URL to use when the button is in Image mode and the member is not subscribed
		UnSubscribelImageUrl	String		Image URL to use when the button is in Image mode and the member is subscribed
		McUnsubMessage	String	"Stop receiving notification emails for this Collection"	Message to show on the button if the user is subscribed.
		McSubMessage	String	"Start receiving notification emails for this Collection"	Message to show on the button if the user is not subscribed.



pbMembershipRedirect	This control will automatically redirect the user to another page, specified by the control, if the current date does not fall within the early renewal period specified by the Membership. This can be placed on your renewal page to stop users from renewing their membership earlier than you prefer.	RedirectUrl	String		Location to redirect the member to.
pbMembershipStatus	Displays the current status of a membership	ExpiryMessage	string	Your membership will expire in {remainingdays} days(s), {renewlink}	Sets the message displayed by this control. It supports the following dynamic tag values: {remainingdays} {renewlink} {startdate} {enddate} {membershipname}
		RenewUrl	String		Url to redirect to for renewal
		RenewLinkText	String	click here to renew	Text on the renewal link
		ReminderDays	String		30 Number of days to determine
pbMemberAddressFormSubmit	Allows a submission of a form to update a member's address book.	DeleteButtonControlType	Button ImageButton LinkButton	Button	Determines how to render the delete button
	This control acts like a regular form and will provide the properties of a pbFormSubmit in addition to those listed here.	DeleteButtonCssClass	String	deletebutton	Determines the CSS class to give to the delete control
		DeleteButtonButtonText	String	Delete	Determines the text to show on the delete button
		DeleteButtonImageUrl	String		Image to use for the delete button when in image mode
		DeleteButtonConfirmMessage	String		Confirmation message to use when deleting (causes a popup alert when the button is pressed)
		DefaultItemtext	String	Select a Address	Empty item text to show in the address dropdown
		SubmitButtonDivCssClass	String	memberAddressSaveButton	Css class to give to the div around the submit button



pbMemberWindowsAuth	Allows a user to log in using the Windows users accessible to the server. Place this control on your login page.	DeleteButtonDivCssClass	String	memberAddressSaveButton	Css class to give to the div around the submit button
		DropDownDivCssClass	String	memberAddressDropDown	Css class to give to the div around the

Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
Member.Username	These can be used in Member list Control templates, such as the Members search					
Member.Password						
Member.Active						
Member.SignupDate						
Member.FirstName						
Member.LastName						
Member.Email						
Member.Address						
Member.Address2						
Member.Suburb						
Member.State						
Member.Postcode						
Member.Country						
Member.PhoneNo						
Member.FaxNo						
Member.MobileNo						
Member.DateOfBirth						
Member.Gender						
Member.WebsiteUrl						
Member.PointBalance						
Member.Notes						
Member.Status						



Emailtags

Value Tags	Description	Use	Properties	Value	Default	Notes
Member.Username						
Member.Password						
Member.Active						
Member.SignupDate						
Member.FirstName						
Member.LastName						
Member.Email						
Member.Address						
Member.Address2						
Member.Suburb						
Member.State						
Member.Postcode						
Member.Country						
Member.PhoneNo						
Member.FaxNo						
Member.MobileNo						
Member.DateOfBirth						
Member.Gender						
Member.WebsiteUrl						
Member.PointBalance						
Member.Notes						
Member.Status						
Member.Roles						
Member.IsOrg						
Member.Company						
Member.IsOrgAdmin						
Member.LastModified						
Member.Searchable						
Member.DeletionScheduled						
Member.DeletionScheduledDateTime						
Member.LoginRedirectUrl						



Reference Guide

Member.MemberPrimaryRole
Member.MemberPrimaryRoleName
Member.IdentityProvider
Member.IdentityImported
Member.IdentityToken
Member.IdentityName
Member.IdentityFullName
Member.IsTaxExempt





Links Module

Skintags

Skin Tags	Description	Use	Properties	Value	Default	Notes
[pbCollectionSummary]	Please refer the 'General' section	http://www.biogrow.com.au/Links.aspx				
[pbCollectionList]		http://bhaustralia.com.au/Links.aspx				
[pbCollectionGrid]						
[pbCollection]						

Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
Link.Target						
Link.Url						
Link.OnClick						
Link.PageUrl						

Emailtags

Value Tags	Description	Use	Properties	Value	Default	Notes
<no tags>						



News Module:

Skin tags

Skin Tags	Description	Use	Properties	Value	Default	Notes
[pbCollectionSummary]	Please refer to the general section	http://www.stemcellcentre.ed				
[pbCollectionList]		u.au/newsevents/news.aspx				
[pbCollectionGrid]		http://brightongrammar.vic.e				
[pbCollection]		du.au/BGS_Portal/ParentsStu				

Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
[News.ArticleDate]	Inserts the news items article date	http://www.stemcellcentre.ed u.au/newsevents/news.aspx http://brightongrammar.vic.e du.au/BGS_Portal/ParentsStu dentsandStaff/News.aspx				[News.Article Date("dd/MM /yyyy")] -> "02/11/2009" [News.Article Date("dd/MM /yy")] -> "02/11/09" [News.Article Date("dd/MM /yyyy hh:mm tt")] -> "02/11/2009 12:35 PM"
[News.Author]	Inserts news item author	http://www.stemcellcentre.ed u.au/newsevents/news.aspx http://brightongrammar.vic.e du.au/BGS_Portal/ParentsStu dentsandStaff/News.aspx				

Emailtags

Value Tags	Description	Use	Properties	Value	Default	Notes
<no tags>						





Polls Module:

Skintags

Skin Tags	Description	Use	Properties	Value	Default	Notes
pbPoll	Displays a single Poll on the page and allows the user to submit their vote. Also displays the results of a Poll on the page as a bar graph. Setting the Collection property causes the control to pick up the 'Current Poll' selected for that collection, otherwise the latest Poll from any collection is picked. The control can also select a Poll at random.	http://www.macromeats.com.au http://aussieform.com.au/	Collection	String		Sets the Poll collection to
			CheckIfVoted	True False	True	If true, allows only one vote per user; the user's IP
			RedirectOnVote	True False	False	If true, redirects the
			RandomPoll	True False	False	If true, selects a random poll
			ButtonText	String	Vote	Sets the text
			CssClass	String	pbPoll	Sets the container CSS
			DisplayCounts	True False	True	Displays the count of votes
			DisplayPercent	True False	True	Displays the percent of
			RadioButtonColumns	Int32	1	No. of radio button
			GraphWidth	Unit		Sets the max. width of the
			GraphBarHeight	Unit		Sets the bar height on the
			LinkToPollDetails	True False	True	If true, clicking the Poll
			ShowResults	ShowResultsMode	Auto	question links Auto, Never, Al
pbResultBar	Displays the results of the poll in a bar graph	http://www.macromeats.com.au http://aussieform.com.au/	Answer	Text		
			VoteCount	Number		
			VoteTotal	Number		
			DisplayCount	True/False		
			DisplayPcent	True/False		
			BarHeight	Size(Unit)		



Control Tags

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbPoll pbCtPoll	Displays a single Poll on the page and allows the user to submit their vote. Also displays the results of a Poll on the page as a bar graph. Setting the Collection property causes the control to pick up the 'Current Poll' selected for that		CssClass	String	pbPoll	Apply a CSS
			DisplayPercent	True False	True	If 'True' will display the
			GraphWidth	Unit		Set the width
			GraphBarHeight	Unit		Set the height
			LinkToPollDetails	True False	True	If 'True' will link to the poll

Valuetags

Value Tag	Description	Use	Properties	Value	Default	Notes
<no tags>						

Emailtags

Value Tag	Description	Use	Properties	Value	Default	Notes
<no tags>						



Products Module:

Skin Tag	Description	Use	Properties	Value	Default	Notes
pbProductAddCheckedToCart	Used in conjunction with "pbProductAddToCartCheckbox" to add multiple products to the checkout. Inserts an 'Add to Cart' button on the product details page, or in a products-related List control. Always adds a quantity of 1 to the Cart unless [pbProductAddQuantity] is present.	http://www.pelleleathers.com.au/Collection/Ranges/Ascona.aspx	GoToCart	True False	True	If true, the user is redirected to
			GoToCheckout	True False	False	If true, the user is redirected to the first step
			Text	String	Add to cart	Lets you override the
			ImageUrl	String		Specifies an image path to
			EnableTimer	True False	False	If 'True' set the timer for
			TimeCounter	Int32	5	Set the time
			ErrorText	String	Only items from one range can be added to the cart	Set the text to display on errors
			PropertyErrorText	String		Error message to display if not all
			AccountNumber	String		The Google Analytics
			DomainName	String		Enter the domain name to enable sub-
			SetAllowLink	String	true	The value to set for the "_setAllowLink" option. This
			SetAllowHash	String	false	The value to set for the "_setAllowHash" option. This
			EnableGoogleAnalyticsCartAdd	True False	False	If true, the shopping cart will process any previous



pbProductAddToCartCheckbox	Used in control templates to provide a checkbox selection for adding multiple products to the cart with a "pbProductAddCheckedToCart" tag	Checked	True False	Determines whether this box is checked on page load		
pbProductAddComments	Use with the pbProductAddToCart button: Inserts a comments textbox so the user can enter a comment against the product they purchase.	CssClass	String	textbox	Overrides the CSS class on	
		Width	Unit		Sets the width	
		Height	Unit		Sets the	
		Rows	Int32	4	Sets the number of lines in the	
		DefaultComment	String		Set a default comment to	
		Value	String		Insert a value into the	
		IsRequired	True False	False	Sets whether a comment must be	
		ErrorText	String	Please enter a comment	Message to show when	
pbProductAddQuantity	For use with the pbProductAddToCart button: Inserts a quantity textbox, so the user can enter the quantity they want to purchase.	http://bremerton.com.au/TheWines/BuyOnline.aspx	TextboxWidth	Unit	40px	Sets the width of the quantity field.
		http://www.henryandlily.com.au/Products/ClutchingToyLara.aspx	EnableArrows	True False	False	*Further notes: this tag is always used If 'True' will display arrows that allow the
			ShowSpinButtons	True False	False	
			DecimalPlaces	Int32	0	Set the amount of
			TextAlign	HorizontalAlign	Right	NotSet, Left, Ce
			RemoveSpinButtonText	True False	FALSE	Removes hidden span
pbProductAddToCart	For use with E-Commerce: Inserts an 'Add to Cart' button on the product details page, or in a products-related List control.	http://bremerton.com.au/TheWines/BuyOnline.aspx	RedirectTo	String	Set the page to redirect to after adding to cart if not	



Always adds a quantity of 1 to the Cart unless [pbProductAddQuantity] is present.

<http://www.henryandlily.com.au/Products/ClutchingToyLara.aspx>

GoToCart	True False	True	If true, the user is redirected to
GoToCheckout	True False	False	If true, the user is redirected to the first step
Text	String	Add to cart	Lets you override the
ImageUrl	String		Specifies an image path to
EnableTimer	True False	False	n/a
TimeCounter	Int32	5	n/a
ErrorText	String	Item could not be added to cart	The text
PropertyErrorText	String		
EnableAjax	True False	True	If 'False', then Ajax is
OnClientClick	String		The javascript to execute
AccountNumber	String		The Google Analytics
DomainName	String		Enter the domain name to enable sub-
SetAllowLink	String	true	The value to set for the "_setAllowLink" option. This
SetAllowHash	String	false	The value to set for the "_setAllowHash" option. This
EnableGoogleAnalyticsCartAdd	True False	False	If true, the shopping cart will process any previous

pbProductAddToCartAdv

Used with collection lists/summaries. Allows the user to add multiple items to the cart at once. Requires pbProductAddToCartCheckbox OR pbProductAddQuantity in the item template.

<http://fruitinbox.com.au/BuilYourOwnBox.aspx>

GoToCart	True False	True	If true, the user is redirected to
GoToCheckout	True False	False	If true, the user is redirected to the first step



pbProductFeaturedGrid pbAdvProductFeaturedGrid	Lists featured products in a grid format.	Text	String	Add to cart	Lets you override the
		ImageUrl	String		Specifies an image path to
		EnableTimer	True False	False	n/a
		TimeCounter	Int32	5	n/a
		ErrorText	String	Only items from one range can	The text
		PropertyErrorText	String		Error message to display if not all
		AccountNumber	String		The Google Analytics
		DomainName	String		Enter the domain name to enable sub-
		SetAllowLink	String	true	The value to set for the "_setAllowLink" option. This
		SetAllowHash	String	false	The value to set for the "_setAllowHash" option. This
		EnableGoogleAnalyticsCartAdd	True False	False	If true, the shopping cart will process any previous
		CssClass	String	pbGrid	Allows you to override the
		Columns	Int32	1	Number of
		Collection	String		Sets the control to pick up items from
		Template	String		Allows you to select a
		ShowInactive	True False	False	If true the control will
		ShowInvisible	True False	False	If 'True' will show items
		ObjectType	String		collection/cat
		MaxRows	Int32	0	Unlimited row
		Category	String		Filter the collection by
		Filter	String		Filter the



ShowBookmarksOnly	True False	False	If 'True' will only show
Sort	String		Sort the
RandomSort	True False	False	If true, items in the list are
SortField	String		Orders the grid by the
SortDirection	String	ASC	Switches the order of the
IncludeMemberContent	True False	False	If 'True' will display
MemberContentOnly	True False	False	If 'True' will display
ApprovedMemberContentOnly	True False	True	Will display only members content that
CurrentMemberOnly	True False	False	If 'True' will display for the set up the
Member	String		member's ID
TopPagerVisible	True False	False	Displays a
BottomPagerVisible	True False	True	Displays a
PageSize	Int32	10	Sets the number of
			items per
EnableAjax	True False	False	If 'True' will display an ajax
CategoryParameter	String		Parameter name which
TopPagerCssClass	String		Allows you to override the
BottomPagerCssClass	String		Allows you to override the
CurrentItemNameAsCategory	True False	False	n/a
HideOldItems	True False	False	If 'True' will
HideCurrentItem	True False	True	Set to 'True' by default. If displayed on a
OldItemAsStartDate	True False	True	
MaxAge	Int32	0	Maximum age
MinAge	Int32	0	Minimum age
Direction	RepeatDirection	Horizontal	Horizontal,Ver
GridLines	GridLines	None	None,Horizont
Layout	RepeatLayout	Table	Table,Flow
Templates			



			HeaderTemplate			
			ItemTemplate			
			AlternatingItemTemplate			
			SeparatorTemplate			
			FooterTemplate			
pbProductFeaturedList pbAdvProductFeaturedList	Lists featured products, using an unordered list.	http://www.promotionswarehouse.com.au/	ListCssClass	String	list	Apply a CSS class to the list
			CssClass	String	pbList	Allows you to override the
Collection			String		Sets the control to pick up items from	
Template			String		Allows you to select a	
ShowInactive			True False	False	If true the control will	
ShowInvisible			True False	False	If 'True' will show pages	
ObjectType			String		collection/cat	
MaxRows			Int32	0	Unlimited row	
Category			String		Filter the collection by	
Filter			String		Filter the	
ShowBookmarksOnly			True False	False	If 'True' will only show	
Sort			String		Sort the	
RandomSort			True False	False	If true, items in the list are	
SortField			String		Orders the grid by the	
SortDirection			String	ASC	Switches the order of the	
IncludeMemberContent			True False	False	If 'True' will show	
MemberContentOnly			True False	False	If 'True' will display	
ApprovedMemberContentOnly			True False	True	If 'True' will show only members	
CurrentMemberOnly			True False	False	If 'True' will display for	
Member			String		set up the member's ID	
TopPagerVisible			True False	False	Displays a	



BottomPagerVisible	True False	True	Displays a
PageSize	Int32	10	Sets the number of items per
EnableAjax	True False	False	If 'True' will display an ajax
CategoryParameter	String		Parameter name which
TopPagerCssClass	String		Allows you to override the
BottomPagerCssClass	String		Allows you to override the
CurrentItemNameAsCategory	True False	False	n/a
HideOldItems	True False	False	If 'True' will not display old
HideCurrentItem	True False	True	Set to 'True' by default. If displayed on a detail page,
OldItemAsStartDate	True False	True	
MaxAge	Int32	0	Maximum age
MinAge	Int32	0	Minimum age
Templates			
HeaderTemplate			
ItemTemplate			
AlternatingItemTemplate			
SeparatorTemplate			
FooterTemplate			
pbProductFeaturedSummary pbAdvProductFeaturedSummary			
ListCssClass	String	summary	
CssClass	String	pbSummary	Allows you to override the
Collection	String		Sets the control to pick up items from
Template	String		Allows you to select a
ShowInactive	True False	False	If true the control will
ShowInvisible	True False	False	If 'True' will show pages
ObjectType	String		collection/cat
MaxRows	Int32	0	The maximum number of
StartingRow	Int32	0	n/a

Lists items within any collection, using an unordered list. By default this will dynamically pick up items underneath the current collection page. You can override this by setting the Collection property. Unlike the CollectionList, this control picks up only a set number of items specified by the MaxRows property.



Category	String		Filter the collection by
Filter	String		Filter the
ShowBookmarksOnly	True False	False	If 'True' will show only
Sort	String		Sort the
RandomSort	True False	False	If true, items in the list are
SortField	String		Orders the summary by
SortDirection	String	ASC	Switches the order of the summary
IncludeMemberContent	True False	False	If 'True' will show
MemberContentOnly	True False	False	If 'True' will display
ApprovedMemberContentOnly	True False	True	If 'True' will show only members
CurrentMemberOnly	True False	False	If 'True' will display for
Member	String		set up the member's ID
CategoryParameter	String		Parameter name which
HideOldItems	True False	False	Maximum age
HideCurrentItem	True False	True	Minimum age
OldItemAsStartDate	True False	True	
Templates			
HeaderTemplate			
ItemTemplate			
AlternatingItemTemplate			
SeparatorTemplate			
FooterTemplate			
pbProductGroupSummary pbAdvProductGroupSummary	Displays a summary list of items within a Group.	http://cigars.simpleid.com.au/Products/CigarCollection/Cigars/CubanCigars.aspx	CssClass
			String
			pbSummary
			Apply a CSS class to the summary list
Template	String		Set the
NoDataMessage	String	No Grouped Products	template for Messaged displayed if



			IncludeMemberContent	True False	False	If 'True' will display
			MemberContentOnly	True False	False	If 'True' will display
			ApprovedMemberContentOnly	True False	True	If 'True' will display only members content that
			CurrentMemberOnly	True False	False	If 'True' will display only
			Member	String		Specify a member to
			ShowInvisible	True False	False	If 'True' will display items
			ShowInactive	True False	False	If 'True' will display items
			Category	String		Choose a category to
pbProductPrice	Displays the price of a product, which updates dynamically based on properties selected, role-based pricing options, etc. This requires the [pbProductProperties] tag to be on the same page.	http://www.henryandlily.com.au/Products/ClutchingToyLara.aspx http://delovelysoycandles.com.au/collections/Warm_Tuscan_Apricot.aspx	CalcTax	True False	True	Show the price either included Tax
			ShowTaxOnly	True False	False	Show the Tax Amount of the product
pbProductProperties	Displays the Product Properties on a product details page, using drop-down lists to let the user select their properties (for E-Commerce).	http://oneluv.com.au/Shopping/WHEELOFWALRUS.aspx http://www.bandicoots.com.au/BikeTshirts/EngineTshirts/BonnevilleT120R.aspx	Width	Unit	150px	Sets the width of the dropdown
			ImageWidth	Unit		Allows you to set the max width on property value
			ImageHeight	Unit		Sets the max height on thumbnails in
			CalcTax	True False	True	Set to 'True' by default. If 'True' will
			UseSelector	True False	False	If 'True' then display a list of properties rather than a dropdown.



ThumbWidth	Unit	24px	The width of the thumbnail to display if
ThumbHeight	Unit	24px	The height of the thumbnail to display if
PopupImageWidth	Unit	120px	The width of the popup image to
PopupImageHeight	Unit	120px	The height of the popup image to
EnablePopup	True False	True	If 'True' then display a popup image when
PopupOffsetX	Int32	30	The X offset to display the
PopupOffsetY	Int32	10	The Y offset to display the
PopupTrackMouse	True False	True	If 'True' then the popup will track the mouse
EnablePriceInfo	True False	True	Enables
EnablePricePrefix	True False	True	Enables a

pbProductPropertyList	Displays Product Properties on a product details page, within a table. Allows the user to add a Product Property to their cart (when using Ecommerce). By default the control displays every Property value with one table per Property.	http://activehiregroup.com.au/DivisionsMenu/GeneralHire/GENERATORS1.aspx	GoToCart	True False	True	If true the user is redirected to their Shopping
			GoToCheckout	True False	False	If true the user is redirected to
			ImageHeight	Unit		When the Image column is displayed,
			ImageWidth	Unit		When the Image column is displayed,
			Name	String		If set, only a single table will be displayed,



CssClass	String	pbProductPropertyList	Sets the CSS class around
ShowPropertyName	True False	True	Displays the Property
ShowAddToCart	True False	True	Displays Add to Cart
ShowImage	True False	False	Displays the
ShowDescription	True False	True	Displays the Description
ShowWeight	True False	False	Displays the
ShowHeight	True False	False	Displays the
ShowWidth	True False	False	Displays the
ShowDepth	True False	False	Displays the
ShowPrice	True False	True	Displays the
ShowColumnHeaders	True False	True	Displays the column names
ColumnNameImage	String	Image	Sets the Image
ColumnNameValue	String	Option	Sets the Property
ColumnNameDescription	String	Description	Sets the Description
ColumnNameWeight	String	Weight	Sets the
ColumnNameHeight	String	Height	Sets the
ColumnNameWidth	String	Width	Sets the Width
ColumnNameDepth	String	Depth	Sets the Depth
ColumnNamePrice	String	Price	Sets the Price
ColumnNameAddToCart	String		Sets the Add to Cart
AddToCartLinkText	String	Add to Cart	Sets the text on the Add to
CalcTax	True False	True	Show the price either

pbProductRelatedList pbAdvProductRelatedList	Shows a list of all related products. (this control can only be used on a product item details template)	CssClass	String	pbList	Allows you to override the
		Template	String		Allows you to select a
		NoDataMessage	String	No Related Products	Message to show the user when there
		IncludeMemberContent	True False	False	If 'True' will show
		MemberContentOnly	True False	False	If 'True' will display



ApprovedMemberContentOnly	True False	True	If 'True' will show only members
CurrentMemberOnly	True False	False	If 'True' will display for
Member	String		set up the member's ID
ShowInvisible	True False	False	If true the control will
ShowInactive	True False	False	If true the control will
Category	String		Choose a category to
TopPagerVisible	True False	False	If 'True' then the pager will
BottomPagerVisible	True False	True	If 'True' then the pager will be displayed
PageSize	Int32	10	The number
EnableAjax	True False	False	If 'True' then ajax will be
BottomPagerCssClass	String		The CSS class to set for the
TopPagerCssClass	String		the CSS class to set for the
Templates			
HeaderTemplate			
ItemTemplate			
AlternatingItemTemplate			
SeparatorTemplate			
FooterTemplate			
pbProductRelatedSummary pbAdvProductRelatedSummary	Shows a summary of all related products. (this control can only be used on a product item details template)	http://www.brainboost.com.au/Programs/Programs2/How_to_ask_questions.aspx	
CssClass	String	pbSummary	Allows you to override the CSS class on the control
Template	String		Allows you to select a
NoDataMessage	String	No Related Products	Message to show the user when there
IncludeMemberContent	True False	False	If 'True' will show
MemberContentOnly	True False	False	If 'True' will display



			ApprovedMemberContentOnly	True False	True	If 'True' will show only members
			CurrentMemberOnly	True False	False	If 'True' will display for
			Member	String		set up the member's ID
			ShowInvisible	True False	False	If true the control will
			ShowInactive	True False	False	If true the control will
			Category	String		Choose a category to
Templates						
HeaderTemplate						
ItemTemplate						
AlternatingItemTemplate						
SeparatorTemplate						
FooterTemplate						
pbProductSearch	Provides an advanced search control for searching through Product collections. Note this search will only ever return Products.	http://www.rankinsdirect.com.au/shop.aspx	Collection	String		Sets the control to pick up items from
			ResultsPage	String		Sets the results page that the user will be redirected to upon submitting a search. This



SearchFields	String	keyword,collection,category,price,min/max	Specifies the fields that the search control should provide. The default is "keyword,collection,category,price", which provides a keywords field, a collection dropdown, category dropdown and price min/max
FieldLabels	String		This list works similar to the SearchFields property, and should match up with the fields specified on that property. It overrides the labels given to each field (by default they will use the field name as the label). E.g. "Keywords,Col



CategoryLevels	Int32	1	The number of category search fields to include - these will be different category levels. E.g. Specifying 3
ShowAllOption	True False	True	If true, dropdowns contain a "show all"
ShowLabelInsideField	True False	False	n/a
Dependency	String		Lets you set up field dependencies, so that field B is disabled until field A has been selected. You don't have to
ButtonText	String	Search	Lets you override the
UseDropDownFields	True False	False	If true, the fields are generated as dropdown
AllOptionText	String	All	When ShowAllOption="true", sets the text for the "All" text for the
CssClass	String	pbProductSearch	The CSS class to set on the
ShowCurrentSearchTerms	True False	False	Select category and collection dropdown
ShowLastSearchTerms	True False	False	Select category and collection



ShowLastVisitedCategory	True False	False	Select category dropdown item based on
ShowCurrentLocation	True False	False	Select category and collection
CacheMaxAge	Integer	5	How long the previous search is
PartialMatch	True False	False	How long the previous search is
AutoRefreshWhenDropdownChanges	True False	False	If 'True' then the search will automatically
HideSearchButton	True False	False	If 'True' then the search button is hidden. Use in
PerformImmediateSearch	True False	False	If 'True' then initiate a search as soon as the page is loaded. Use in
CategorySortField	String		Orders the categories by
CategorySortDirection	String	ASC	Orders the categories by
NavigateToLastSearchPage	True False	False	Set to "True" to enable the following behaviour: When navigating from a search results page to another page, such as a
UseSliderForPrice	True False	False	If true, a slider control will replace the



SliderBuffer	Int32	0	This value is added to the selected max price and
SliderMinValue	Int32	0	Minimum
SliderMaxValue	Int32	500	Maximum
SliderSelectionStart	Int32	50	Must be greater than the SliderMinValue
SliderSelectionEnd	Int32	450	Must be greater than the SliderMinValue
SliderSmallChange	Int32	20	Controls the
SliderBigChange	Int32	100	Controls the
SliderOrientation	Horizontal Vertical	Horizontal	Controls
SliderTrackPostition	Center TopLeft BottomRight	Center	
SliderHeight	Int32	40	Controls the
SliderWidth	Int32	400	Controls the
CheckboxListFields	String	""	Comma separated list of field names
CheckboxListColumns	Int32		3 Number of columns that the checkbox Controls
CheckboxListRepeatDirection	Horizontal Vertical	Horizontal	
CheckboxTextAlign	Right Left	Right	Text / image appears to the
HideDisabledCheckboxLists	True False	True	When true, dependent checkbox list fields are not
UseLegacyControls	True False	True	Set to false when images
ImageRegionName	String	""	Region name that contains the image for
ImageWidth	Int32	20	Width of the dropdown /
ImageHeight	Int32	20	Height of the dropdown /
MinImageWidth	Int32	20	Min width of the dropdown



pbProductSearchResults pbAdvProductSearchResults	A list control similar to the [pbCollectionList], required to list search results from a [pbProductSearch].	http://www.henryandlily.com.au/SearchResults.aspx	MinImageHeight	Int32	20	Min height of the dropdown
			SortAdditionalFields	True False	FALSE	Sorts the results
x		http://www.rankinsdirect.com.au/ProductSearchResults.aspx	Sort	String	SortOrder	Sort the results
			Collection	String		Sets the control to pick up items from
			TopPagerVisible	True False	False	Shows a pager
			BottomPagerVisible	True False	True	Shows a pager
			CssClass	String	pbList	Allows you to override the
			Template	String		Allows you to select a different
			CurrentPage	Int32	0	
			PageSize	Int32	10	Sets the number of items per
			ShowInactive	True False	False	If true will also list inactive
			IncludeMemberContent	True False	False	If 'True' will show
			MemberContentOnly	True False	False	If 'True' will display
			ApprovedMemberContentOnly	True False	True	If 'True' will show only members
			CurrentMemberOnly	True False	False	If 'True' will display for
			MatchAllCategories	True False	True	If 'True', performs and AND on the selected categories, showing only items that
			Member	String		set up the member's ID
			EnableAjax	True False	False	If 'True' will display an ajax
			EnablePaging	True False	False	If 'True', then allow custom pbPager



			MaxResults	Int32	0	Limit the
			Templates			
			HeaderTemplate			
			ItemTemplate			
			AlternatingItemTemplate			
			SeparatorTemplate			
			FooterTemplate			
			FirstItemTemplate			Available for inline
			LastItemTemplate			Available for inline
			LastAlternatingItemTemplate			Available for inline
			NoDataTemplate			Available for inline
pbProductSearchSummary	Used in conjunction with pbProductSearchResults, this provides a brief summary of the number of results. It should be placed on your results page.	http://www.rankindirect.com.au/ProductSearchResults.aspx	Message	String	Your search returned {Count} products	Lets you override the text displayed - use the [Count] placeholder in
pbProductStockLevel	Show the product Stock level.	http://oneluv.com.au/Shopping/WHEELOFWALRUS.aspx	NoStockText	String	No Stock	Text displayed when there is no stock
			NoStockCssClass	String	nostock	Used to apply a CSS class
			LowStockText	String	Low Stock	Text displayed when the
			LowStockCssClass	String	lowstock	Used to apply a CSS class
			InStockText	String	In Stock	Text displayed when there is
			InStockCssClass	String	instock	Used to apply a CSS class
			ShowQty	True False	False	If 'True' will show the
pbProductUserValue	Used with collection lists/summaries. Allows user to enter a comment when adding items to the cart.	http://anythingbaby.com.au/Products_For_Hire/Capsules_Car_Seats_and_Booster_Seats.aspx	Field	String		Set the additional field name to render from
			CssClass	String	textbox	Page Template and



		Width	Unit	Apply a width to the
		IsRequired	True False	False
		RequiredMessage	String	Required
				Used in conjunction with the
pbProductUserComments	Used with collection lists/summaries. Allows user to enter a comment when adding items to the cart	CssClass	"textbox"	Control Template
		Width		n/a
		Height		n/a
		Rows		"4"
		IsRequired	True False	False
				Sets whether a comment must be
		ErrorText	String	Please enter a comment
pbCartRelatedProducts	Inline Templated control to show related products for all products in a users shoppingcart	Category	String	Filter related products by
		ExcludeItemsInCart	True False	True
		MaxItems	Int32	0
		Filter	String	
		Sort	String	
		RandomSort	True False	False
		Grouped	True False	False
				Display the result as groups of related products for
		ShowInactive	True False	False
		ShowInvisible	True False	False
				If True then show inactive
				If True then show invisible
		Templates		
		HeaderTemplate		
		FirstItemTemplate		
		ItemTemplate		



```

.....
AlternatingItemTemplate
.....
LastItemTemplate
.....
LastAlternatingItemTemplate
.....
SeparatorTemplate
.....
FooterTemplate
.....
GroupHeaderTemplate
.....
  
```

Control Tags

Value Tags	Description	Use	Properties	Value	Default	Notes
pbProductAddQuantity pbCtProductAddQuantity	Inserts a textbox with a numbered field. Used to insert more than one item into the shopping cart.	http://fruitinbox.com.au/Buil dYourOwnBox.aspx	TextboxWidth	Unit	50px	Sets the width of the quantity field.
		http://bremerton.com.au/The Wines/BuyOnline.aspx	ShowSpinButtons	True False	False	*Further notes: this tag is always used Show the up and down arrow buttons
			DecimalPlaces	Int32	0	Set the amount of
			TextAlign	HorizontalAlign	Right	NotSet, Left,
pbProductAddToCart pbCTProductAddToCart	Creates a link that will add product to cart.	http://bremerton.com.au/The Wines/BuyOnline.aspx	GoToCart	True False	True	If true, the user is redirected to
		http://cfmvic.com.au/Product s/Catering- Equipment/Refrigeration/Und er-Bars.aspx	GoToCheckout	True False	False	If true, the user is redirected to the first step
			RedirectTo	String		Set the page to redirect to after adding to cart if not
			Text	String	Add to cart	Lets you override the
			ImageUrl	String		Specifies an image path to
			EnableTimer	True False	False	
			TimeCounter	Int32	5	



			OutOfStockMessage	String	Not enough stock to fulfill requ	The text displayed
			ErrorText	String	Item could not be added to cart	Error message to display if
			PropertyErrorText	String		Error message to display if not all
pbProductAddToCartCheckbox pbCtProductAddToCartCheckbox	Used in control templates to provide a checkbox selection for adding multiple products to the cart with a "pbProductAddCheckedToCart" tag		Checked	True False		Determines whether the checkbox is checked on page load
pbProductGroupSummary pbCtProductGroupSummary pbAdvCtProductGroupSummary	Used to display a Product Group summary.	http://cigars.simpleid.com.au/Products/CigarCollection/Cigars/CubanCigars.aspx	CssClass	String	pbSummary	Apply a CSS class to the summary list
			Template	String		Set the template for
			NoDataMessage	String	No Grouped Products	Messaged displayed if
			IncludeMemberContent	True False	False	If 'True' will display
			MemberContentOnly	True False	False	If 'True' will display
			ApprovedMemberContentOnly	True False	True	If 'True' will display only members content that
			CurrentMemberOnly	True False	False	If 'True' will display only
			Member	String		Specify a member to
			ShowInvisible	True False	False	If 'True' will display items
			ShowInactive	True False	False	If 'True' will display items
			Category	String		Choose a category to
			Templates			
			HeaderTemplate			
			ItemTemplate			
			AlternatingItemTemplate			



		SeparatorTemplate				FooterTemplate
pbProductPrice pbCtProductPrice	Displays the price of a product. If member pricing has been applied, it will automatically pick up the correct pricing if the user has been	http://www.fiera.com.au/Shopp.aspx http://oneluv.com.au/Shopping/TheLatest.aspx	CalcTax	True False	True	Include tax in the calculation
			ShowTaxOnly	True False	False	Show only the amount of tax
pbCtProductProperties pbProductProperties	Displays product properties if they have been applied to an item.	http://www.eziconcepts.com.au/Products/ElementCovers/TheCottageSeries.aspx	Width	Unit	150px	Sets the width of the dropdown boxes.
			ImageWidth	Unit		Allows you to set the max width on property value
			ImageHeight	Unit		Sets the max height on thumbnails in
			CalcTax	True False	True	Set to 'True' by default. If 'True' will
pbProductStockLevel pbCtProductStockLevel	Displays the current amount of stock for a particular item.		NoStockText	String	No Stock	Text displayed when there is
			NoStockCssClass	String	nostock	Used to apply a CSS class
			LowStockText	String	Low Stock	Text displayed when the
			LowStockCssClass	String	lowstock	Used to apply a CSS class
			InStockText	String	In Stock	Text displayed when there is
			InStockCssClass	String	instock	Used to apply a CSS class
			ShowQty	True False	False	If 'True' will show the
pbProductUserComments pbCtProductUserComments	Used with collection lists/summaries. Allows user to enter a comment when adding items to the cart.		CssClass	String	textbox	Apply a CSS class to the
			Width	Unit		Specify a width for the
			Height	Unit		Specify a height for the



			Rows	Int32	4	Specify how many rows for
			Value	String		Insert a value into the
pbProductUserValue pbCtProductUserValue	Used with collection lists/summaries. Allows user to enter a comment when adding items to the cart.		Field	String		Set the field
			CssClass	String	textbox	Apply a CSS class to the
			Width	Unit		Set the width
			GetFieldId	String		
pbCompareProducts	Allows a user to compare products For use with http://www.printersupermarket.com	http://www.printersupermarket.com	ControlType	Button Image Link		How to render
			Text	String		Text to show
			ImageUrl	String		Image to use
			Tooltip	String		Tooltip to
			CompareButtonCssClass	String		Css class to
			CompareCheckboxCssClass	String		Css class to
			ResultsPage	String		Page to show
			UsePopupWindow	True False	TRUE	Whether to
			PopupWindowHeight	Unit	600px	
			PopupWindowWidth	Unit	750px	
pbCompareProductList pbCtCompareProductList	Inline-templatable control for use with http://www.printersupermarket.com	http://www.printersupermarket.com	ListCssClass	String	list	Css class to give to the list
			CssClass	String	pbList	Css class to give to the list container
			Templates			
			HeaderTemplate			
			FirstItemTemplate			
			AlternatingItemTemplate			
			SeparatorTemplate			
			FooterTemplate			
			LastItemTemplate			
			LastAlternatingItemTemplate			
			NoDataTemplate			

Valuetags

Value Tags	Description	Use	Properties	Value	Default	Notes
------------	-------------	-----	------------	-------	---------	-------

Product.BaseWeight



- Product.Code
- Product.OrderMaxQty
- Product.OrderMinQty
- Product.OurPrice
- Product.ProductDate
- Product.RetailPrice
- Product.Special
- Product.SpecialPrice
- Product.Capped
- Product.StockLowQOH
- Product.StockMinQOH
- Product.StockQOH
- Product.TaxExempt
- Product.TaxRate
- Product.Featured
- Product.IsStock
- Product.Price0
- Product.Price1
- Product.Price2
- Product.Price3
- Product.Price4
- Product.Price5
- Product.Price6
- Product.Price7
- Product.Price8
- Product.Price9
- Product.StockBackOrderQOH
- Product.StockReorderQOH

Emailtags

Value Tags	Description	Use	Properties	Value	Default	Notes
<no tags>						



Template Email Tags

Order Confirmation Email:

The following tags are used in templating the emails that are sent to the customer or administrator when an order is placed through the eCommerce module. Email templates need to be html files

Skintag	Description
Order.Number	Order template tags
Order.Date	
Order.BillToName	
Order.BilltoDateOfBirth	
Order.BillToGender	
Order.BillToAddress	
Order.BillToAddress2	
Order.BillToSuburb	
Order.BillToState	
Order.BillToPostcode	
Order.BillToCountry	
Order.BillToEmail	
Order.BillToPhone	
Order.BillToFax	
Order.BillToMobile	
Order.ShipToName	
Order.ShipToDateOfBirth	
Order.ShipToGender	
Order.ShipToAddress	
Order.ShipToAddress2	
Order.ShipToSuburb	
Order.ShipToState	
Order.ShipToPostcode	
Order.ShipToCountry	
Order.ShipToEmail	
Order.ShipToPhone	
Order.ShipToFax	
Order.ShipToMobile	
Order.PayMethod	
Order.PostageType	
Order.PostageAmount	
Order.TaxAmount	
Order.SubTotal	
Order.Total	
Order.Comment	
Order.SurchargeAmount	



Order.SurchargeRate
Order.DiscountTotal
Order.Promocode
Order.HowDidYouHear
Order.Company
Order.EmailComment
Order.CreditCardType
Order.referralurl

ItemTable	<i>Inserts a table listing each product/item that has been ordered</i>
Id	<i>Item table template tags</i>
OrderId	
Siteld	
ItemType	
ItemId	
ItemCode	
ItemName	
ItemDescription	
ItemQty	
ItemUnitPrice	
ItemTaxCode	
ItemTaxRate	
ItemOptions	
ItemComments	
Comments	
UsePoints	
IsDownload	
DownloadUrl	
MaxDownloads	
DownloadCount	
McObjectid	
ItemWeight	
ItemHeight	
ItemWidth	
ItemDepth	
ItemCapped	
ItemTax	
ItemTotalTax	
ItemTotal	
ItemUnitPriceIncTax	
ItemTotalIncTax	

Form email:



Item:

Item.HtmlTitle	Using in the normal pbForm,
Item.Alias	pbEventRegistrationForm
Item.Category	
Item.CreatedDate	
Item.Description	
Item.Id	
Item.ImageUrl	
Item.Keywords	
Item.Name	
Item.PageUrl	
Item.SiteObjectType	
Item.Summary	

Member:

Member.Username	Using in the normal pbForm,
Member.Password	pbEventRegistrationForm
Member.Active	
Member.SignupDate	
Member.FirstName	
Member.LastName	
Member.Email	
Member.Address	
Member.Address2	
Member.Suburb	
Member.State	
Member.Postcode	
Member.Country	
Member.Phone	
Member.Fax	
Member.MobileNo	
Member.DateOfBirth	
Member.Gender	
Member.Bookmarks	
Member.Status	

Event:

Event.Duration	Using in
Event.EndDate	pbEventRegistrationForm
Event.PricePerSeat	
Event.StartDate	
Event.TotalSeats	
Event.VenueAddress	
Event.VenueAddress2	
Event.VenueCountry	
Event.VenueEmail	
Event.VenueFax	



Event.VenueMobile
Event.VenueName
Event.VenuePhone
Event.VenuePostcode
Event.VenueState
Event.VenueSuburb

E-Marketing Email:

Skin Tag	Description	Properties	Value	Default	Notes
pbContent	Inserts an editable content region that is managed in the console with a WYSIWYG editor. All pbContent tags must have a 'region name' specified	RegionName	Any name, e.g. "Default"	n/a	Each tag within a template must have a different RegionName. The RegionName is used as the label on the tab above the editor in the console
		Name	as "RegionName"	as "RegionName"	as "RegionName"
		toolset	n/a	n/a	n/a
pbImage	Inserts an editable image region that is managed in the console. All pbImage tags must have a 'image name' specified	ImageName	Any name, e.g. "Default"	n/a	Each tag within a template must have a different ImageName. The ImageName is used as the label on the tab above the editor in the console
		RegionName	as "RegionName"	as "RegionName"	as "RegionName"
		Name	as "RegionName"	as "RegionName"	as "RegionName"
pbItem	Inserts an editable collection item that is managed in the console. All pbItem tags must have a 'name' specified	ItemName	Any name, eg. "Default"	n/a	Each tag within a template must have a different Name. The Name is used as the label on the tab above the editor in the console
		Link	True/False	"False"	Render the item name as a link to the item's web page. If False nothing is rendered.
		RegionName	as "RegionName"	as "RegionName"	as "RegionName"
		Name	as "RegionName"	as "RegionName"	as "RegionName"
		collection	n/a	n/a	



pbItemField	Insert an Item field into the email	ItemName	Name of pbitem, eg. "Default"	n/a	The name of the pbitem tag to extract the field value from
		Field	Field name, eg. "Name" or "Summary"	n/a	The field to display
		RegionName	as "RegionName"	as "RegionName"	as "RegionName"
		Name	as "RegionName"	as "RegionName"	as "RegionName"
		FieldName	as "Field"	as "Field"	as "Field"
pbPreview	Inserts a link to the on-line preview version of the newsletter	n/a			
pbUnsubscribe	Inserts a link to the unsubscribe confirm page	n/a			
pbSubscriber	Inserts a field from the subscriber into the email	Key	A Subscriber value field	n/a	eg. "Firstname", "Lastname", "Email", "Address", "Suburb", etc.
		Name	as "Key"	as "Key"	as "Key"
		Value	as "Key"	as "Key"	as "Key"
		Field	as "Key"	as "Key"	as "Key"
pbPartnerValue	Inserts a field from the partner into the email	Key	A Partner value field	n/a	eg. "Name", "Logo", etc.
		Name	as "Key"	as "Key"	as "Key"
		Value	as "Key"	as "Key"	as "Key"
pbSiteValue	Inserts a field from the site settings into the email	Key	A Site value field	n/a	e.g. "Name", "OwnerName", "OwnerAddress", "OwnerSuburb", "OwnerABN", "PostalAddress", etc.
		Name	as "Key"	as "Key"	as "Key"
		Value	as "Key"	as "Key"	as "Key"
pbReferFriend	Inserts a link to the Refer a friend page	n/a			

Refer Friend Email

pbSubscriber
SignUpUrl
Comment

Key="Name" and Key="Email" | example: [pbSubscriber Key="Name"] [pbSubscriber Key="Email"]

Member Console Email:

Skin Tag

Description



[Member.Comments]

Inserts the comments from the email form in the email template

Forums

Skin Tag

- Status
- ForumName
- ThreadName
- PostName
- PostMessage
- PostMemberName
- PostDateTime
- QuickLink
- QuickApproveLink

Description

